



SLOVENSKI STANDARD

SIST EN 302 842-2 V1.4.1:2015

01-oktober-2015

Radijska oprema za digitalno povezavo VHF (VDL) zrak-tla in zrak-zrak, 4. način - Tehnične karakteristike in merilne metode za aeronavtično mobilno (letalsko) opremo - 2. del: Splošni opis in plast za podatkovne povezave

VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 2: General description and data link layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 842-2 V1.4.1:2015](https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cdde50c2/sist-en-302-842-2-v1-4-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cdde50c2/sist-en-302-842-2-v1-4-1-2015>

Ta slovenski standard je istoveten z: EN 302 842-2 V1.4.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
35.100.20	Podatkovni povezovalni sloj	Data link layer
49.090	Oprema in instrumenti v zračnih in vesoljskih plovilih	On-board equipment and instruments

SIST EN 302 842-2 V1.4.1:2015

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 842-2 V1.4.1:2015](https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015>

ETSI EN 302 842-2 V1.4.1 (2015-04)



**VHF air-ground and air-air Digital Link (VDL)
Mode 4 radio equipment;
Technical characteristics and methods of measurement
for aeronautical mobile (airborne) equipment;
Part 2: General description and data link layer**

Reference

REN/AERO-00019-2

Keywords

aeronautical, digital, radio, testing, VHF**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 842-2 V1.4.1:2015<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc5162/etsi-en-302-842-2-v1-4-1-2015>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
Introduction	9
1 Scope	10
2 References	12
2.1 Normative references	12
2.2 Informative references.....	12
3 Definitions and abbreviations.....	13
3.1 Definitions	13
3.1.1 Basic reference model definitions.....	13
3.1.2 Service conventions definitions	13
3.1.3 General definitions.....	13
3.1.4 Definition of bit order.....	17
3.2 Abbreviations	17
4 General description of VDL Mode 4 mobile station link layer	18
4.1 Overview of VDL Mode 4	18
4.1.1 Void.....	19
4.1.2 Relationship to OSI reference model.....	19
4.1.3 VDL Mode 4 services	21
4.1.4 ADS-B function.....	21
4.1.5 Operational scenarios.....	22
4.1.6 VDL Mode 4 fundamentals	22
4.1.7 Possible configuration of airborne equipment.....	23
4.1.8 Classes of equipment.....	25
4.1.9 Transceiver cross-links	25
4.1.10 Overall structure of specifications for VDL Mode 4	26
4.1.11 Equipment performance verification	27
5 Minimum performance specification under standard test conditions.....	28
5.1 MAC sublayer	28
5.1.1 Services.....	28
5.1.2 MAC sublayer services.....	28
5.1.3 MAC sublayer parameters	28
5.1.3.1 General.....	28
5.1.3.2 Parameter M1 (number of slots per superframe).....	29
5.1.3.3 Parameter M2_inc and M2_limit (MAC layer control parameters for network entry)	29
5.1.3.4 Inspection of m2 filter following transceiver failure.....	30
5.1.4 Time synchronization	30
5.1.4.1 Primary.....	30
5.1.4.2 Secondary.....	30
5.1.4.3 Alignment to UTC second	31
5.1.4.4 Data quality level	31
5.1.5 Slot idle/busy notification.....	31
5.1.5.1 Slot idle detection.....	31
5.1.5.2 Slot busy detection	31
5.1.5.3 Slot occupied detection	31
5.1.5.4 Signal level indication.....	31
5.1.6 Transmission processing.....	32
5.1.7 Received transmission processing	32
5.2 VSS sublayer.....	32
5.2.1 Services.....	32
5.2.1a Multiple access	32
5.2.1.1 Error detection.....	33
5.2.1.2 Channel congestion	33

5.2.2	Burst format	33
5.2.2.1	VSS burst structure	33
5.2.2.2	Version number	34
5.2.2.3	Source address.....	34
5.2.2.4	Message ID	34
5.2.2.5	Information field	35
5.2.2.6	Reservation fields.....	35
5.2.2.7	Autonomous/directed flag	36
5.2.3	VSS sublayer parameters	36
5.2.3.1	General	36
5.2.3.2	Parameter VS1 (number of ground quarantined slots)	37
5.2.3.3	Parameter VS2 (minimum CCI performance).....	37
5.2.3.4	Parameter VS4 (quarantine slot re-use range).....	38
5.2.3.5	Parameter VS5 (maximum burst length).....	38
5.2.4	VSS quality of service parameters	38
5.2.4.1	General	38
5.2.4.2	Parameter Q1 (priority)	38
5.2.4.3	Parameters Q2a to Q2d (slot selection range constraint for level n)	39
5.2.4.4	Parameter Q3 (replace queued data)	40
5.2.4.5	Parameter Q4 (number of available slots)	40
5.2.5	Received transmission processing	40
5.2.6	Reserved access protocol specification.....	41
5.2.6.1	Reservation table	41
5.2.6.2	Selecting slots for transmission or reservation	42
5.2.6.3	Reserved transmissions	43
5.2.6.4	Reservation conflicts	44
5.2.6.5	Transmission conflicts for mobile stations	44
5.2.7	Random access protocol specification	45
5.2.7.1	General	45
5.2.7.2	Random access parameters.....	45
5.2.7.3	Random access procedures.....	47
5.2.8	Void	47
5.2.9	Null reservation protocol specification.....	47
5.2.9.1	Null reservation burst format	47
5.2.10	Periodic broadcast protocol specification	48
5.2.10.1	Periodic broadcast reservation burst format	48
5.2.10.2	Periodic broadcast timers	49
5.2.10.3	Periodic broadcast parameters.....	49
5.2.10.4	Periodic broadcast reception procedures	50
5.2.10.5	Periodic broadcast transmission procedures.....	51
5.2.11	Incremental broadcast protocol specification	54
5.2.11.1	Incremental broadcast reservation burst format	54
5.2.11.2	Incremental broadcast parameters	54
5.2.11.3	Incremental broadcast reception procedures	55
5.2.11.4	Incremental broadcast transmission procedures	55
5.2.12	Combined periodic broadcast and incremental broadcast protocol specification	56
5.2.12.1	Combined periodic broadcast and incremental broadcast reservation burst	56
5.2.13	Big negative dither (BND) broadcast protocol specifications	56
5.2.13.1	BND reservation burst format	56
5.2.13.2	BND broadcast parameters.....	57
5.2.13.3	BND broadcast reception procedures	57
5.2.13.4	BND broadcast transmission procedures	57
5.2.14	Unicast request protocol specification	57
5.2.14.1	Unicast request reservation burst format.....	57
5.2.14.1a	Unicast request parameters.....	58
5.2.14.2	Unicast request reception procedures	59
5.2.14.3	Unicast request transmission procedures	60
5.2.15	Information transfer request protocol specification	60
5.2.15.1	Information transfer request reservation burst format	60
5.2.15.2	Information transfer request reception procedures	61
5.2.16	Directed request protocol specification.....	62
5.2.16.1	Directed request reservation burst format	62

5.2.16.2	Directed request parameters	65
5.2.16.3	Directed request reception procedures	66
5.2.16.4	Directed request transmission procedures	67
5.2.16.5	Directed request response procedures	68
5.2.17	Block reservation protocols specification	69
5.2.17.1	Superframe block reservation burst format	69
5.2.17.2	Second frame block reservation burst format.....	70
5.2.17.3	Void.....	71
5.2.17.4	Superframe block reservation reception procedures	71
5.2.17.5	Second frame block reservation parameters.....	73
5.2.17.6	Second frame block reservation reception procedures	73
5.2.17.7	Void.....	73
5.2.17.7a	Procedures for responding to a rebroadcast request for superframe block reservation	73
5.2.18	Response protocol specification	73
5.2.18.1	Response burst format.....	73
5.2.19	General request protocol specification.....	74
5.2.19.1	General request burst format	74
5.2.19.2	General request procedures	75
5.2.20	General response protocol specification	75
5.2.20.1	General response burst format.....	75
5.2.20.2	General response procedures.....	77
5.2.21	Retransmission procedures	77
5.3	DLS sublayer.....	77
5.3.1	Services.....	77
5.3.1.1	General	77
5.3.1.2	Data transfer	77
5.3.1.3	Station address encoding	78
5.3.1.4	DLS burst formats	79
5.3.2	DLS system parameters	80
5.3.2.1	Parameter ND4 (maximum length of a UDATA burst)	80
5.3.3	DLS procedures	80
5.3.3.1	Broadcast	80
5.3.3.2	DLS not supported	81
5.3.3.3	User data packet reception	81
5.3.3.4	CTRL DLPDU	81
5.4	Link Management Entity (LME) sublayer	81
5.4.1	Services.....	81
5.4.2	Synchronization burst format.....	81
5.4.2.1	General	81
5.4.2.2	Fixed and variable data fields.....	82
5.4.2.3	Fixed data field format	82
5.4.2.4	Variable data field format	85
5.4.2.5	Synchronization burst request	85
5.4.2.6	Broadcast link management burst	85
5.4.3	Control (CTRL) parameter formats	86
5.4.3.1	Encoding	86
5.4.3.2	VDL Mode 4 parameter identification	86
5.4.3.3	Ground-initiated modification parameters	87
5.4.3.4	Ground-initiated information parameters	90
5.4.3a	LME timers and parameters.....	92
5.4.3a.1	General	92
5.4.3a.2	Counter L1 (maximum number of missed reservations) and Timer TL3 (inter miss timer)	93
5.4.4	LME procedures	93
5.4.4.1	Synchronization burst procedures	93
5.4.4.2	Peer Entity Contact Table (PECT).....	95
5.4.4.3	Network entry protocol specifications	96
5.4.5	Additional material for ADS-B applications	102
5.4.5.1	Information field formats	102
5.4.5.2	ADS-B request format.....	103
5.5	Void.....	103
5.6	Definitions for Compact Position Reporting	103
5.6.1	Introduction.....	103

5.6.2	Parameter symbols, data types, constants and variables	103
5.6.2.1	Parameter symbols	103
5.6.2.2	Data types.....	104
5.6.2.3	Constants.....	104
5.6.2.4	Variables	104
5.6.2.5	Functions.....	104
5.6.2.6	Patch constants	104
5.6.3	Fixed data field position encoding.....	104
5.6.4	Fixed data field position local decoding	104
5.6.5	Fixed data field position global decoding	104
5.6.6	Position Report Processing	104
6	General design requirements	104
6.1	Controls and indicators.....	104
6.2	Warm up.....	104
6.3	Airworthiness	104
6.4	Intended function.....	104
6.5	International Telecommunications Union regulations.....	104
6.6	Fire protection	105
6.7	Operation of controls.....	105
6.8	Accessibility of controls	105
6.9	Effects of tests	105
6.10	Failure of the VDL Mode 4 equipment	105
6.11	Software management	105
6.12	Transceiver configuration.....	105
6.13	Provision for multiple redundant VDL4 transceivers.....	105
6.14	Reception capability.....	105
6.15	Transmission capability.....	105
6.16	Monitoring of proper operation.....	105
6.17	Power-up self test	105
7	Protocol test procedures	105
7.1	General	105
7.1.1	Input voltage.....	105
7.1.2	Power input frequency.....	106
7.1.3	Adjustment of equipment.....	106
7.1.4	Equipment configuration	106
7.1.5	Test equipment precautions	106
7.1.6	Ambient conditions.....	106
7.1.7	Connected loads.....	106
7.2	Required test rig	106
7.3	Protocol test-suite description methodology	109
7.4	Detailed protocol test procedures	109
7.4.1	Test-suite overview.....	109
7.4.2	Declarations	115
7.4.3	Constraints	115
7.4.3.1	Abbreviations	115
7.4.3.1.1	Subfield mnemonics	115
7.4.3.1.2	Special characters used in the subfield definitions	116
7.4.3.1.3	Station addresses and positions	116
7.4.3.1.4	Tables of values for use in CPR test cases	118
7.4.3.1.5	Tables of values for use in content checking test cases	129
7.4.3.1.6	VDL4 burst formats.....	131
7.4.3.2	Test cases	151
7.4.3.2.1	Test case macros.....	152
7.4.3.2.2	Test case descriptions.....	155
Annex A (informative): Cross reference matrix		379
Annex B (informative): Description of ISO/IEC 9646 test methodology.....		405
B.1	Overview of the structure of the ISO/IEC 9646 test suites	405

B.2	The test case description.....	405
B.3	The queue action	407
B.4	The repeat construct	407
B.5	Macro definitions	408
B.6	Test case naming	408
Annex C (informative): Bibliography		409
History		410

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 842-2 V1.4.1:2015](https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Aeronautics (AERO).

The present document is part 2 of a multi-part deliverable covering the VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment, as identified below:

Part 1: "Physical layer";

Part 2: "General description and data link layer";

Part 3: "Additional broadcast aspects";

Part 4: "Point-to-point functions".

The present document is accompanied by an equivalent ground-based standard, ETSI EN 301 842 [i.5] parts 1 to 5, covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment.

NOTE: Minimum Operational Performance Specifications (MOPS) are also being developed for VDL Mode 4. EUROCAE have previously published Interim MOPS for VDL Mode 4 [i.6] which are a sub set of ETSI EN 302 842-1 [2], ETSI EN 302 842-2 (the present document), ETSI EN 302 842-3 [6] and ETSI EN 302 842-4 [7]. ETSI EN 302 842-1 [2], ETSI EN 302 842-2 (the present document), ETSI EN 302 842-3 [6] and ETSI EN 302 842-4 [7] comply with the requirements of EC Mandate M/318 [i.7].

National transposition dates

Date of adoption of this EN:	6 April 2015
Date of latest announcement of this EN (doa):	31 July 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2016
Date of withdrawal of any conflicting National Standard (dow):	31 January 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [i.2].

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- equipment comply with ETSI EN 302 842-1 [2].

NOTE: The present document has been produced with a view to maintaining consistency of numbering with the equivalent standard for ground equipment (see ETSI EN 301 842 [i.5] parts 1 to 4). Where requirements are the same, they have been given the same number. Some new airborne requirements have been inserted between requirements that were sequential in ETSI EN 301 842 [i.5] parts 1 to 4. This has led to a non-standard form of numbering for new requirements in some places.

(standards.iteh.ai)

[SIST EN 302 842-2 V1.4.1:2015](https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-7085cddc50c2/sist-en-302-842-2-v1-4-1-2015>

1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [i.2].

The present document provides part 2 of the technical specifications.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VDL SARPs [i.2] and ICAO VDL4 Technical Manual [i.1].

NOTE: In clause 5.1.4, Tertiary time, as described by the ICAO VDL4 Technical Manual [i.1], has not been included as a requirement in the present document due to the opinion of the ETSI Working Group that insufficient evidence was available to be able to verify correct operation of a "floating network" of stations operating on tertiary time.

Manufacturers should note that in future the tuning range for the transmitter and the receiver may cover any 25 kHz channel from 108,000 MHz to 111,975 MHz.

The present document applies to "aeronautical mobile (airborne and in some cases ground vehicles)" equipment which will hereinafter be referred to as "mobile" equipment.

The scope of the present document is limited to mobile stations. The equivalent specification for ground stations is ETSI EN 301 842 [i.5].

The VDL Mode 4 system provides digital communication exchanges between aircraft and ground based systems and other aircraft supporting surveillance and communication applications. The supported modes of communication include:

- broadcast and point-to-point communication;
- broadcast services including Automatic Dependent Surveillance - Broadcast (ADS-B), Traffic Information Service - Broadcast (TIS-B), Flight Information Service - Broadcast (FIS-B) capabilities and GNSS Augmentation Service - Broadcast (GNS-B);
- air-air and ground-air services;
- operation without ground infrastructure.

VDL Mode 4 is designed to be an Air/Ground subsystem of the Aeronautical Telecommunication Network (ATN) (see ICAO ATN SARPs [i.3]) using the AM(R)S band and it is organized according to the Open Systems Interconnection (OSI) model (defined by ISO). It provides reliable sub network services to the ATN system. Other networks can also be supported but have not been the focus of the present document.

The present document is derived from the standards and specifications in:

- ICAO VDL4 Technical Manual [i.1] produced under the auspices of the International Civil Aviation Organization (ICAO).
- Other relevant standards as defined in clause 2.

It is envisaged that manufacturers may provide equipment supporting:

- broadcast services only;
- point-to-point services only;
- both broadcast and point-to-point services.

ETSI EN 302 842-1 [2] deals with tests of the physical layer. The present document defines the core link layer requirements for the VDL Mode 4 mobile station necessary to support all types of equipment. This includes a simple position broadcast functionality.

The present document deals with tests of the link layer sufficient to support core link layer functionality, and it also includes requirements and tests sufficient to recognize and respond to transmissions associated with point-to-point communication. The present document does not address requirements for the full ADS-B message set, or for other broadcast applications that can be supported by the VDL Mode 4 equipment. These are covered by ETSI EN 302 842-3 [6]. Detailed requirements for point-to-point communication are beyond the scope of the present document, but can be found in ETSI EN 302 842-4 [7]. ETSI EN 302 842-4 [7] also includes the interface to the Aeronautical Telecommunication Network (ATN) as defined in ICAO ATN SARPs [i.3].

As the measured values of equipment performance may be a function of the method of measurement, standard test conditions and methods of test are recommended in the present document.

The present document is organized as follows:

- Clause 2 provides references to relevant documents.
- Clause 3 provides general definitions, abbreviations and symbols used.
- Clause 4 describes the VDL Mode 4 mobile station link layer.
- Clause 5 provides performance specifications for the VDL Mode 4 mobile station and any additional mobile functions necessary to support ground station co-ordination.
- Clause 6 provides general design requirements.
- Clause 7 provides protocol tests for core link layer functions.
- Annex A provides a detailed cross-reference to the relevant requirements contained in ICAO VDL4 Technical Manual [i.1].
- Annex B provides a description of the ISO/IEC 9646 [5] test methodology.
- Annex C provides a Bibliography.

Note that the system can support a very wide range of functions. It is not practical to provide specific tests for all aspects of its functionality. The approach used is to provide detailed tests for the core link layer functionality and to provide tests of those remaining requirements which, if wrongly implemented, could cause a deterioration in the service offered by other VDL Mode 4 stations. Therefore:

- a detailed set of protocol tests are provided for the core link layer functionality necessary to support broadcast functions;
- a detailed test of position encoding and decoding is provided because of the importance of position in the management of the VDL Mode 4 link specifically and the need to support ADS-B applications in general.

Mandating and Recommendation Phrases

- a) "Shall":
 - The use of the word "Shall" indicates a mandated criterion; i.e. compliance with the particular procedure or specification is mandatory and no alternative may be applied.
- b) "Should":
 - The use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicates that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ISO/IEC 13239 (2002): "Information technology - Telecommunications and information exchange between systems - High-level data link control (HDLC) procedures".
- [2] ETSI EN 302 842-1 (V1.3.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 1: Physical layer".
- [3] ISO/IEC 7498-1 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model".
- [4] ISO/IEC 10731 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services".
- [5] ISO/IEC 9646 (all parts): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework".
- [6] ETSI EN 302 842-3 (V1.4.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 3: Additional broadcast aspects".
- [7] ETSI EN 302 842-4 (V1.3.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 4: Point-to-point functions".
- [8] EUROCAE ED-14G/RTCA DO-160G: "Environmental Conditions and Test Procedures for Airborne Equipment", May 2011.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ICAO Doc 9816 (First Edition 2004): "Manual on VHF Digital Link (VDL) Mode 4 - Part 2: Detailed Technical Specifications".
- [i.2] ICAO Annex 10 to the Convention on International Civil Aviation: "Aeronautical Telecommunications, Volume III: Communication Systems, Part I: Digital Data Communication Systems, Chapter 6", including Amendment 88 (applicable 14/11/13).
- [i.3] ICAO 9705-CD: "Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN)".

- [i.4] Eurocontrol (2003): "VDL Mode 4 Airborne Architecture Study documentation".
- [i.5] ETSI EN 301 842 (all parts): "VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment.
- [i.6] EUROCAE ED-108A: "MOPS for VDL Mode 4 Aircraft Transceiver for ADS-B".
- [i.7] EC Mandate M/318: "Mandate to CEN/CENELEC/ETSI for standardization in the field of air traffic management systems and Galileo local components".

3 Definitions and abbreviations

3.1 Definitions

3.1.1 Basic reference model definitions

The present document is based on the concepts developed in the open systems interconnect basic reference model. For the purposes of the present document, the terms and definitions given in ISO/IEC 7498-1 [3] apply for:

- layer;
- sublayer;
- entity;
- service;
- physical layer;
- data link layer.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.1.2 Service conventions definitions

SIST EN 302 842-2 V1.4.1:2015
<https://standards.iteh.ai/catalog/standards/sist/005c2c99-d2c8-4f11-aa5b-70151e111111>

For the purposes of the present document, the terms and definitions given in ISO/IEC 10731 [4] apply for:

- service provider;
- request;
- indication;
- confirm.

3.1.3 General definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 302 842-1 [2], clause 3.1.3 and the following apply:

Aeronautical Mobile Service (AMS): mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

Aeronautical Telecommunications Network (ATN): internetwork architecture that allows ground, air/ground, and aircraft data sub networks to interoperate by adopting common interface services and protocols based on the International Organization for Standardization Open Systems Interconnection Reference Model

aircraft address: 24-bit address available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance

NOTE: An aircraft may choose not to use this unique address and can use instead a non-unique address.