

SLOVENSKI STANDARD SIST EN 301 489-4 V2.1.1:2013

01-februar-2013

Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) -Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 4. del: Posebni pogoji za fiksne radijske povezave in pomožno opremo

Electromagnetic compatibility and Radio spectrum Matters (ERM) - ElectroMagnetic Compatibility (EMC) standard for radio equipment and services - Part 4: Specific conditions for fixed radio links and ancillary equipment

iTeh STANDARD PREVIEW (standards.iteh.ai)

Electromagnetic compatibility and Radio spectrum Matters (ERM) - ElectroMagnetic Compatibility (EMC) standard for radio equipment and services Part 4: Specific conditions for fixed radio links, Broadband Data Transmission System Base stations, ancillary equipment and services

Ta slovenski standard je istoveten z: EN 301 489-4 Version 2.1.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 301 489-4 V2.1.1:2013

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-4 V2.1.1:2013</u> https://standards.iteh.ai/catalog/standards/sist/a132d275-fd39-436f-a956-565401ac8322/sist-en-301-489-4-v2-1-1-2013



ETSI EN 301 489-4 V2.1.1 (2012-11)



Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 4: Specific conditions for fixed radio links and

Reference

REN/ERM-EMC-316

Keywords EMC, FWA, point-to-point, radio, regulation, RLL, WH

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret Nº 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la iTeh Sous-Préfecture de Grasse (06) N° 7803/88

(standards.iteh.ai)

SIST EN 301 489-4 V2.1.1:2013 https://standards.iteh.ai/catalog/standards/sist/a132d275-fd39-436f-a956-565401ac83 Important notice -v2-1-1-2013

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2012. All rights reserved.

DECT[™], PLUGTESTS[™], UMTS[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. 3GPP[™] and LTE[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intelle	Intellectual Property Rights		
Forew	Foreword		
Introd	uction	5	
1	Scope	6	
2	References	6	
2.1	Normative references	6	
2.2	Informative references	6	
3	Definitions and abbreviations	7	
31	Definitions	······/ 7	
3.2	Abbreviations		
4	Test conditions	8	
4.1	General	8 0	
4.1.1	Finiscion tests	ð	
4.1.2	Emission tests	9 0	
4.1.5	Arrangements for test signals		
421	Arrangements for test signals at the input of the transmitter	11	
4.2.2	Arrangements for test signals at the output of the transmitter	11	
4.2.3	Arrangements for test signals at the input of the receiver R. K.V.I.K.W.	11	
4.2.4	Arrangements for test signals at the output of the receiver	11	
4.3	Exclusion bands	11	
4.3.1	Exclusion bands for receivers	12	
4.3.2	Exclusion bands for transmitters	12	
5	<u>SISTEN 301489-4 V2.1.12013</u>	12	
5	Concrel 565401 as 2222/aist on 201 480 4 v2 1 1 2012	12	
5.1	Equipment which can provide a communications link	12	
5.2 5.2	Equipment which does not provide a communications link	12	
5.5 5.4	Ancillary equipment	12	
5.5	Fauipment classification	12	
5.5		10	
6	Performance criteria	12	
6.1	Performance criterion for Continuous pnenomena applied to Transmitters (CT) and Receivers (CR)	13	
0.2 6.3	Specific performance criteria	13	
0.3 631	Digital signal ports	13	
6311	Performance criterion for continuous nhenomena	13	
6312	Performance criterion for transient phenomena	13	
6.3.2	Analogue voice frequency signal ports	13	
6.3.2.1	Performance criterion for continuous phenomena	14	
6.3.2.2	Performance criterion for transient phenomena	14	
6.3.3	Ethernet and packet-data interfaces	14	
6.3.3.1	Performance criterion for continuous phenomena	14	
6.3.3.2	Performance criterion for transient phenomena	14	
6.3.4	Service and maintenance interfaces	14	
6.3.5	Synchronization interfaces	14	
6.3.5.1	Performance criterion for continuous phenomena	14	
6.3.5.2	Performance criteria for transient phenomena	14	
6.3.6	Remote alarm interfaces	14	
6.3.6.1	Performance criterion for continuous phenomena	15	
6.3.6.2	Performance criterion for transient phenomena	15	
0.4	Performance criteria for ancinary equipment tested on a stand alone basis	15	
7	Applicability overview tables	15	

ETSI EN 301 489-4 V2.1.1 (2012-11)

7.1	Emission	15
7.1.1	General	15
7.1.2	Special conditions	15
7.2	İmmunity	15
7.2.1	General	15
7.2.2	Special conditions	16
Anne	x A (informative): Examples of Fixed Radio Link equipment within the scope of the present document	17
A.1	Fixed Radio Systems; Point-to-point equipment; intended for operation in the frequency bands from 1,3 GHz to 86 GHz	17
A.2	Fixed Radio Systems; Point-to-Multipoint equipment; intended for operation in the frequency band below 1 GHz and in frequency bands from 1 GHz to 40 GHz	17
A.3	Fixed Radio Systems; Point-to-Multipoint equipment; intended for operation in the 40,5 GHz to 43,5 GHz frequency band	17
Anne	x B (informative): Void	18
Histor	ry	19

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-4 V2.1.1:2013</u> https://standards.iteh.ai/catalog/standards/sist/a132d275-fd39-436f-a956-565401ac8322/sist-en-301-489-4-v2-1-1-2013

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Directive 98/34/EC [i.2] as amended by Directive 98/48/EC [i.11].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

See article 5.1 of Directive 1999/5/EC [id] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The present document is part 4 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

SIST FN 301 489-4 V2 1 1 2013				
https://standards.iNational transposition dates d39-436f-a956-				
Date of adoption of this EN:	13 19 November 2012			
Date of latest announcement of this EN (doa):	28 February 2013			
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2013			
Date of withdrawal of any conflicting National Standard (dow):	31 August 2014			

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.10].

1 Scope

The present document, together with EN 301 489-1 [1], covers the assessment of Fixed Radio Links, and ancillary equipment in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port of the radio equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for Analogue and Digital Fixed Radio Links operating as fixed Point-to-Point, and Point-to-Multipoint systems as defined in annex A, including the associated ancillary equipment.

Examples of Fixed Radio Links are given in annex A.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and EN 301 489-1 [1], the provisions of the present document take precedence.

The processing and protection switch, (de)modulator, transmitter, receiver, RF filters, branching networks, feeders are covered by the present document. The multiplexing and/or de-multiplexing elements are covered if they form part of the transmitter, receiver and/or transceiver.

The environmental classification and the emission and immunity requirements used in the present document are as stated in EN 301 489-1 [1], except for any special conditions included in the present document.

2 Referencesh STANDARD PREVIEW

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies. 489-4 V2.11:2013

Referenced documents which are not found to be publicly available in the expected location might be found at <u>http://docbox.etsi.org/Reference</u>. 565401ac8322/sist-en-301-489-4-v2-1-1-2013

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

[1] ETSI EN 301 489-1 (V1.9.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.3] ITU-R Recommendation F.1191-1: "Bandwidths and unwanted emissions of digital radio-relay systems".

- [i.4] ITU-R Recommendation F.746-3: "Radio-frequency channel arrangements for radio-relay systems".
- [i.5] ETSI EN 302 217-2-2: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 2-2: Digital systems operating in frequency bands where frequency co-ordination is applied; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
- [i.6] ETSI EN 302 217-3: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 3: Equipment operating in frequency bands where both frequency coordinated or uncoordinated deployment might be applied; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
- [i.7] ETSI EN 302 326-2: "Fixed Radio Systems; Multipoint Equipment and Antennas; Part 2: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive for Digital Multipoint Radio Equipment".
- [i.8] ETSI EN 301 460-1: "Fixed Radio Systems; Point-to-multipoint equipment; Part 1: Point-tomultipoint digital radio systems below 1 GHz - Common parameters".
- [i.9] ETSI EN 301 997-1: "Transmission and Multiplexing (TM); Multipoint equipment; Radio Equipment for use in Multimedia Wireless Systems (MWS) in the frequency band 40,5 GHz to 43,5 GHz; Part 1: General requirements".
- [i.10] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.11] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations. (standards.iteh.ai)
- 3 Definitions and abbreviations⁰¹³ https://standards.iteh.ai/catalog/standards/sist/a132d275-fd39-436f-a956-

565401ac8322/sist-en-301-489-4-v2-1-1-2013

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 301 489-1 [1], clause 3 and the following apply:

Base Station (BS): alternative name for Central Station

Central Station (CS): which can be subdivided into two units:

- the exchange unit, also called Central Controller Station (CCS) (interface to the local switch); and
- the radio unit, also called Central Radio Station (CRS) (central base band/radio transceiver).
- NOTE: In some deployments the term Base Station is also used in place of Central Station. For the purposes of the present standard either terms are assumed and are completely interchangeable.

CHannel Separation (CHS): CHannel Separation (CHS) is taken as *XS*/2 for alternated frequency channel arrangements according to ITU-R Recommendation F.1191-1 [i.3] and *XS* for co-channel and interleaved frequency channel arrangements as defined by ITU-R Recommendation F.746-3 [i.4], *XS* is the radio-frequency separation between the centre frequencies of adjacent radio-frequency channels on the same polarization and in the same direction of transmission.

operating frequency range: range(s) of radio frequencies covered by the Equipment Under Test (EUT) without any change of units

Repeater Station (RS): radio repeater outstations with or without subscriber interfaces

Terminal station (TS): outstations with subscriber interfaces

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
BER	Bit Error Ratio
BS	Base Station
CCS	Central Controller Station
CHS	Channel Separation
CR	Continuous phenomena applied to Receivers
CRS	Central Radio Station
CS	Central Station
CT	Continous phenomena applied to Transmitters
DC	Direct Current
EM	ElectroMagnetic
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
RF	Radio Frequency
RS	Repeater Station
TR	Transient phenomena applied to Receivers
TS	Terminal Station
TT	Transient phenomena applied to Transmitters

4 Test conditions

For the purposes of the present document, the test conditions of EN 301 489-1 [1], clause 4, shall apply as appropriate.

For the purposes of the present document, the test conditions of EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for fixed radio links are specified in the present document.

4.1 General SIST EN 301 489-4 V2.1.1.2013

https://standards.iteh.ai/catalog/standards/sist/a132d275-fd39-436f-a956-

For emission and immunity tests the test modulation's test arrangements 2 etc.1, as specified in the present document, clauses 4.1.1 to 4.3.2, shall apply.

4.1.1 Test conditions and configurations

This clause defines the test conditions and configurations for the emission and immunity tests as follows:

• a transmitter shall, as a minimum, comprise the element between E' and A' of figure 1. Additionally the transmitter may comprise any of the other elements from the transmitter chain shown in figure 1. If these additional elements are part of the transmitter or system they shall also meet the requirements of the present document;



- NOTE 1: For the purposes of defining the reference points, the branching network (B' to C') does not include a hybrid.
- NOTE 2: Points B' and C' may coincide, dependent on the equipment configuration.

Figure 1: Elements of a transmitter

• a receiver shall, as a minimum, comprise the element between A and E of figure 2. Additionally the receiver may comprise any of the other elements from the receiver chain shown in figure 2. If these additional elements are part of the receiver or system they shall also meet the requirements of the present document;



NOTE 1: For the purposes of defining the reference points, the branching network (B to C) does not include a hybrid.

NOTE 2: Points B and C may coincide, dependent on the equipment configuration.

Figure 2: Elements of a receiver

- a transceiver shall comprise as a minimum the elements E' to A' and A to E shown in figures 1 and 2, and additionally it may comprise any combinations of the other elements. If these additional elements are part of the transceiver they shall also meet the requirements of the present document;
- the equipment shall be tested under conditions which are within the manufacturer's declared range of humidity, temperature and supply voltage;
- the test configuration shall be as close to normal intended use as possible;
- if the equipment is part of a system, or can be connected to ancillary equipment, then it shall be acceptable to test the equipment while connected to the minimum configuration of ancillary equipment necessary to exercise the ports;
- ports which in normal operation are connected to ancillary or other equipment shall be either connected to such equipment, or to a representative termination to simulate the input/output characteristics of the ancillary or other equipment. Radio Frequency (RF) input/output ports shall be correctly terminated;
- if the equipment has a large number of ports, then a sufficient number shall be selected to simulate actual operation conditions and to ensure that all the different types of termination are tested;
- ports which are not connected to cables during normal intended operation, e.g. service connectors, programming connectors, temporary connectors etc. shall not be connected to any cables for the purpose of ElectroMagnetic Compatibility (EMC) testing. Where cables have to be connected to these ports, or interconnecting cables have to be extended in length in order to exercise the EUT, precautions shall be taken to ensure that the evaluation of the EUT is not affected by the addition or extension of these cables;
- the test conditions, test configuration and mode of operation shall be recorded in the test report.

4.1.2 Emission tests

The provisions EN 301 489-1 [1], clause 8 shall apply with the following modification.

For Point-to-Multipoint systems a communications link shall be established, which shall comprise of the Central Station and a minimum of one Terminal Station. These stations are tested separately.

4.1.3 Immunity tests

The provisions of EN 301 489-1 [1], clause 9.1 shall apply with the following modifications.

The test configuration shall for transmitters be in accordance with the principle of figure 3, and for receivers it shall be in accordance with the principle of figure 4, and for transceiver shall be in accordance with the principle of figure 5.

The measuring equipment shall be located outside the test environment. Adequate measures shall be taken to avoid any effects of the unwanted signals on the measuring equipment.