



**Electronic Signatures and Infrastructures (ESI);
Testing Conformance and Interoperability of Trusted Lists;
Part 1: Specifications for testing conformance of
XML representation of Trusted Lists**

PREVIEW
https://standards.iteh.ai/catalog/standards/sist/d1d8695c-3bad-49d0-af3a-d3e04304504e/etsi-ts-119-614-1-v1.1.1-2016-06

Reference

DTS/ESI-0019614-1

Keywordsconformance, electronic signature, security,
testing**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	8
3 Abbreviations	8
4 Overview	8
5 Testing Trusted Lists	9
5.1 Testing auxiliary types	9
5.1.1 Testing multilingual string types	9
5.1.1.1 Testing lang attribute.....	9
5.1.1.2 Testing tsl:NonEmptyString type.....	9
5.1.1.3 Testing tsl:NonEmptyNormalizedString type.....	10
5.1.1.4 Testing tsl:MultiLangStringType type	10
5.1.1.5 Testing tsl:MultiLangNormStringType type.....	11
5.1.2 Testing tsl:InternationalNamesType type	11
5.1.3 Testing tsl:InternationalNamesType type	11
5.1.4 Testing types for managing URIs	11
5.1.4.1 Testing tsl:NonEmptyURIType type.....	11
5.1.4.2 Testing tsl:NonEmptyURLISType type	12
5.1.4.3 Testing tsl:NonEmptyMultiLangURIType type.....	12
5.1.4.4 Testing tsl:NonEmptyMultiLangURLISType type.....	12
5.1.5 Testing Country Codes	12
5.1.5.1 Test assertions common to Trusted Lists from EUMS, from non EUMS, and the List of Lists from European Commission.....	12
5.1.5.2 Test assertions for non EUMS Trusted Lists.....	12
5.1.5.3 Test assertions for exceptions within EUMS Trusted Lists	13
5.1.6 Testing tsl:AddressType type	13
5.1.6.1 Introduction.....	13
5.1.6.2 Testing tsl:PostalAddressListType type.....	13
5.1.6.3 Testing tsl:ElectronicAddressType type	13
5.2 Testing the elements of the XML representation of the Trusted List.....	14
5.2.1 Introduction.....	14
5.2.2 Testing TSLTag attribute.....	14
5.2.3 Testing tsl:SchemeInformation element	14
5.2.3.1 Testing tsl:TSLVersionIdentifier element.....	14
5.2.3.2 Testing tsl:TSLSequenceNumber element.....	14
5.2.3.3 Testing tsl:TSLType element.....	15
5.2.3.3.1 Test assertions for EUMS Trusted Lists.....	15
5.2.3.3.2 Test assertions for EC List of Lists.....	15
5.2.3.3.3 Test assertions for non EUMS Trusted Lists	15
5.2.3.4 Testing tsl:SchemeOperatorName element	16
5.2.3.5 Testing tsl:SchemeOperatorAddress element	16
5.2.3.6 Testing tsl:SchemeName element	16
5.2.3.7 Testing tsl:SchemeInformationURI element.....	16
5.2.3.8 Testing tsl:StatusDeterminationApproach element.....	17
5.2.3.8.1 Testing tsl:StatusDeterminationApproach for EUMS Trusted Lists	17
5.2.3.8.2 Testing tsl:StatusDeterminationApproach for non-EUMS Trusted Lists	17
5.2.3.9 Testing tsl:SchemeTypeCommunityRules element	17
5.2.3.9.1 Introduction	17
5.2.3.9.2 Test assertions specific to EUMS Trusted Lists	18
5.2.3.9.3 Test assertions specific to EC List of Trusted Lists.....	18

5.2.3.9.4	Test assertions specific to no EUMS Trusted Lists	18
5.2.3.10	Testing tsl:SchemeTerritory element	18
5.2.3.11	Testing tsl:PolicyOrLegalNotice element	18
5.2.3.12	Testing HistoricalInformationPeriod element	18
5.2.3.13	Testing tsl:PointersToOtherTSL element	19
5.2.3.14	Testing tsl:ListIssueDateTime element	19
5.2.3.15	Testing tsl:NextUpdate element	19
5.2.3.16	Testing tsl:DistributionPoints element	19
5.2.3.17	Testing tsl:SchemeExtensions element	20
5.2.3.17.1	Test assertions for EUMS Trusted Lists	20
5.2.3.17.2	Test assertions for non EUMS Trusted Lists	20
5.3	Testing tsl:TSPInformation element	20
5.3.1	Testing tsl:TSPName element	20
5.3.2	Testing tsl:TSPTradeName element	20
5.3.3	Testing tsl:TSPAddress element	21
5.3.4	Testing tsl:TSPInformationURI element	21
5.3.5	Testing tsl:TSPInformationExtensions element	21
5.3.5.1	Test assertions for EUMS Trusted Lists	21
5.4	Testing ServiceInformation element	21
5.4.1	Testing tsl:ServiceTypeIdentifier element	21
5.4.2	Testing tsl:ServiceName element	22
5.4.3	Testing tsl:ServiceDigitalIdentity element	22
5.4.3.1	Test assertions common to any tsl:ServiceDigitalIdentity element	22
5.4.3.2	Test assertions specific to tsl:ServiceDigitalIdentity child element of tsl:ServiceInformation element	23
5.4.4	Testing tsl:ServiceStatus element	25
5.4.4.1	Introduction	25
5.4.4.2	Test assertions common to any tsl:ServiceStatus element	25
5.4.4.3	Test assertions specific to tsl:ServiceStatus child element of tsl:TSPService	25
5.4.5	Testing tsl:StatusStartingTime element	25
5.4.5.1	Test assertions common to any tsl:StatusStartingTime element	25
5.4.5.2	Test assertions specific to tsl:StatusStartingTime child element of tsl:TSPService	26
5.4.6	Testing tsl:SchemeServiceDefinitionURI element	26
5.4.7	Testing tsl:ServiceSupplyPoints element	26
5.4.8	Testing tsl:TSPServiceDefinitionURI element	26
5.4.9	Testing tsl:ServiceInformationExtensions element	26
5.4.9.1	Testing tsl:ExpiredCertsRevocationInfo element	26
5.4.9.2	Testing sie:Qualifications element	27
5.4.9.3	Testing tslx:TakenOverBy element	28
5.4.9.4	Testing tsl:AdditionalServiceInformation element	29
5.5	Testing tsl:ServiceHistory element	29
5.5.1	Testing tsl:ServiceTypeIdentifier element	29
5.5.2	Testing tsl:ServiceName element	30
5.5.3	Testing tsl:ServiceDigitalIdentity element	30
5.5.4	Testing tsl:ServiceStatus element	31
5.5.5	Testing tsl:StatusStartingTime element	31
5.5.6	Testing tsl:ServiceInformationExtensions element	31
5.6	Testing ds:Signature element	32

Annex A (normative): Test assertions derived from XML Schema35

A.1	Introduction	35
A.2	Testing auxiliary types contents	35
A.2.1	Introduction	35
A.2.2	Testing tsl:NonEmptyNormalizedString instances	35
A.2.3	Testing tsl:NonEmptyString instances	36
A.2.4	Testing tsl:MultiLangStringType instances	36
A.2.5	Testing tsl:MultiLangNormStringType instances	36
A.2.6	Testing tsl:InternationalNamesType instances	36
A.2.7	Testing tsl:NonEmptyURIType instances	37
A.2.8	Testing tsl:NonEmptyURILISTType instances	37
A.2.9	Testing tsl:NonEmptyMultiLangURIType instances	38

A.2.10	Testing tsl:NonEmptyMultiLangURIListType instances	38
A.2.11	Testing tsl:AttributedNonEmptyURIType instances	38
A.2.12	Testing tsl:AddressType instances	39
A.2.12.1	Testing structure	39
A.2.12.2	Testing tsl:PostalAddressListType instances	39
A.2.12.2.1	Testing tsl:PostalAddressListType instances	39
A.2.12.2.2	Testing tsl:PostalAddressType instances	40
A.2.12.3	Testing tsl:ElectronicAddressType instances	40
A.2.13	Testing tsl:ExtensionType instances	40
A.2.14	Testing tsl:ExtensionsListType instances	40
A.3	Testing Trusted List structure	41
A.3.1	Testing tsl:TrustServiceStatusList element	41
A.3.2	Testing tsl:SchemeInformation element	41
A.3.3	Testing tsl:PolicyOrLegalNoticeType type	42
A.3.4	Testing tsl:OtherTSLPointersType type	42
A.3.5	Testing tsl:ServiceDigitalIdentityListType type	43
A.3.6	Testing tsl:DigitalIdentityListType type	43
A.3.7	Testing tsl:DigitalIdentityType type	43
A.3.8	Testing tsl:AdditionalInformationType type	44
A.3.9	Testing tsl:TrustServiceProviderList	44
A.3.10	Testing tsl:TSPTType type	44
A.3.11	Testing tsl:TSPInformationType	45
A.3.12	Testing tsl:TSPServicesListType	45
A.3.13	Testing tsl:TSPServiceType	45
A.3.14	Testing tsl:TSPServiceInformationType	46
A.3.15	Testing tsl:ServiceSupplyPointsType	46
A.3.16	Testing tsl:ServiceHistoryType	47
A.3.17	Testing tsl:ServiceHistoryInstanceType	47
A.3.18	Testing Extensions	48
A.3.18.1	Testing tsl:AdditionalServiceInformationType type	48
A.3.18.2	Testing sie:QualificationsType type	48
A.3.18.2.1	Testing sie:QualificationsType	48
A.3.18.2.2	Testing sie:QualificationElement element	48
A.3.18.2.3	Testing sie:Qualifiers element	49
A.3.18.2.4	Testing sie:CriteriaListType type	49
A.3.18.3	Testing tsIx:ExtendedKeyUsageType type	50
A.3.18.4	Testing tsIx:TakenOverByType type	50
A.3.18.5	Testing tsIx:CertSubjectDNAttribute	51
A.3.18.6	Testing tsIx:MimeType	51
A.4	Test assertions for xades:ObjectIdentifierType	51
History	53

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electronic Signatures and Infrastructures (ESI).

The present document is part 1 of a multi-part deliverable covering Testing Conformance and Interoperability of Trusted Lists, as identified below:

Part 1: "Specifications for testing conformance of XML representation of Trusted Lists".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines the set of checks to be performed for testing conformance of Trusted Lists as specified in ETSI TS 119 612 [1].

Checks specified by the present document are exclusively constrained to elements specified by ETSI TS 119 612 [1], certain elements defined in ETSI TS 101 903 [2], and certain elements specified in XMLSig [3].

Regarding XML elements, the present document explicitly differentiates between structural requirements that are defined by the different XML Schemas where the tested elements are defined, and the rest of the requirements specified by ETSI TS 119 612 [1].

The present document is intentionally not linked to any software development technology and is also intentionally agnostic on implementation strategies. This is one of the reasons why the test assertions set includes tests on the correctness of the structure of all the elements specified by the XML Schemas associated with ETSI TS 119 612 [1].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 119 612 (V2.2.1): "Electronic Signatures and Infrastructures (ESI); Trusted Lists".
- [2] ETSI TS 101 903: "Electronic Signatures and Infrastructures (ESI); XML Advanced Electronic Signatures (XAdES)".
- [3] W3C Recommendation (2008): "XML-Signature Syntax and Processing (Second Edition)".
- [4] IETF RFC 2368: "The mailto URL scheme".
- [5] IETF RFC 3061: "A URN Namespace of Object Identifiers".
- [6] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
- [7] IETF RFC 5646: "Tags for Identifying Languages".
- [8] ISO/IEC 10646:2014: "Information technology - Universal Coded Character Set (UCS)".
- [9] Recommendation ITU-T X.509: "Information technology - Open Systems Interconnection - The Directory: Public-key and attribute certificate frameworks".
- [10] FIPS Publication 180-4 (2012): "Secure Hash Standard (SHS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] OASIS: "Test Assertions Model Version 1.0".

3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

DER	Distinguished Encoding Rules
EC	European Commission
EUMS	European Union Member State
HTTP	Hyper Text Transfer Protocol
OCSP	Online Certificate Status Protocol
OID	Object IDentifier
TSP	Trusted Service Providers
URI	Uniform Resource Identifier
URN	Uniform Resource Name
XML	eXtensible Markup Language
XMLDSIG	eXtensible Markup Language Digital SIGNature

4 Overview

The present clause describes the main aspects of the technical approach used for specifying the set of tests to be performed for testing conformance of Trusted Lists against ETSI TS 119 612 [1].

Several types of tests are identified, namely:

- 1) Tests on the Trusted List structure that are directly derived from the XML Schemas associated to ETSI TS 119 612 [1]. These tests are specified in annex A.
- 2) Tests on the Trusted List structure that are not defined by the XML schemas associated to ETSI TS 119 612 [1] and that in consequence may not be tested by a XML Schema validator tool.
- 3) Tests on values of specific elements and/or attributes that cannot be tested by a XML Schema validator tool.
- 4) Tests on interrelationship between different elements present in the Trusted List (URIs that point to certain elements, for instance).
- 5) Tests on computations reflected in the contents of the Trusted Lists (digests of certain elements of some certificates, for instance).

Tests are defined as test assertions following the work produced by OASIS in "Test Assertions Model Version 1.0" [i.1].

For each Trusted List element, the present document defines a number of test assertions corresponding to the requirements specified in ETSI TS 119 612 [1].

Each test assertion includes:

- 1) Unique identifier for further referencing. The identifiers of the assertions start with a code identifying the set of requirements the assertion corresponds to, namely: "TL_EUMS".

- 2) Reference to the **Normative source** for the test.
- 3) The **Target** of the assertion. In the normative part, this field identifies ETSI TS 119 612 [1].
- 4) **Prerequisite (optional)** is, according to [i.1], "a logical expression (similar to a Predicate) which further qualifies the Target for undergoing the core test (expressed by the Predicate) that addresses the Normative Statement". It is used for building test assertions corresponding to requirements that are imposed under certain conditions.
- 5) **Predicate** fully and unambiguously defining the assertion to be tested.
- 6) **Prescription level**. Three levels are defined: mandatory, preferred and permitted, whose semantics are as specified in [i.1].
- 7) **Tag**: information on the element tested by the assertion. This indicates that Trusted Lists as specified in ETSI TS 119 612 [1] is the origin of the assertion.

Unless indicated otherwise by the name of the clause where the test assertions are defined, any test assertion applies for both European Union Member States (EUMS hereinafter) Trusted Lists and non EUMS Trusted Lists.

The present document also defines some specific test assertions for the European Commission (EC hereinafter) List of Lists.

Table 1 shows the prefixes used in the present document associated to the URIs of the corresponding namespaces.

Table 1: Prefixes used

XML Namespace URI	Prefix
http://uri.etsi.org/02231/v2#	tsl
http://uri.etsi.org/02231/v2/additionaltypes#	tslx
http://uri.etsi.org/TrstSvc/SvcInfoExt/eSigDir-1999-93-EC-TrustedList/#	sie
http://www.w3.org/2000/09/xmldsig#	ds
http://uri.etsi.org/01903/v1.3.2#	xades

5 Testing Trusted Lists

5.1 Testing auxiliary types

5.1.1 Testing multilingual string types

5.1.1.1 Testing lang attribute

TA id: TL_EUMS/MLANGSTR/1

Normative source: ETSI TS 119 612 [1], clause 5.1.4. XML Schema defined in ts_119612v020201_201601xsd.xsd.

Target: European Union Member State Trusted List.

Predicate: The value of the lang attribute is one of the values for European languages specified in IETF RFC 5646 [7] and in clause E.1 of ETSI TS 119 612 [1].

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.1.2 Testing tsl:NonEmptyString type

TA id: TL_EUMS/NEMPTYSTR/1

Normative source: ETSI TS 119 612 [1], clause 5.1.4. XML Schema defined in ts_119612v020201_201601xsd.xsd.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type is not empty.

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.1.3 Testing `tsl:NonEmptyNormalizedString` type

For testing contents of instances of `tsl:NonEmptyStringType` the test assertions defined in clause 5.1.1.2, and the following test assertions shall apply:

TA id: TL_EUMS/NEMPTYNORMSTR/1

Normative source: ETSI TS 119 612 [1], clause 5.1.4. XML Schema defined in `ts_119612v020201_201601xsd.xsd`.

Target: European Union Member State Trusted List.

Prerequisite: Use of combining characters is needed but it is possible not to use the combining characters listed in ISO/IEC 10646 [8], clause B.1.

Predicate: The content of one instance of this type does not include any of the following whitespace characters: carriage return (`#xD`), line feed (`#A`), and tab (`#9`).

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.1.4 Testing `tsl:MultiLangStringType` type

For testing contents of instances of `tsl:MultiLangStringType` the test assertions defined in clauses 5.1.1.1 and 5.1.1.2, and the following test assertions shall apply:

TA id: TL_EUMS/MLANGSTR/1

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type is a string of characters from the Universal Character Set (UCS) as defined by ISO/IEC 10646 [8].

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/2

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type is UTF-8 encoded.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/3

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type does not contain any signature to identify the UCS.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/4

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type does not include private-use characters from the private use zone in the Basic Multilingual Plane and from the private-use Planes 0F and 10 in Group 00.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/5

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type does not include tag characters.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/6

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type is plain text without any mark-up element or tag from languages as SGML, HTML, XML, XHTML, RGF, TeX and others.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/7

Normative source: ETSI TS 119 612 [1], clause E.2.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type follows the semantic rules defined by the Unicode Standard for the corresponding characters.

Prescription level: preferred

Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/8
Normative source: ETSI TS 119 612 [1], clause E.2.
Target: European Union Member State Trusted List.
Prerequisite: It is possible to express the content of one instance of this type without using combining characters.
Predicate: The content does not use combining characters.
Prescription level: mandatory
Tag: EUMS Trusted List.

TA id: TL_EUMS/MLANGSTR/9
Normative source: ETSI TS 119 612 [1], clause E.2.
Target: European Union Member State Trusted List.
Prerequisite: Use of combining characters is needed but it is possible not to use the combining characters listed in ISO/IEC 10646 [8], clause B.1.
Predicate: The content of one instance of this type does not use the combining characters in ISO/IEC 10646 [8], clause B.1.
Prescription level: mandatory
Tag: EUMS Trusted List.

5.1.1.5 Testing `tsl:MultiLangNormStringType` type

For testing contents of instances of `tsl:MultiLangNormStringType`, the test assertions defined in clauses 5.1.1.3 and 5.1.1.4 shall apply.

5.1.2 Testing `tsl:InternationalNamesType` type

For testing each `tsl:Name` child element of instances of `tsl:InternationalNamesType` the test assertions defined in clause 5.1.1.5, and the following test assertions shall apply:

TA id: TL_EUMS/INTNAMES/1
Normative source: ETSI TS 119 612 [1], clause 5.1.4.
Target: European Union Member State Trusted List.
Predicate: Instances of this type contain one `tsl:Name` child element whose attribute `lang` has the value "en".
Prescription level: mandatory
Tag: EUMS Trusted List.

5.1.3 Testing `tsl:InternationalNamesType` type

For testing each `tsl:Name` child element test assertions defined in clause 5.1.1.5 shall apply.

5.1.4 Testing types for managing URIs

5.1.4.1 Testing `tsl:NonEmptyURIType` type

TA id: TL_EUMS/NEMPTUYURI/1
Normative source: XML Schema defined in `ts_119612v020201_201601xsd.xsd`.
Target: European Union Member State Trusted List.
Predicate: The content of one instance of this type is not empty.
Prescription level: mandatory
Tag: EUMS Trusted List.

TA id: TL_EUMS/NEMPTUYURI/2
Normative source: XML Schema defined in `ts_119612v020201_201601xsd.xsd`.
Target: European Union Member State Trusted List.
Predicate: The value of the content of one instance of this type is a valid URI Reference as specified in IETF RFC 3986 [6].
Prescription level: mandatory
Tag: EUMS Trusted List.

5.1.4.2 Testing `tsl:NonEmptyURIListType` type

For testing each `tsl:URI` child element of an instance of `tsl:NonEmptyURIListType` the test assertions of clause 5.1.4.1 shall apply.

TA id: TL_EUMS/NEMPTYURI/1

Normative source: XML Schema defined in `ts_119612v020201_201601xsd.xsd`.

Target: European Union Member State Trusted List.

Predicate: The content of one instance of this type is not empty.

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.4.3 Testing `tsl:NonEmptyMultiLangURIType` type

For testing contents of instances of `tsl:NonEmptyMultiLangURIType`, the test assertions defined in clause 5.1.4.1, and the following test assertion shall apply:

TA id: TL_EUMS/NEMPTYMLANGURI/1

Normative source: ETSI TS 119 612 [1], clause 5.1.4. XML Schema defined in `ts_119612v020201_201601xsd.xsd`.

Target: European Union Member State Trusted List.

Predicate: The value of the `lang` attribute is one of the values for European languages specified in IETF RFC 5646 [7] and in clause E.1 of ETSI TS 119 612 [1].

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.4.4 Testing `tsl:NonEmptyMultiLangURIListType` type

For each `tsl:URI` child element of one instance of this type the test assertions specified in clause 5.1.4.3 shall apply.

5.1.5 Testing Country Codes

5.1.5.1 Test assertions common to Trusted Lists from EUMS, from non EUMS, and the List of Lists from European Commission

TA id: TL_COMM/CC/1

Normative source: ETSI TS 119 612 [1], clause 5.1.5.

Target: European Union Member State Trusted List.

Predicate: The characters of a country code are capital letters.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_COMM/CC/2

Normative source: ETSI TS 119 612 [1], clause 5.1.5.

Target: European Union Member State Trusted List.

Prerequisite: The value of the country code corresponds to a country

Predicate: Valid country code values are as specified in ISO 3166-1 with exceptions as specified in test assertions TL_EUMS_CC/1 and TL_EUMS_CC_2.

Prescription level: mandatory

Tag: EUMS Trusted List.

5.1.5.2 Test assertions for non EUMS Trusted Lists

TA id: TL_NO_EUMS/CC/1

Normative source: ETSI TS 119 612 [1], clause 5.1.5.

Target: non European Union Member State Trusted List.

Prerequisite: The country code value is neither one of the codes corresponding to European Union Member States, nor "EU".

Predicate: The following are valid exceptional Country code values: commonly used extensions with regional scope, and another identifier recognised for identifying multi-state grouping.

Prescription level: mandatory

Tag: Country code value exception.

5.1.5.3 Test assertions for exceptions within EUMS Trusted Lists

TA id: TL_EUMS/CC/1

Normative source: ETSI TS 119 612 [1], clause 5.1.5.

Target: European Union Member State Trusted List.

Prerequisite: The country identified by the country code is United Kingdom

Predicate: The country code value is "UK".

Prescription level: mandatory

Tag: Country Code value exception.

TA id: TL_EUMS/CC/2

Normative source: ETSI TS 119 612 [1], clause 5.1.5.

Target: European Union Member State Trusted List.

Prerequisite: The country identified by the country code is Greece

Predicate: The country code value is "EL".

Prescription level: mandatory

Tag: Country Code value exception.

5.1.6 Testing tsl:AddressType type

5.1.6.1 Introduction

One instance of `tsl:AddressType` type is a sequence of two elements, namely `tsl:PostalAddresses` (instance of `tsl:PostalAddressListType`), and `tsl:ElectronicAddress` (instance of `tsl:ElectronicAddressType` type).

For testing one instance of `AddressType` type the test assertions defined in clauses 5.1.6.2 and 5.1.6.3 shall apply.

5.1.6.2 Testing tsl:PostalAddressListType type

One instance of `tsl:PostalAddressListType` type contains one or more `tsl:PostalAddress` children elements.

For testing each of the present `tsl:StreetAddress`, `tsl:Locality`, `tsl:StateOrProvince`, `tsl:PostalCode`, and `tsl:CountryName` children elements, the test assertions defined in clause 5.1.1.2 shall apply.

For testing the `lang` attribute the test assertions defined in clause 5.1.1.1 shall apply.

5.1.6.3 Testing tsl:ElectronicAddressType type

One instance of `tsl:ElectronicAddressType` type contains one or more `tsl:URI` children elements.

For testing each `tsl:URI` child element of instances of `tsl:ElectronicAddressType` the test assertions defined in clause 5.1.4.3 shall apply.

Furthermore the following test assertions shall apply for testing the rest of the contents of instances of `tsl:ElectronicAddressType`:

TA id: TL_EUMS/TSL/EADDR/1

Normative source: ETSI TS 119 612 [1], clause 5.3.5.2.

Target: European Union Member State Trusted List.

Predicate: One instance of `tsl:ElectronicAddressType` contains one `tsl:URI` child element containing a URI Reference identifying an e-mail address compliant with the URI scheme defined in IETF RFC 2368 [4] AND whose `lang` attribute has the value that identifies English as language.

Prescription level: mandatory

Tag: EUMS Trusted List.

TA id: TL_EUMS/TSL/EADDR/2

Normative source: ETSI TS 119 612 [1], clause 5.3.5.2.

Target: European Union Member State Trusted List.

Predicate: One instance of `tsl:ElectronicAddressType` contains one or more `tsl:URI` child element containing a URI Reference identifying an e-mail address compliant with the URI scheme defined in IETF RFC 2368 [4] AND whose `lang` attribute has a value identifying a language different to English.

Prescription level: permitted

Tag: EUMS Trusted List.