



SLOVENSKI STANDARD
oSIST ISO 13474:2012
01-januar-2012

Akustika - Osnove za izračun porazdelitve ravni zvočne izpostavljenosti zaradi impulznih zvočnih dogodkov za potrebe vrednotenja hrupa v okolju

Acoustics - Framework for calculating a distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Acoustique - Cadre pour le calcul d'une distribution des niveaux d'exposition sonore pour les sons impulsionnels pour les besoins de l'évaluation du bruit environnemental

<https://standards.iteh.ai/catalog/standards/sist/d1f999e9-c556-418c-b75a-8d340013aa3/sist-iso-13474-2012>

Ta slovenski standard je istoveten z: ISO 13474:2009

ICS:

17.140.01	Akustična merjenja in blaženje hrupa na splošno	Acoustic measurements and noise abatement in general
-----------	---	--

oSIST ISO 13474:2012

en

INTERNATIONAL STANDARD

ISO
13474

First edition
2009-06-15

Acoustics — Framework for calculating a distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment

*Acoustique — Cadre pour le calcul d'une distribution des niveaux
d'exposition sonore pour les sons impulsionnels pour les besoins de
l'évaluation du bruit environnemental*

iTeh STANDARDS REVIEW
(standards.iteh.ai)

SIST ISO 13474:2012

<https://standards.iteh.ai/catalog/standards/sist/d1f999e9-c556-418c-b75a-8d340013aaa3/sist-iso-13474-2012>



Reference number
ISO 13474:2009(E)

© ISO 2009

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

SIST ISO 13474:2012

<https://standards.iteh.ai/catalog/standards/sist/d1f999e9-c556-418c-b75a-8d340013aaa3/sist-iso-13474-2012>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Basic equations	6
4.1 General	6
4.2 Probability of occurrence	6
4.3 Band sound exposure level.....	7
4.4 Frequency-weighted sound exposure level.....	8
4.5 Long-term average single-event sound exposure level	8
4.6 Equivalent level from multiple events	10
5 Calculation of a statistical distribution	10
6 Calculation of attenuation	14
6.1 General	14
6.2 Geometric divergence.....	14
6.3 Atmospheric absorption	14
6.4 Insertion loss by screening objects	15
6.5 Terrain shielding.....	15
6.6 Contributions to excess attenuation	16
6.6.1 General	16
6.6.2 Refraction	16
6.6.3 Ground reflection and absorption	17
7 Classification	19
7.1 General	19
7.2 Classification of atmospheric absorption.....	19
7.3 Classification of excess attenuation	19
7.3.1 General	19
7.3.2 Lookup table requirements	20
7.3.3 Range-dependent sound speed profiles.....	21
7.3.4 Directed sound speed profiles	21
8 Probability of occurrence of sound speed profiles	22
8.1 General	22
8.2 Using direct measurements of wind and temperature profiles	22
8.3 Similarity relationships for the atmospheric surface layer.....	23
8.4 Using measurements of turbulent fluxes.....	24
8.5 Using routinely gathered weather station data	25
8.6 Using directly measured or calculated sound speed profiles as input	26
9 The source	26
9.1 General	26
9.2 Demolition and muzzle blasts	26
9.2.1 General	26
9.2.2 Source descriptors	27
9.2.3 Determination by measurement.....	27
9.2.4 Determination by estimation	28
9.3 Projectile sound.....	28
9.3.1 General	28

ISO 13474:2009(E)

9.3.2	Flat trajectories	28
9.3.3	High-elevation trajectories and rocket trajectories	28
10	Uncertainties	28
Annex A (informative)	Example of the estimation of the statistical distribution of single-event sound exposure levels	30
Annex B (informative)	Uncertainty	37
Bibliography	40

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 13474:2012

<https://standards.iteh.ai/catalog/standards/sist/d1f999e9-c556-418c-b75a-8d340013aaa3/sist-iso-13474-2012>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13474 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

It cancels and replaces ISO/TS 13474:2003, which has been technically revised.

INTERNATIONAL STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 13474:2012

<https://standards.iteh.ai/catalog/standards/sist/d1f999e9-c556-418c-b75a-8d340013aaa3/sist-iso-13474-2012>

Introduction

The aim of this International Standard is to provide a framework for the evaluation of descriptor quantities for use in environmental noise assessment. Part of this framework includes an engineering method for calculating a statistical distribution of event sound exposure levels at locations which are some distance from high-energy impulsive sound sources. It is specifically intended for environmental noise assessment and not for the assessment of the risk of damage to buildings or the risk of injury to animals or people.

In ISO 9613-2, the immission level from sources such as traffic and industry is calculated for a so-called “downwind” condition. The long-term average level is estimated using a correction factor, C_{met} . This concept holds for distances where sound from such sources is assessed as environmental noise. ISO 9613-2 excludes impulses in its scope and holds only for A-weighting, for near-ground sources and receivers and for distances up to about 1 000 m. For high-energy impulsive sound sources, the impulsive sound event duration is short, and low frequencies are more prominent than for traffic and industrial sound sources. Lower-frequency sounds are generally less attenuated over a given distance in the atmosphere than higher frequencies and, as a consequence, the level-influencing effects of propagation over much larger distances need to be taken into account.

A general outline is given of a method that takes into account ground reflection, shielding by topography and the meteorological effects of refraction and turbulence. Starting from the source strength, this method calculates a distribution of immission levels for a set of replica atmospheres, each replica being a specific combination of atmospheric-absorption class and excess-attenuation class. To carry out practical calculations using the procedure, it is useful to exploit the statistical contribution of the meteorological and ground surface conditions. In particular, histograms of the frequencies of occurrence of the wind velocity, wind direction, temperature, humidity and atmospheric stability can be used to describe the classes. From the distribution of the immission levels, a number of assessment metrics can be obtained. For instance, the long-term averaged immission level can be calculated as a weighted average. The weighting factors are determined by the probability of occurrence of each replica atmosphere during the relevant time period for the location of interest.

8d340013aaa3/sist-iso-13474-2012

Acoustics — Framework for calculating a distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment

1 Scope

This International Standard specifies the framework of an engineering method for calculating a statistical distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment. This International Standard is applicable to impulse sounds propagating over large distances (e.g. 0,5 km to 30 km) from sources such as mine blasting, artillery fire and bomb explosions, using conventional explosives of moderate charge mass (e.g. 0,05 kg to 1 000 kg of TNT equivalent). The effects of meteorological conditions and terrain upon sound propagation are considered.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1996-1, *Acoustics — Description, measurement and assessment of environmental noise — Part 1: Basic quantities and assessment procedures*

ISO 3534-1, *Statistics — Vocabulary and symbols — Part 1: General statistical terms and terms used in probability*

ISO 9613-1, *Acoustics — Attenuation of sound during propagation outdoors — Part 1: Calculation of the absorption of sound by the atmosphere*

ISO 9613-2, *Acoustics — Attenuation of sound during propagation outdoors — Part 2: General method of calculation*

ISO 17201-1, *Acoustics — Noise from shooting ranges — Part 1: Determination of muzzle blast by measurement*

ISO 17201-2, *Acoustics — Noise from shooting ranges — Part 2: Estimation of muzzle blast and projectile sound by calculation*

ISO 17201-4, *Acoustics — Noise from shooting ranges — Part 4: Prediction of projectile sound*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

VDI MSR 8/559, *Standard Method to Measure the Sound Exposure Emissions and Immissions from Large Weapons (Standardmethode zur Messung der Geräuschemissionen und -immissionen von schweren Waffen)*, Edmund Buchta (ed.), in *Meß-, Steuerungs- und Regelungstechnik*, No. 8/559, Fortschritt-Berichte, VDI Verlag, Düsseldorf, 1996 (in English and German)

ISO 13474:2009(E)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 atmospheric absorption
attenuation of sound by air, resulting from viscous molecular processes, molecular rotation and molecular vibration

3.2 atmospheric-absorption class
range of meteorological parameters yielding approximately the same attenuation of sound by air, all within a specified uncertainty

NOTE See also atmospheric absorption.

3.3 atmospheric stability
tendency of the atmosphere to reduce or enhance vertical motion of the air

NOTE Enhanced (or reduced) vertical motion of the air usually implies enhanced (or reduced) atmospheric turbulence.

3.4 atmospheric-stability class
subset formed from partitioning the set of atmospheres according to stability

NOTE See also atmospheric stability.

3.5 direct path
position displacement vector, in metres, originating at the source and describing a straight trajectory terminating at the receiver

NOTE The direct path may intercept objects such as buildings or terrain.

3.6 directed sound speed
algebraic sum of the adiabatic sound speed and the horizontal component of the wind velocity along the direct path

NOTE Directed sound speed is expressed in metres per second.

3.7 directed sound speed profile
sound speed along the direct path, expressed as a function of height

NOTE See directed sound speed.

3.8 event
single short burst, or rapid sequence of bursts, associated with a sound source

NOTE A single activity, such as firing a gun, could produce multiple sound events. In the case of firing an explosive projectile from a high-velocity gun, sound events are associated with each of the following sound sources: the muzzle blast, the ballistic shock and the projectile impact.

3.9 event duration

T

time interval starting just before immission, at time t_1 , and ending just after immission, at time t_2 , to encompass all significant sound of a single short blast or rapid sequence of blasts

NOTE The time interval $t_2 - t_1$ is expressed in seconds.

3.10 exceedance level

sound level of a stated type, in decibels, exceeded by no more and no less than a stated percentage of samples

NOTE The sampling set shall be identified, e.g. percentage of times during a stated time interval or percentage of firing events from an exercise.

3.11 excess attenuation

that part of sound attenuation not included when accounting for geometric divergence (from a small sound source in non-refracting and non-moving air), atmospheric absorption of sound waves along the direct path from source to receiver and attenuation of screens and/or barriers

NOTE Excess attenuation is expressed in decibels.

3.12 excess-attenuation class

range of combined directed sound speed profiles and ground types yielding approximately the same attenuations, all within a specified uncertainty

3.13 ground condition

sound reflection and absorption properties of outdoor surface(s) along the sound path(s) between source and receiver

3.14 impulsive sound event

occurrence of a single short blast or series of blasts of sound in which the pressure-time history, close to the source, includes a rapid rise to the peak sound pressure followed by decay of the pressure

3.15 sound pressure

p

difference between instantaneous total pressure and static pressure

[ISO 80000-8:2007, 8-9.2]

NOTE 1 Sound pressure is expressed in pascals.

NOTE 2 The symbol p is often used without modification to represent a root-mean-square sound pressure. However, root-mean-square values should preferably be indicated by the subscript "eff".

[ISO/TR 25417:2007, 2.1]

3.16 open-air explosion

blast, taking place out-of-doors, in which no part of the exploding material or gaseous products is limited by a container or any other obstructing surface

ISO 13474:2009(E)**3.17****peak sound pressure**

p_{peak}
greatest absolute sound pressure during a certain time interval

NOTE 1 Peak sound pressure is expressed in pascals.

NOTE 2 A peak sound pressure may arise from a positive or negative sound pressure.

[ISO/TR 25417:2007, 2.4]

NOTE 3 This definition is technically in accordance with ISO 10843.

3.18**peak sound pressure level**

$L_{p, \text{peak}}$
ten times the logarithm to the base 10 of the ratio of the square of the peak sound pressure, p_{peak} , to the square of a reference value, p_0 , expressed in decibels

$$L_{p, \text{peak}} = 10 \lg \frac{p_{\text{peak}}^2}{p_0^2} \text{ dB}$$

where the reference value, p_0 , is 20 μPa

NOTE Because of practical limitations of the measuring instruments, p_{peak}^2 is always understood to denote the square of a frequency-weighted or frequency-band-limited peak sound pressure. If a specific frequency weighting as specified in IEC 61672-1 is applied, this should be indicated by appropriate subscripts; e.g. $L_{p, C \text{ peak}}$ denotes the C-weighted peak sound pressure level.

[ISO/TR 25417:2007, 2.5]

3.19**receiver height**

h_r
distance, in metres, of the sound receiver above the local ground surface

NOTE This definition is technically in accordance with ISO 9613-2.

3.20**replica atmosphere**

conditions representing the atmosphere corresponding to a stated excess-attenuation class and a stated atmospheric-absorption class

3.21**roughness height**

distance above local ground level to the elevation where the time-average horizontal wind velocity becomes non-zero

NOTE 1 The roughness height is expressed in metres.

NOTE 2 The time interval over which the wind velocity is averaged is 300 s.

3.22**sound exposure** E_T

integral of the square of the sound pressure, p , over a stated time interval or event duration T (starting at t_1 and ending at t_2) (see 3.9)

$$E_T = \int_{t_1}^{t_2} p^2(t) dt$$

NOTE 1 Sound exposure is expressed in pascals squared seconds, Pa²·s.

NOTE 2 Because of practical limitations of the measuring instruments, p^2 is always understood to denote the square of a frequency-weighted and frequency-band-limited sound pressure. If a specific frequency weighting as specified in IEC 61672-1 is applied, this should be indicated by appropriate subscripts; e.g. $E_{A,1h}$ denotes the A-weighted sound exposure over 1 h.

NOTE 3 When applied to a single event of impulsive or intermittent sound, the quantity is called “single-event sound exposure” and the symbol E is used without a subscript.

NOTE 4 This definition is technically in accordance with ISO 80000-8:2007, 8-18.

[ISO/TR 25417:2007, 2.6]

3.23**sound exposure level** $L_{E,T}$

ten times the logarithm to the base 10 of the ratio of the sound exposure, E_T , to a reference value, E_0 , expressed in decibels

$$L_{E,T} = 10 \lg \frac{E_T}{E_0} \text{ dB}$$

where the reference value, E_0 , is 4×10^{-10} Pa²·s

NOTE 1 If a specific frequency weighting as specified in IEC 61672-1 is applied, this should be indicated by appropriate subscripts; e.g. $L_{E,A,1h}$ denotes the A-weighted sound exposure level over 1 h.

NOTE 2 When applied to a single event, the quantity is called “single-event sound exposure level” and the symbol L_E is used without further subscript.

NOTE 3 This definition is technically in accordance with ISO 80000-8:2007, 8-24.

[ISO/TR 25417:2007, 2.7]

3.24**source height** h_s

distance of the sound source above the local ground surface

NOTE 1 The source height is expressed in metres.

NOTE 2 This definition is technically in accordance with ISO 9613-2.

3.25**source forward direction**

horizontal and vertical rotation angles assigned as references in the source-directivity coordinate system