INTERNATIONAL STANDARD



First edition 2007-02-01

Cork stoppers — Determination of releasable 2, 4, 6-trichloroanisol (TCA)

Bouchons en liège — Dosage du 2, 4, 6-trichloroanisol (TCA) relargable

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 20752:2007</u> https://standards.iteh.ai/catalog/standards/sist/80c788f5-05c4-405a-8d29-20e82c7698d3/iso-20752-2007



Reference number ISO 20752:2007(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 20752:2007</u> https://standards.iteh.ai/catalog/standards/sist/80c788f5-05c4-405a-8d29-20e82c7698d3/iso-20752-2007

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Page

Forev	word	iv
Intro	duction	v
1	Scope	. 1
2	Normative references	. 1
3	Terms and definitions	. 1
4	Symbols and abbreviated terms	1
5	Principle	. 2
6	Reagents	. 2
7	Apparatus	. 2
8	Sampling	3
9	Procedure	3
10	Expression of results	4
11	Test report II en STANDARD PREVIEW	5
Biblic	ography	. 6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 20752 was prepared by Technical Committee ISO/TC 87, Cork.

iTeh STANDARD PREVIEW (standards.iteh.ai)

Introduction

This method intends to simulate migration phenomena that may occur when cork stoppers are used to close wine bottles.

It consists of determining the releasable 2,4,6-trichloroanisol (TCA) based on an equilibrium between the solid (cork) and the liquid (hydro-alcoholic simulator) matrices, after submitting a sample of cork stoppers to a period of maceration in a hydro-alcoholic solution.

iTeh STANDARD PREVIEW (standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Cork stoppers — Determination of releasable 2, 4, 6-trichloroanisol (TCA)

1 Scope

This International Standard specifies a test method to determine releasable 2,4,6-trichloroanisol (TCA) from cork stoppers.

This International Standard is applicable to all types of cork stoppers.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 633¹⁾, Cork — Vocabulary

3 Terms and definitions

<u>ISO 20752:2007</u>

(standards.iteh.ai)

https://standards.iteh.ai/catalog/standards/sist/80c788f5-05c4-405a-8d29-

For the purposes of this document, the terms and definitions given in ISO 633, and the following, apply.

3.1

simulator

solution that intends to simulate the wine

3.2

internal standard

compound of known concentration added to a sample to facilitate the qualitative identification and/or quantitative determination of the sample components

4 Symbols and abbreviated terms

GC/ECD Gas chromatography/electron-capture detector

GC/MS Gas chromatography/mass spectrometry

SPME Solid phase microextraction

TCA 2,4,6-Trichloroanisol

¹⁾ Under revision.

Principle 5

Determination of releasable 2,4,6-trichloroanisol (TCA) from cork stoppers, previously subjected to maceration in a wine simulator, using solid-phase microextraction followed by the detection and quantification of this compound by GC/MS or GC/ECD.

Reagents 6

Use only reagents of recognized analytical grade and distilled water.

- Hydro-alcoholic solution, 12 % (volume fraction). 6.1
- 6.2 Absolute ethanol.
- Sodium chloride (NaCl). 6.4
- **2,4,6-Trichloroanisol (TCA)** d_5 , purity ≥ 98 % (for GC/MS). 6.5
- **2,4,6-Trichloroanisol (TCA)**, purity \ge 99 %. 6.6
- Selected internal standard, purity \ge 99 % (for GC/ECD), of 2.3.6-T.C.A, for example. 6.7

Apparatus 7

iTeh STANDARD PREVIEW

Standard laboratory apparatus and the following.

Balance, with a resolution of at least 0,1 mg. ISO 20752:2007 7.1 log/standards/sist/80c788f5-05c4-405a-8d29-

Glass maceration flasks, with a stopper of glass or metal or any other material not absorbing TCA, 7.2 and with a capacity appropriate to the sample size.

Glass flasks (vial), of 10 ml minimum capacity (solution shall occupy at least 50 % of the vial capacity), 7.3 with a silicone/PTFE septum and an appropriate stopper.

SPME fibre, 100 µm polydimethlysiloxane PDMS, with either a manual support or a support suitable for 7.4 automatic operation.

- 7.5 Heating source for the vial, set at a temperature of 35 °C.
- 7.6 Automatic stirring system, for the SPME.
- 7.7 Appropriated gas, of chromatographic purity.
- 7.8 Gas chromatograph, with a mass detector (MS) or an electron-capture detector (ECD).
- Capillary column of light polarity silica glass. 7.9

EXAMPLE

Operating conditions: length 30 m, inside diameter 0,25 mm, film thickness 0,25 µm, stationary phase: diphenyl copolymer (5%) and dimethylsiloxane (95%).

8 Sampling

The size of the sample to be tested will be agreed upon by the customer and supplier.

9 Procedure

9.1 Calibration

Add known concentrations to the wine simulator to obtain the set of calibration solutions for TCA. Standard solutions from 0,5 ng/l to 50 ng/l can be used.

Evaluate regularly the calibration curve obtained, re-evaluate it whenever any large change is recorded by the GC/MS or GC/ECD.

9.2 Sample preparation

Subject straight cork stoppers, "*ras-de-bague*", to maceration for $24 h \pm 2 h$ at room temperature, using enough simulator to keep the stoppers totally immersed.

For bar-top stoppers, cut off the flange before macerating.

EXAMPLE

50 stoppers of 45 mm × 24 mm in a 2 flask NDARD PREVIEW

For cork stoppers for sparkling wines, immerse only the discs of hatural cork and 1 cm of the agglomerate without cutting the stoppers.

 ISO 20752:2007

 9.3 SPME
 https://standards.iteh.ai/catalog/standards/sist/80c788f5-05c4-405a-8d29-20e82c7698d3/iso-20752-2007

9.3.1 Test portion

Take a volume of the solution to be analysed not greater than 50 % of the vial capacity (7.3); for example; 10 ml of the solution to be analysed for a vial of 20 ml, in such a way that the fibre does not touch the liquid. Saturate the test portion with NaCl (approximately 0,30 g/ml) (6.3).

Add the Internal standard solution, 12 % (by volume) ethanol/water (6.1), to the test portion in the vial in such a way that the ethanol content and the total volume of the liquid do not change significantly.

EXAMPLE

Add 100 µl of internal standard solution for a total liquid volume of 10 ml.

The concentration of the internal standard solution shall be in the calibration curve range and shall be as close as possible to the specification.

9.3.2 Adsorption

Stir at a temperature of 35 °C \pm 2 °C for a minimum of 15 min in the vial open space.