
**Diesel fuel — Assessment of lubricity
using the high-frequency reciprocating
rig (HFRR) —**

**Part 2:
Limit**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Carburant diesel — Évaluation du pouvoir lubrifiant au banc alternatif
à haute fréquence (HFRR) —*

Partie 2: Limite

ISO 12156-2:2007

<https://standards.iteh.ai/catalog/standards/sist/0305a2fd-5087-4ead-b6d6-ff234de891b2/iso-12156-2-2007>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12156-2:2007

<https://standards.iteh.ai/catalog/standards/sist/0305a2fd-5087-4ead-b6d6-f234de891b2/iso-12156-2-2007>

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12156-2 was prepared by a joint working group of Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles* and ISO/TC 28, *Petroleum products and lubricants*.

This second edition cancels and replaces the first edition (ISO 12156-2:1998), which has been technically revised.

ISO 12156 consists of the following parts, under the general title *Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR)*:

- *Part 1: Test method*
- *Part 2: Limit*

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO 12156-2:2007

<https://standards.iteh.ai/catalog/standards/sist/0305a2fd-5087-4ead-b6d6-ff234de891b2/iso-12156-2-2007>

Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR) —

Part 2: Limit

1 Scope

This part of ISO 12156 specifies the performance requirement (limit) necessary to ensure reliable operation of diesel fuel injection equipment with respect to lubrication by fuel of such equipment.

It applies to fuels used in diesel engines.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12156-1, *Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR) — Part 1: Test method*

3 Test method

The test method for the assessment of diesel fuel lubricity to comply with the limit specified in this part of ISO 12156 shall be the method specified in ISO 12156-1.

4 Limit

The performance requirement (limit) for diesel fuel in compliance with this part of ISO 12156 shall be a wear scar diameter corrected to a standardized water vapour pressure of 1,4 kPa (WS1,4) not greater than 460 μm .

5 Designation

This part of ISO 12156 may be used to specify a lubricity requirement for a fuel for use in a diesel engine. This requirement shall be designated as follows:

Lubricity ISO 12156-2

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12156-2:2007

<https://standards.iteh.ai/catalog/standards/sist/0305a2fd-5087-4ead-b6d6-ff234de891b2/iso-12156-2-2007>

ICS 75.160.20

Price based on 1 page