



# DRAFT INTERNATIONAL STANDARD ISO/DIS 6944-1

ISO/TC 92/SC 2

Secretariat: ANSI

Voting begins on:  
2005-11-16

Voting terminates on:  
2006-04-17

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

## Fire containment — Elements of building construction —

### Part 1: Ventilation ducts

*Endiguement du feu — Éléments de construction —*

*Partie 1: Conduits de ventilation*

(Revision of ISO 6944:1985)

ICS 13.220.50; 91.140.30

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/DIS 6944-1](https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cd228bb/iso-dis-6944-1)

[https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-](https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cd228bb/iso-dis-6944-1)

[9b6cd228bb/iso-dis-6944-1](https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cd228bb/iso-dis-6944-1)

**In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.**

**Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.**

**To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.**

**Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.**

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/DIS 6944-1](#)

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>

**Copyright notice**

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

# Contents

Page

|   |    |
|---|----|
| Foreword.....   | v  |
| Introduction .....  | vi |
| 1 Scope .....   | 1  |
| 2 Normative references .....                                      | 1  |
| 3 Terms and definitions.....                                      | 2  |
| 4 Test equipment .....  | 2  |
| 4.1 General.....  | 2  |
| 4.2 Furnace.....  | 2  |
| 4.3 Fan A.....  | 4  |
| 4.4 Fan B.....  | 6  |
| 4.5 Volume flow measuring station.....                            | 8  |
| 4.6 Condensing unit.....  | 8  |
| 4.7 Damper.....   | 8  |
| 4.8 Velocity measuring station .....                              | 8  |
| 4.9 Equipment for measuring gas pressure.....                     | 8  |
| 4.10 Thermal movement measuring device.....                       | 8  |
| 4.11 Force measuring device.....                                  | 8  |
| 5 Test conditions .....   | 9  |
| 6 Test specimen .....   | 9  |
| 6.1 Size.....   | 9  |
| 6.2 Number .....  | 10 |
| 6.3 Design .....  | 10 |
| 7 Installation of test specimen .....                             | 12 |
| 7.1 General.....  | 12 |
| 7.2 Standard supporting construction.....                         | 12 |
| 7.3 Non-standard supporting constructions.....                    | 14 |
| 7.4 Restraint of ducts .....                                      | 14 |
| 8 Conditioning.....   | 14 |
| 8.1 General.....  | 14 |
| 8.2 Hygroscopic sealing materials.....                            | 14 |
| 9 Application of instrumentation.....                             | 15 |
| 9.1 Thermocouples .....   | 15 |
| 9.2 Pressure.....   | 20 |
| 10 Test procedure .....   | 20 |
| 10.1 General.....   | 20 |
| 10.2 Control of conditions to permit assessment of integrity..... | 20 |
| 10.3 Test measurements and observations .....                     | 21 |
| 10.4 Termination of the test .....                                | 22 |
| 11 Performance criteria .....                                     | 22 |
| 11.1 Integrity.....   | 22 |
| 11.2 Insulation .....   | 22 |
| 11.3 Smoke Leakage.....   | 22 |
| 12 Test report .....  | 23 |
| 13 Field of direct application of test results .....              | 23 |
| 13.1 General.....   | 23 |

|         |   |    |
|---------|---|----|
| 13.2    | Vertical and horizontal ducts .....           | 23 |
| 13.3    | Sizes of ducts .....                          | 23 |
| 13.4    | Pressure difference .....                     | 24 |
| 13.5    | Height of vertical ducts .....                | 24 |
| 13.6    | Suspension devices for horizontal ducts ..... | 25 |
| 13.7    | Supporting construction .....                 | 25 |
| 13.8    | Steel ducts .....                             | 25 |
| Annex A | (informative) General guidance .....          | 26 |
| A.1     | General .....                                 | 26 |
| A.2     | Notes on apparatus .....                      | 26 |
| A.3     | Notes on test specimens .....                 | 26 |
| A.4     | Notes on test conditions .....                | 28 |
| A.5     | Notes on procedure .....                      | 28 |
| A.6     | Notes on test conditions .....                | 28 |
| A.7     | Notes on procedure .....                      | 29 |
| A.8     | Notes on performance criteria .....           | 29 |
| A.9     | Use of alternative elbow .....                | 29 |
| A.10    | Avoidance of flame impingement .....          | 30 |

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/DIS 6944-1](#)

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6944-1 was prepared by Technical Committee ISO/TC 92, *Fire safety*, Subcommittee SC 2, *Fire containment*.

This edition cancels and replaces ISO 6944 (1985).

ISO 6944 consists of the following parts, under the general title *Fire containment — Elements of building construction*:

- iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**
- <https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>  
[ISO/DIS 6944-1](#)
- *Part 1: Ventilation ducts*
  - *Part 2: Grease ducts*

## Introduction

The purpose of this test is to measure the ability of a representative duct or duct assembly that is part of an air distribution system, to resist the spread of fire from one fire compartment to another with fire attack from inside or outside the duct. It is applicable to vertical and horizontal ducts, with or without branches, taking into account joints and exhaust openings, as well as suspension devices and penetration points.

This International standard is very similar to EN 1366-1, but includes an alternative arrangement for testing elbows.

The test measures the length of time for which ducts, of specified dimensions, suspended as they would be in practice, satisfy defined criteria when exposed to fire from (separately) both inside and outside the duct.

All ducts inside the furnace are fully restrained in all directions. Outside the furnace, ducts exposed to fire from the outside are tested unrestrained, while ducts exposed to fire from the inside (horizontal only) are tested restrained.

The test takes into account the effect of fire exposure from the outside where a 300 Pa underpressure is maintained in the duct as well as the effect of fire entering the ducts in conditions where forced air movement may or may not be present by maintaining an air velocity of 3 m/s.

Ducts exposed to fire from the inside are supplied with air in a manner which is indicative of the "fan off" and "fan on" situations which could arise in practice.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>

# Fire containment — Elements of building construction —

## Part 1: Ventilation ducts

### CAUTION —

The attention of all persons concerned with managing and carrying out this fire resistance test is drawn to the fact that fire testing may be hazardous and that there is a possibility that toxic and/or harmful smoke and gases may be evolved during the test. Mechanical and operational hazards may also arise during the construction of the test elements or structures, their testing and disposal of test residues.

It is strongly recommended that the duct assembly is allowed to cool completely after the fire test before dismantling to minimise the possibility of ignition of combustible residues.

An assessment of all potential hazards and risks to health shall be made and safety precautions shall be identified and provided. Written safety instructions shall be issued. Appropriate training shall be given to relevant personnel. Laboratory personnel shall ensure that they follow written safety instructions at all times.

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

### 1 Scope

This International Standard specifies a method for determining the fire resistance of vertical and horizontal ventilation ducts under standardised fire conditions. The test examines the behaviour of ducts exposed to fire from the outside (duct A) and fire inside the duct (duct B). This Standard is used in conjunction with ISO 834-1.

This International Standard is not applicable to:

- a) ducts whose fire resistance depends on the fire resistance performance of a ceiling;
- b) ducts containing fire dampers at points where they pass through fire separations;
- c) doors of inspection openings, unless included in the duct to be tested;
- d) two or three sided ducts;
- e) fixing of suspension devices to floors or walls.

NOTE Annex A provides general guidance and gives background information.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 834-1, *Fire resistance tests – Elements of building construction – Part 1: General requirements*

EN 1366-1, *Fire resistance tests for service installations – Part 1: Ducts*

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices – Part 1: Orifice plates, nozzles and venturi tubes inserted in circular cross-section conduits*

ISO 5221, *Air distribution and air diffusion – Rules to methods of measuring air flow rate in an air handling duct*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 834-1, ISO 13943 and the following apply.

- 3.1 fire resisting duct**  
a duct used for the distribution or extraction of air and designed to provide a degree of fire resistance
- 3.2 suspension device**  
the components used for suspending and fixing a duct from a floor or supporting a duct from a wall
- 3.3 supporting devices**  
the wall, partition or floor which the duct passes through in the test
- 3.4 compensator**  
a device that is used to prevent damage from the forces generated by expansion

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

### 4 Test equipment

[ISO/DIS 6944-1  
https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1](https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1)

#### 4.1 General


In addition to the test equipment specified in ISO 834-1, the following is required:

#### 4.2 Furnace

This shall be capable of subjecting ventilation ducts to the standard heating and pressure conditions specified in ISO 834-1 and be suitable for testing ducts in the vertical (see figure 1) or horizontal (see figure 2) orientation.

Dimensions in millimetres






iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO DIS 6944-1

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>



Key

- |  |  |
|--|--|
| 1 furnace wall   | 9 furnace floor  |
| 2 sealed end   | 10 leakage measuring station (see figure 3 for details)      |
| 3 fire stopping as in practice                                 | 11 gas velocity measuring station (see figure 4 for details) |
| 4 fire protection system                                       | 12 duct A  |
| 5 joint in fire protection system                              | 13 duct B  |
| 6 furnace roof   |  |
| 7 furnace chamber  |  |
| 8 openings providing a total area of 50% of duct cross section |  |

W width


H height

D diameter

Note – The drawing shows two ducts being tested together. It is also permitted to test each duct singularly in the furnace.

Figure 1 — Test arrangement for vertical ducts

Dimensions in millimetres



<https://standards.itech.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>

- |     |  |
|-----|--|
| Key |  |
| 1   | furnace wall   |
| 2   | duct with 90° elbow  |
| 3   | sealed end   |
| 4   | fire stopping as in practice                                 |
| 5   | fire protection system                                       |
| 6   | location of restraint positions                              |
| 7   | joints in fire protection system                             |
| 8   | duct A   |
| 9   | duct B   |
| 10  | supporting construction                                      |
| 11  | furnace chamber  |
| 12  | openings providing a total area of 50% of duct cross section |
| 13  | sealed end of elbow  |
| 14  | 200 mm minimum supporting construction                       |
| 15  | leakage measuring station (see figure 3 for details)         |
| 16  | gas velocity measuring station (see figure 4 for details)    |


W Width or diameter

Note – The drawing shows two ducts being tested together. It is also permitted to test each duct singularly in the furnace.

Figure 2 — Test arrangement for horizontal ducts

### 4.3 Fan A

This shall be able to produce at the start and throughout the test an underpressure of  $(300 \pm 15)$  Pa within duct A (see figure 3) and shall be connected either directly, or by a suitable length of flexible ducting, to the measuring station described in 4.5.



iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO/DIS 6944-1

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35fd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>

Key

- |   |  |    |                                     |
|---|--|----|-------------------------------------|
| 1 | pressure sensor to furnace             | 12 | support for flow measuring system   |
| 2 | pressure sensor on centre line of duct | 13 | thermocouple 1,5 mm diameter        |
| 3 | office plate, venture or similar       | 14 | flow straightener (where necessary) |
| 4 | pressure differential (300 Pa)         | 15 | flange                              |
| 5 | pressure sensor in laboratory          | 16 | support for duct outside furnace    |
| 6 | pressure differential control box      | 17 | test duct                           |
| 7 | pressure control dilution damper       | 18 | thermocouple located 2d from 3      |
| 8 | pneumatic actuator manual control      | 19 | condensing device                   |

- |    |                          |    |                   |
|----|--------------------------|----|-------------------|
| 9  | balancing damper         | 20 | horizontal duct A |
| 10 | fan                      | 21 | vertical duct A   |
| 11 | flexible connecting duct |    |                   |

**Figure 3 — Leakage measuring station for duct A**

#### **4.4 Fan B**

This shall be able to produce an air velocity when extracting gas from duct B (see figure 4), of at least 3 m/s measured at ambient temperature in the duct before the test. It shall be connected either directly, or by a suitable length of flexible ducting, to the velocity measuring station described in 4.8. The fan shall be provided with a by-pass vent that can be opened prior to the damper described in 4.7 being shut.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/DIS 6944-1](https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1)

<https://standards.iteh.ai/catalog/standards/sist/53f43ead-35dd-444b-a8a2-9b6cde228bbb/iso-dis-6944-1>