

ETSI TS 102 939-2 V1.1.1 (2015-03)



**Digital Enhanced Cordless Telecommunications (DECT);
Ultra Low Energy (ULE);
Machine to Machine Communications;
Part 2: Home Automation Network (phase 2)**

STANDARDS PREVIEW
iTech (standards-itec.ai)
<https://standards.iteh.ai/standards/etec/etec-102-939-2-v1.1.1-8e8a-497e-ba59-87b5a37b1401/>
2015-03-15

Reference

DTS/DECT-ULE000268-2

Keywords

access, data, DECT, environment, IMT-2000,
intelligent homes & buildings, internet,
interoperability, interworking, M2M, mobility,
packet mode, profile, radio, synchronization,
TDD, TDMA
ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>
Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	9
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	12
3.3 Abbreviations	13
4 Description of services and features.....	16
4.1 DECT Ultra Low Energy	16
4.1.0 General.....	16
4.1.1 Back-compatibility with ULE Phase 1.....	16
4.1.2 Coexistence with other DECT services	16
4.1.3 Example applications covered by ULE Phase 2	16
4.1.3.0 General.....	16
4.1.3.1 Simple medical pendant alarms.....	17
4.1.3.2 Software Upgrade Over The Air.....	17
4.1.3.3 M2M devices with audio capability.....	18
4.2 Requirements for ULE Phase 2.....	18
4.2.1 Device types.....	18
4.2.1.0 General.....	18
4.2.1.1 ULE Phase 2 RFP	18
4.2.1.1.1 General description.....	18
4.2.1.1.2 Requirements.....	18
4.2.1.2 PP type IV: hybrid device with voice/data support	18
4.2.1.2.1 General description.....	18
4.2.1.2.2 Requirements.....	19
4.2.2 U-plane interworking and protocol architecture	19
4.2.3 Performance Objectives	19
4.3 Services and features implemented by ULE phase 2.....	19
4.3.0 General.....	19
4.3.1 MAC / PHY layer	19
4.3.2 DLC layer	19
4.3.3 NWK layer.....	19
4.3.4 Interworking and Application layer	20
4.3.5 Security	20
4.3.6 Management Entity.....	20
4.3.7 Speech services and codecs	20
5 Service and feature definitions	20
5.1 ULE Phase 2.....	20
5.1.1 PHL service definitions	20
5.1.2 MAC service definitions	20
5.1.3 DLC service definitions	21
5.1.4 NWK feature definitions.....	21
5.1.5 Application feature definitions	22
5.1.6 Management Entity (ME) definitions	22
5.1.7 U-plane service and interworking definitions	22
5.1.8 ULE device types.....	22
5.1.9 Speech services and speech coding definitions.....	22
5.1.10 Call Control (CC) and mobility management service definitions.....	22

6	Profile specific requirements	23
6.1	General	23
6.2	Specific conventions.....	23
6.2.1	Use of symbols in support status tables	23
6.3	DECT ULE phase 1 device types	23
6.3.1	Types of devices supported by the present document.....	23
6.3.2	Specific procedures for specific device types	23
6.4	Physical layer (PHL) requirements.....	24
6.4.1	Physical layer (PHL) services	24
6.4.2	Modulation schemes	24
6.4.3	PHL service to procedure mapping.....	24
6.5	MAC layer requirements	25
6.5.1	MAC layer services	25
6.5.2	MAC service to procedure mapping	26
6.6	DLC layer.....	28
6.6.1	DLC layer services.....	28
6.6.2	DLC service to procedure mapping	29
6.7	NWK layer	30
6.7.1	General.....	30
6.7.2	NWK features	30
6.7.3	NWK features to procedures mapping.....	32
6.8	Application Layer.....	33
6.8.1	Application features	33
6.8.2	Application features to procedures mapping.....	33
6.9	Distributed communications.....	34
6.10	Management Entity (ME).....	34
6.10.1	Management Entity (ME) services	34
6.10.2	Management Entity (ME) mode to procedures mapping	34
6.11	U-plane services and interworking requirements	35
6.11.1	U-plane and interworking services	35
6.11.2	U-plane and interworking service to procedure mapping	36
6.12	Speech Services.....	36
6.12.1	Speech Services features.....	36
6.12.2	Speech Services to procedures mapping	37
6.13	General class/service/interworking support.....	37
6.13.1	Class/service support	37
6.13.2	Protocol interworking support	37
7	Profile specific procedures description	38
7.0	General	38
7.1	Back compatibility with ULE Phase 1	38
7.1.0	General.....	38
7.1.1	Back compatibility with a ULE Phase 1 Fixed Part (FP).....	38
7.1.2	Back compatibility with a ULE Phase 1 Portable Part (PP)	38
8	Physical Layer (PHL) procedures	38
9	Management Entity (ME) procedures	38
9.1	ULE phase 1 Management	38
9.2	Channel selection and collision avoidance procedures.....	38
9.3	Channel selection and collision avoidance procedures for US region.....	39
9.3.0	General.....	39
9.3.1	Overall architecture of ULE channel selection processes	39
9.3.2	Process M0 (RFP side pre-selection process)	39
9.3.3	Broadcast mechanism	39
9.3.4	Process M1 (PP side channel selection process).....	40
9.3.5	Setup attempt and evaluation of responses	40
9.3.6	Process M2 (collision handling/collision avoidance process).....	41
9.4	Channel selection and collision avoidance procedures for Japan region.....	41
9.4.0	General.....	41
9.4.1	Overall architecture of ULE channel selection processes	41
9.4.2	Process M0 (RFP side pre-selection process)	41
9.4.3	Broadcast mechanism	42

9.4.4	Process M1 (PP side channel selection process).....	42
9.4.5	Setup attempt and evaluation of responses	42
9.4.6	Process M2 (collision handling/collision avoidance process).....	43
10	MAC layer procedures	43
10.1	Radio Control Bits.....	43
10.1.1	Quiet Channel Indication	43
10.1.2	PHS Detection Indication	43
10.2	Downlink broadcast (A-field).....	44
10.2.0	General.....	44
10.2.1	N_T messages.....	44
10.2.2	Q_T messages.....	44
10.2.2.1	Q_T - static system information.....	44
10.2.2.2	Q_T - FP capabilities	44
10.2.2.2.1	Standard FP Capabilities	44
10.2.2.2.2	Extended FP Capabilities.....	45
10.2.2.2.3	Extended FP Capabilities part 2	46
10.3	Slot types and slot use	46
10.3.1	Full Slot	46
10.3.1.1	General	46
10.3.1.2	Use of full slot in C/O bearers.....	46
10.3.1.3	Use of full slot in C/L dummy bearers	46
10.3.2	Short Slot	46
10.3.2.1	General	46
10.3.2.2	Use of short slot in C/O bearers	46
10.3.3	Long Slot	47
10.3.3.1	General.....	47
10.3.3.2	Use of long slot in C/O bearers	47
10.4	No-emission compatibility mode procedures.....	47
10.4.1	General.....	47
10.5	U-plane C/L downlink services	47
10.5.0	General.....	47
10.5.1	U-plane C/L downlink multicast unacknowledged service.....	47
10.5.1.0	General	47
10.5.1.1	Logical channels and instance separation	48
10.5.1.2	Addressing and management of multicast groups	48
10.5.1.3	Procedure	48
10.5.1.4	SI_P subfield format	48
10.5.2	U-plane C/L downlink over the dummy bearer	48
10.5.2.0	General	48
10.5.2.1	Multiplexing cycle	48
10.5.2.2	Single-burst transmission	48
10.5.2.3	Identification of C/L downlink insertion.....	49
10.5.2.4	Announcement via the B_U paging channel and identification of instances	49
10.5.3	U-plane C/L downlink over additional C/L bearers.....	49
10.5.3.0	General	49
10.5.3.1	Channel selection and transmission start.....	49
10.5.3.2	MAC signalling in the additional C/L downlink bearer	49
10.5.3.3	Single-burst transmission	50
10.5.3.4	Announcement via the B_U paging channel and identification of instances	50
10.6	ULE Paging Procedures (phase 2).....	50
10.6.0	General.....	50
10.6.1	P_U Paging Message Formats	50
10.6.2	Paging Descriptors for ULE Paging	50
10.6.2.1	Basic concepts of the ULE paging system	50
10.6.2.2	Basic operation of the descriptors	51
10.6.2.3	Allocation of descriptors	51
10.6.2.4	Format for descriptors in ULE phase 1	51
10.6.2.4.0	General	51
10.6.2.4.1	Master/slave types	51
10.6.2.4.2	CA subscription capability	52

10.6.2.4.3	Format A.....	52
10.6.2.4.4	Format B.....	53
10.6.2.4.5	Format C.....	54
10.6.2.5	Descriptors in ULE phase 2	55
10.6.2.5.1	Descriptor codes	55
10.6.2.5.2	Descriptor detailed descriptions	55
10.6.2.5.2.0	General	55
10.6.2.5.3	Additional conventions for ULE phase 2 descriptors	56
10.6.2.5.4	Coding of additional C/L bearer position	57
10.6.2.5.4.0	General	57
10.6.2.5.5	Discrimination between multicast transmissions over the dummy and over additional C/L bearers	57
10.6.2.5.6	Time references for multicast transmissions	58
10.6.3	CA mask mechanism	58
10.7	Repeater compatibility procedures	58
10.7.1	General.....	58
10.7.2	Identification of a WRS	58
10.7.3	ULE page delay mechanism	58
10.7.4	Roaming.....	59
10.7.4.1	General	59
10.7.4.2	Regular DECT roaming	60
10.7.4.3	ULE roaming.....	60
10.7.4.4	ULE bearer replacement (inter-cell).....	61
10.8	Additional requirements for I channel services	61
10.8.1	Lifetime management with TWO separate maximum MAC packet lifetimes	61
10.8.1.0	General	61
10.8.1.1	Operation of the counters	61
11	DLC layer procedures	62
11.1	Specific procedures for C/L downlink multicast channels	62
11.1.1	Procedures for C/L downlink multicast channels	62
11.1.1.1	LU14 Enhanced Frame RELay service with CCM (EFREL-CCM) for C/L downlink multicast channels.....	62
11.1.1.2	LU13 Enhanced Frame RELay service with CRC (EFREL-CRC) for C/L downlink multicast channels.....	62
11.1.1.2.0	General	62
11.1.1.2.1	Use of LU13 in multicast links.....	63
11.1.1.3	LU10 Enhanced Frame RELay service (EFREL) for C/L downlink multicast channels	63
11.1.1.4	FU10a frame operation for C/L downlink multicast channels	63
11.1.1.5	Transmission Class 1 over C/L downlink multicast channels	63
11.1.2	Security procedures for C/L downlink multicast channels	63
11.1.2.1	CCM Authenticated Encryption of C/L downlink multicast channels.....	63
11.1.2.2	Initialization Vector for multicast channels	63
11.1.2.3	Security provisions regarding the key for multicast channels.....	64
12	NWK layer procedures	64
12.1	Specific procedures for C/L downlink multicast channels	64
12.1.1	Security procedures for C/L downlink multicast channels	64
12.1.1.1	Cipher keys for CCM encryption of C/L multicast channels	64
12.1.1.2	Multicast encryption parameter assignation procedure, FT initiated	64
12.1.1.2.0	General	64
12.1.1.2.1	Procedure description	64
12.1.1.2.2	Security provision.....	64
12.1.1.2.3	Coding of the operation messages	64
12.1.1.3	Multicast encryption parameter retrieval procedure, PT initiated	67
12.1.1.3.0	General	67
12.1.1.3.1	Procedure description	67
12.1.1.3.2	Security provisions	67
12.1.1.3.3	Coding of the operation messages	68
12.1.2	Control procedures for C/L downlink multicast channels	70
12.1.2.1	Subscription to C/L downlink multicast channels.....	70
12.1.2.2	Activation of security procedures	70

12.1.2.3	Un-subscription to C/L downlink multicast channels	70
12.1.2.4	Parameters for the C/L downlink multicast service	70
12.2	Terminal capabilities and FP broadcasts	70
12.2.1	Terminal capability indication	70
12.2.2	FP broadcasts	72
12.2.2.1	Higher layer information FP broadcast	72
12.2.2.1.0	General	72
12.2.2.1.1	Higher layer information in standard FP broadcast (Qh = 3)	73
12.2.2.1.2	Higher layer information in Extended FP broadcast (Qh = 4)	73
12.2.2.1.3	Extended Higher Layer capabilities part 2 (Qh = 11)	73
12.3	Specific procedures for "hybrid" devices	74
12.3.1	Incoming calls for "hybrid voice" devices	74
12.3.1.1	General requirements	74
12.3.1.2	Paging descriptors for incoming calls	75
12.3.1.3	Incoming call procedure	75
12.3.2	Interactions of ULE and "circuit mode"	76
12.3.2.1	General requirements	76
12.3.2.2	ULE request whilst "circuit mode" active	76
12.3.2.3	"Circuit mode" request whilst ULE active	76
12.3.2.4	Suspend / resume ULE service	77
12.4	SUOTA push mode	77
12.4.1	General requirements	77
12.4.2	Paging descriptors for SUOTA push mode	77
12.4.3	Push mode procedure	77
12.5	Additional requirements for ULE NWK Control	77
12.5.1	Default ULE PVC transaction parameters	77
12.5.2	Default MAC parameters for implicitly created MBC	78
13	Services and Interworking procedures	78
13.1	Specific procedures for ULE phase 2	78
13.1.1	Service channels transported via <<IWU-to-IWU>> IE	78
13.1.1.1	General concepts	78
13.1.1.2	Configuration and control service channel	78
13.1.1.2.0	General	78
13.1.1.2.1	ULE Common Control Protocol procedures	79
13.1.1.3	CCM encrypted general purpose service channel	79
13.1.1.3.0	General	79
13.1.1.3.1	Services provided by the DECT sub-system	79
13.1.1.3.2	Transport of the general purpose service channel	80
13.1.1.3.3	Security procedures	80
13.1.1.3.4	Segmentation and reassembling	81
13.1.1.3.5	MAC Release Reason Emulation	82
13.1.2	IWU procedures for C/L downlink multicast service	83
13.1.2.1	General	83
13.1.2.2	U-plane procedures	83
13.1.2.3	C-plane procedures	83
14	Application procedures	83
14.1	Hybrid device voice service	83
14.1.0	Introduction	83
14.1.1	General requirements	83
14.2	Hybrid device data service	84
14.2.0	Introduction	84
14.2.1	General requirements	84
14.3	Software Upgrade Over The Air (SUOTA) for ULE devices	84
14.3.0	Introduction	84
14.3.1	General requirements	84
Annex A (normative):	Parameters and Information Elements	85
A.1	Constants, variables and operating parameters	85
A.1.1	Operating parameters	85
A.1.1.1	Channel selection algorithms	85

A.1.1.2	MAC layer	85
A.1.1.3	DLC layer	85
History		86

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cfca599-8e8a-497e-ba59-87b5a37b1340/etsi-ts-102-939-2-v1.1.1-2015-03>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is based on ETSI EN 300 175 parts 1 [1] to 8 [8], ETSI EN 300 444 [9], ETSI EN 301 649 [16] and ETSI TS 102 939-1 [12].

The present document has been developed in accordance to the rules of documenting a profile specification as described in ISO/IEC 9646-6 [i.1].

The present document is part 2 of a multi-part deliverable covering Machine to Machine Communications based on DECT Ultra Low Energy (ULE), as identified below:

Part 1: "Home Automation Network (phase 1)".

Part 2: "Home Automation Network (phase 2)".

Further phases with additional functionality may be defined in the future by other parts of this multi-part deliverable.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

DECT Ultra Low Energy (ULE) is based on the DECT base standard ETSI EN 300 175 parts 1 [1] to 8 [8], and the DECT Packet Radio Service (DPRS) ETSI EN 301 649 [16]. However DECT ULE includes substantial differences from its parent technology in order to achieve Ultra Low Power consumption.

From the point of view of DECT standardization DECT ULE is an Application Profile (AP) based on the DECT base standard (ETSI EN 300 175, parts 1 [1] to 8 [8]). This application profile may reuse definitions and procedures defined in other DECT applications profiles when needed or convenient. This is the case, for instance, of the DECT Generic Access Profile (GAP) ETSI EN 300 444 [9], the DECT Packet Radio Service (DPRS) ETSI EN 301 649 [16] and DECT Ultra Low Energy (ULE) Part 1 [12].

All DECT devices claiming to be compliant with this Application Profile will offer at least the basic services defined as mandatory. In addition to that, optional features can be implemented to offer additional DECT ULE services.

The aim of the DECT ULE standard is to guarantee a sufficient level of interoperability and to provide an easy route for development of DECT ULE applications. The DECT ULE standard also guarantees compatibility between DECT ULE applications and existing DECT applications (such as GAP or NG-DECT) running over the same spectrum and even in the same device.

1 Scope

The present document covers the following DECT ULE services and features:

- Back-compatibility with ULE Phase 1 [12].
- Regional variants of ULE for US and Japan.
- Support for hybrid devices which utilize ULE and non-ULE services (such as voice).
- Software Update Over The Air (SUOTA), compatible with the same feature as defined in New Generation DECT Part 4 [13].
- Compatibility mode for FTs that also support No-Emissions Mode (NEMo [13]).
- Connectionless Downlink, which is the capability to transmit ULE messages to multiple devices.
- Repeater compatibility support for FP and PP.

The set of DECT ULE services and features defined in the present document is named "Home Automation Network (phase 2)", and is primarily targeted to provide a global M2M solution within domestic scenarios. However, this does not prevent the use of the present document in other scenarios.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".

- [9] ETSI EN 300 444: "Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [10] ETSI TS 102 527-3: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 3: Extended Wideband Speech Services".
- [11] ETSI TS 102 527-1: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 1: Wideband speech".
- [12] ETSI TS 102 939-1: "Digital Enhanced Cordless Telecommunications (DECT); Ultra Low Energy (ULE); Machine to Machine Communications; Part 1: Home Automation Network (phase 1)".
- [13] ETSI TS 102 527-4: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; Part 4: Light Data Services; Software Update Over The Air (SUOTA), content downloading and HTTP based applications".
- [14] ETSI TS 102 497: "Digital Enhanced Cordless Telecommunications (DECT); DECT in the 1 920 MHz to 1 930 MHz Unlicensed Personal Communications Services (UPCS) frequency band; Specific requirements".
- [15] ARIB STD-T101: "Radio Equipment Used For TDMA Digital Enhanced Cordless Telecommunications"; (English version).
- [16] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".
- [17] ETSI EN 300 700: "Digital Enhanced Cordless Telecommunications (DECT); Wireless Relay Station (WRS)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 9646-6: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 6: Protocol profile test specification".
- [i.2] Recommendation ITU-T G.726 (12/1990): "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [i.3] Recommendation ITU-T G.711 (11/1988): "Pulse code modulation (PCM) of voice frequencies".
- [i.4] Recommendation ITU-T G.722 (11/1988): "7 kHz audio-coding within 64 kbit/s".
- [i.5] Recommendation ITU-T G.729.1 (05/2006): "G.729 based embedded variable bit-rate coder: An 8-32 kbit/s scalable wideband coder bitstream interoperable with G.729".
- [i.6] ISO/IEC JTC1/SC29/WG11 (MPEG): International Standard ISO/IEC 14496-3:2009: "Information Technology - Coding of audio-visual objects - Part 3: Audio".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI TS 102 939-1 [12], ETSI TS 102 527-1 [11], ETSI TS 102 527-4 [13] and the following apply:

circuit mode: DECT connections involving setup of the MAC connection using Basic Connection control or Advanced Connection control, but not the "expedited" setup messages

NOTE: Such connections generally last of the order of several seconds (or several minutes for voice calls).

hybrid device: ULE device supporting voice and/or non-ULE data service

Last Minute Scan (LMS): RSSI scan which is generally performed at the last opportunity before transmission (e.g. in the frame before transmission)

Least Interfered Channel (LIC): slot/carrier pair which has the lowest level of interference, usually within a certain level of tolerance or range of values

NOTE: Calculation of the LIC generally requires a full matrix RSSI scan of all available slot/carrier combinations.

packet mode: DECT connections involving setup of the MAC connection using the Advanced Connection control "expedited" messages

NOTE: Such connections generally last of the order of a few frames only.

Personal Handy-phone System (PHS): cordless network telephony system operating in the 1 880 – 1 930 MHz frequency band

NOTE: PHS is used mainly in Japan, China, Taiwan, and some other Asian countries and regions.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

BA (bits)	B-field identification bits, the bits from the A-field header that provide indication for the content of the B-field of one MAC layer packet
BCK	bit used for I _p channel flow control in MAC I _p error correction services
B _S	Slow Broadcast channel
B _U	ULE Broadcast channel
C	for conditional to support (process mandatory)
C	higher layer control Channel (see C _S and C _F)
C _F	higher layer signalling Channel (Fast)
C-plane	Control plane
C _S	higher layer signalling Channel (Slow)
E+U	Mode of the B-field E/U multiplexer carrying U-plane data and signalling
G _F	higher layer information control channel (fast) (a logical channel to the MAC layer)
G _{FA}	higher layer information control channel (slow) (a logical channel to the MAC layer)
I	for out-of-scope (provision optional, process optional) not subject for testing
I	higher layer Information channel (see I _N and I _P)
I _N	higher layer Information channel (unprotected)
I _P	higher layer Information channel protected (in general, any variant)
I _{PF}	higher layer Information channel (protected) transported multiplexed with signalling in the E+U type slots
I _{PM}	higher layer Information channel, multi-subfield (protected) B-field with error detection only
I _{PMR}	higher layer Information channel, multi-subfield (protected) B-field with MOD-2 protected channel operation (ARQ)

I _{PQ}	higher layer Information channel (protected) with single subfield format and error detection only
I _{PQR}	higher layer Information channel (protected) with single subfield format and error correction using MOD-2 retransmission mechanism
LAPC	DLC layer C-plane protocol entity
L _c	a DLC layer C-plane protocol entity
LU	DECT DLC U-Plane Service
M	for mandatory to support (provision mandatory, process mandatory, see clause 6.2.1).
M	MAC control channel
M0	RFP channel pre-selection algorithm for ULE
M1	PP channel selection algorithm for ULE
M2	PP collision handling and avoidance algorithm for ULE
M _T	MAC control channel on A-tail field, or one message on such channel
M _U	MAC control channel on B-field for ULE
N	identities channel
N/A	for not-applicable (in the given context the specification makes it impossible to use this capability, see clause 6.2.1)
N _S	split identities channel on B-field for ULE
N _T	identities information channel or one message in such channel
O	for optional to support (provision optional, process mandatory, see clause 6.2.1)
O.x	option comprising number of items
P	Paging channel
P _T	one P-channel message
P _U	ULE Paging channel on B-field
Q	system information channel
Q _C	compound System Information Channel of B-field for ULE
Q _H	Q field header
Q _T	system information and Multiframe marker
RN	Received sequence Number
RR	a frame type of the DLC C-plane entity
Rx	Receiver side
S/T	ISDN S/T Interface
SI _p	higher layer connectionless channel (protected)
Tx	Transmitter side
U	ISDN U-Interface
X	excluded, not allowed
ZAP	ability first to assign and then to re-program the account data held in the PP

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Authentication Code
ACK	ACKnowledgement
ADPCM	Adaptive Differential Pulse Code Modulation
AES	Advanced Encryption Standard
AI	Air Interface
AP	Application Profile
ARI	Access Rights Identity
ARQ	Automatic Retransmission reQuest
C/L	ConnectionLess
CA	Channel Active
CBC-MAC	Cipher Block Chaining Message Authentication Code
CC	Call Control, a NWK layer functional grouping.
CCM	Counter with CBC-MAC
CHO	Connection HandOver
CI	Common Interface
CLIP	Calling Line Identification Presentation
CLMS	ConnectionLess Message Service
CRC	Cyclic Redundancy Check