

Designation: D 6083 - 05

# Standard Specification for Liquid Applied Acrylic Coating Used in Roofing<sup>1</sup>

This standard is issued under the fixed designation D 6083; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This specification covers liquid-applied water-dispersed acrylic latex elastomeric protective roof coatings.

1.2 This specification does not provide guidance for application.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

## 2. Referenced Documents

2.1 ASTM Standards: <sup>2</sup>

- C 794 Test Method for Adhesion-in-Peel of Elastomeric Joint Sealants
- D 16 Terminology for Paint, Related Coatings, Materials, and Applications
- D 471 Test Method for Rubber Property-Effect of Liquids
- D 522 Test Methods for Mandrel Bend Test of Attached Dorganic Coatings
- D 562 Test Method for Consistency of Paints Measuring Krebs Unit (KU) Viscosity Using a Stormer-Type Viscometer
- D 624 Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomers
- D 903 Test Method for Peel or Stripping Strength of Adhesive Bonds
- D 1079 Terminology Relating to Roofing, Waterproofing, and Bituminous Materials
- D 1644 Test Methods for Nonvolatile Content of Varnishes

- D 1653 Test Methods for Water Vapor Transmission of Organic Coating Films
- D 2196 Test Methods for Rheological Properties of Non-Newtonian Materials by Rotational (Brookfield type) Viscometer
- D 2370 Test Method for Tensile Properties of Organic Coatings
- D 2697 Test Method for Volume Nonvolatile Matter in Clear or Pigmented Coatings
- D 4798 Practice for Accelerated Weathering Test Conditions and Procedures for Bituminous Materials (Xenon-Arc Method)
- G 21 Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi

## 3. Terminology

3.1 For definitions of terms used in this specification, see Terminologies D 16 and D 1079.

## 4. Packaging and Materials

4.1 Shipping containers shall be marked with the name of the material, the stock number, lot number, ASTM designation number and year of issue, quantity therein, shelf-life date, and the name of the manufacturer or supplier.

## 5. Materials and Manufacture

5.1 *Composition*—The product, as manufactured, shall be in liquid form for application to the roof surface by brushing, squeegeeing, rolling, or spraying. The product shall be composed of a water-based acrylic latex elastomeric emulsion polymer, to which various pigments and other additives have been added to give the required physical properties.

## 6. Liquid and Cured Film Physical Properties

6.1 Although the product is supplied as a liquid, its performance is based on the functional properties of the cured material in film form. The coating is formed into a film fully adhered to the substrate.

6.2 *Liquid Property Requirements*—The liquid coating shall comply with the property requirements in Table 1.

6.3 *Film Physical Property Requirements*—The cured film shall comply with the requirements listed in Table 2.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D08 on Roofing and Waterproofing and is the direct responsibility of Subcommittee D08.18 on Nonbituminous Organic Roof Coverings.

Current edition approved April 1, 2005. Published April 2005. Originally approved in 1997. Last previous edition approved in 1997 as D 6083 – 97a.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.