



# SLOVENSKI STANDARD

## SIST-TS ISO/TS 19101-2:2009

01-september-2009

---

; Yc[ fUzg\_Y]bZfa UWY!FYZfYb b]a cXY'!'&"XY.'DcXcVY

Geographic information - Reference model - Part 2: Imagery

Information géographique - Modèle de référence - Partie 2: Imagerie

Ta slovenski standard je istoveten z: ISO/TS 19101-2:2008

[SIST-TS ISO/TS 19101-2:2009](https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-flf6c26550d5/sist-ts-iso-ts-19101-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-flf6c26550d5/sist-ts-iso-ts-19101-2-2009>

**ICS:**

35.240.70	Uporabniške rešitve IT v znanosti	IT applications in science
-----------	-----------------------------------	----------------------------

**SIST-TS ISO/TS 19101-2:2009**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST-TS ISO/TS 19101-2:2009](https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009>

# TECHNICAL SPECIFICATION

**ISO/TS  
19101-2**

First edition  
2008-06-01

---

---

## Geographic information — Reference model —

### Part 2: Imagery

*Information géographique — Modèle de référence —*

*Partie 2: Imagerie*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST-TS ISO/TS 19101-2:2009

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-be5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009>



Reference number  
ISO/TS 19101-2:2008(E)

© ISO 2008

## ISO/TS 19101-2:2008(E)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ISO/TS 19101-2:2009](https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	v
Introduction .....	vi
1 Scope .....	1
2 Conformance .....	1
2.1 General.....	1
2.2 Enterprise conformance .....	1
2.3 Sensor conformance .....	1
2.4 Imagery data conformance .....	1
2.5 Imagery services conformance .....	1
2.6 Image processing system conformance .....	1
3 Normative references .....	2
4 Terms and definitions.....	2
5 Abbreviated terms and symbols .....	7
5.1 Abbreviated terms .....	7
5.2 Symbols .....	9
6 Notation .....	10
7 Enterprise Viewpoint – community objectives and policies .....	10
7.1 General.....	10
7.2 Geographic imagery community objective.....	10
7.3 Geographic imagery scenario .....	10
7.4 Geographic imagery policies .....	11
7.4.1 Introduction to policies .....	11
7.4.2 Policy development guidelines .....	12
7.4.3 Policies .....	12
8 Information Viewpoint – knowledge based decisions .....	13
8.1 Introduction to Information Viewpoint.....	13
8.1.1 Introduction to types of geographic imagery .....	13
8.1.2 Creating knowledge from imagery .....	14
8.1.3 General Feature Model .....	16
8.1.4 Topics relevant across data, information, and knowledge .....	17
8.2 Sensor data package .....	18
8.2.1 General.....	18
8.2.2 Sensors and platforms .....	18
8.2.3 Optical sensing .....	19
8.2.4 Microwave sensing .....	21
8.2.5 LIDAR sensor .....	24
8.2.6 Sonar sensor .....	27
8.2.7 Digital images from film .....	28
8.2.8 Scanned maps.....	28
8.2.9 Calibration, validation and metrology .....	28
8.2.10 Position and attitude determination .....	29
8.2.11 Image acquisition request .....	30
8.3 Geographic imagery information – processed, located, gridded .....	30
8.3.1 General.....	30
8.3.2 IG_Scene.....	30
8.3.3 Derived imagery .....	34
8.3.4 Imagery metadata .....	37
8.3.5 Encoding rules for imagery .....	38

## ISO/TS 19101-2:2008(E)

8.3.6	Imagery compression .....	39
8.4	Geographic imagery knowledge – inference and interpretation .....	40
8.4.1	General .....	40
8.4.2	Knowledge from imagery .....	40
8.4.3	Image understanding and classification .....	40
8.4.4	IG_KnowledgeBase .....	42
8.5	Geographic imagery decision support – context-specific applications .....	44
8.5.1	General .....	44
8.5.2	Decision support services .....	44
8.5.3	Geographic portrayal .....	45
8.5.4	Fitness for Use Context .....	48
8.5.5	Decision fusion .....	50
9	Computational Viewpoint – services for imagery .....	50
9.1	Task-oriented computation .....	50
9.2	Computational patterns .....	50
9.3	Geographic imagery services .....	52
9.4	Service chaining for imagery .....	53
9.5	Service metadata .....	53
10	Engineering Viewpoint – deployment approaches .....	54
10.1	General .....	54
10.2	Distributed system for geographic imagery .....	54
10.3	Imagery Collection Node .....	55
10.4	Sensor Processing Node .....	56
10.5	Imagery Archive Node .....	57
10.6	Value Added Processing Node .....	58
10.7	Decision Support Node .....	59
10.8	Channels: networks and DCPs .....	60
10.8.1	Imagery considerations for channels .....	60
10.8.2	Space to ground communications .....	60
Annex A (normative)	Abstract test suite .....	61
Annex B (informative)	ISO Reference Model for Open Distributed Processing (RM-ODP) .....	63
Annex C (informative)	Imagery use cases .....	64
Annex D (informative)	Principles relating to remote sensing of the Earth from space .....	68
Bibliography	.....	71

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 19101-2 was prepared by Technical Committee ISO/TC 211, *Geographic information/Geomatics*.

ISO 19101 consists of the following parts, under the general title *Geographic information — Reference model*:

- *Part 1: Fundamental*<sup>1)</sup>
- *Part 2: Imagery* [Technical Specification]

---

1) To be published. (Revision of ISO 19101:2002)

## Introduction

This Technical Specification provides a reference model for processing of geographic imagery which is frequently done in open distributed manners. The motivating themes addressed in this reference model are given below.

In terms of volume, imagery is the dominant form of geographic information.

- Stored geographic imagery volume will grow to the order of an exabyte.
- National imagery archives are multiple petabytes in size; ingesting a terabyte per day.
- Individual application data centers are archiving hundreds of terabytes of imagery.
- Tens of thousands of datasets have been catalogued but are not yet online.

Large volumes of geographic imagery will not be portrayed directly by humans. Human attention is the scarce resource, and is insufficient to view petabytes of data. Semantic processing will be required: for example, automatic detection of features; data mining based on geographic concepts.

Information technology allows the sharing of geographic information products through processing of geographic imagery. Standards are needed to increase creation of products. A number of existing standards are used for the exchange of geographic imagery.

Examples of technical, legal, and administrative hurdles to moving imagery online include

- technical issues of accessibility – geocoding, geographic access standards,
- maintenance of intellectual property rights,
- maintenance of individual privacy rights as resolution increases, and
- technical issues of compatibility requiring standards.

Governments have been the predominant suppliers of remotely sensed data in the past. This is changing with the commercialization of remotely sensed data acquisition. Geographic imagery is a key input to decision support for policy makers.

The ultimate challenge is to enable the geographic imagery collected from different sources to become an integrated digital representation of the Earth widely accessible for humanity's critical decisions.

Currently a large number of standards exist that describe imagery data. The processing of imagery across multiple organizations and information technologies (IT) is hampered by the lack of a common abstract architecture. The establishment of a common framework will foster convergence at the framework level. In the future, multiple implementation standards are needed for data format and service interoperability to carry out the architecture defined in this Technical Specification.

The objective of this Technical Specification is the coordinated development of standards that allow the benefits of distributed geographic image processing to be realized in an environment of heterogeneous IT resources and multiple organizational domains. An underlying assumption is that uncoordinated standardization activities made without a plan cannot be united under the necessary framework.

This Technical Specification provides a reference model for the processing of geographic imagery which is frequently done in open distributed manners. The basis for defining an information system in this



Technical Specification is the Reference Model for Open Distributed Processing (RM-ODP) [78]. A brief description of RM-ODP can be referenced in Annex B. The basis for defining geographic information in this specification is the ISO 19100 family of standards.

The RM-ODP [78] viewpoints are used in the following fashion:

- Typical users and their business activities, and policies to carry out those activities, are addressed in the Enterprise Viewpoint.
- Data structures and the progressive addition of value to the resulting products are found in the schemas of the Information Viewpoint.
- Individual processing services and the chaining of services are addressed in the Computational Viewpoint.

Approaches to deploy the components of the Information and Computational viewpoints to distributed physical locations are addressed in the Engineering Viewpoint.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ISO/TS 19101-2:2009](https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-be5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-be5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST-TS ISO/TS 19101-2:2009

<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-bef5-f1f6c26550d5/sist-ts-iso-ts-19101-2-2009>

# Geographic information — Reference model —

## Part 2: Imagery

### 1 Scope

This part of ISO 19101 defines a reference model for standardization in the field of geographic imagery processing. This reference model identifies the scope of the standardization activity being undertaken and the context in which it takes place. The reference model includes gridded data with an emphasis on imagery. Although structured in the context of information technology and information technology standards, this Technical Specification is independent of any application development method or technology implementation approach.

### 2 Conformance

#### 2.1 General

To conform to this Technical Specification, all of the conditions specified for at least one of the conformance classes described below shall be satisfied.

#### 2.2 Enterprise conformance

Any enterprise that claims conformance to this Technical Specification shall satisfy all of the conditions specified in the Test module in A.1.

#### 2.3 Sensor conformance

Any sensor for which conformance to this Technical Specification is claimed shall satisfy all of the conditions specified in the Test module in A.2.

#### 2.4 Imagery data conformance

Any enterprise for which conformance to this Technical Specification is claimed shall satisfy all of the conditions specified in the Test module in A.3.

#### 2.5 Imagery services conformance

Any enterprise for which conformance to this Technical Specification is claimed shall satisfy all of the conditions specified in the Test module in A.4.

#### 2.6 Image processing system conformance

Any image processing system for which conformance to this Technical Specification is claimed shall satisfy all of the conditions specified in the Test module in A.5.

## ISO/TS 19101-2:2008(E)

### 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19115, *Geographic information — Metadata*

ISO 19119:2005, *Geographic information — Services*

ISO 19123, *Geographic information — Schema for coverage geometry and functions*

### 4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 4.1

##### **band**

range of wavelengths of electromagnetic radiation that produce a single response by a sensing device

#### 4.2

##### **calibration**

process of quantitatively defining a system's responses to known, controlled signal inputs

[CEOS WGCV]

#### 4.3

##### **computational viewpoint**

**viewpoint** on an ODP system and its environment that enables distribution through functional decomposition of the system into objects which interact at **interfaces**

[ISO/IEC 10746-3]

#### 4.4

##### **coverage**

**feature** that acts as a function to return values from its range for any direct position within its spatial, temporal, or spatiotemporal domain

[ISO 19123]

#### 4.5

##### **digital elevation model**

dataset of elevation values that are assigned algorithmically to 2-dimensional coordinates

#### 4.6

##### **digital number**

##### **DN**

integer value representing a measurement as detected by a **sensor**

#### 4.7

##### **engineering viewpoint**

**viewpoint** on an ODP system and its environment that focuses on the mechanisms and functions required to support distributed interaction between objects in the system

[ISO/IEC 10746-3]

**4.8****enterprise viewpoint**

**viewpoint** on an ODP system and its environment that focuses on the purpose, scope and policies for that system

[ISO/IEC 10746-3]

**4.9****feature**

abstraction of real world phenomena

[ISO 19101]

**4.10****geographic feature**

representation of real world phenomenon associated with a location relative to the Earth

**4.11****geographic imagery**

**imagery** associated with a location relative to the Earth

**4.12****geographic imagery scene**

**geographic imagery** whose data consists of measurements or simulated measurements of the natural world produced relative to a specified vantage point and at a specified time

[Derived from ISO 22028-1]

NOTE A geographic imagery scene is a representation of an environmental landscape; it may correspond to a remotely sensed view of the natural world or to a computer-generated virtual scene simulating such a view.

**4.13****grid**

network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way

[ISO 19123]

**4.14****imagery**

representation of phenomena as images produced by electronic and/or optical techniques

NOTE In this Technical Specification, it is assumed that the phenomena have been sensed or detected by one or more devices such as radar, cameras, photometers, and infrared and multispectral scanners.

**4.15****information viewpoint**

**viewpoint** on an ODP system and its environment that focuses on the semantics of information and information processing

[ISO/IEC 10746-3]

**4.16****interface**

named set of **operations** that characterizes the behaviour of an entity

[ISO 19119]

## ISO/TS 19101-2:2008(E)

## 4.17

**interoperability**

capability to communicate, execute programs, or transfer data among various functional units in a manner that requires the user to have little or no knowledge of the unique characteristics of those units

[ISO 2382-1]

## 4.18

**knowledge base**

data base of knowledge about a particular subject

NOTE The data base contains facts, inferences, and procedures needed for problem solution [Webster Computer].

## 4.19

**measurable quantity**

attribute of a phenomenon, body or substance that may be distinguished qualitatively and determined quantitatively

[VIM]

## 4.20

**measurement**

set of operations having the object of determining the value of a quantity

[VIM]

## 4.21

**measurand**

particular quantity subject to measurement

[VIM]

EXAMPLE Vapour pressure of a given sample of water at 20 °C.

NOTE The specification of a measurand may require statements about quantities such as time, temperature and pressure.

## 4.22

**metadata**

data about data

[ISO 19115]

## 4.23

**metric traceability**

property of the result of a measurement or the value of a standard whereby it can be related to stated references, usually national or international standards, through an unbroken chain of comparisons all having stated uncertainties

[derived from VIM]

## 4.24

**operation**

specification of a transformation or query that an object may be called to execute

[ISO 19119]

NOTE An operation has a name and a list of parameters.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

SIST-TS ISO/TS 19101-2:2009  
<https://standards.iteh.ai/catalog/standards/sist/9e164975-b98b-4b1b-be5-f18c26550d5/sist-ts-iso-ts-19101-2-2009>

**4.25****orthoimage**

image in which by orthogonal projection to a reference surface, displacement of image points due to sensor orientation and terrain relief has been removed

NOTE The amount of displacement depends on the resolution and the level of detail of the elevation information and on the software implementation.

**4.26****picture original**

representation of a two-dimensional hardcopy or softcopy input image in terms of the colour-space coordinates (or an approximation thereof)

NOTE Picture originals could be obtained from printed maps, printed pictures of a geographic imagery scene, or drawings of geographic information, etc.

**4.27****picture portrayal**

representations of image data in terms of the colour-space coordinates that are appropriate for, and tightly coupled to, the characteristics of a specified real or virtual output device and viewing

NOTE Picture portrayals are geared for visual display whether in hardcopy or softcopy.

**4.28****pixel**

smallest element of a digital image to which attributes are assigned

NOTE 1 This term originated as a contraction of "picture element".

NOTE 2 Related to the concept of a grid cell.

**4.29****policy**

set of rules related to a particular purpose

[ISO/IEC 10746-2]

**4.30****radiance**

at a point on a surface and in a given direction, the radiant intensity of an element of the surface, divided by the area of the orthogonal projection of this element on a plane perpendicular to the given direction

[ISO 31-6]

**4.31****radiant energy**

energy emitted, transferred or received as radiation

[ISO 31-6]

**4.32****record**

finite, named collection of related items (objects or values)

**4.33****remote sensing**

collection and interpretation of information about an object without being in physical contact with the object