

SLOVENSKI STANDARD SIST ETS 300 199 E1:2003

01-december-2003

Digitalno omrežje z integriranimi storitvami (ISDN) – Dopolnilna storitev: predaja klica ob zasedenosti (CFB) – Opis storitve

Integrated Services Digital Network (ISDN); Call Forwarding Busy (CFB) supplementary service; Service description

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten SIST ETS 300 199 Edition 1 https://standards.iteli.avcatalog/standards/sist/05238ae-6521-4507-8ce5-

cf7a8574be8b/sist-ets-300-199-e1-2003

ICS:

33.080 Digitalno omrežje z

integriranimi storitvami

(ISDN)

Integrated Services Digital

Network (ISDN)

SIST ETS 300 199 E1:2003 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 199 E1:2003



EUROPEAN TELECOMMUNICATION

ETS 300 199

December 1994

Source: ETSI TC-NA Reference: DE/NA-012204

ICS: 33.080

Key words: ISDN, supplementary service

iTeh STANDARD PREVIEW
Integrated Services Digital Network (ISDN);

Call Forwarding Busy (CFB) supplementary service

https://standards.iteh.ai**Service**d**description**507-8ce5-cf7a8574be8b/sist-ets-300-199-e1-2003

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Page 2

ETS 300 199: December 1994

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 199 E1:2003

Contents

Fore	eword			5		
1	Scope			7		
2	Normative references7					
3	Definitions					
4	Symbols and abbreviations					
5	Description					
6	Procedures					
	6.1 Provision and withdrawal					
	6.2	Normal p	Normal procedures			
		6.2.1	Activation, deactivation and registration	10		
			6.2.1.1 Activation			
			6.2.1.2 Deactivation	11		
			6.2.1.3 Registration	12		
		6.2.2	Erasure	12		
		6.2.3	Invocation and operation	12		
		iT	e 6.2.3.1 Served user is user determined user busy	12		
			6.2.3.2 Served user is network determined user busy	13		
			6.2.3.3 n a Forwarded-to user's view	13		
			6.2.3.4 Calling user's view			
		6.2.4	Interrogation	15		
	6.3	6.2.4 Interrogation Exceptional procedures 1518 300 199 E12003 6.3.195 //standar Activation, deactivation and registration 4507-8ce5-				
		6 3 PS://standards.fl	Activation, deactivation and registration 4507-8005-	16		
			6.3 ¹⁷ 1.8574be8b/sisActivation 99-e1-2003	16		
			6.3.1.2 Deactivation	17		
			6.3.1.3 Registration			
		6.3.2	Erasure			
		6.3.3	Invocation and operation			
		6.3.4	Interrogation	18		
7	Intercommunication considerations					
	7.1		king with non-ISDNs			
	7.2	Interwork	king with private ISDNs	19		
8	Interac	tion with oth	ner supplementary services	19		
O	8.1 Advice of charge services					
	0	8.1.1	Charging information at call set-up time			
		8.1.2	Charging information during the call			
		8.1.3	Charging information at the end of the call	20		
	8.2 Call waiting					
	8.3					
	8.4	Explicit call transfer				
	8.5	Number identification services				
		8.5.1	Calling line identification presentation			
		8.5.2	Calling line identification restriction			
		8.5.3	Connected line identification presentation			
		8.5.4	Connected line identification restriction			
	8.6		ser group			
	8.7 Completion of calls to busy subscribers					
	8.8		nce services			
		8.8.1	Conference call, add-on			

Page 4 ETS 300 199: December 1994

8.8.2	Meet-me conference	22
Direct dialling in		22
		22
8.10.1		
8.10.2		
8.10.3	Call forwarding no reply	22
8.10.4	Call deflection	22
Freephone		23
Malicious call identification		23
Multiple subscriber number		
Subaddressing		
Terminal portability		
Three party		
User-to-user signalling		24
		25
	Direct dia Diversion 8.10.1 8.10.2 8.10.3 8.10.4 Freephor Malicious Multiple s Subaddre Terminal Three pa User-to-u	Direct dialling in

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 199 E1:2003

Page 5 ETS 300 199: December 1994

Foreword

This European Telecommunication Standard (ETS) has been produced by the Network Aspects (NA) Technical Committee of the European Telecommunications Standards Institute (ETSI).

In accordance with CCITT Recommendation I.130 [1], the following three level structure is used to describe the supplementary telecommunications services as provided by European public telecommunications operators under the pan-European Integrated Services Digital Network (ISDN):

- Stage 1: is an overall service description, from the user's standpoint;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

This ETS details the stage 1 aspects (overall service description) for the Call Forwarding Busy (CFB) supplementary service. The stage 2 and stage 3 aspects are detailed in ETS 300 203 (1994) and ETS 300 207 (1994) respectively.

Proposed transposition dates

Date of latest announcement of this ETS (doa):

31 March 1995

Date of latest publication of new National Standard or endorsement of this ETS (dop/e): PREVIE 30 September 1995

Date of withdrawal of any conflicting National Standard (dow): 30 September 1995

SIST ETS 300 199 E1:2003

Page 6

ETS 300 199: December 1994

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 199 E1:2003

1 Scope

This standard defines the stage one of the Call Forwarding Busy (CFB) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators. Stage one is an overall service description from the user's point of view (see CCITT Recommendation I.130 [1]), but does not deal with the details of the human interface itself.

This standard defines the interworking requirements of private ISDNs with the public ISDN.

In addition this standard specifies the base functionality where the service is provided to the user via a private ISDN.

This standard does not specify the additional requirements where the service is provided to the user via a telecommunications network that is not an ISDN but does include interworking requirements of other networks with the public ISDN.

Charging principles are outside the scope of this standard.

Interaction with supplementary services not listed in clause 8 are outside the scope of this standard.

The CFB supplementary service enables a served user to have the network redirect to another user calls which are addressed to the served user's ISDN number and meet busy. The CFB supplementary service may operate on all calls, or just those associated with specified basic services. The served user's ability to originate calls is unaffected by the CFB supplementary service.

The CFB supplementary service is applicable to all circuit-switched telecommunication services.

This standard is applicable to the stage two and stage three standards for the ISDN CFB supplementary service. The terms "stage two" and "stage three" are also defined in CCITT Recommendation I.130 [1]. Where the text indicates the status of a requirement, (i.e. as strict command or prohibition, as authorization leaving freedom, as a capability or possibility), this shall be reflected in the text of the relevant stage two and stage three standards.

Furthermore, conformance to this standard is met by conforming to the stage three standards with the field of application appropriate to the equipment being implemented. Therefore, no method of testing is provided for this standard.

2 Normative references

This standard incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to, or revisions of, any of these publications apply to this standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

[1]	CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
[2]	CCITT Recommendation I.112 (1988): "Vocabulary of terms for ISDNs".
[3]	CCITT Recommendation I.221 (1988): "Common specific characteristics of services".
[4]	CCITT Recommendation I.210 (1988): "Principles of telecommunication services supported by an ISDN and the means to describe them".
[5]	CCITT Recommendation E.164 (1991): "Numbering plan for the ISDN era".
[6]	CCITT Recommendation Q.9 (1988): "Vocabulary of switching and signalling terms".

Page 8

ETS 300 199: December 1994

3 Definitions

For the purposes of this standard, the following definitions apply:

Integrated Services Digital Network (ISDN): See CCITT Recommendation I.112 [2], § 2.3, definition 308.

(basic) service; telecommunications service: See CCITT Recommendation I.112 [2], § 2.2, definition 201.

served user: The user to whom the CFB supplementary service is provided.

user A: The calling user in a call which is subject to diversion.

user B: The served user when a call (from user A) is subject to the CFB supplementary service.

NOTE: In the context of multiple diversions, a suffix is used, e.g. 1, 2, ... n, n+1, ... m, to

denote the successive diverting users. For example, user B3 is also the diverted-to

user with respect to the diversion applied at user B2.

user C: The forwarded-to user in a call which is subject to the CFB supplementary service. In the case of a call which is subject to multiple diversions, user C is the forwarded-to user with respect to the final call forwarding.

forwarded-to user: A user to whom the call is redirected as a result of forwarding.

diverted-to user: A user to whom a call is redirected as a result of diversion.

busy: See CCITT Recommendation I.221 [3], § 3.1.5. (Standards.iteh.ai)

supplementary service: See CCITT Recommendation I.210 [4], paragraph 2.4.

SIST ETS 300 199 E1:2003

ISDN number: A number conforming into aither numbering is plan 2 and 6 structure 8 cspecified in CCITT

Recommendation E.164 [5]. cf7a8574be8b/sist-ets-300-199-e1-2003

basic access: See CCITT Recommendation Q.9 [6], § 1, definition 1551.

primary rate access: See CCITT Recommendation Q.9 [6], § 1, definition 1552.

address: See CCITT Recommendation E.164 [5], § 12.

subaddress: See CCITT Recommendation E.164 [5], § 12.2.

user determined user busy: see CCITT Recommendation I.221 [3], § 3.1.4.

network determined user busy: See CCITT Recommendation I.221 [3], § 3.1.4.

(call) forwarding: A general term applied to any functionality whereby a call is redirected automatically by the service provider to another user. The forms of forwarding are: unconditional, whereby all calls are redirected; busy, whereby calls encountering busy are redirected; and, no reply, whereby calls which are not answered within a time period are redirected.

diversion: A general term which includes all forms of forwarding, and includes deflection whereby calls are redirected by the user instead of being answered.

Page 9 ETS 300 199: December 1994

basic call procedures: The procedures by which a call (as an instance of a basic telecommunication service) is established and terminated.

diverting user: A user for whom the call is subjected to diversion.

4 Symbols and abbreviations

CFB Call Forwarding Busy

ISDN Integrated Services Digital Network

PSTN Public Switched Telephone Network

5 Description

The CFB supplementary service shall be available to users who are connected to the network via a basic access or a primary rate access.

The CFB supplementary service enables a served user to have the network redirect to another user calls which are addressed to the served user's ISDN number and meet busy. The CFB supplementary service may operate on all calls, or just those associated with specified basic services. The served user's ability to originate calls is unaffected by the CFB supplementary service.

As a service provider option, a subscription option can be provided to enable the served user to receive an indication that the CFB supplementary service has been activated. This indication shall be provided when the served user originates a call if the CFB supplementary service has been activated for the served user's ISDN number and for the basic service requested for the call.

The maximum number of diversions permitted for each call is a service provider option with an upper limit of five diversions. When counting the number of diversions, all types of diversion are included.

6 **Procedures** <u>SIST ETS 300 199 E1:2003</u>

https://standards.iteh.ai/catalog/standards/sist/b58238ae-652f-4507-8ce5-

6.1 Provision and withdrawal/4be8b/sist-ets-300-199-e1-2003

II en STANDAKI

The CFB supplementary service shall be provided after prior arrangement with the service provider.

As a service provider option, the CFB supplementary service can be provided on a per ISDN number basis, or the CFB supplementary service can apply to the whole access. If a service provider offers both of these options, then it shall be a subscription option to choose which of these options applies.

In addition, the CFB supplementary service (including options) can be subscribed to for all basic services subscribed to by the user, or as a service provider option, the user can identify particular basic service(s) for which the CFB supplementary service shall apply.

As a service provider option, the service can be offered with one or more of four subscription options, which can apply separately to each basic service subscribed to. If the CFB supplementary service is provided on a per ISDN number basis, then these options can apply separately to each ISDN number. For each subscription option, only one value can be selected. Subscription options are summarized in table 1.