
**Information to be included in
specification sheets — Data projectors**

*Information à inclure dans les feuilles de spécifications — Projecteurs
de données*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 21118:2005](https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005)

[https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-
361a04172b39/iso-iec-21118-2005](https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 21118:2005

<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Terms and definitions	1
3 Measuring methods and conditions	2
4 Items in specification sheets	2
Annex A (normative) Specification sheets	6
Annex B (informative) Measuring methods and conditions	10
Bibliography	15

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 21118:2005](https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005)

<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 21118 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 28, *Office equipment*.

TECH STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 21118:2005
<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

Information to be included in specification sheets — Data projectors

1 Scope

This International Standard is applicable for information to be included in specification sheets about front projection type, fixed resolution and light valve system, and data projectors having a computer signal input port capable of projecting the image outputs from a computer, VCR or other devices.

NOTE 1 It also covers Data projectors that have a video signal input port as well as a computer signal input port.

NOTE 2 It is not applicable to units with a rear projection system or with a video input terminal alone.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

light valve

a system which creates an optical image by electrical means using light from a separate source

<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

2.2

telephoto end

the maximum focal length position of the zoom lens

2.3

wide-angle end

the minimum focal length position of the zoom lens

2.4

resize

process which converts an input image signal from one resolution and dot number to an image with a different resolution or dot number

2.5

lens shift

a specific function which enables changing the location of the image on the projection screen by moving the lens vertically (up/down) and/or horizontally (left/right) without moving the projector itself

2.6

image position(a measure of the affect of lens shift)

the reference point is defined as the point on the projection screen that is intersected by the physical axis of the projection lens

up image position = (Distance between top edge and reference point)

down image position = (Distance between bottom edge and reference point)

left image position = (Distance between left edge and reference point)

right image position = (Distance between right edge and reference point)

when image position is variable by lens shift feature, maximum and minimum positions should be specified

example specification of image positions for a data projector with lens shift:

up/down 1:10 to 10:1, right /left 1:3 to 3:1

this means that the up image position with maximum lens shift upward is 10 times the up image position with no lens shift

similarly the down image position with maximum lens shift downward is 10 times the down image position with no lens shift

likewise, the right image position with maximum lens shift right is 3 times the right image position with no lens shift

likewise, the left image position with maximum lens shift is 3 times the left image position with no lens shift

note that if there is no lens shift in the horizontal direction right/left 1:1 would be the value given for right/left image position.

2.7

front projection system

a projection system (of a projector) focuses an image onto a screen by projected light. The image from a light-reflecting screen is viewed from the projector side of the screen

2.8

rear projection system

a projection system (of a projector) focuses an image onto a screen by projected light

NOTE The image is viewed from the opposite side of the light transmitting screen.

ISO/IEC 21118:2005
<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

3 Measuring methods and conditions

Annex B (informative) shows measuring methods and conditions for the performance specification items in Table 1.

4 Items in specification sheets

Item, item specification and specification examples are shown in Table 1. They are fundamental properties, which must be included in the specification sheets.

The lower-limit values of the projector must maintain 80% of the values in specification sheets for the brightness, contrast ratio and light output uniformity.

The specification sheets must have a statement, which says that they are made in accordance with this standard.

They must use the same number as Table 1 exactly.

Items may be omitted if the projector has no function for it. When an item is omitted, numbers of the following items may not be changed.

An example specification sheet is shown in Annex A (normative).

NOTE When items and values are extracted from specification sheets, they can be listed in any order and their number may not be specified.

Table 1 — Performance specification item

No.	Item	Item specification	Specification example
1	Product number, type name, or model number	The product name, type name, model numbers, or product numbers must be entered.	
2	Display system	The light valve type must be indicated.	a) LCD, micro mirror, other b) transmitting, reflecting c) single panel, 3 panel, other
3	Optical system	The optics for colour separation and convergence must be indicated.	a) Dichroic mirror separation-prism convergence system b) Time sharing separation/convergence system c) other
4	Display device		
4.1	Size of effective display area	Size, number of panels and aspect ratio must be indicated.	1,3" × 3, aspect ratio 4:3
4.2	Number of pixels	The numbers of pixels per sheet, numbers of sheets, and total numbers of pixels must be indicated.	480 000 pixels (800 × 600) × 3 sheets, 1 440 000 pixels in total
4.3	Other	Features of display device must be indicated.	without micro lens
5	Projection lens		
5.1	Zoom	Zoom magnifications must be indicated.	Power zoom (1× to 1,4×)
5.2	Focus	Method of focus adjustment must be indicated.	Manual, or powered
5.3	Lens shift	Image position for maximum and minimum lens shift (if any) must be specified	Up/down 1:10 to 10:1, right /left 1:3 to 3:1 (in case of variable lens shift in both horizontal and vertical directions) Up/down 10:1 right/left 1:1 (in case of no right/left lens shift)
5.4	Focal length (mm) Aperture	Focal length and Aperture must be indicated.	$f = 52 \text{ mm} - 73 \text{ mm}$ $f/2,5 - 2,9$
6	Light source	The light source lamp type (name), wattage, and quantity must be indicated. Lamp number can be omitted if only one lamp is used.	300 W metal halide lamp
7	Screen size [Projection distance]	The minimum and maximum sizes of the projected image must be indicated. The associated projection distance must also be indicated. Telephoto end is for minimum size and wide-angle end for maximum size must be given for a zoom lens.	Image size 0,4 m × 0,3 m minimum to 2 m × 1,5 m maximum for projection distance 0,8 m minimum to 4 m maximum
8	Number of colours	The maximum number of reproducible colours must be indicated.	Full-colour reproduction (16 700 000 colours)
9	Light output	The light output on a projected screen must be measured and indicated.	Average value of production units must be indicated. 800 lm (see Annex B, B.2.2)
10	Contrast ratio (full white/full black)	The ratio of illuminance between the white and black areas of images must be indicated.	Average value of production units must be indicated. 200:1 (full white/full black) (see Annex B, B.2.3)
11	Light output uniformity	The ratio between the center luminance and 4-peripheral-point average luminance of a full-white image must be indicated.	Average value of production units must be indicated. 85 % (see Annex B, B.2.4)

Table 1 (continued)

No.	Item	Item specification	Specification example
12	Audio output	The output power must be indicated. Either stereo or monaural must be indicated as well.	10 W + 10 W stereo (see Annex B, B.3)
13	Speaker	The diameter and quantity must be indicated.	Ø5 cm × 2
14	Displayable scanning frequency		
14.1	Horizontal	The range of displayable horizontal frequencies must be indicated.	15 kHz to 100 kHz
14.2	Vertical	The range of displayable vertical frequencies must be indicated.	50 Hz to 120 Hz
15	Display resolution		
15.1	For computer signal input	The maximum display resolution for computer input must be indicated. Notational convention method must be indicated as well. When display resolution is beyond the panel native resolution, it also must be indicated. The displayable video signal type (system) and resolution must be indicated. If there are two or more signal types (systems), all of them may be specified.	Maximum display resolution 1024 dots × 768 dots (resizing) Panel display resolution 800 dots × 600 dots
15.2	For video signal input	If there are two or more signal types (systems), all of them may be specified.	NTSC: 550 TV lines, (S-video input) PAL/SECAM: 350 TV lines (see Annex B, B.4)
16	Computer signal input/output	The signal type, connector type and number of connectors must be indicated. Any order of entries and contents are acceptable. If the terminal has several functions, this may be entered as a remark.	RGB input: 2 lines RGB output: 1 line RGB input port (mini-D-sub 15-pin) RGB output port (mini-D-sub 15-pin) Audio input port (RCA pin L/R)
17	Video signal input/output	The signal type, connector type, and number of connectors must be indicated. Any order of entries and contents are acceptable. If the terminal has several functions, this may be entered as a remark.	Video/S-video input: 1 line Video input port (RCA pin) S-video port (mini-DIN 4-pin) Audio input port (RCA pin L/R)
18	Control signal input/output	The control signal input/output port and other relevant descriptions must be given. Any order of entries and contents are acceptable.	RS-232C and mouse input ports
19	Acoustic Noise	If the noise values other than the maximum value is entered, its working condition must be indicated.	Noise measurements must be made by ISO 9296 ^[1] . 35dB(A weighted) At eco mode, 30dB(A weighted) (see Annex B, B.5.2)
20	Operating temperature (operating humidity)	The temperatures (relative humidity) at which the product normally operates must be indicated. The humidity need not always be indicated.	5 °C to 35 °C (20 % to 70 %)
21	Power requirements	The rated voltage and frequency must be indicated.	AC100V, 50/60Hz
22	Power consumption	The maximum power consumption must be indicated in watts. Information about standby and power-saving modes can optionally be entered.	380 W (see Annex B, B.6)

Table 1 (continued)

No.	Item	Item specification	Specification example
23	Outside dimensions	The outside dimensions (width, height, and depth) of the product must be indicated in millimeters. The width, height, and depth may be indicated in any order. If there are any exceptions, they must be specified within parentheses.	W 300 mm × H 150 mm × D 400 mm (without protrusions)
24	Weight	The weight of the product must be indicated in kilograms. If there are any exceptions, they must be specified within parentheses.	15 kg (detachable remote controller included)
25	Accessories	The names and quantities of the accessories supplied together with the product must be indicated.	Remote controller, lens cap, RGB cable, mouse cable, power cable, and instruction manual
26	Other functions	Features and special functions other than those indicated from 1 to 25 must be indicated.	

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 21118:2005](https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005)

<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

Annex A (normative)

Specification sheets

Annex A provides for information to be included in specification sheets.

This specification sheets are made according to ISO 21118.

1 Product number, type name, or model number

Product number: _____ Type name: _____

2 Display system

- | | | |
|--|---|---|
| a) <input type="checkbox"/> Liquid crystal | <input type="checkbox"/> Micro-mirror | <input type="checkbox"/> Other () |
| b) <input type="checkbox"/> Transparent | <input type="checkbox"/> Reflective | |
| c) <input type="checkbox"/> Single display element | <input type="checkbox"/> Three display elements | <input type="checkbox"/> Other () |

3 Optical system

- a) ☐ Dichroic mirror separation/ prism convergence
- b) ☐ Colour wheel
- c) ☐ Other ()

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 21118:2005
<https://standards.iteh.ai/catalog/standards/sist/cb926063-b44a-487e-8b1c-361a04172b39/iso-iec-21118-2005>

4 Display device

- a) Size: _____ type Aspect ratio: _____: _____
- b) Number of pixels: _____ pixels (_____ × _____) × _____ sheets
- Total number of pixels: _____ pixels
- c) Other additional items: _____

5 Projection lens

- | | | | |
|-----------------|-----------------------------------|---------------------------------|--|
| a) Zoom | <input type="checkbox"/> Motor | <input type="checkbox"/> Manual | Zoom ratio _____ : 1 |
| b) Focus | <input type="checkbox"/> Motor | <input type="checkbox"/> Manual | |
| c) Lens shift | <input type="checkbox"/> Fixed | shift amount | _____ |
| | <input type="checkbox"/> Variable | shift amount | (up/down) _____ |
| | | shift amount | <input type="checkbox"/> Motor <input type="checkbox"/> Manual
(left/right) _____ |
| d) Focal length | f= _____ mm - _____ mm | | |
| e) Aperture | f/ _____ - _____ | | |

6 Light source

- a) Lamp type/name _____
- b) Lamp power _____ W
- c) Number of lamps _____ piece(s)

7 Screen size

- a) Minimum screen size _____ type Throw distance _____ m
- b) Maximum screen size _____ type Throw distance _____ m

Specification sheets

8 Number of colours _____

9 Light output _____ 1m

10 Contrast ratio _____ (full white/full black)

11 Light output uniformity _____ %

12 Audio output ☐ Monaural ☐ Stereo ☐ Other ()

Output _____ W

13 Speaker Diameter _____ cm

Number of speaker _____ piece

14 Displayable scanning frequency

Horizontal _____ kHz to _____ kHz

Vertical _____ Hz to _____ Hz

15 Display resolution

15-1 Computer signal input

Maximum input resolution _____ dot X _____ dot

Convention method

Panel native resolution _____ dot X _____ dot

15-2 Video signal input

Displayable signal ☐ NTSC ☐ PAL ☐ SECAM ☐ Other (1080i, 720p, 480p)☐ PAL-M ☐ PAL-N ☐ M-NTSCResolution _____ TV lines ☐ NTSC ☐ PAL ☐ SECAM ☐ Other ()☐ Composite input ☐ S input ☐ Other ()