



Designation: C 726 – 05

Standard Specification for Mineral Fiber Roof Insulation Board¹

This standard is issued under the fixed designation C 726; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers the composition and physical properties of mineral fiber insulation board used above structural roof decks as a base for built-up roofing and single ply membrane systems in building construction.

1.2 The use of thermal insulation materials covered by this specification may be regulated by building codes or other agencies that address fire performance, or both. The fire performance of the material should be addressed through standard fire test methods established by the appropriate governing documents.

1.3 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of the regulatory limitations prior to use.*

2. Referenced Documents

2.1 The following standards, of the issue in effect on the date of material purchase, form a part of this specification to the extent specified herein:

2.2 *ASTM Standards:*²

C 165 Test Method for Measuring Compressive Properties of Thermal Insulations

C 168 Terminology Relating to Thermal Insulating Materials

C 177 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of

the Guarded Hot Plate Apparatus

C 203 Test Methods for Breaking Load and Flexural Properties of Block-Type Thermal Insulation

C 209 Test Methods for Cellulosic Fiber Insulating Board

C 390 Practice for Sampling and Acceptance of Preformed Thermal Insulation Lots²

C 518 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus

C 1363 Test Method for the Thermal Performance of Building Assemblies by Means of a Hot Box Apparatus

D 312 Specification for Asphalt Used in Roofing

D 450 Specification for Coal-Tar Pitch Used in Roofing, Dampproofing, and Waterproofing

D 2126 Test Method for Response of Rigid Cellular Plastics to Thermal and Humid Aging

E 84 Test Method for Surface Burning Characteristics of Building Materials

2.3 *Other Referenced Documents:*

CAN/ULC-S102-M88 Standard Method of Test for Surface Burning Characteristics of Building Materials and Assemblies³

3. Terminology

3.1 *Definitions*—Terms used in this specification are defined in Terminology **C 168**.

4. Ordering Information

4.1 Orders for material purchased under this specification shall include:

4.1.1 Designation of this specification,

4.1.2 Product name,

4.1.3 Board dimensions,

4.1.4 Quantity of material, and

4.1.5 Special packaging or marking, (13.1 and 13.2) if required.

¹ This specification is under the jurisdiction of ASTM Committee C16 on Thermal Insulation and is the direct responsibility of Subcommittee C16.20 on Homogeneous Inorganic Thermal Insulations.

Current edition approved April 1, 2005. Published April 2005. Originally approved in 1972. Last previous edition approved in 2000 as C 726 – 00a.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from Underwriters' Laboratories of Canada, 7 Crouse Road, Scarborough, Ontario, Canada M1R 3A9.