

SLOVENSKI STANDARD
SIST EN 12602:2008+A1:2013

01-november-2013

Nadomešča:
SIST EN 12602:2008

Montažni armirani elementi iz avoklaviranega celičnega betona

Prefabricated reinforced components of autoclaved aerated concrete

Vorgefertigte bewehrte Bauteile aus dampfgehärtetem Porenbeton

iTeh STANDARD PREVIEW
Eléments préfabriqués armés en béton cellulaire autoclavé
(standards.iteh.ai)

Ta slovenski standard je istoveten z:[EN 12602:2008+A1:2013](#)

https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist_en_12602_2008a1_2013

ICS:

91.100.30

Beton in betonski izdelki

Concrete and concrete products

SIST EN 12602:2008+A1:2013

en,fr,de

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 12602:2008+A1:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 12602:2008+A1

July 2013

ICS 91.100.30

Supersedes EN 12602:2008

English Version

Prefabricated reinforced components of autoclaved aerated concrete

Eléments préfabriqués armés en béton cellulaire autoclavé

Vorgefertigte bewehrte Bauteile aus dampfgehärtetem Porenbeton

This European Standard was approved by CEN on 21 March 2008 and includes Amendment 1 approved by CEN on 23 May 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

iTeh STANDARD PREVIEW

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

[SIST EN 12602:2008+A1:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword	10
1 Scope	12
2 Normative references	12
3 Terms, definitions, symbols and abbreviations	14
3.1 Terms and definitions	14
3.2 Symbols	15
3.2.1 General symbols	15
3.2.2 Subscripts	16
3.2.3 Symbols used in this European Standard (including normative annexes, except Annex C)	16
3.3 Abbreviations	22
4 Properties and requirements of materials	22
4.1 Constituent materials of autoclaved aerated concrete	22
4.1.1 General	22
4.1.2 Release of dangerous substances	23
4.2 Autoclaved aerated concrete parameters	23
4.2.1 General	23
4.2.2 Dry density	23
4.2.3 Characteristic strength values	25
4.2.4 Compressive strength	25
4.2.5 Tensile strength and flexural strength	25
4.2.6 Stress-strain diagram	26
4.2.7 Modulus of elasticity	26
4.2.8 Poisson's ratio	26
4.2.9 Coefficient of thermal expansion	27
4.2.10 Drying shrinkage	27
4.2.11 Creep	27
4.2.12 Specific heat	28
4.2.13 Thermal conductivity	28
4.2.14 Water vapour permeability	30
4.2.15 Water tightness	30
4.3 Reinforcement	30
4.3.1 Steel	30
4.3.2 Structural reinforcement	31
4.3.3 Effective diameter of coated bars	32
4.3.4 Non-structural reinforcement	33
4.4 Bond	33
4.5 Thermal prestress	34
4.5.1 General	34
4.5.2 Declared mean initial prestrain $\varepsilon_{0m,g}$	34
5 Properties and requirements of components	35
5.1 General	35
5.1.1 Mechanical resistance	35
5.1.2 Acoustic properties	35
5.1.3 Reaction to fire and resistance to fire	35
5.1.4 Design thermal resistance and design thermal conductivity	36
5.2 Technical requirements and declared properties	36
5.2.1 Dimensions and tolerances	36
5.2.2 Mass of the components	37
5.2.3 Dimensional stability	37
5.2.4 Load-bearing capacity	38
5.2.5 Deflections	38
5.2.6 Joint strength	38

5.2.7	Minimum requirements	39
5.3	Durability	41
5.3.1	General	41
5.3.2	Environmental conditions	41
5.3.3	Corrosion protection of reinforcement	42
5.3.4	Freeze and thaw resistance	43
6	Evaluation of conformity.....	43
6.1	Introduction	43
6.2	Initial type-testing of the component	43
6.3	Factory production control	44
6.3.1	General	44
6.3.2	Process control	44
6.3.3	Finished products	45
6.4	Initial inspection of the factory and the factory production control	45
6.4.1	Information to be supplied.....	45
6.4.2	Inspection.....	45
6.4.3	Reports	46
6.5	Surveillance, assessment and acceptance of the factory production control	46
6.5.1	Inspection tasks	46
6.5.2	Frequency of inspections	46
6.5.3	Reports	46
6.6	Actions to be taken in the event of non-conformity	46
7	Basis for design	54
7.1	Design methods	54
7.2	Limit states	54
7.3	Actions.....	55
8	Marking, labelling and designation	55
8.1	Standard designation.....	55
8.2	Production detail information	56
8.3	Additional information on accompanying documents <small>SIST EN 12602:2008+A1:2013 https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-</small>	56
Annex A (normative) Design by calculation		57
A.1	General	57
A.2	Ultimate limit states (ULS) General design assumptions	57
A.3	Ultimate limit states (ULS): design for bending and combined bending and axial compression.....	59
A.3.1	Design assumptions	59
A.3.2	Stress-strain diagram for AAC.....	59
A.3.3	Stress-strain diagram for reinforcing steel	60
A.3.4	Minimum reinforcement.....	62
A.4	Shear.....	63
A.4.1	Shear design for components predominantly under transverse load	63
A.5	Ultimate limit states induced by structural deformation (buckling).....	68
A.5.1	General	68
A.5.2	Method based on Euler formula	69
A.5.3	Modified model column method	70
A.6	Punching	76
A.6.1	General	76
A.6.2	Scope and definitions	76
A.6.3	Design method for punching shear	78
A.7	Primary torsion/combined primary torsion and shear	79
A.8	Concentrated forces.....	81
A.9	Serviceability limit states (SLS).....	82
A.9.1	General	82
A.9.2	Limitation of stresses under serviceability conditions	82
A.9.3	Serviceability limit states of cracking	83
A.9.4	Serviceability limit states of deformation.....	83

EN 12602:2008+A1:2013 (E)

A.10 Detailing of reinforcement	86
A.10.1 General	86
A.10.2 Bond	87
A.10.3 Anchorage	87
A.11 Support length.....	91
Annex B (normative) Design by testing	93
B.1 General	93
B.2 Safety evaluation.....	94
B.2.1 General	94
B.2.2 Brittle and ductile failure.....	94
B.3 Ultimate limit state	94
B.3.1 General	94
B.3.2 Transversely loaded components	95
B.3.3 Longitudinally loaded components.....	97
B.3.4 Simultaneously transversely and longitudinally loaded wall components	100
B.3.5 Anchorage	101
B.4 Serviceability limit states.....	103
B.4.1 Crack width control.....	103
B.4.2 Deformations.....	103
Annex C (normative) Resistance to fire design of AAC components and structures.....	104
C.1 General	104
C.1.1 Scope.....	104
C.1.2 Distinction between principles and application rules	104
C.1.3 Terms and definitions	104
C.1.4 Symbols.....	106
C.1.5 Units.....	107
C.2 Basic principles.....	108
C.2.1 Performance requirements	108
C.2.2 Design values of material properties	108
C.2.3 Assessment methods	108
C.3 Material properties	109
C.3.1 General	109
C.3.2 AAC	110
C.3.3 Steel	112
C.4 Structural fire design methods	113
C.4.1 General	113
C.4.2 Tabulated data.....	113
C.4.3 Simplified design methods	118
C.4.4 Anchorage	122
C.5 Protective layers	122
Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at elevated temperature.....	123
Annex CB (informative) Joints between AAC components satisfying resistance to fire E.....	126
CB.1 Floor and roof components with dry joints.....	126
CB.2 Floor and roof components with mortar joints	126
CB.3 Vertical and horizontal wall components with dry joints	127
CB.4 Vertical and horizontal wall components with mortar joints.....	127
Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC beams	129
CC.1 Basis of temperature profiles	129
CC.2 Temperature profiles for AAC wall, floor and roof components	129

CC.3 Temperature profiles for AAC beams.....	132
CC.4 Calculation assumptions	141
Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact	142
Annex D (informative) Recommended values for partial safety factors	144
D.1 General	144
D.2 Ultimate Limit States (ULS).....	144
D.3 Serviceability Limit States (SLS)	146
Annex E (informative) Recommendations for the consideration of prestress in the design of prefabricated reinforced AAC components.....	147
E.1 Calculation of prestrain from test results	147
E.1.1 General	147
E.1.2 Symbols.....	148
E.1.3 Cross-section values of AAC components	149
E.1.4 Calculation of prestrain ε_0 from steel measurement.....	149
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account	149
E.3 Splitting forces due to prestress	150
E.4 Methods to prevent end cracks due to prestress	151
Annex F (informative) Statistical methods for quality control.....	152
F.1 Quality control.....	152
Annex G (normative) [A] Factory production control of stainless reinforcing steel based on at least three samples – Minimum acceptance criteria for individual values and corresponding mean values [A]	154
Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of autoclaved aerated concrete under the EC Construction Product Directive, 2005/85/EC.....	155
Z.A.1 Clauses of this European Standard addressing the provisions of EC Construction Products Directive	155
Z.A.2 Procedures for the attestation of conformity of products.....	163
Z.A.2.1 Systems of attestation of conformity	163
Z.A.2.2 EC Certificate and Declaration of conformity	165
Z.A.3 CE marking and labelling.....	166
Z.A.3.1 General	166
Z.A.3.2 Declaration of geometrical data and material properties	167
Z.A.3.3 Declaration of product properties	170
Z.A.3.4 Declaration of compliance with given design specification.....	172
Z.A.3.5 [A] Declaration of compliance with the manufacturers' designed specification [A]	173
Z.A.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue.....	176
Z.A.3.7 [A] Example on Technical information in the CE-marking [A].....	177
Bibliography.....	179

Figures

Figure 1 — Determination of dry thermal conductivity $\lambda_{10\text{dry}}$.....	29
Figure A.1 — Determination of effective span l_{eff}	58
Figure A.2 — Bi-linear stress-strain diagram for AAC in compression for cross-sectional design	60
Figure A.3 — Design stress-strain diagram for reinforcing steel	61
Figure A.4 — Strain diagrams in the ultimate limit state.....	62
Figure A.5 — Notation for components subjected to shear.....	65
Figure A.6 —Structural model and possible load cases for the modified model column method.....	71

Figure A.7 — Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented	74
Figure A.8 — Application of punching provisions in non-standard cases	77
Figure A.9 — Critical perimeter around loaded areas located away from an unsupported edge	77
Figure A.10 — Critical perimeter near an opening	78
Figure A.11 — Critical sections near unsupported edges	78
Figure A.12 — Idealised box section	81
Figure A.13 — Definition of the areas to be introduced in Equation (A.39)	82
Figure A.14 — Moment curvature relationship.....	86
Figure A.15 — Effective length of transverse anchorage bars	89
Figure A.16 — Envelope line for determining the tensile force in the longitudinal reinforcement.....	90
Figure A.17 — Support length a_0	92
Figure B.1 — Definition of shear span l_s	95
Figure B.2 — Typical reinforcement layouts in AAC-components	96
Figure B.3 — Diagram for determination of the column factor k	99
Figure B.4 — N/M - interaction diagram of the cross-section representing the results of three test series 100	
Figure B.5 — Envelope line for determining the section of the actual bending moment, M_{da}	103
Figure C.1 — Coefficient $k_c(\theta)$ allowing for decrease of compressive strength, f_{ck} , of AAC at elevated temperature.....	110
A1 Figure C.2 A1	111
A1 Figure C.3 A1 — Coefficient $k_s(\theta)$ allowing for decrease of characteristic strength f_{yk} of tension and compression reinforcement.....	112
A1 Figure C.4 A1 — Sections of AAC components showing nominal axis distance a and nominal concrete cover c of reinforcement	114
A1 Figure C.5 A1 — Reduction of strength and cross-section for sections exposed to fire	120
A1 Figure C.6 A1 — Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and a_z values.....	120
Figure CA.1 — Stress-strain relationship of AAC under compression at elevated temperature	123
Figure CA.2 — Stress-strain relationship of reinforcing steel at elevated temperature.....	125
Figure CB.1 — Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint.....	126
Figure CB.2 — Examples of mortar joints in structures made of floor or roof components.....	126
Figure CB.3 — Example of dry joints with two sealing strips in structures made of horizontal wall components	127
Figure CB.4 — Examples of thin layer mortar joints in structures made of vertical or horizontal wall components	128
Figure CC.1 — Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m ³	129
Figure CC.2 — Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m ³	130
Figure CC.3 — Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m ³	131
Figure CC.4 — Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m ³	132

Figure CC.5 — Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m ³	133
Figure CC.6 — Temperature profiles in °C for AAC-beams ($b \times h = 150 \text{ mm} \times 200 \text{ mm}$) with a dry density of 300 kg/m ³ , exposed on three sides to standard fire.....	133
Figure CC.7 — Temperature profiles in °C for AAC-beams ($b \times h = 150 \text{ mm} \times 200 \text{ mm}$) with a dry density of 400 kg/m ³ , exposed on three sides to standard fire.....	134
Figure CC.8 — Temperature profiles in °C for AAC-beams ($b \times h = 150 \text{ mm} \times 200 \text{ mm}$) with a dry density of 500 kg/m ³ , exposed on three sides to standard fire.....	135
Figure CC.9 — Temperature profiles in °C for AAC-beams ($b \times h = 150 \text{ mm} \times 200 \text{ mm}$) with a dry density of 600 kg/m ³ , exposed on three sides to standard fire.....	136
Figure CC.10 — Temperature profiles in °C for AAC-beams ($b \times h = 300 \text{ mm} \times 400 \text{ mm}$) with a dry density of 300 kg/m ³ , exposed on three sides to standard fire.....	137
Figure CC.11 — Temperature profiles in °C for AAC-beams ($b \times h = 300 \text{ mm} \times 400 \text{ mm}$) with a dry density of 400 kg/m ³ , exposed on three sides to standard fire.....	138
Figure CC.12 — Temperature profiles in °C for AAC-beams ($b \times h = 300 \text{ mm} \times 400 \text{ mm}$) with a dry density of 500 kg/m ³ , exposed on three sides to standard fire.....	139
Figure CC.13 — Temperature profiles in °C for AAC-beams ($b \times h = 300 \text{ mm} \times 400 \text{ mm}$) with a dry density of 600 kg/m ³ , exposed on three sides to standard fire.....	140
Figure E.1 — Analysis of prestress by means of an assumed external force	148
Figure ZA.1 — Example of CE marking with Method 1	170
Figure ZA.2 — Example of CE marking with Method 2	171
Figure ZA.3a — Example of CE marking with Method 3a.....	173
Figure ZA.3b — Example of CE marking with Method 3b	175
Figure ZA.4 — Example of simplified label. https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013	177
Tables	
Table 1 — Density classes	24
Table 2a A_1 — Compressive strength classes for AAC	25
Table 2b — Drying shrinkage classes for AAC A_1	27
Table 3 — Creep classes	28
Table 4 — Dry thermal conductivity $\lambda_{10\text{dry}}$ of AAC for 50 % and 90 % of production with a confidence level of $\gamma = 90\%$ (compiled according to EN 1745).....	30
Table 5a — List of steel grades for stainless reinforcing steel	31
Table 5b — Mandrel diameter for the bending test	32
Table 5c A_1 — Welding strength classes and welding strength factors k_W	32
Table 6 — Bond classes A_1	33
Table 7 — Prestress classes	34
Table 8 — Dimensional tolerances of components.....	37
Table 9 — Final shrinkage strains $\varepsilon_{0\infty}$ for AAC components	37
Table 10 — Thickness classes of structural components	39
Table 11 — Exposure classes and protective measures related to environmental conditions	42
Table 12 — Initial type-testing of the AAC components	47
Table 13 — Testing of the finished product; AAC components for structural uses	50
Table 14 — Testing of the finished product; AAC components for non-structural uses	53
Table A.1 — Bond Classes	89

Table B.1 — Design loadbearing capacity R_{cd} of components	102
Table C.1 — Thermal conductivity of AAC $\lambda(\theta)$ at elevated temperature	111
Table C.2 — Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m ³ and 700 kg/m ³	114
Table C.3a — Minimum wall thickness and axis distance a_{min} for separating loadbearing AAC walls. AAC dry density 350 kg/m ³ to 700 kg/m ³ and structural or non-structural reinforcement for resistance to fire REI	115
Table C.3b — Minimum wall thickness and minimum axis distance a_{min} for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m ³ to 700 kg/m ³ and structural or non-structural reinforcement for resistance to fire R	115
Table C.4 — Minimum dimensions (height h_{min} and width b_{min}) in mm and minimum axis distance a_{min} in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length 116	
Table C.5 — Minimum thickness h_{min} in mm and minimum axis distance a_{min} in mm of AAC floor and roof components in relation to maximum span length	117
Table C.6 — Reduction of the dimensions of AAC cross-section from fire exposed surfaces	122
Table CA.1 — Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature	123
Table CA.2 — Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature	124
Table CC.1	141
Table CC.2	141
Table CD.1 — Minimum wall thickness and minimum axis distance a_{min} of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m ³ to 700 kg/m ³ with structural or non structural reinforcement for resistance to fire REI-M and EI-M	142
Table CD.2 — Minimum amount of reinforcement for AAC components used in walls with mechanical impact	143
Table D.1 — Safety parameter for failure type	144
Table D.2 — Safety parameter for accuracy when determining the material parameter	144
Table D.3 — Safety parameters depending on variation	145
Table D.4 — Partial safety factors	145
Table F.1 — Control factor k_n as a function of samples n with a fractile value of 5 % ($p = 0,95$) and a confidence level of $\gamma \approx 0,75$ (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of $V_R = 0,10$	153
Table F.2 — Coefficient k_s as a function of samples n with a fractile value of 5 % ($p = 0,95$) and a confidence level $\gamma \approx 0,75$ (using bayesian procedures with "vague" prior distribution).	153
Table ZA.1a — Harmonised clauses for loadbearing wall components	156
Table ZA.1b — Harmonised clauses for retaining wall components	157
Table ZA.1c — Harmonised clauses for roof components	158
Table ZA.1d — Harmonised clauses for floor components	159
Table ZA.1e — Harmonised clauses for linear components	160
Table ZA.1f — Harmonised clauses for non-loadbearing wall and noise barriers components	161
Table ZA.1g — Harmonised clauses for cladding components	162
Table ZA.1h — Harmonised clauses for small box culvert components	163
Table ZA.2a — Systems of attestation of conformity	164
Table ZA.2b — Assignment of evaluation of conformity tasks (for structural components) under system 2+ ¹⁾	164

Table ZA.2c — Assignment of evaluation of conformity tasks (for non structural or light structural components) under system 4 ¹⁾	165
---	-----

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 12602:2008+A1:2013

<https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013>

EN 12602:2008+A1:2013 (E)

Foreword

This document (EN 12602:2008+A1:2013) has been prepared by Technical Committee CEN/TC 177 "Prefabricated reinforced components of autoclaved aerated concrete or light-weight aggregate concrete with open structure", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2014, and conflicting national standards shall be withdrawn at the latest by January 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 23 May 2013.

This document supersedes EN 12602:2008.

The start and finish of text introduced or altered by amendment is indicated in the text by tags **A₁** **A₁**.

A₁ This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association and supports essential requirements of EU Directive(s).

For relationship with EU Directive 89/106/EEC, see informative Annex ZA, which is an integral part of this document. **A₁**

This document uses the methods given in the Guidance paper L, clause 3.3, of the European Commission.
<https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-2b63109571/iteh-ai-12602-2008-1-2013>

This European Standard is used together with a national application document. The national application document may only contain information on those parameters which are left open in this European Standard for national choice, known as Nationally Determined Parameters, to be used for the design of the construction products and civil engineering works to be constructed in the country concerned, i.e.:

- values and/or classes where alternatives are given in this European Standard,
- values to be used where a symbol only is given in this European Standard,
- country specific data (geographical, climatic, etc.), e.g. snow map,
- procedure to be used where alternative procedures are given in this European Standard.

It may contain:

- decisions on the application of informative annexes,
- references to non-contradictory complementary information to assist the user to apply this European Standard.

There is a need for consistency between this document for construction products and the technical rules for works. That means all the information accompanying the CE Marking of the construction products should clearly mention which Nationally Determined Parameters have been taken into account.

EN 12602 describes the design principles and requirements for safety, serviceability and durability of reinforced prefabricated components of autoclaved aerated concrete. The design of the components is based on the limit state concept used in conjunction with partial factors.

EN 12602 is intended to be used together with Eurocodes EN 1990, EN 1991 (all parts) and EN 1998.

Numerical values for partial factors and other reliability parameters are recommended as basic values that provide an acceptable level of reliability. They have been selected assuming that an appropriate level of workmanship and of quality management applies.

This European Standard gives values, procedures and classes with notes indicating where national choices may have to be made. Therefore the National Standard implementing EN 12602 should be used with a national application document containing all Nationally Determined Parameters to be used for the design of prefabricated reinforced components of autoclaved aerated concrete to be constructed in the relevant country.

National choice is allowed in EN 12602 through the following clauses:

A.3.2	A.9.4.1
A.3.3	A.10.2.2
A.4.1.2.1	A.10.3
A.4.1.3.2	B.3.2.2
A.4.1.3.3	B.3.3.2
A.5.2	B.3.3.3.2
A.5.3.3.3 (3)	Annex D

iTeh STANDARD PREVIEW (standards.iteh.ai)

A.8

[SIST EN 12602:2008+A1:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/bbdd560d-ac25-47a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013>

Regulatory classes are only given for "Reaction to fire" and "Resistance to fire". All other classes used in this European Standard, i.e. density classes and strength classes, are technical classes.

Annexes A, B, C, CA,  CC, CD and G  are normative.

Annexes CB, D, E, F and ZA are informative.

This document includes a Bibliography.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

EN 12602:2008+A1:2013 (E)

1 Scope

This European Standard is for prefabricated reinforced components of autoclaved aerated concrete to be used in building construction for:

a) Structural elements:

- loadbearing wall components;
- retaining wall components;
- roof components;
- floor components;
- linear components (beams and piers).

b) Non-structural elements:

- nonloadbearing wall components (partition walls);
- cladding components (without fixtures) intended to be used for external facades of buildings;
- small box culverts used to form channels for the enclosure of services;
- components for noise barriers.

**ITech STANDARD PREVIEW
(standards.iteh.ai)**

Depending on the type and intended use of elements for which the components are utilised, the components can be applied - in addition to their loadbearing and encasing function - for purposes of fire resistance, sound insulation and thermal insulation indicated in the relevant clauses of this European Standard.
EN 12602:2008+A1:2013
http://standard.iteh.ai/catalog/standards/estbhd560aac2347a9-85e6-8b68130b8713/sist-en-12602-2008a1-2013

Components covered by this standard are only intended to be subjected to predominantly non-dynamic actions, unless special measures are introduced in the relevant clauses of this European Standard.

The term "reinforced" relates to reinforcement used for both structural and non-structural purposes.

This European Standard does not cover:

- rules for the application of these components in structures;
- joints (except their strength and integrity E of resistance to fire);
- fixtures;
- finishes for external components, such as tiling.

NOTE AAC components may be used in noise barriers if they are designed to fulfil also the requirements of EN 14388.

2 Normative references

A1 The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies. **A1**

EN 678, *Determination of the dry density of autoclaved aerated concrete*

EN 679, *Determination of the compressive strength of autoclaved aerated concrete*

EN 680, *Determination of the drying shrinkage of autoclaved aerated concrete*

EN 772-16, *Methods of test for masonry units — Part 16: Determination of dimensions*

EN 772-20, *Methods of test for masonry units — Part 20: Determination of flatness of faces of aggregate concrete, manufactured stone and natural stone masonry units*

EN 989, *Determination of the bond behaviour between reinforcing bars and autoclaved aerated concrete by the "Push-Out" test*

EN 990, *Test methods for verification of corrosion protection of reinforcement in autoclaved aerated concrete and lightweight aggregate concrete with open structure*

EN 991, *Determination of the dimensions of prefabricated reinforced components made of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1351, *Determination of flexural strength of autoclaved aerated concrete*

EN 1352, *Determination of static modulus of elasticity under compression of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1355, *Determination of creep strains under compression of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1356, *Performance test for prefabricated reinforced components of autoclaved aerated concrete or lightweight aggregate concrete with open structure under transverse load*

**The STANDARD PREVIEW
(standard preview)**

EN 15304, *Determination of the freeze-thaw resistance of autoclaved aerated concrete*

EN 1737, *Determination of shear strength of welded joints of reinforcement mats or cages for prefabricated components made of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

https://standards.iec.ch/catalog/standards/sist_en_12602-2008_a1-2013/8b68130b8713/sist_en_12602-2008_a1-2013

EN 1738, *Determination of steel stresses in unloaded reinforced components made of autoclaved aerated concrete*

EN 1739, *Determination of shear strength for in-plane forces of joints between prefabricated components of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1740, *Performance test for prefabricated reinforced components made of autoclaved aerated concrete or lightweight aggregate concrete with open structure under predominantly longitudinal load (vertical components)*

EN 1741, *Determination of shear strength for out-of-plane forces of joints between prefabricated components made of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1742, *Determination of shear strength between different layers of multilayer components made of autoclaved aerated concrete or lightweight aggregate concrete with open structure*

EN 1992-1-1:2004, *Eurocode 2: Design of concrete structures — Part 1-1: General rules and rules for buildings*

EN 10080, *Steel for the reinforcement of concrete — Weldable reinforcing steel — General*

EN 10088-5, *Stainless steels — Part 5: Technical delivery conditions for bars, rods, wire, sections and bright products of corrosion resisting steels for construction purposes*

EN 12269-1, *Determination of the bond behaviour between reinforcing steel and autoclaved aerated concrete by the "beam test" — Part 1: Short term test*

EN 12269-2, *Determination of the bond behaviour between reinforcing steel and autoclaved aerated concrete by the "beam test" — Part 2: Long term test*