



SLOVENSKI STANDARD

oSIST prEN 16772:2014

01-oktober-2014

Kakovost vode - Navodila za metode vzorčenja nevretenčarjev v hiporhaičnih conah rek

Water quality - Guidance on methods for sampling invertebrates in the hyporheic zone of rivers

Wasserbeschaffenheit - Anleitung für die Probenahme von Invertebraten (Wirbellosen) in der hyporheischen Zone von Flüssen

Qualité de l'eau - Lignes directrices relatives aux méthodes d'échantillonnage des invertébrés dans la zone hyporhéique de rivières

Ta slovenski standard je istoveten z: prEN 16772

ICS:

13.060.10	Voda iz naravnih virov	Water of natural resources
13.060.70	Preiskava bioloških lastnosti vode	Examination of biological properties of water

oSIST prEN 16772:2014

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 16772

July 2014

ICS 13.060.70

English Version

Water quality - Guidance on methods for sampling invertebrates in the hyporheic zone of rivers

Qualité de l'eau - Lignes directrices relatives aux méthodes
d'échantillonnage des invertébrés dans la zone
hyporhéique de rivières

Wasserbeschaffenheit - Anleitung für die Probenahme von
Invertebraten (Wirbellosen) in der hyporheischen Zone von
Flüssen

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 230.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

	Page
Foreword.....	3
Introduction	4
1 Scope	6
2 Terms and definitions	6
3 Survey objectives	8
4 Sampling strategy	9
5 Sampling methods.....	10
5.1 General.....	10
5.2 Karaman-Chappuis pit [15]	10
5.3 Bou-Rouch pump [16]	11
5.4 Vacuum pump [18].....	13
5.5 Standpipe trap [19]	15
5.6 Williams corer [5].....	16
5.7 Colonization devices [21].....	17
5.8 Freeze coring [22]	19
6 Sample processing	20
Annex A (informative) Examples of sampling strategies for three different types of investigation.....	21
A.1 Case Study 1 – Assessing regional biodiversity and species richness	21
A.2 Case Study 2 – Assessing impacts on fish spawning sites.....	21
A.3 Case Study 3: Assessing the impacts of pollution	21
Bibliography	22

Foreword

This document (prEN 16772:2014) has been prepared by Technical Committee CEN/TC 230 “Water analysis”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16772:2016

<https://standards.iteh.ai/catalog/standards/sist/2e93a73d-4697-4af4-a79a-a25dfe059619/sist-en-16772-2016>

Introduction

The term "hyporheic" is derived from two Greek words: *hypo* (under) and *rheos* (flow), and was first used by Orghidan in 1959 [1] to delineate the area of saturated subsurface sediments beneath and lateral to the wetted channel that contains a mix of surface water and groundwater. In the last 50 years, scientific understanding of the hyporheic zone has improved [2] and the term has been modified and expanded by hydrologists, hydrogeologists, chemists and biologists to reflect the importance of:

- the upwelling and downwelling of water into and out of the stream bed and the mixing ratio of surface water and groundwater;
- the nature and rate of biogeochemical processes resulting from upwelling of interstitial water or downwelling of surface water;
- the ecotonal nature of the hyporheic zone which provides important habitat for benthic taxa, specialist hyporheic organisms and groundwater fauna, including both macroinvertebrates and meiofauna. The latter include Microcrustacea, Rotifera and Nematoda as well early instars of many aquatic insects.

In this standard the hyporheic zone is defined as the spatio-temporally dynamic ecotone between the surficial benthic sediments and the underlying aquifer. Within the hyporheic zone, water, solutes and biota are exchanged with the stream above, the groundwater below and the saturated sediments lateral to the channel. The term "hyporheic zone" is applied to the physical habitat while the term "hyporheos" coined by Williams and Hynes in 1974 [4] is used to describe the faunal community inhabiting it.

Over the past few decades, the importance of the hyporheic zone has been increasingly recognized, with the vertical dimension added to spatial concepts of lateral and longitudinal connectivity. Together with the temporal dimension this has created a four-dimensional understanding of river ecosystems [4, 5, 6]. As the hyporheic zone is an ecotone between surface water and groundwater, abiotic conditions may reflect a transition between the two. Table 1 provides a general comparison of the physical characteristics of each environment.

Table 1 — Physical characteristics of typical groundwater and hyporheic environments compared with surface waters

Physical characteristic	Groundwater	Hyporheic
Light	Constant darkness	Constant darkness
Current velocity	Much lower	Lower
Annual and daily temperature range	Much smaller	Smaller
Substrate stability	Much higher	Higher

Approaches to river conservation and management recognize the need for a better understanding of the interactions between surface water and groundwater when undertaking investigations in the field. As the ecotone between the two, the hyporheic zone plays a vital part in ecosystem functioning in many rivers, including a critical role in the flow of energy, cycling of nutrients and organic compounds, as well as pollution attenuation. The hyporheic zone contributes to overall river biodiversity. It also provides a nursery for young life-stages of some fish and invertebrates and a potential refuge for benthos during adverse environmental conditions, such as flooding, low flows, chemical pollution, stream-bed drying or freezing. The hyporheic zone may therefore enhance the recovery of the benthic community following disturbance.

An increased interest in the hyporheic zone has resulted, in part, from international legislation, such as EC directives: the Habitats Directive [9], the Water Framework Directive [10], the Groundwater Directive [11] and the Nitrates Directive [12]. Although investigations into the hyporheic zone are not explicit within these directives, they do require national regulatory authorities to adopt a more integrated approach to the management of river catchments as a whole. Consequently, an understanding of the hyporheic zone, including its functions and the potential threats to these, is vital in order to comply fully with the requirements of these directives.

Investigations of the hyporheic zone may also be needed more generally for catchment management, river restoration, site-based investigations or for research. Consequently, the purpose of any study should be carefully considered when selecting the most appropriate method for sampling the hyporheos, especially if the collection of water quality and associated sediment data is also required.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 16772:2016

<https://standards.iteh.ai/catalog/standards/sist/2e93a73d-4697-4af4-a79a-a25dfe059619/sist-en-16772-2016>

1 Scope

This document provides guidance on methods for sampling invertebrates in the hyporheic zone of wadable rivers. It describes each method, including details of the equipment involved and its use in the field. Guidance is given on developing a sampling strategy and selecting an appropriate survey technique for the purpose of investigation. Benthic macroinvertebrate sampling is covered elsewhere by other published standards (see bibliography). Selected literature with references in support of this document is given in the bibliography.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

- 2.1**
aquifer
underground layer of water-bearing permeable rock or unconsolidated sediments from which groundwater can be extracted
- 2.2**
benthic
relating to the surface sediments
- 2.3**
benthos
faunal community inhabiting the surface sediments of rivers
- 2.4**
biofilm
coating on a substrate composed of microorganisms, extra-cellular polysaccharides, other materials that organisms produce, and particles trapped or precipitated within the matrix
- 2.5**
biomass
total mass of living organisms per unit surface area or volume
- 2.6**
catchment basin
area from which precipitation and groundwater will collect and contribute to the flow of a specific river
- 2.7**
diversity
taxonomic richness of a community and the distribution of individuals across taxa
- 2.8**
downwelling
movement of water in a downward direction, typically from the surface stream to the hyporheic zone or groundwater
- 2.9**
ecotone
transition area between two adjacent ecosystems
- 2.10**
exposed river sediments
particles, typically comprising cobbles, gravel, sand and silt, deposited by flowing water but exposed as water levels fall

2.11**groundwater**

all water that is below the surface of the ground

2.12**hyporheic flow**

flow of water through the hyporheic zone

2.13**hyporheic zone**

spatio-temporally dynamic ecotone between the surficial benthic sediments and the underlying aquifer

2.14**hyporheos**

faunal community inhabiting the hyporheic zone

2.15**interstitial**

referring to the spaces between sediment particles

2.16**macroinvertebrate**

invertebrate that is easily visible without magnification

[SOURCE: EN ISO 10870:2012, definition 2.8 – modified, "(> 0,5 mm)" was not adopted]

2.17**meiofauna**

invertebrates that pass through a 500- μ m or 1-mm sieve but are retained on a 45 μ m- or 63- μ m sieve

2.18**permeability**

capacity of a rock or sediments to transmit water

2.19**pool**

habitat feature characterized by distinctly deeper parts of the channel that are usually no longer than one to three times the channel's bankfull width, and where the hollowed river bed profiles are sustained by scouring

[SOURCE: EN 14614: 2004, definition 2.24]

2.20**porosity**

proportion of a given volume of rock or sediments that is occupied by pores

2.21**reach**

major sub-division of a river, defined by physical, hydrological, and chemical character that distinguishes it from other parts of the river system upstream and downstream

[SOURCE: EN 14614: 2004, definition 2.25]

2.22**riffle**

fast-flowing shallow water with distinctly broken or disturbed surface over gravel/pebble or cobble substrate

[SOURCE: EN 14614: 2004, definition 2.28]

prEN 16772:2014 (E)**2.23****riparian zone**

area of land adjoining a river channel (including the river bank) capable of directly influencing the condition of the aquatic ecosystem (e.g. by shading and leaf litter input)

[SOURCE: EN 14614: 2004, definition 2.29 – modified, the NOTE was not adopted]

2.24**stream ordering**

methods for classifying rivers and streams related to the complexity of the drainage basin, generally with progressively higher order numbers usually assigned to streams with greater discharge lower down the catchment.

[SOURCE: EN 14614: 2004, definition 2.37]

2.25**substrate**

material making up the bed of a river

[SOURCE: EN 14614: 2004, definition 2.40]

2.26**upwelling**

movement of water in an upward direction, typically from the groundwater or hyporheic zone to the surface stream.

3 Survey objectives

The objectives of the survey should be clearly defined before selecting which method to use for sampling the hyporheic zone, because the suitability of each method varies according to the purpose of study. Table 2 summarizes each sampling method according to its suitability for particular objectives. This includes consideration of:

- attributes and variations in hyporheic fauna, sediments and the interstitial environment;
- whether the method can be applied instream and/or in the riparian zone;
- whether data collected are fully quantitative or semi-quantitative.

All methods can be used to describe diversity, taxon richness, abundance and biomass, recognizing their known limitations.

Table 2 — Overview of sampling methods described in this standard and their suitability for particular surveys

	Karaman-Chappuis pit	Bou-Rouch pump	Vacuum pump	Stand-pipe trap	Williams corer	Colonization devices	Freeze coring
Migration/dispersal	No	No	No	Yes	No	Yes	No
Spatial heterogeneity	No	Yes	Yes	Yes	Yes	Yes	Yes
Temporal variability	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Interstitial sediment transport	No	No	No	Yes	No	Yes	No
Sediment characteristics	No	No	No	No	No	No	Yes
Used instream	No	Yes	Yes	Yes	Yes	Yes	Yes
Used in riparian zone	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Quantitative	No	No	No	No	Yes	Yes	Yes
Semi-quantitative	No	Yes	Yes	Yes	Yes	No	No

SIST EN 16772:2016

4 Sampling strategy

The design of a sampling strategy will vary according to the purpose of the investigation. Sampling site location may be influenced by pre-existing monitoring networks or previous investigations. The following should be considered:

- sampling method;
- number and location of sampling sites;
- number of replicates per site required to characterize site heterogeneity (e.g. upwelling and downwelling, sediment characteristics);
- sampling frequency;
- sampling depth;
- seasonal variability;
- abiotic data requirements;
- spatial and temporal scale of investigation.

Scale is important when examining the hyporheic zone, as various processes occur at different spatial scales. For example, at a stream-bed (patch) scale the size, shape, sorting and stability of sediments are the primary determinants of porosity and permeability. These factors have a major influence on community composition