

SLOVENSKI STANDARD SIST ISO 7870-1:2010

01-julij-2010

Nadomešča: SIST ISO 7870:1996

Kontrolne (procesne) karte - 1. del: Splošne smernice

Control charts - Part 1: General guidelines

iTeh STANDARD PREVIEW Cartes de contrôle - Partie 1: Lignes directrices générales (standards.iteh.ai)

Ta slovenski standard je istoveten zsr ISOISO-7870-1:2007 https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-

<u>ICS:</u>

03.120.30 Uporaba statističnih metod

Application of statistical methods

SIST ISO 7870-1:2010

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 7870-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010

SIST ISO 7870-1:2010

INTERNATIONAL STANDARD

ISO 7870-1

First edition 2007-10-01

Control charts —

Part 1: General guidelines

Cartes de contrôle —

Partie 1: Lignes directrices générales iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 7870-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010



Reference number ISO 7870-1:2007(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 7870-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewordiv		
Intro	duction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	6
5	Concepts	6
5.1	Control chart	6
5.2	Statistical control of a process	7
5.3	Acceptance of a process	7
5.4	Management of a process with a natural drift	8
5.5	Risks of decision errors	8
5.6	Design of data collection	8
5.7	Control charts for variables and attributes data	9
6	Types of control charts S.T.A. N.D.A.D.D.D.D.D.D.D.D.D.D.D.D.D.D.D.D.D.	10
7	Charts for process stability	
7.1	General (standards.iteh.ai)	
7.2	Partial listing of Shewhart and related control charts	
8	Charts for process acceptance ^{SIST ISO 7870-1:2010}	
8.1	General https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-	
8.2	Acceptance control charts ⁷ ca6775df205/sist-iso-7870-1-2010	
8.3	Modified control charts (control charts with modified limits)	13
9	Process adjustment	13
Biblio	ography	15
2.2.10	עייי,	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 7870-1 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 4, *Applications of statistical methods in process management*.

This first edition of ISO 7870-1 cancels and replaces ISO 7870:1993.

(standards.iteh.a

ISO 7870 consists of the following parts, under the general title Control charts:

— Part 1: General guidelines

<u>SIST ISO 7870-1:2010</u> ps://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010

The following parts are planned:

- Part 2: Shewhart control charts
- Part 3: Process acceptance control charts
- Part 4: Process adjustment control charts
- Part 5: Specialized control charts
- Part 6: Guide to the application of statistical control charts

Introduction

Every production, service, or administrative process contains a certain amount of variability due to the presence of a large number of causes. The observed results from a process are, as a result, not constant. Studying this variability to gain an understanding of its characteristics provides a basis for taking action on a process.

Control charts are a fundamental tool of statistical process control (SPC). They provide a simple graphical method that can be used to:

- a) indicate if the process is, or is not, stable, i.e. operating within a stable system of random causes, also known as inherent variability and referred to as being in a "state of statistical control";
- b) estimate the magnitude of the inherent variability of the process;
- c) compare information from samples representing the current state of a process against limits reflecting this variability, with the objective of determining whether the process has remained stable or not and variability has been reduced or not;
- d) identify, investigate and possibly reduce/eliminate the effect of special causes of variability, which may drive the process to an unacceptable level of performance:
- e) aid in the regulation of a process through the identification of patterns of variability such as trends, runs, cycles and the like;
- f) determine if the process is behaving in a predictable and stable manner so that it will be possible to assess if the process is able to meet specifications, tebb9250-273a-45ta-9a38-7ca6775df205/sist-iso-7870-1-2010
- g) determine whether or not the process can be expected to satisfy product or service requirements and process capability for the characteristic(s) being measured;
- h) provide a basis for process adjustment through prediction using statistical models;
- i) assist in the assessment of the performance of a measurement system.

A major virtue of the control chart is its ease of construction and use. It provides the production or service operator, engineer, administrator and manager with an on-line indicator about the behaviour of the process. However, in order for the control chart to be a reliable and efficient indicator of the state of the process, careful attention must be paid at the planning stage to such matters as selecting the appropriate type of chart for the process under study and determining a proper sampling scheme.

General concepts useful to a successful design of a control chart are presented in this part of ISO 7870.



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 7870-1:2010</u> https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010

Control charts —

Part 1: General guidelines

1 Scope

This part of ISO 7870 presents key elements and philosophy of the control chart approach, and identifies a wide variety of control charts (including those related to the Shewhart control chart and those stressing process acceptance or on-line process adjustment).

It presents an overview of the basic principles and concepts and illustrates the relationship among various control chart approaches to aid in the selection of the most appropriate standard for given circumstances. It does not specify statistical control methods using control charts. These methods will be specified in future parts of ISO 7870.

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies: tandards/sist/eb69250-273a-45ta-9a38-7ca6775dt205/sist-iso-7870-1-2010

ISO 3534-2:2006, Statistics — Vocabulary and symbols — Part 2: Applied statistics

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3534-2 and the following apply. In some cases, additional clarification on terms from ISO 3534-2 is provided.

3.1

control chart

chart on which some statistical measure of a series of samples is plotted in a particular order to steer the process with respect to that measure and to control and reduce variation

NOTE 1 The particular order is usually based on time or sample number order.

NOTE 2 The control chart operates most effectively when the measure is a process variable which is correlated with an ultimate product or service characteristic.

[ISO 3534-2:2006, 2.3.1]

3.2

Shewhart control chart

control chart with Shewhart control limits intended primarily to distinguish between the variation in the plotted measure due to random causes and that due to special causes

[ISO 3534-2:2006, 2.3.2]

3.3

acceptance control chart

control chart intended primarily to evaluate whether or not the plotted measure can be expected to satisfy specified tolerances

[ISO 3534-2:2006, 2.3.3]

3.4

process adjustment control chart

control chart which uses a prediction model of the process to estimate and plot the future course of the process if no change is made, and to quantify the change to be made to keep the process deviations within acceptable limits

[ISO 3534-2:2006, 2.3.3]

3.5

cumulative sum control chart CUSUM chart

control chart where the cumulative sum of deviations of successive sample values from a reference value is plotted to detect shifts in the level of the measure plotted

NOTE 1 The ordinate of each plotted point represents the algebraic sum of the previous ordinate and the most recent deviation from the reference, target or control value.

NOTE 2 value. The best discrimination of changes in level is achieved when reference value is equal to the overall average iTeh STANDARD PREVIEW

NOTE 3 The chart can be used in control, diagnostic or predictive mode.

NOTE 4 When used in control mode it can be interpreted graphically by a mask (e.g. *V*-mask) superimposed on the graph. A signal occurs if the path of the CUSUM intersects of touches the boundary of the mask.

[ISO 3534-2:2006, 2.3.5]

https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-7ca6775df205/sist-iso-7870-1-2010

3.6

variables control chart

Shewhart control chart in which the measure plotted represents data on a continuous scale

[ISO 3534-2:2006, 2.3.6]

3.7

attribute control chart

Shewhart control chart in which the measure plotted represents countable or categorized data

[ISO 3534-2:2006, 2.3.7]

3.8

c chart

count control chart attribute control chart for the number of incidences where the opportunity for occurrence is fixed

NOTE Incidences of a particular type, for example, number of absentees, number of sales leads, form the count. In the quality field, incidences are often expressed as nonconformities and the fixed opportunity relates to samples of

constant size or fixed amount of material. Examples are "flaws in each 100 square metres of fabric" and "errors in each 100 invoices".

[ISO 3534-2:2006, 2.3.8]

3.9 u chart count per unit control chart

attribute control chart for the number of incidences per unit where the opportunity is variable

NOTE Incidences of a particular type, for example, number of absentees and number of sales leads, form the count. In the quality field, incidences are often expressed as nonconformities and the variable opportunity relates to subgroups of variable size or variable amounts of material.

[ISO 3534-2:2006, 2.3.9]

3.10

np chart

number of categorized units control chart

attribute control chart for number of units of a given classification where the sample size is constant

NOTE In the quality field, the classification usually takes the form of "nonconforming units".

[ISO 3534-2:2006, 2.3.10]

3.11

p chart

proportion or percent categorized units control chart

attribute control chart for number of units of a given classification per total number of units in the sample expressed either as a proportion or percent

NOTE 1 In the quality field, the classification usually takes the form of "nonconforming unit".

NOTE 2 The "p" chart is applied particularly when the sample size is variable.

NOTE 3 The plotted measure can be expressed as a proportion or as a percentage.

https://standards.iteh.ai/catalog/standards/sist/eb6b9250-273a-45fa-9a38-

[ISO 3534-2:2006, 2.3.11]

7ca6775df205/sist-iso-7870-1-2010

3.12

Xbar control chart

average control chart

variables control chart for evaluating the process level in terms of subgroup averages

[ISO 3534-2:2006, 2.3.12]

3.13

median control chart

variables control chart for evaluating the process level in terms of subgroup medians

[ISO 3534-2:2006, 2.3.13]

3.14

moving average control chart

control chart for evaluating the process level in terms of the arithmetic average of each successive n observations

NOTE 1 This chart is particularly useful when only one observation per subgroup is available. Examples are process characteristics such as temperature, pressure and time.

NOTE 2 The current observation replaces the oldest of the latest *n* + 1 observations.

NOTE 3 It has the disadvantage of an unweighted carry-over effect lasting *n* points.

[ISO 3534-2:2006, 2.3.14]