



SLOVENSKI STANDARD

SIST EN 2665-001:2014

01-marec-2014

Nadomešča:

SIST EN 2665-001:2002

Aeronavtika - Odklopniki, tripolni, temperaturno kompenzirani, za naznačene tokove od 20 A do 50 A - 001. del: Tehnična specifikacija

Aerospace series - Circuit breakers, three-pole, temperature compensated, rated current 20 A to 50 A - Part 001: Technical specification

Luft- und Raumfahrt - Schutzschalter, dreipolig, temperaturkompensiert, Nennströme von 20 A bis 50 A - Teil 001: Technische Lieferbedingungen

Série aérospatiale - Disjoncteurs tripolaires compensés en température, intensités nominales 20 A à 50 A - Partie 001: Spécification technique

Ta slovenski standard je istoveten z: EN 2665-001:2013

ICS:

49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems
--------	--	--

SIST EN 2665-001:2014

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 2665-001:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014>

EUROPEAN STANDARD

EN 2665-001

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2013

ICS 49.060

English Version

Aerospace series - Circuit breakers, three-pole, temperature compensated, rated current 20 A to 50 A - Part 001: Technical specification

Série aérospatiale - Disjoncteurs tripolaires compensés en température, intensités nominales 20 A à 50 A - Partie 001 : Spécification technique

Luft- und Raumfahrt - Schutzschalter, dreipolig, temperaturkompensiert, Nennströme von 20 A bis 50 A - Teil 001: Technische Lieferbedingungen

This European Standard was approved by CEN on 28 September 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Description	4
5 Design	5
6 Characteristic	6
7 Tests.....	7
8 Qualification tests.....	15
9 Quality assurance	18
10 Marking	18
11 Delivery conditions.....	18
12 Packaging	19
13 Storage.....	19

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 2665-001:2014
<https://standards.itech.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014>

Foreword

This document (EN 2665-001:2013) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2014, and conflicting national standards shall be withdrawn at the latest by June 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 2665-001:1999.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

[SIST EN 2665-001:2014](https://standards.iteh.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014)

<https://standards.iteh.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014>

EN 2665-001:2013 (E)**1 Scope**

This European Standard specifies the three-pole temperature compensated circuit breakers without signal contacts, rated from 20 A to 50 A and used in aircraft on-board circuits. It describes specific environmental, electrical and mechanical characteristics and the stringency of tests to be applied according to test methods of EN 3841-100.

These circuit breakers are intended for use in aircraft with electrical supplies in accordance with EN 2282.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies..

EN 2083, *Aerospace series — Copper or copper alloy conductors for electrical cables — Product standard*

EN 2282, *Aerospace series — Characteristics of aircraft electrical supplies*

EN 2665-004, *Aerospace series — Circuit breakers, three-pole, temperature compensated, rated current 20 A to 50 A — Part 004: UNC thread terminals — Product standard*

EN 2825, *Aerospace series — Burning behaviour of non metallic materials under the influence of radiating heat and flames — Determination of smoke density*

EN 2826, *Aerospace series — Burning behaviour of non metallic materials under the influence of radiating heat and flames — Determination of gas components in the smoke*

EN 3841-100 (all parts), *Aerospace series — Circuit breakers — Test Methods — Part 100: General*

EN 3844-1, *Aerospace series — Flammability of non metallic materials — Part 1: Small burner test, vertical — Determination of the vertical flame propagation*

EN 9133, *Aerospace series — Quality management systems — Qualification procedure for aerospace standards*

TR 6083, *Aerospace series — Cut-outs for installation of electrical components* ¹⁾

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3841-100 apply.

4 Description

These circuit breakers are operated by a "push-pull" type single push button (actuator) and with delayed action "trip-free" tripping. Their function is assured up to the short-circuit current.

1) Published as ASD-STAN Technical Report at the date of publication of this standard. <http://www.asd-stan.org/>

5 Design

5.1 Materials

5.1.1 Metallic materials

All metallic parts shall be resistant to corrosion or finished against corrosion. When dissimilar materials are in close contact, an adequate protection against corrosion shall be used so that the electromotive force of the galvanic couple does not exceed 0,25 V.

When bimetals are used, an eventual corrosion shall not affect the good operation of the circuit breaker.

5.1.2 Insulation materials

The insulating parts shall be made of auto-extinguishing or non-flammable materials; they shall not emit damaging or explosive vapours, even in presence of fire or internal electric arc.

They shall be insensitive to moulds and microorganisms action.

Application of any material or protective coating, which might crack, break on flake shall be forbidden.

Materials which are not specified or which are not specially described shall be as light as possible for the requested use.

Materials shall be selected according to security criteria (toxicity, smoke density) as defined in contractual documents.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

5.2 Design

[SIST EN 2665-001:2014](https://standards.iteh.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014)

5.2.1 Insulating box

The insulating box shall integrate besides the mechanism, the connection and attachment unit.

5.2.2 Free release mechanism

Design of circuit breaker mechanism shall allow free release; i.e. the circuit breaker cuts out in case of overload, and remains cut out even if the actuator is kept by force in engaged position.

A new engagement of circuit breaker is only possible after a first total release of the control actuator.

The operation in these conditions shall not affect further performances of the circuit breaker.

5.2.3 Attachment

All visible parts shall be black colored and non-reflective.

5.2.4 Electrical connection units

They shall be able to receive the lugs.

5.2.5 Control actuator

In engaged position, the visible part of the control actuator shall be of the colour stated in the product standard. In disengaged (or opened) position, the control actuator shall show a white strip.

The outer part of this actuator shall be isolated from all under voltage parts.

EN 2665-001:2013 (E)

The control actuator shall not stay in a transition position, or give a false indication about the circuit breaker condition. It shall not be removable.

When pushing it, power contacts of the circuit breaker engage.

When pulling it, power contacts of the circuit breaker open.

The circuit breaker rating is indicated in indelible white colour on the front part of the control actuator.

The product standard gives the digits positioning.

5.2.6 Rating inviolability

The circuit breaker shall be designed in such a way that the calibration unit cannot be reached without breaking a sealing.

5.2.7 Leakage lines

The leakage lines and the minimal space to be foreseen between the under voltage parts and any other part of the circuit breaker made of non-insulating material, as well as between the under voltage parts of opposite polarity, shall be sufficient to avoid any default or arcing in all uses and climatic conditions.

5.2.8 Protection against non-release

Electrical overload happening on a circuit breaker locked in its engaged position (sticked contacts or non-operating release mechanism), shall cause the opening of the circuit by circuit breaker destruction without any fire or important smoke release.

6 Characteristic

<https://standards.iteh.ai/catalog/standards/sist/28f482cb-5b7f-48e8-882d-85b0e9c88ef7/sist-en-2665-001-2014>

6.1 General characteristics

See Table 1.

Table 1 — General characteristics

Designation	Requirements
Assembly	See product standard.
Mass	See product standard.
Operational altitude	See product standard.
3 input terminals on power supply side (identified by digit A1, B1, C1)	See product standard.
3 output terminals on distribution side (identified by digit A2, B2, C2)	
Operational ambient temperatures limits	From – 55 °C to 90 °C
Temperature compensation	From – 55 °C to 90 °C See product standard.
Rating marking	On control actuator (indelible white)

6.2 Ratings

See product standard.

6.3 Nominal voltage of operational circuits

See product standard.

6.4 Dimensional characteristics

See product standard.

6.5 Recommended panel mounting dimensions

Panel cut-out : the panel cut-out is in accordance with the designation TR6083C202 (for EN 2665-004).

Spacing : 60 mm horizontal and 45 mm vertical from the centers of the mounting holes.

Panel thickness : 1 mm to 3 mm.

7 Tests

7.1 Mechanical tests

See Table 2.

STANDARD PREVIEW
(standards.iteh.ai)

Table 2 — Mechanical characteristics

Tests		Requirements			
Visual check		EN 3841-201			
Operational force	Closing force (push)	EN 3841-502	8 N to 80 N		
	Opening force (pull)		5 N to 45 N		
Mechanical strength	Actuator	Travel			
		EN 3841-501 For value, see product standard.			
		Transverse load			
	Longitudinal load	Push	EN 3841-503	≥ 110 N	
		Pull		≥ 110 N	
	Attachment nut	Tightening torque		EN 3841-504	≥ 5,5 N.m
		Rotation torque			≥ 3 N.m
	Main contact connection	Screw tightening torque		EN 3841-505	≥ 2,5 N.m
Tensile force as per F_1 (see Figure 1 in product standard).			≥ 110 N		
Pressure force as per F_2 (see Figure 1 in product standard).			≥ 55 N		

EN 2665-001:2013 (E)

7.2 Environmental tests

See Table 3.

Table 3 — Environmental conditions (1 of 2)

Tests		Requirements	
Combined tests. Ambient temperature 70 °C and vibrations (see notes).	Sinusoidal (see Figure 1). Duration: — circuit breaker in the "closed" position; — 0,9 I_n load – Seven cycles/axis – 1 octave/min; — no load – Two cycles/axis – 1 octave/min. — circuit breaker in the "opened" position; — two cycles/axis – 1 octave/min.	See EN 3841-506.	5 Hz to 80 Hz – Constant amplitude 2 a = 0,76 mm
			80 Hz to 500 Hz – Constant acceleration = 10 g_n
			500 Hz to 2 000 Hz – Constant acceleration = 5 g_n
	Random (see Figure 2). Duration: — circuit breaker in the "closed" position; — 0,9 I_n load – 15 min/axis; — no load – 15 min/axis; — circuit breaker in the "opened" position; — 15 min/axis.		10 Hz to 2 000 Hz – Constant acceleration = 5,8 g_n
Low frequencies (see Figure 3). Applicability: see product standard. Duration: — circuit breaker in the "closed" position; — 0,9 I_n load – Two cycles/axis; — no load – Two cycles/axis. — circuit breaker in the "opened" position; — two cycles/axis.	See EN 3841-511.	10 Hz to 27 Hz to 10 Hz – Constant acceleration = 10 g_n	
		10 Hz to 5 Hz – Constant acceleration = 3,5 g_n	
Combined tests. Ambient temperature 85 °C, cabin max. altitude 4 600 m and vibrations (see notes).	Sinusoidal – Applicability: see product standard. Duration: — circuit breaker in the "closed" position; — 0,9 I_n load – Four cycles/axis – 1 octave/min; — no load – Two cycles/axis – 1 octave/min. — circuit breaker in the "opened" position; — two cycles/axis – 1 octave/min.	See EN 3841-511.	5 Hz to 54 Hz – Constant shift 2 a = 0,5 mm
			54 Hz to 2 000 Hz – Constant acceleration = 3 g_n

Table 3 — Environmental conditions (2 of 2)

Tests	Requirements
Mechanical shocks (see notes)	50 g_n – 11 ms – Half sine wave See EN 3841-507.
Constant accelerations	See product standard.
Sand and dust	See product standard.
Corrosion (salt spray)	See EN 3841-402, category S.
Humidity	See EN 3841-403, category A.
Explosion-proofing	See product standard.
Contaminating liquids	Cleaning and extinguishing products See EN 3841-405.
Flammability (glow wire test)	See EN 3841-406.
Inflammability	See test EN 3844-1, code B.
Smoke density	See test EN 2825, code A or code B.
Toxicity	See test EN 2826, code B.
Overvoltage caused by lightning only on main contacts	See EN 3841-308. Requirement: no tripping

NOTE 1 Vibration tests performed on circuit breakers in closed position without load and in opened position, are carried out in order to detect contact opening and closure.

NOTE 2 For vibration and shock tests, the contact-opening or contact-closure shall be less than or equal to 10 μ s on the power and the signal contacts.

NOTE 3 Shock tests are performed one on each way for each of the three directions (i.e. six shocks in all).

NOTE 4 Circuit breaker in the closed position = main contacts closed.
Circuit breaker in the opened position = main contacts opened.

NOTE 5 Any additional vibrations testing (e.g. Sustained Engine Imbalance) shall be contractually agreed between users and manufacturers.