



SLOVENSKI STANDARD

SIST EN 4604-009:2014

01-oktober-2014

Nadomešča:

SIST EN 4604-009:2011

Aeronavtika - Kabli, električni, za prenos signala - 009. del: Kabli, koaksialni, lahki, 50 ohmov, 180 °C, tip KW (lahki WN) - Standard za proizvod

Aerospace series - Cable, electrical, for signal transmission - Part 009: Cable, coaxial, light weight, 50 ohms, 180 °C, type KW (light WN) - Product standard

Luft- und Raumfahrt - Elektrische Leitungen für Signalübertragungen - Teil 009: Koaxialkabel, Leichtbauweise, 50 Ohm, 180 °C, Typ KW (WN Leichtbauweise) - Produktnorm

Série aérospatiale - Câbles électriques pour transmission de signaux - Partie 009 : Câble, coaxial, allégé 50 ohms, 180 °C, type KW (WN allégé) - Norme de produit

Ta slovenski standard je istoveten z: EN 4604-009:2014

ICS:

49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems
--------	--	--

SIST EN 4604-009:2014

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 4604-009:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014>

EUROPEAN STANDARD

EN 4604-009

NORME EUROPÉENNE

EUROPÄISCHE NORM

July 2014

ICS 49.060

Supersedes EN 4604-009:2011

English Version

Aerospace series - Cable, electrical, for signal transmission -
Part 009: Cable, coaxial, light weight, 50 ohms, 180 °C, type KW
(light WN) - Product standard

Série aérospatiale - Câbles électriques pour transmission
de signaux - Partie 009 : Câble, coaxial, allégé 50 ohms,
180 °C, type KW (WN allégé) - Norme de produit

Luft- und Raumfahrt - Elektrische Leitungen für
Signalübertragungen - Teil 009: Koaxialkabel,
Leichtbauweise, 50 Ohm, 180 °C, Typ KW (WN
Leichtbauweise) - Produktnorm

This European Standard was approved by CEN on 12 October 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Required characteristics	4
5 Quality assurance	11
6 Designation	11
7 Identification and marking	12
8 Colours of components and jacket.....	12
9 Packaging, labelling and delivery lengths	12
10 Technical specification	12

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 4604-009:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014>

Foreword

This document (EN 4604-009:2014) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2015, and conflicting national standards shall be withdrawn at the latest by January 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 4604-009:2011.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

[SIST EN 4604-009:2014](https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014)

<https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014>

EN 4604-009:2014 (E)**1 Scope**

This European Standard specifies the required characteristics of a light weight coaxial cable, 50 Ω , type KW for use in aircraft electrical systems at operating temperature between – 55 °C and 180 °C and specially for high frequency up to 6 GHz. Nevertheless, if needed, – 65 °C is also acceptable as shown by rapid change of temperature test.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 3475-100 (all parts), *Aerospace series — Cables, electrical, aircraft use — Test methods — Part 100: General*

EN 4604-001, *Aerospace series — Cable, electrical, for signal transmission — Part 001: Technical specification*

EN 4604-002, *Aerospace series — Cable, electrical, for signal transmission — Part 002: General*

TR 6058, *Aerospace series — Cable code identification list* ¹⁾

ASTM B566, *Standard specification for copper-clad aluminium wire* ²⁾

ITC STANDARD PREVIEW
(standards.iteh.ai)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 3475-100 and the following apply.

3.1**Epsilon (ϵ)**

value of dielectric constant

4 Required characteristics**4.1 Material, constructions, dimensions and mass****4.1.1 Material**

See Table 1.

1) Published as ASD-STAN Technical Report at the date of publication of this standard. <http://www.asd-stan.org/>


2) Published by: ASTM National (US) American Society for Testing and Materials. <http://www.astm.org/>

Table 1 — Material

	Material	Finish	Colour
Conductor	Single-strand (copper clad aluminium as per ASTM B566 class 15 A)	1 µm silver plated	—
Dielectric	Fluorocarbon dielectric with low epsilon	—	—
Screen (foil)	Foil, silver plated copper or silver alloy		—
Shield	Reinforced braid (copper clad aluminium as per ASTM B566 class 15 A)	1 µm silver plated	—
Jacket	Fluorocarbon	—	Turquoise

4.1.2 Construction, dimensions and mass

See Figure 1 and Table 2.



Key

- 1 Conductor
- 2 Dielectric
- 3 Screen
- 4 Shield
- 5 Jacket

SIST EN 4604-009:2014
<https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014>

Figure 1 — Construction

Table 2 — Dimensions and mass

Diameter (mm)									Mass	
Conductor			Dielectric		Shield	Cable			g/m	
min.	nom.	max.	min.	max.		min.	nom.	max.	nom.	max.
2,28	2,30	2,32	6,1	6,3	6,87 ± 0,2	7,5	7,65	7,8	85	95

The dielectric diameter (min. – max.) shall be maintained during the connection (after unwrapping off screen).

EN 4604-009:2014 (E)

4.2 General characteristics

- operating temperature: – 55 °C to 180 °C,
- minimum bend radius:
 - in static use: 80 mm,
 - in dynamic use: 120 mm.
- performances are guaranteed up to 6 GHz.


4.3 Electrical characteristics

- characteristic impedance: $Z_c = (50 \pm 3) \Omega$ at 200 MHz,
- capacitance per unit length: $C_p = 88$ pF/m max.,
- transfer impedance up to 400 MHz: 20 m Ω /m max.,
- operating voltage: 1 000 V RMS max.,
- maximum power handling (at sea level): see Table 3 and Figure 2,
- attenuation versus frequency: see Table 3 and Figure 2,
- velocity of propagation ≥ 243 000 km/s.

Table 3 — Maximum attenuation, power handling and return loss

Frequency MHz	50	100	400	1 000	5 000	6 000
Attenuation dB/100 m	3,5	5,5	10	15	35	41
Power handling W	8 000	5 000	3 000	2 000	800	700
Return loss dB	1,1	1,1	1,15	1,15	1,2	1,35

Values of power have to be confirmed by measurement or calculation.



- Attenuation (dB/100 m)
- ◆ P (W)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Figure 2 — Maximum attenuation curve (ascending) – Power curve (descending)

4.4 Tests

See Table 4.

[SIST EN 4604-009:2014](https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014)
<https://standards.iteh.ai/catalog/standards/sist/fd55d149-4e72-4961-a4a0-85d269aad35f/sist-en-4604-009-2014>