



SLOVENSKI STANDARD SIST TBR 033:2000

01-junij-2000

8 [[]HJbc`ca fYy`Y`n]bHY[f]fUb]a]g]cf]hj Ua]f]G8 B!`NU HYj Y`nUdf]_`1]HYj
HYfa]bUg_YcdfYa Yj `dU_YfbYa `bU]bi `bU`G8 B`ni dcfUvc`cgbcj bY[UXcglcdU
=G8 B

Integrated Services Digital Network (ISDN); Attachment requirements for packet mode terminal equipment to connect to an ISDN using ISDN basic access

iteh STANDARD PREVIEW
(standards.iteh.ai)

[SIST TBR 033:2000](https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a78f4d1b203/sist-tbr-033-2000)

Ta slovenski standard je istoveten z: **TBR 033 Edition 1**

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST TBR 033:2000

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST TBR 033:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000>



TECHNICAL
BASIS for
REGULATION

TBR 33

December 1997

Source: SPS

Reference: DTBR/SPS-05119

ICS: 33.020

Key words: ISDN, packet mode, terminal, basic, access

iTeh STANDARD PREVIEW
(standards.itih.ai)
Integrated Services Digital Network (ISDN);
Attachment requirements for packet mode terminal equipment
to connect to an ISDN using ISDN basic access

SIST.TBR.033:2000

Downloaded from <https://standards.itih.ai> on 2025-10-22 10:21:00

a98f4dfb203/sist-tbr-033-2000

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 033:2000](https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000)

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000>

Contents

Foreword	11
1 Scope	13
2 Normative references	13
3 Definitions and abbreviations	14
3.1 Definitions	14
3.2 Abbreviations	15
4 General	16
4.1 General requirements for the access of the PH	16
4.1.1 Channel used for the access of the PH	16
4.1.2 Requirements for layer 1	17
4.1.2.1 Requirements for complete layer 1 (comprising D-channel and B-channels as a whole)	17
4.1.2.2 Requirements for layer 1 with respect to the selected channel	17
4.1.3 Requirements for layer 2 of the D-channel	17
4.1.3.1 Requirements for data link connections with SAPI 0	17
4.1.3.2 Requirements for data link connections with SAPI 16	18
4.1.3.3 Requirements for data link connections with SAPI 63	18
4.1.4 Notification classes	19
4.1.5 Requirements for layer 3 of the D-channel	19
4.1.5.1 Outgoing calls	19
4.1.5.2 Incoming calls	19
4.1.5.3 Use of outgoing and incoming calls to support access of the PH	20
5 Definitions of primitives	20
6 Safety requirements	20
7 Electro-Magnetic Compatibility (EMC) requirements	20
8 Overvoltage protection requirements	20
8.1 Impulse transfer from mains, common mode	20
8.2 Impulse transfer from mains, transverse mode	20
8.3 Conversion of common mode to transverse mode	20
9 Layer 1 requirements	21
9.1 Physical characteristics (on-demand layer 1)	21
9.2 Electrical characteristics (on-demand layer 1)	21
9.3 Functional characteristics (on-demand layer 1)	21
9.4 Interface procedure (on-demand layer 1)	21
9.4.1 D-channel access procedure	21
9.4.1.1 Interframe (layer 2) time fill	21
9.4.1.2 Multipoint contention resolution mechanism	21
9.4.1.3 Collision detection	22
9.4.2 Activation/deactivation	22
9.4.2.1 TE states	22
9.4.2.2 Signals	22
9.4.2.3 Activation/deactivation procedure for TEs	22
9.4.2.3.1 Specification of the procedure	22
9.4.2.3.2 Timer values	22
9.4.2.4 TE activation times	22

	9.4.2.5	Deactivation times.....	22
	9.4.3	Frame alignment procedures.....	23
	9.4.4	Multiframing.....	23
	9.4.5	Idle Channel Code on the B-Channels.....	23
9.5		Power feeding (on-demand layer 1).....	23
9.6		Semi-permanent layer 1 requirements.....	23
	9.6.1	Activation/deactivation.....	23
	9.6.1.1	TE States.....	23
		9.6.1.1.1 State F1 (Inactive).....	23
		9.6.1.1.2 State F2 (Sensing).....	23
		9.6.1.1.3 State F3 (Deactivated).....	23
		9.6.1.1.4 State F6 (synchronized).....	23
		9.6.1.1.5 State F7 (activated).....	23
		9.6.1.1.6 State F8 (lost framing).....	23
	9.6.2	Signals.....	24
	9.6.3	Specification of the Activation/deactivation procedure for semi-permanent layer 1 TEs.....	24
	9.6.4	TE activation times.....	27
	9.6.5	Deactivation times.....	27
10		Layer 2 D-channel requirements.....	28
	10.1	Frame structure for peer-to-peer communication.....	28
	10.1.1	General.....	28
	10.1.2	Flag sequence.....	28
	10.1.3	Address field.....	28
	10.1.4	Control field.....	28
	10.1.5	Information field.....	29
	10.1.6	Transparency.....	29
	10.1.7	Frame Check Sequence (FCS) field.....	29
	10.1.8	Format convention.....	29
		10.1.8.1 Numbering convention.....	29
		10.1.8.2 Order of bit transmission.....	29
		10.1.8.3 Field mapping convention.....	29
	10.1.9	Invalid or incompatible frames.....	29
10.2		Elements of procedures and formats of fields for data link layer peer-to-peer communication.....	29
	10.2.1	General.....	29
	10.2.2	Address field format.....	29
	10.2.3	Address field variables.....	29
		10.2.3.1 Address field extension bit (EA).....	30
		10.2.3.2 Command/Response field bit (C/R).....	30
		10.2.3.3 Service Access Point Identifier (SAPI).....	30
		10.2.3.4 Terminal Endpoint Identifier (TEI).....	30
		10.2.3.4.1 TEI for broadcast data link connection.....	30
		10.2.3.4.2 TEI for point-to-point data link connection.....	30
	10.2.4	Control field formats.....	30
		10.2.4.1 Information transfer (I) format.....	30
		10.2.4.2 Supervisory (S) format.....	30
		10.2.4.3 Unnumbered (U) format.....	30
	10.2.5	Control field parameters and associated state variables.....	31
		10.2.5.1 Poll/Final bit.....	31
		10.2.5.2 Multiple frame operation - variables and sequence numbers.....	31
		10.2.5.2.1 Modulus.....	31
		10.2.5.2.2 Send state variable V(S).....	31
		10.2.5.2.3 Acknowledge state variable V(A).....	31
		10.2.5.2.4 Send sequence number N(S).....	31
		10.2.5.2.5 Receive state variable V(R).....	31
		10.2.5.2.6 Receive sequence number N(R).....	31
	10.2.6	Frame types.....	31
		10.2.6.1 Commands and responses.....	31
		10.2.6.2 Information (I) command.....	32

	10.2.6.3	Set Asynchronous Balanced Mode Extended (SABME) command.....	32
	10.2.6.4	DISConnect (DISC) command	32
	10.2.6.5	Unnumbered Information (UI) command.....	32
	10.2.6.6	Receive Ready (RR) command/response	33
	10.2.6.7	REJect (REJ) command/response	33
	10.2.6.8	Receive Not Ready (RNR) command/response.....	33
	10.2.6.9	Unnumbered Acknowledgement (UA) response	33
	10.2.6.10	Disconnected Mode (DM) response	33
10.3		Provision of point-to-point signalling connections	33
10.4		Procedures for unacknowledged information transfer	33
	10.4.1	Transmission of unacknowledged information	33
	10.4.2	Receipt of unacknowledged information	33
10.5		Terminal Endpoint Identifier (TEI) management procedures.....	34
	10.5.1	General.....	34
	10.5.2	TEI assignment procedure	34
	10.5.2.1	Expiry of timer T202	34
	10.5.3	TEI check procedure	34
	10.5.4	TEI removal procedure.....	34
	10.5.4.1	Action taken by the data link layer entity receiving the MDL-REMOVE-REQUEST primitive	34
	10.5.4.2	Conditions for TEI removal	34
	10.5.5	TEI identity verify procedure.....	34
	10.5.5.1	General	34
	10.5.5.2	Operation of the TEI identity verify procedure	34
	10.5.6	Formats and codes	34
10.6		Procedures for establishment and release of multiple frame operation	35
	10.6.1	Establishment of multiple frame operation.....	35
	10.6.1.1	General.....	35
	10.6.1.2	Establishment procedures	35
	10.6.1.2.1	Establishment initiation	35
	10.6.1.2.2	Establishment response	35
	10.6.1.3	Procedure on expiry of timer T200	36
	10.6.2	Termination of multiple frame operation.....	36
10.7		Procedures for information transfer in multiple frame operation	36
	10.7.1	Transmitting I-frames	36
	10.7.2	Receiving I-frames	36
	10.7.2.1	P bit set to 1	36
	10.7.2.2	P bit set to 0.....	36
	10.7.3	Receiving acknowledgements.....	37
	10.7.4	Receiving REJ frames.....	37
	10.7.5	Receiving RNR frames.....	38
	10.7.5.1	Receiving a valid RNR command or response.....	38
	10.7.5.2	Expiry of timer T200 during "peer receiver busy"	38
	10.7.5.3	Receiving a valid RNR command or response during "peer receiver busy"	39
	10.7.5.4	Receiving a valid RR or REJ command or response during "peer receiver busy".....	39
	10.7.5.5	Appropriate supervisory response frame.....	39
	10.7.6	Waiting acknowledgement	40
10.8		Re-establishment of multiple frame operation	40
10.9		Exception condition reporting and recovery	41
	10.9.1	N(S) sequence error.....	41
	10.9.2	Invalid frame condition	41
	10.9.3	Frame rejection condition	41
	10.9.4	Multiple-assignment of TEI value	41
10.10		List of system parameters.....	42
	10.10.1	Timer T200.....	42
	10.10.2	Maximum number of retransmissions (N200).....	42
	10.10.3	Maximum number of octets in an information field (N201)	42
	10.10.4	Maximum number of transmission of the TEI identity request message (N202)	42
	10.10.5	Maximum number of outstanding I-frames (k)	42

	10.10.6	Timer T202	42
	10.10.7	Layer 2 response time	42
11	Layer 3 D-channel requirements		43
	11.1	Overview of call control	43
	11.1.1	Call states at the user side of the interface	43
	11.1.1.1	Null state (U0)	43
	11.1.1.2	Call initiated (U1)	43
	11.1.1.3	Call proceeding (U3)	43
	11.1.1.4	Call present (U6)	43
	11.1.1.5	Call received (U7)	44
	11.1.1.6	Connect request (U8)	44
	11.1.1.7	Incoming call proceeding (U9)	44
	11.1.1.8	Active (U10)	44
	11.1.1.9	Disconnect request (U11)	44
	11.1.1.10	Disconnect indication (U12)	44
	11.1.1.11	Release request (U19)	44
	11.1.2	Network call states	44
	11.1.2.1	Null state (N0)	44
	11.1.2.2	Call initiated (N1)	44
	11.1.2.3	Outgoing call proceeding (N3)	44
	11.1.2.4	Call present (N6)	45
	11.1.2.5	Call received (N7)	45
	11.1.2.6	Connect request (N8)	45
	11.1.2.7	Incoming call proceeding (N9)	45
	11.1.2.8	Active (N10)	45
	11.1.2.9	Disconnect request (N11)	45
	11.1.2.10	Disconnect indication (N12)	45
	11.1.2.11	Release request (N19)	45
	11.1.2.12	Call abort (N22)	45
	11.1.3	States associated with the global call reference	46
	11.1.3.1	Call states at the user side of the interface	46
	11.1.3.1.1	Null (Rest 0)	46
	11.1.3.1.2	Restart (Rest 2)	46
	11.1.3.2	Call states at the network side of the interface	46
	11.1.3.2.1	Null (Rest 0)	46
	11.1.3.2.2	Restart request (Rest 1)	46
11.2	Message functional definitions and content		46
	11.2.1	Alerting	47
	11.2.2	Call proceeding	48
	11.2.3	Connect	48
	11.2.4	Connect acknowledge	49
	11.2.5	Disconnect	49
	11.2.6	Release	50
	11.2.7	Release complete	50
	11.2.8	Setup	51
	11.2.9	Status	52
	11.2.10	Status enquiry	52
	11.2.11	Messages used with the global call reference	52
	11.2.11.1	Restart	52
	11.2.11.2	Restart acknowledge	52
11.3	General message format and information elements coding		53
	11.3.1	Overview	53
	11.3.2	Protocol discriminator	53
	11.3.3	Call reference	53
	11.3.4	Message type	53
	11.3.5	Other information elements	55
	11.3.5.1	Coding rules	55
	11.3.5.1.1	Codeset 0	55
	11.3.5.2	Extensions of codesets	56
	11.3.5.3	Locking shift procedure	56
	11.3.5.4	Non-locking shift procedure	56
	11.3.5.5	Bearer capability	56

	11.3.5.6	Call state.....	58
	11.3.5.7	Called party number	58
	11.3.5.8	Called party subaddress	58
	11.3.5.9	Calling party number.....	58
	11.3.5.10	Calling party subaddress	60
	11.3.5.11	Cause	61
	11.3.5.12	Channel identification	61
	11.3.5.13	Restart indicator.....	61
11.4		Call control procedures for the control of packet-mode access of the PH	62
	11.4.1	Call establishment at the originating interface.....	62
	11.4.1.1	Call request.....	62
	11.4.1.2	Overlap sending.....	62
	11.4.1.3	Call proceeding.....	62
	11.4.1.4	Call confirmation indication.....	62
	11.4.1.5	Call connected	63
	11.4.2	Call establishment at the destination interface.....	63
	11.4.2.1	Incoming call.....	63
	11.4.2.2	Compatibility checking.....	63
	11.4.2.3	Channel selection-destination.....	64
	11.4.2.4	Overlap receiving.....	64
	11.4.2.5	Call confirmation	64
	11.4.2.6	Call accept.....	65
	11.4.2.7	Active indication.....	65
	11.4.2.8	Non-selected user clearing.....	65
	11.4.3	Call clearing.....	65
	11.4.3.1	Terminology.....	65
	11.4.3.2	Exception conditions.....	65
	11.4.3.3	Clearing initiated by the user.....	66
	11.4.3.4	Clearing initiated by the network.....	66
	11.4.3.4.1	Clearing when tones/announcements provided	66
	11.4.3.4.2	Clearing when tones/announcements not provided	66
	11.4.3.4.3	Completion of clearing	66
	11.4.3.5	Clear collision.....	66
11.4.4		Call rearrangements.....	67
11.4.5		Call collisions.....	67
11.4.6		Handling of error conditions	67
	11.4.6.1	Call reference procedural errors.....	67
	11.4.6.2	Message type or message sequence errors	67
	11.4.6.3	Duplicated information elements	67
	11.4.6.4	Mandatory information element errors.....	67
	11.4.6.4.1	Mandatory information element missing.....	67
	11.4.6.5	Non-mandatory information element errors.....	67
	11.4.6.5.1	Unrecognized information element.....	68
	11.4.6.5.2	Non-mandatory information element content error	68
	11.4.6.6	Status enquiry procedure.....	69
	11.4.6.7	Receiving a STATUS message.....	69
	11.4.7	User notification procedure	70
	11.4.8	Restart procedure.....	70
11.5		TE timers	70
12	X.25.....		71
	12.1	X.25 requirements	71
	12.2	X.25 procedures	71
	12.2.1	Data link protocol supporting the X.25 packet level protocol	71
	12.2.2	X.25 packet level protocol	71
	12.2.3	Outgoing and incoming virtual calls.....	71
	12.2.4	Identification of X.25 terminals	71

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST TBR 033:2000

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-98fd4ff2038f/sist-tbr-033-2000>

Annex A (normative):	TBR Requirements Table (TBR-RT)	72
A.1	Guidance for completion of the TBR-RT	72
A.2	General classification of requirements TBR-RT	73
A.3	Layer 1 and overvoltage requirements TBR-RT	75
A.3.1	On-demand layer 1 requirement tables	75
A.3.2	Semi-permanent layer 1 requirement tables	79
A.4	Layer 2 TBR-RT	83
A.5	Layer 3 TBR-RT	86
Annex B (normative):	Conformance test principles for layer 1	88
B.1	Scope and general information	88
B.1.1	Scope	88
B.1.2	General information	88
B.1.3	Definitions and abbreviations	88
B.1.4	Environmental conditions	88
B.1.5	Test case selection	89
B.2	Electrical characteristics tests	92
B.3	Functional characteristic tests	92
B.4	Interface procedure tests	92
B.4.1	The TTCN Graphical form (TTCN.GR)	92
B.4.2	The TTCN Machine Processable form (TTCN.MP)	92
B.5	Power feeding	93
Annex C (normative):	Layer 2 tests	94
C.1	The TTCN Graphical form (TTCN.GR)	94
C.2	The TTCN Machine Processable form (TTCN.MP)	94
Annex D (normative):	Layer 3 tests	95
D.1	The TTCN Graphical form (TTCN.GR)	95
D.2	The TTCN Machine Processable form (TTCN.MP)	95
Annex E (normative):	Partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma	96
E.1	Introduction	96
E.2	References	96
E.3	Proforma structure and contents	96
E.4	Table/item identification	96
E.5	Guidance on completing the PIXIT	96
E.6	Environmental test conditions	96

STANDARD PREVIEW
(standards.iteh.ai)

[SIST TBR 033:2000](http://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dffb203/sist-tbr-033-2000)

<http://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dffb203/sist-tbr-033-2000>

E.7	Layer 1 PIXIT	97
E.8	Layer 2 PIXIT	99
E.9	Layer 3 PIXIT	102
Annex F (informative): Justifications for the requirements in the TBR		104
F.1	Principles applicable to the whole TBR	104
F.1.1	General principles	104
F.1.2	Requirements versus definitions	104
F.1.3	Error conditions	104
F.1.4	General editorial changes to text from the base standards	105
F.1.5	Detailed list of changes with respect to the base standards	105
F.1.6	Untested requirements	106
F.1.7	Primitives	106
F.1.8	Supplementary services	106
F.1.9	Article 4(e) of the Directive	106
F.2	Changes with respect to TBR 3	106
F.2.1	Changes for layer 1	107
F.2.1.1	Protection requirements	107
F.2.1.2	Detailed list of changes with respect to TBR 3	107
F.2.2	Changes for layer 2 of the D-channel	108
F.2.3	Changes for layer 3 of the D-channel	109
Annex G (normative): List of supported telecommunication services		112
G.1	Basic telecommunication services	112
G.2	Supplementary services for the access connection	112
Annex H (informative): Examples for TE access configurations with small sets of requirements		113
Annex J (informative): Bibliography		115
History		116

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST TBR 033:2000
<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-4dffb203/sist-tbr-033-2000>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST TBR 033:2000](https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000)

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000>

Foreword

This Technical Basis for Regulation (TBR) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This TBR resulted from a mandate from the Commission of the European Community (CEC) to provide harmonized standards for the support of the Council Directive 91/263/EEC ("The Terminal Equipment Directive").

Annex F provides information relating to the articles of the Directive 91/263/EEC.

Annexes A, B, C, D, E and G are normative whereas annexes F, H and J are informative.

Overview of the Abstract Test Suites (ATs)

This TBR is accompanied by the following ATs (see annexes B, C and D):

- T33L1_7 (layer 1);
- T33L2_3 (layer 2);
- T33L3_5 (layer 3).

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST TBR 033:2000](https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000)

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST TBR 033:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/2cf94e20-1c18-4bc7-9701-a98f4dff203/sist-tbr-033-2000>

1 Scope

This Technical Basis for Regulation (TBR) specifies the technical requirements under articles 4(c) to 4(f) of Directive 91/263/EEC for Terminal Equipment (TE) to be attached to the pan-European Integrated Services Digital Network (ISDN) at an interface at the T reference point or coincident S and T reference point for a basic access. These requirements are intended to ensure that the essential requirements of Directive 91/263/EEC continue to be met when up to eight Terminal Equipments are simultaneously connected at the coincident S and T reference point. These requirements are taken from TBR 3 [9], ETS 300 007 [10], ETS 300 047-3 [12], ETS 300 012 [11], ETS 300 102-1 [13] and ETS 300 125 [14]. This TBR does not contain the essential requirements of Article 4 (g) for interworking via the public network, and so does not provide any guarantee of correct terminal-to-terminal operation.

NOTE 1: Although this TBR provides the technical attachment requirements, it does not contain the full specification of the user side of the ISDN user-network interface. Important information necessary for correct working can be found only in the base standards mentioned above.

This TBR specifies these requirements for TE that:

- a) access Packet Handler (PH) of an ISDN through either on-demand B- or D-channel mode or semi-permanent B-channel mode basic services (case B of X.31) and those supplementary services that are specified in annex G; and
- b) is capable of handling either incoming calls only, outgoing calls only or both incoming and outgoing calls.

This TBR applies to all TE that is intended for connection to the forms of ISDN access referred to above, irrespective of whether the TE provides additional interfaces, telecommunications services or functions for which other TBRs or national approval requirements apply.

This TBR does not specify the requirements for a packet mode TE that uses on-demand B-channel circuit mode access (case A of X.31); the requirements for such a TE are contained in TBR 3 [9].

NOTE 2: This TBR is not applicable to TE which may be supplied in some countries for connection to an ISDN telecommunications service corresponding to, but not compatible with, the pan-European ISDN basic access standards.

2 Normative references

This TBR incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this TBR only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] CCITT Recommendation G.117 (1988): "Transmission aspects of unbalance about earth (Definitions and methods)".
- [2] CCITT Recommendation I.411 (1988): "ISDN user-network interfaces - Reference configurations".
- [3] CCITT Recommendation I.430 (1988): "Basic user-network interface - Layer 1 specification".
- [4] EN 60603-7 (1993): "Connectors for frequencies below 3 MHz for use with printed boards; Part 7: Detail specification for connectors, 8-way, including fixed and free connectors with common mating features; (IEC 603-7:1990)".
- [5] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General Concepts".