

SLOVENSKI STANDARD**DSIST TBR 033:% - ,****01-Uj [i gh% - ,**

Digitalno omrežje z integriranimi storitvami (ISDN) - Zahteve za priključitev terminalske opreme v paketnem načinu na ISDN z uporabo osnovnega dostopa ISDN

Integrated Services Digital Network (ISDN); Attachment requirements for packet mode terminal equipment to connect to an ISDN using ISDN basic access

Ta slovenski standard je istoveten z: TBR 033 Edition 1

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

DSIST TBR 033:% - , en



TECHNICAL BASIS for REGULATION

TBR 33

December 1997

Source: SPS

Reference: DTBR/SPS-05119

ICS: 33.020

Key words: ISDN, packet mode, terminal, basic, access

Integrated Services Digital Network (ISDN); Attachment requirements for packet mode terminal equipment to connect to an ISDN using ISDN basic access

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

Contents

Foreword	11
1 Scope	13
2 Normative references.....	13
3 Definitions and abbreviations	14
3.1 Definitions	14
3.2 Abbreviations	15
4 General.....	16
4.1 General requirements for the access of the PH	16
4.1.1 Channel used for the access of the PH.....	16
4.1.2 Requirements for layer 1	17
4.1.2.1 Requirements for complete layer 1 (comprising D-channel and B-channels as a whole)	17
4.1.2.2 Requirements for layer 1 with respect to the selected channel	17
4.1.3 Requirements for layer 2 of the D-channel.....	17
4.1.3.1 Requirements for data link connections with SAPI 0.....	17
4.1.3.2 Requirements for data link connections with SAPI 16.....	18
4.1.3.3 Requirements for data link connections with SAPI 63.....	18
4.1.4 Notification classes.....	19
4.1.5 Requirements for layer 3 of the D-channel.....	19
4.1.5.1 Outgoing calls	19
4.1.5.2 Incoming calls.....	19
4.1.5.3 Use of outgoing and incoming calls to support access of the PH.....	20
5 Definitions of primitives	20
6 Safety requirements	20
7 Electro-Magnetic Compatibility (EMC) requirements	20
8 Overvoltage protection requirements	20
8.1 Impulse transfer from mains, common mode	20
8.2 Impulse transfer from mains, transverse mode	20
8.3 Conversion of common mode to transverse mode.....	20
9 Layer 1 requirements	21
9.1 Physical characteristics (on-demand layer 1)	21
9.2 Electrical characteristics (on-demand layer 1).....	21
9.3 Functional characteristics (on-demand layer 1).....	21
9.4 Interface procedure (on-demand layer 1)	21
9.4.1 D-channel access procedure	21
9.4.1.1 Interframe (layer 2) time fill.....	21
9.4.1.2 Multipoint contention resolution mechanism.....	21
9.4.1.3 Collision detection.....	22
9.4.2 Activation/deactivation	22
9.4.2.1 TE states	22
9.4.2.2 Signals	22
9.4.2.3 Activation/deactivation procedure for TEs	22
9.4.2.3.1 Specification of the procedure	22
9.4.2.3.2 Timer values	22
9.4.2.4 TE activation times	22

	9.4.2.5	Deactivation times.....	22	
	9.4.3	Frame alignment procedures.....	23	
	9.4.4	Multiframing	23	
	9.4.5	Idle Channel Code on the B-Channels	23	
9.5		Power feeding (on-demand layer 1).....	23	
9.6		Semi-permanent layer 1 requirements.....	23	
	9.6.1	Activation/deactivation	23	
		9.6.1.1 TE States	23	
			9.6.1.1.1 State F1 (Inactive).....	23
			9.6.1.1.2 State F2 (Sensing)	23
			9.6.1.1.3 State F3 (Deactivated)	23
			9.6.1.1.4 State F6 (synchronized)	23
			9.6.1.1.5 State F7 (activated).....	23
			9.6.1.1.6 State F8 (lost framing).....	23
	9.6.2	Signals	24	
	9.6.3	Specification of the Activation/deactivation procedure for semi-permanent layer 1 TEs.....	24	
	9.6.4	TE activation times	27	
	9.6.5	Deactivation times	27	
10		Layer 2 D-channel requirements	28	
10.1		Frame structure for peer-to-peer communication	28	
	10.1.1	General.....	28	
	10.1.2	Flag sequence	28	
	10.1.3	Address field	28	
	10.1.4	Control field.....	28	
	10.1.5	Information field	29	
	10.1.6	Transparency.....	29	
	10.1.7	Frame Check Sequence (FCS) field.....	29	
	10.1.8	Format convention	29	
		10.1.8.1 Numbering convention	29	
		10.1.8.2 Order of bit transmission.....	29	
		10.1.8.3 Field mapping convention	29	
	10.1.9	Invalid or incompatible frames	29	
10.2		Elements of procedures and formats of fields for data link layer peer-to-peer communication	29	
	10.2.1	General	29	
	10.2.2	Address field format.....	29	
	10.2.3	Address field variables.....	29	
		10.2.3.1 Address field extension bit (EA).....	30	
		10.2.3.2 Command/Response field bit (C/R)	30	
		10.2.3.3 Service Access Point Identifier (SAPI).....	30	
		10.2.3.4 Terminal Endpoint Identifier (TEI)	30	
			10.2.3.4.1 TEI for broadcast data link connection. 30	
			10.2.3.4.2 TEI for point-to-point data link connection	30
	10.2.4	Control field formats	30	
		10.2.4.1 Information transfer (I) format	30	
		10.2.4.2 Supervisory (S) format	30	
		10.2.4.3 Unnumbered (U) format	30	
	10.2.5	Control field parameters and associated state variables	31	
		10.2.5.1 Poll/Final bit.....	31	
		10.2.5.2 Multiple frame operation - variables and sequence numbers	31	
			10.2.5.2.1 Modulus.....	31
			10.2.5.2.2 Send state variable V(S)	31
			10.2.5.2.3 Acknowledge state variable V(A)	31
			10.2.5.2.4 Send sequence number N(S).....	31
			10.2.5.2.5 Receive state variable V(R).....	31
			10.2.5.2.6 Receive sequence number N(R).....	31
	10.2.6	Frame types.....	31	
		10.2.6.1 Commands and responses	31	
		10.2.6.2 Information (I) command.....	32	

10.2.6.3	Set Asynchronous Balanced Mode Extended (SABME) command.....	32
10.2.6.4	DISConnect (DISC) command	32
10.2.6.5	Unnumbered Information (UI) command.....	32
10.2.6.6	Receive Ready (RR) command/response	33
10.2.6.7	REject (REJ) command/response	33
10.2.6.8	Receive Not Ready (RNR) command/response.....	33
10.2.6.9	Unnumbered Acknowledgement (UA) response	33
10.2.6.10	Disconnected Mode (DM) response	33
10.3	Provision of point-to-point signalling connections	33
10.4	Procedures for unacknowledged information transfer	33
10.4.1	Transmission of unacknowledged information.....	33
10.4.2	Receipt of unacknowledged information	33
10.5	Terminal Endpoint Identifier (TEI) management procedures.....	34
10.5.1	General.....	34
10.5.2	TEI assignment procedure	34
10.5.2.1	Expiry of timer T202	34
10.5.3	TEI check procedure	34
10.5.4	TEI removal procedure.....	34
	10.5.4.1 Action taken by the data link layer entity receiving the MDL-REMOVE-REQUEST primitive	34
	10.5.4.2 Conditions for TEI removal	34
10.5.5	TEI identity verify procedure.....	34
	10.5.5.1 General	34
	10.5.5.2 Operation of the TEI identity verify procedure	34
10.5.6	Formats and codes	34
10.6	Procedures for establishment and release of multiple frame operation	35
10.6.1	Establishment of multiple frame operation	35
10.6.1.1	General	35
10.6.1.2	Establishment procedures	35
	10.6.1.2.1 Establishment initiation	35
	10.6.1.2.2 Establishment response	35
	10.6.1.3 Procedure on expiry of timer T200	36
10.6.2	Termination of multiple frame operation.....	36
10.7	Procedures for information transfer in multiple frame operation	36
10.7.1	Transmitting I-frames	36
10.7.2	Receiving I-frames	36
	10.7.2.1 P bit set to 1	36
	10.7.2.2 P bit set to 0	36
10.7.3	Receiving acknowledgements.....	37
10.7.4	Receiving REJ frames.....	37
10.7.5	Receiving RNR frames.....	38
	10.7.5.1 Receiving a valid RNR command or response	38
	10.7.5.2 Expiry of timer T200 during "peer receiver busy"	38
	10.7.5.3 Receiving a valid RNR command or response during "peer receiver busy".....	39
	10.7.5.4 Receiving a valid RR or REJ command or response during "peer receiver busy".....	39
	10.7.5.5 Appropriate supervisory response frame.....	39
10.7.6	Waiting acknowledgement	40
10.8	Re-establishment of multiple frame operation	40
10.9	Exception condition reporting and recovery.....	41
10.9.1	N(S) sequence error.....	41
10.9.2	Invalid frame condition	41
10.9.3	Frame rejection condition	41
10.9.4	Multiple-assignment of TEI value	41
10.10	List of system parameters.....	42
10.10.1	Timer T200	42
10.10.2	Maximum number of retransmissions (N200)	42
10.10.3	Maximum number of octets in an information field (N201)	42
10.10.4	Maximum number of transmission of the TEI identity request message (N202)	42
	10.10.5 Maximum number of outstanding I-frames (k)	42

10.10.6	Timer T202	42
10.10.7	Layer 2 response time	42
11	Layer 3 D-channel requirements	43
11.1	Overview of call control	43
11.1.1	Call states at the user side of the interface	43
11.1.1.1	Null state (U0)	43
11.1.1.2	Call initiated (U1).....	43
11.1.1.3	Call proceeding (U3)	43
11.1.1.4	Call present (U6)	43
11.1.1.5	Call received (U7)	44
11.1.1.6	Connect request (U8).....	44
11.1.1.7	Incoming call proceeding (U9)	44
11.1.1.8	Active (U10)	44
11.1.1.9	Disconnect request (U11)	44
11.1.1.10	Disconnect indication (U12)	44
11.1.1.11	Release request (U19).....	44
11.1.2	Network call states.....	44
11.1.2.1	Null state (N0)	44
11.1.2.2	Call initiated (N1).....	44
11.1.2.3	Outgoing call proceeding (N3)	44
11.1.2.4	Call present (N6)	45
11.1.2.5	Call received (N7)	45
11.1.2.6	Connect request (N8).....	45
11.1.2.7	Incoming call proceeding (N9)	45
11.1.2.8	Active (N10)	45
11.1.2.9	Disconnect request (N11)	45
11.1.2.10	Disconnect indication (N12)	45
11.1.2.11	Release request (N19).....	45
11.1.2.12	Call abort (N22).....	45
11.1.3	States associated with the global call reference.....	46
11.1.3.1	Call states at the user side of the interface	46
11.1.3.1.1	Null (Rest 0)	46
11.1.3.1.2	Restart (Rest 2).....	46
11.1.3.2	Call states at the network side of the interface	46
11.1.3.2.1	Null (Rest 0)	46
11.1.3.2.2	Restart request (Rest 1).....	46
11.2	Message functional definitions and content	46
11.2.1	Alerting.....	47
11.2.2	Call proceeding.....	48
11.2.3	Connect	48
11.2.4	Connect acknowledge	49
11.2.5	Disconnect	49
11.2.6	Release.....	50
11.2.7	Release complete	50
11.2.8	Setup	51
11.2.9	Status.....	52
11.2.10	Status enquiry	52
11.2.11	Messages used with the global call reference	52
11.2.11.1	Restart.....	52
11.2.11.2	Restart acknowledge	52
11.3	General message format and information elements coding	53
11.3.1	Overview	53
11.3.2	Protocol discriminator	53
11.3.3	Call reference	53
11.3.4	Message type.....	53
11.3.5	Other information elements	55
11.3.5.1	Coding rules	55
11.3.5.1.1	Codeset 0.....	55
11.3.5.2	Extensions of codesets	56
11.3.5.3	Locking shift procedure.....	56
11.3.5.4	Non-locking shift procedure	56
11.3.5.5	Bearer capability	56

	11.3.5.6	Call state.....	58
	11.3.5.7	Called party number	58
	11.3.5.8	Called party subaddress	58
	11.3.5.9	Calling party number.....	58
	11.3.5.10	Calling party subaddress	60
	11.3.5.11	Cause	61
	11.3.5.12	Channel identification	61
	11.3.5.13	Restart indicator.....	61
11.4	Call control procedures for the control of packet-mode access of the PH	62	
11.4.1	Call establishment at the originating interface.....	62	
11.4.1.1	Call request.....	62	
11.4.1.2	Overlap sending.....	62	
11.4.1.3	Call proceeding.....	62	
11.4.1.4	Call confirmation indication.....	62	
11.4.1.5	Call connected	63	
11.4.2	Call establishment at the destination interface.....	63	
11.4.2.1	Incoming call.....	63	
11.4.2.2	Compatibility checking	63	
11.4.2.3	Channel selection-destination.....	64	
11.4.2.4	Overlap receiving.....	64	
11.4.2.5	Call confirmation	64	
11.4.2.6	Call accept	65	
11.4.2.7	Active indication.....	65	
11.4.2.8	Non-selected user clearing.....	65	
11.4.3	Call clearing.....	65	
11.4.3.1	Terminology	65	
11.4.3.2	Exception conditions	65	
11.4.3.3	Clearing initiated by the user	66	
11.4.3.4	Clearing initiated by the network.....	66	
11.4.3.4.1	Clearing when tones/announcements provided	66	
11.4.3.4.2	Clearing when tones/announcements not provided	66	
11.4.3.4.3	Completion of clearing	66	
11.4.3.5	Clear collision	66	
11.4.4	Call rearrangements.....	67	
11.4.5	Call collisions.....	67	
11.4.6	Handling of error conditions	67	
11.4.6.1	Call reference procedural errors.....	67	
11.4.6.2	Message type or message sequence errors	67	
11.4.6.3	Duplicated information elements	67	
11.4.6.4	Mandatory information element errors.....	67	
11.4.6.4.1	Mandatory information element missing.....	67	
11.4.6.5	Non-mandatory information element errors.....	67	
11.4.6.5.1	Unrecognized information element	68	
11.4.6.5.2	Non-mandatory information element content error	68	
11.4.6.6	Status enquiry procedure.....	69	
11.4.6.7	Receiving a STATUS message	69	
11.4.7	User notification procedure	70	
11.4.8	Restart procedure.....	70	
11.5	TE timers	70	
12	X.25	71	
12.1	X.25 requirements	71	
12.2	X.25 procedures	71	
12.2.1	Data link protocol supporting the X.25 packet level protocol	71	
12.2.2	X.25 packet level protocol	71	
12.2.3	Outgoing and incoming virtual calls.....	71	
12.2.4	Identification of X.25 terminals	71	

Page 8**TBR 33: December 1997**

Annex A (normative):	TBR Requirements Table (TBR-RT)	72
A.1	Guidance for completion of the TBR-RT	72
A.2	General classification of requirements TBR-RT	73
A.3	Layer 1 and overvoltage requirements TBR-RT	75
A.3.1	On-demand layer 1 requirement tables.....	75
A.3.2	Semi-permanent layer 1 requirement tables.....	79
A.4	Layer 2 TBR-RT.....	83
A.5	Layer 3 TBR-RT.....	86
Annex B (normative):	Conformance test principles for layer 1	88
B.1	Scope and general information.....	88
B.1.1	Scope	88
B.1.2	General information.....	88
B.1.3	Definitions and abbreviations	88
B.1.4	Environmental conditions	88
B.1.5	Test case selection	89
B.2	Electrical characteristics tests	92
B.3	Functional characteristic tests	92
B.4	Interface procedure tests	92
B.4.1	The TTCN Graphical form (TTCN.GR)	92
B.4.2	The TTCN Machine Processable form (TTCN.MP)	92
B.5	Power feeding.....	93
Annex C (normative):	Layer 2 tests	94
C.1	The TTCN Graphical form (TTCN.GR)	94
C.2	The TTCN Machine Processable form (TTCN.MP)	94
Annex D (normative):	Layer 3 tests	95
D.1	The TTCN Graphical form (TTCN.GR)	95
D.2	The TTCN Machine Processable form (TTCN.MP)	95
Annex E (normative):	Partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma	96
E.1	Introduction	96
E.2	References	96
E.3	Proforma structure and contents	96
E.4	Table/item identification	96
E.5	Guidance on completing the PIXIT	96
E.6	Environmental test conditions.....	96

E.7	Layer 1 PIXIT	97
E.8	Layer 2 PIXIT	99
E.9	Layer 3 PIXIT	102
Annex F (informative): Justifications for the requirements in the TBR		104
F.1	Principles applicable to the whole TBR	104
F.1.1	General principles	104
F.1.2	Requirements versus definitions.....	104
F.1.3	Error conditions.....	104
F.1.4	General editorial changes to text from the base standards	105
F.1.5	Detailed list of changes with respect to the base standards.....	105
F.1.6	Untested requirements	106
F.1.7	Primitives	106
F.1.8	Supplementary services.....	106
F.1.9	Article 4(e) of the Directive.....	106
F.2	Changes with respect to TBR 3.....	106
F.2.1	Changes for layer 1.....	107
F.2.1.1	Protection requirements	107
F.2.1.2	Detailed list of changes with respect to TBR 3.....	107
F.2.2	Changes for layer 2 of the D-channel	108
F.2.3	Changes for layer 3 of the D-channel	109
Annex G (normative): List of supported telecommunication services		112
G.1	Basic telecommunication services	112
G.2	Supplementary services for the access connection	112
Annex H (informative): Examples for TE access configurations with small sets of requirements		113
Annex J (informative): Bibliography		115
History.....		116

Page 10
TBR 33: December 1997

Blank page

Foreword

This Technical Basis for Regulation (TBR) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This TBR resulted from a mandate from the Commission of the European Community (CEC) to provide harmonized standards for the support of the Council Directive 91/263/EEC ("The Terminal Equipment Directive").

Annex F provides information relating to the articles of the Directive 91/263/EEC.

Annexes A, B, C, D, E and G are normative whereas annexes F, H and J are informative.

Overview of the Abstract Test Suites (ATSSs)

This TBR is accompanied by the following ATSSs (see annexes B, C and D):

- T33L1_7 (layer 1);
- T33L2_3 (layer 2);
- T33L3_5 (layer 3).