



## SLOVENSKI STANDARD

DSIST TBR 034:2000 - ,

01!Uj [ i gh2000 - ,

---

### Digitalno omrežje z integriranimi storitvami (ISDN) - Zahteve za priključitev terminalske opreme v paketnem načinu na ISDN z uporabo primarnega dostopa

Integrated Services Digital Network (ISDN); Attachment requirements for packet mode terminal equipment to connect to an ISDN using ISDN primary rate access

Ta slovenski standard je istoveten z: TBR 034 Edition 1

---

#### ICS:

33.080

Digitalno omrežje z integriranimi storitvami (ISDN)

Integrated Services Digital Network (ISDN)

DSIST TBR 034:2000 - ,

en





**T**ECHNICAL  
**B**ASIS for  
**R**EGULATION

**TBR 34**

December 1997

---

Source: SPS

Reference: DTBR/SPS-05120

ICS: 33.020

**Key words:** ISDN, packet mode, terminal, primary, access

**Integrated Services Digital Network (ISDN);  
Attachment requirements for packet mode terminal equipment  
to connect to an ISDN using ISDN primary rate access**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.



## Contents

Foreword .....		9
1	Scope .....	11
2	Normative references .....	11
3	Definitions and abbreviations .....	12
3.1	Definitions .....	12
3.2	Abbreviations .....	13
4	General .....	14
4.1	General requirements for the access of the PH .....	14
4.1.1	Channel used for the access of the PH .....	14
4.1.2	Requirements for layer 1 .....	15
4.1.2.1	Requirements for complete layer 1 (comprising D-channel and B-channels as a whole) .....	15
4.1.2.2	Requirements for layer 1 with respect to the selected channel .....	15
4.1.3	Requirements for layer 2 of the D-channel .....	15
4.1.3.1	Requirements for data link connections with SAPI 0 .....	15
4.1.3.2	Requirements for data link connections with SAPI 16 .....	16
4.1.4	Notification classes .....	16
4.1.5	Requirements for layer 3 of the D-channel .....	16
4.1.5.1	Outgoing calls .....	16
4.1.5.2	Incoming calls .....	17
4.1.5.3	Use of outgoing and incoming calls to support access of the PH .....	17
5	Definitions of primitives .....	17
6	Safety requirements .....	17
7	Electro-Magnetic Compatibility (EMC) requirements .....	17
8	Overvoltage protection requirements .....	18
8.1	Impulse transfer from mains, common mode .....	18
8.2	Impulse transfer from mains, transverse mode .....	18
8.3	Conversion of common mode to transverse mode .....	18
9	Layer 1 requirements .....	18
9.1	Physical characteristics (on-demand access) .....	18
9.2	Specification at the output port .....	18
9.3	Specification at the input port .....	18
9.4	Frame structure .....	18
9.5	Operational functions .....	18
9.6	Semi-permanent B-channel access .....	18
10	Layer 2 D-channel requirements .....	19
10.1	Frame structure for peer-to-peer communication .....	19
10.1.1	General .....	19
10.1.2	Flag sequence .....	19
10.1.3	Address field .....	19
10.1.4	Control field .....	19
10.1.5	Information field .....	20
10.1.6	Transparency .....	20
10.1.7	Frame Check Sequence (FCS) field .....	20

10.1.8	Format convention .....	20
10.1.8.1	Numbering convention .....	20
10.1.8.2	Order of bit transmission .....	20
10.1.8.3	Field mapping convention .....	20
10.1.9	Invalid or incompatible frames .....	20
10.2	Elements of procedures and formats of fields for data link layer peer-to-peer communication .....	20
10.2.1	General .....	20
10.2.2	Address field format .....	20
10.2.3	Address field variables .....	20
10.2.3.1	Address field extension bit (EA) .....	20
10.2.3.2	Command/Response field bit (C/R) .....	21
10.2.3.3	Service Access Point Identifier (SAPI) .....	21
10.2.3.4	Terminal Endpoint Identifier (TEI) .....	21
	10.2.3.4.1    TEI for broadcast data link connection .....	21
	10.2.3.4.2    TEI for point-to-point data link connection .....	21
10.2.4	Control field formats .....	21
10.2.4.1	Information transfer (I) format .....	21
10.2.4.2	Supervisory (S) format .....	21
10.2.4.3	Unnumbered (U) format .....	21
10.2.5	Control field parameters and associated state variables .....	22
10.2.5.1	Poll/Final bit .....	22
10.2.5.2	Multiple frame operation - variables and sequence numbers .....	22
	10.2.5.2.1    Modulus .....	22
	10.2.5.2.2    Send state variable V(S) .....	22
	10.2.5.2.3    Acknowledge state variable V(A) .....	22
	10.2.5.2.4    Send sequence number N(S) .....	22
	10.2.5.2.5    Receive state variable V(R) .....	22
	10.2.5.2.6    Receive sequence number N(R) .....	22
10.2.6	Frame types .....	22
10.2.6.1	Commands and responses .....	22
10.2.6.2	Information (I) command .....	23
10.2.6.3	Set Asynchronous Balanced Mode Extended (SABME) command .....	23
10.2.6.4	DISConnect (DISC) command .....	23
10.2.6.5	Unnumbered Information (UI) command .....	23
10.2.6.6	Receive Ready (RR) command/response .....	24
10.2.6.7	REject (REJ) command/response .....	24
10.2.6.8	Receive Not Ready (RNR) command/response .....	24
10.2.6.9	Unnumbered Acknowledgement (UA) response .....	24
10.2.6.10	Disconnected Mode (DM) response .....	24
10.3	Provision of point-to-point signalling connections .....	24
10.4	Procedures for unacknowledged information transfer .....	24
10.4.1	Transmission of unacknowledged information .....	24
10.4.2	Receipt of unacknowledged information .....	24
10.5	Terminal Endpoint Identifier (TEI) management procedures .....	25
10.5.1	General .....	25
10.5.2	TEI assignment procedure .....	25
	10.5.2.1    Expiry of timer T202 .....	25
10.5.3	TEI check procedure .....	25
10.5.4	TEI removal procedure .....	25
	10.5.4.1    Action taken by the data link layer entity receiving the MDL-REMOVE-REQUEST primitive .....	25
	10.5.4.2    Conditions for TEI removal .....	25
10.5.5	TEI identity verify procedure .....	25
	10.5.5.1    General .....	25
	10.5.5.2    Operation of the TEI identity verify procedure .....	25
10.5.6	Formats and codes .....	25
10.6	Procedures for establishment and release of multiple frame operation .....	26
10.6.1	Establishment of multiple frame operation .....	26
	10.6.1.1    General .....	26

	10.6.1.2	Establishment procedures .....	26
		10.6.1.2.1 Establishment initiation .....	26
		10.6.1.2.2 Establishment response .....	26
	10.6.1.3	Procedure on expiry of timer T200 .....	27
10.7	10.6.2	Termination of multiple frame operation.....	27
		Procedures for information transfer in multiple frame operation .....	27
	10.7.1	Transmitting I-frames .....	27
	10.7.2	Receiving I-frames .....	27
		10.7.2.1 P bit set to 1 .....	27
		10.7.2.2 P bit set to 0.....	27
	10.7.3	Receiving acknowledgements.....	28
	10.7.4	Receiving REJ frames.....	28
	10.7.5	Receiving RNR frames.....	29
		10.7.5.1 Receiving a valid RNR command or response.....	29
		10.7.5.2 Expiry of timer T200 during "peer receiver busy" .....	29
		10.7.5.3 Receiving a valid RNR command or response during "peer receiver busy" .....	30
		10.7.5.4 Receiving a valid RR or REJ command or response during "peer receiver busy".....	30
		10.7.5.5 Appropriate supervisory response frame.....	30
	10.7.6	Waiting acknowledgement .....	31
10.8		Re-establishment of multiple frame operation .....	31
10.9		Exception condition reporting and recovery.....	32
	10.9.1	N(S) sequence error.....	32
	10.9.2	Invalid frame condition .....	32
	10.9.3	Frame rejection condition.....	32
	10.9.4	Multiple-assignment of TEI value .....	32
10.10		List of system parameters.....	33
	10.10.1	Timer T200.....	33
	10.10.2	Maximum number of retransmissions (N200).....	33
	10.10.3	Maximum number of octets in an information field (N201) .....	33
	10.10.4	Maximum number of transmission of the TEI identity request message (N202) .....	33
	10.10.5	Maximum number of outstanding I-frames (k) .....	33
	10.10.6	Timer T202.....	33
	10.10.7	Layer 2 response time .....	33
11		Layer 3 D-channel requirements.....	34
	11.1	Overview of call control.....	34
		11.1.1 Call states at the user side of the interface .....	34
			34
		11.1.1.1 Null state (U0).....	34
		11.1.1.2 Call initiated (U1) .....	34
		11.1.1.3 Outgoing call proceeding (U3).....	34
		11.1.1.4 Call present (U6).....	34
		11.1.1.5 Call received (U7) .....	35
		11.1.1.6 Connect request (U8) .....	35
		11.1.1.7 Incoming call proceeding (U9).....	35
		11.1.1.8 Active (U10).....	35
		11.1.1.9 Disconnect request (U11).....	35
		11.1.1.10 Disconnect indication (U12).....	35
		11.1.1.11 Release request (U19) .....	35
		11.1.2 Network call states .....	35
			35
		11.1.2.1 Null state (N0).....	35
		11.1.2.2 Call initiated (N1) .....	35
		11.1.2.3 Outgoing call proceeding (N3).....	35
		11.1.2.4 Call present (N6).....	36
		11.1.2.5 Call received (N7) .....	36
		11.1.2.6 Connect request (N8) .....	36
		11.1.2.7 Incoming call proceeding (N9).....	36
		11.1.2.8 Active (N10).....	36
		11.1.2.9 Disconnect request (N11).....	36
		11.1.2.10 Disconnect indication (N12).....	36
		11.1.2.11 Release request (N19) .....	36

11.1.3	States associated with the global call reference.....	37
11.1.3.1	Call states at the user side of the interface.....	37
	11.1.3.1.1 Null (Rest 0) .....	37
	11.1.3.1.2 Restart (Rest 2).....	37
11.1.3.2	Call states at the network side of the interface .....	37
	11.1.3.2.1 Null (Rest 0) .....	37
	11.1.3.2.2 Restart request (Rest 1).....	37
11.2	Message functional definitions and content .....	37
11.2.1	Alerting.....	38
11.2.2	Call proceeding.....	39
11.2.3	Connect .....	39
11.2.4	Connect acknowledge .....	40
11.2.5	Disconnect.....	40
11.2.6	Release.....	41
11.2.7	Release complete.....	41
11.2.8	Setup .....	42
11.2.9	Status.....	43
11.2.10	Status enquiry.....	43
11.2.11	Messages used with the global call reference.....	43
	11.2.11.1 Restart.....	43
	11.2.11.2 Restart acknowledge .....	43
11.3	General message format and information elements coding .....	44
11.3.1	Overview.....	44
11.3.2	Protocol discriminator .....	44
11.3.3	Call reference .....	44
11.3.4	Message type.....	44
11.3.5	Other information elements .....	46
	11.3.5.1 Coding rules.....	46
	11.3.5.1.1 Codeset 0.....	46
	11.3.5.2 Extensions of codesets .....	47
	11.3.5.3 Locking shift procedure.....	47
	11.3.5.4 Non-locking shift procedure .....	47
	11.3.5.5 Bearer capability .....	47
	11.3.5.6 Call state .....	49
	11.3.5.7 Called party number.....	49
	11.3.5.8 Called party subaddress .....	49
	11.3.5.9 Calling party number .....	49
	11.3.5.10 Calling party subaddress.....	51
	11.3.5.11 Cause.....	52
	11.3.5.12 Channel identification.....	52
	11.3.5.13 Restart indicator .....	52
11.4	Call control procedures for the control of packet-mode access of the PH.....	53
11.4.1	Call establishment at the originating interface.....	53
	11.4.1.1 Call request.....	53
	11.4.1.2 Overlap sending.....	53
	11.4.1.3 Call proceeding .....	53
	11.4.1.4 Call confirmation indication .....	54
	11.4.1.5 Call connected .....	54
11.4.2	Call establishment at the destination interface .....	54
	11.4.2.1 Incoming call .....	54
	11.4.2.2 Compatibility checking .....	54
	11.4.2.3 Channel selection-destination.....	55
	11.4.2.4 Overlap receiving .....	55
	11.4.2.5 Call confirmation .....	55
	11.4.2.6 Call accept .....	56
	11.4.2.7 Active indication .....	56
11.4.3	Call clearing.....	56
	11.4.3.1 Terminology .....	56
	11.4.3.2 Exception conditions .....	56
	11.4.3.3 Clearing initiated by the user.....	56
	11.4.3.4 Clearing initiated by the network .....	57
	11.4.3.4.1 Clearing when tones/announcements provided.....	57



		11.4.3.4.2	Clearing when tones/announcements not provided .....	57
		11.4.3.4.3	Completion of clearing .....	57
	11.4.3.5	Clear collision .....		57
	11.4.4	Call rearrangements .....		57
	11.4.5	Call collisions .....		58
	11.4.6	Handling of error conditions .....		58
		11.4.6.1	Call reference procedural errors .....	58
		11.4.6.2	Message type or message sequence errors .....	58
		11.4.6.3	Duplicated information elements .....	58
		11.4.6.4	Mandatory information element errors .....	58
		11.4.6.4.1	Mandatory information element missing .....	58
		11.4.6.5	Non-mandatory information element errors .....	59
		11.4.6.5.1	Unrecognized information element .....	59
		11.4.6.5.2	Non-mandatory information element content error .....	59
		11.4.6.6	Status enquiry procedure .....	60
		11.4.6.7	Receiving a STATUS message .....	60
	11.4.7	User notification procedure .....		61
	11.4.8	Restart procedure .....		61
	11.5	TE timers .....		61
12	X.25 .....			62
	12.1	X.25 requirements .....		62
	12.2	X.25 procedures .....		62
		12.2.1	Data link protocol supporting the X.25 packet level protocol .....	62
		12.2.2	X.25 packet level protocol .....	62
		12.2.3	Outgoing and incoming virtual calls .....	62
		12.2.4	Identification of X.25 terminals .....	62
	Annex A (normative):	TBR Requirements Table (TBR-RT) .....		63
	A.1	Guidance for completion of the TBR-RT .....		63
	A.2	General classification of requirements TBR-RT .....		64
	A.3	Layer 1 and overvoltage requirements TBR-RT .....		66
	A.4	Layer 2 TBR-RT .....		69
	A.5	Layer 3 TBR-RT .....		72
	Annex B (normative):	Layer 1 tests .....		74
	Annex C (normative):	Layer 2 tests .....		75
	C.1	The TTCN Graphical form (TTCN.GR) .....		75
	C.2	The TTCN Machine Processable form (TTCN.MP) .....		75
	Annex D (normative):	Layer 3 tests .....		76
	D.1	The TTCN Graphical form (TTCN.GR) .....		76
	D.2	The TTCN Machine Processable form (TTCN.MP) .....		76
	Annex E (normative):	Partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma .....		77
	E.1	Introduction .....		77
	E.2	References .....		77

E.3	Proforma structure and contents .....	77
E.4	Table/item identification .....	77
E.5	Guidance on completing the PIXIT .....	77
E.6	Environmental test conditions.....	77
E.7	Layer 1 PIXIT .....	78
E.8	Layer 2 PIXIT .....	78
E.9	Layer 3 PIXIT .....	80
Annex F (informative): Justifications for the requirements in the TBR.....		82
F.1	Principles applicable to the whole TBR .....	82
F.1.1	General principles .....	82
F.1.2	Requirements vs. definitions .....	82
F.1.3	Error conditions .....	82
F.1.4	General editorial changes to text from the base standards .....	83
F.1.5	Detailed list of changes with respect to the base standards .....	83
F.1.6	Untested requirements.....	84
F.1.7	Primitives.....	84
F.1.8	Supplementary services.....	84
F.1.9	Differences in clauses 10 and 11 and the TBR-RT between TBR 33 and this TBR .....	84
F.1.10	Article 4(e) of the Directive .....	85
F.2	Changes with respect to TBR 4.....	85
F.2.1	Changes for layer 1 .....	86
F.2.1.1	Timing considerations.....	86
F.2.1.2	CRC-4 monitoring and E-bits.....	86
F.2.1.3	Protection requirements.....	86
F.2.1.4	Detailed list of changes with respect to TBR 4 .....	86
F.2.2	Changes for layer 2 of the D-channel.....	87
F.2.3	Changes for layer 3 of the D-channel.....	88
Annex G (normative): List of supported telecommunication services.....		91
G.1	Basic telecommunication services.....	91
G.2	Supplementary services for the access connection .....	91
Annex H (informative): Examples for TE access configurations with small sets of requirements.....		92
Annex J (informative): Bibliography .....		94
History .....		95

## Foreword

This Technical Basis for Regulation (TBR) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This TBR resulted from a mandate from the Commission of the European Community (CEC) to provide harmonized standards for the support of the Council Directive 91/263/EEC ("The Terminal Equipment Directive").

Annex F provides information relating to the articles of the Directive 91/263/EEC.

Annexes A, B, C, D, E and G are normative whereas annexes F, H and J are informative.

### Overview of the Abstract Test Suites (ATs)

This TBR is accompanied by the following ATs (see annexes C and D):

- T34L2\_3 (layer 2);
- T34L3\_5 (layer 3).

Blank page

## 1 Scope

This Technical Basis for Regulation (TBR) specifies the technical requirements under Articles 4 (c) to 4 (f) of Council Directive 91/263/EEC ("The Terminal Equipment Directive") for Terminal Equipment (TE) to be attached to the pan-European Integrated Services Digital Network (ISDN) at an interface at the T reference point or coincident S and T reference point for a primary rate access. These requirements are taken from TBR 4 [8], TBR 13 [9], ETS 300 007 [10], ETS 300 046-3 [12], ETS 300 011 [11], ETS 300 102-1 [13] and ETS 300 125 [14]. This TBR does not contain the essential requirements of Article 4 (g) for interworking via the public network, and so does not provide any guarantee of correct terminal-to-terminal operation.

NOTE 1: Although this TBR provides the technical attachment requirements, it does not contain the full specification of the user side of the ISDN user-network interface. Important information necessary for correct working can be found only in the base standards mentioned above.

This TBR specifies these requirements for TE that:

- a) access Packet Handler (PH) of an ISDN through either on-demand B- or D-channel mode or semi-permanent B-channel mode basic services (case B of X.31) and those related supplementary services that are specified in annex G; and
- b) is capable of handling either incoming calls only, outgoing calls only or both incoming and outgoing calls.

This TBR applies to all TE that is intended for connection to the forms of ISDN access referred to above, irrespective of whether the TE provides additional interfaces, telecommunications services or functions for which other TBRs or national approval requirements apply.

This TBR does not specify the requirements for a packet mode TE that uses on-demand B-Channel circuit mode access (case A of X.31); the requirements for such a TE are contained in TBR 4 [8].

NOTE 2: This TBR is not applicable to TE which may be supplied in some countries for connection to an ISDN telecommunications service corresponding to, but not compatible with, the pan-European ISDN primary rate access standards.

## 2 Normative references

This TBR incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to, or revisions of any of these publications apply to this TBR only when incorporated into it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ITU-T Recommendation G.703 (1991): "Physical/electrical characteristics of hierarchical digital interfaces".
- [2] ITU-T Recommendation G.706 (1991): "Frame alignment and cyclic redundancy check (CRC) procedures relating to basic frame structures defined in Recommendation G.704".
- [3] ITU-T Recommendation I.411 (1988): "ISDN user-network interfaces - Reference configurations".
- [4] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General Concepts".
- [5] ISO/IEC 9646-2: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".