



SLOVENSKI STANDARD

SIST EN 12976-2:2017

01-april-2017

Nadomešča:
SIST EN 12976-2:2006

**Toplotni sončni sistemi in sestavni deli - Industrijsko izdelani sistemi - 2. del:
Preskusne metode**

Thermal solar systems and components - Factory made systems - Part 2: Test methods

Thermische Solaranlagen und ihre Bauteile - Vorgefertigte Anlagen - Teil 2:
Prüfverfahren

ITeh STANDARD PREVIEW
(standards.iteh.ai)

Installations solaires thermiques et leurs composants - Installations préfabriquées en
usine - Partie 2: Méthodes d'essai [SIST EN 12976-2:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/d15a1529-a2f4-4b2c-81e3-359307e17847/sist-en-12976-2-2017>

Ta slovenski standard je istoveten z: EN 12976-2:2017

ICS:

27.160

Sončna energija

Solar energy engineering

SIST EN 12976-2:2017

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 12976-2:2017

<https://standards.iteh.ai/catalog/standards/sist/d15a1529-a2f4-4b2c-81e3-359307e17847/sist-en-12976-2-2017>

EUROPEAN STANDARD

EN 12976-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

January 2017

ICS 27.160

Supersedes EN 12976-2:2006

English Version

Thermal solar systems and components - Factory made systems - Part 2: Test methods

Installations solaires thermiques et leurs composants -
Installations préfabriquées en usine - Partie 2 :
Méthodes d'essai

Thermische Solaranlagen und ihre Bauteile -
Vorgefertigte Anlagen - Teil 2: Prüfverfahren

This European Standard was approved by CEN on 15 April 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

European foreword.....	6
Introduction	8
1 Scope.....	10
2 Normative references.....	10
3 Terms and definitions	10
4 Symbols and abbreviations	10
5 Testing.....	11
5.1 Freeze resistance.....	11
5.1.1 General.....	11
5.1.2 Systems using antifreeze fluid.....	11
5.1.3 Drain-back systems	11
5.1.4 Drain-down systems	12
5.1.5 Freeze protection and combined control functions	12
5.1.6 Other systems.....	12
5.2 Over temperature protection	13
5.2.1 Purpose.....	13
5.2.2 Apparatus.....	13
5.2.3 Procedure.....	13
5.2.4 Reporting requirements.....	14
5.3 Pressure resistance	14
5.3.1 Purpose	14
5.3.2 Apparatus.....	14
5.3.3 Safety precaution	15
5.3.4 Procedure.....	15
5.3.5 Reporting requirements.....	16
5.4 Water contamination.....	16
5.5 Testing the resistance against mechanical load	17
5.5.1 Purpose	17
5.5.2 Apparatus.....	17
5.5.3 Safety precaution	17
5.5.4 Calculation procedure for the mechanical load.....	18
5.5.5 Procedure.....	20
5.5.6 Reporting requirements.....	20
5.6 Lightning protection	21
5.7 Safety equipment.....	21
5.7.1 Safety valves.....	21
5.7.2 Safety lines and expansion lines	22
5.7.3 Blow-off lines	22
5.8 Labelling.....	22
5.9 Thermal performance characterization	22
5.9.1 Introduction.....	22
5.9.2 Test procedure	23
5.9.3 Prediction of yearly performance indicators.....	24
5.10 Ability of solar-plus-supplementary systems to cover the load.....	31

5.10.1	General	31
5.10.2	Boundary conditions for auxiliary heating	31
5.10.3	Boundary conditions for daily load.....	32
5.10.4	Determination of the ability to cover the maximum daily load by means of testing the system.....	33
5.10.5	Determination of the ability to cover the maximum daily load by means of numerical simulations.....	33
5.10.6	Determination of the ability to cover the daily load defined by the European load profiles by means of numerical simulations.....	33
5.10.7	Requirements for mixed water at 40 °C	34
5.11	Reverse flow protection	36
5.12	Electrical safety	36
Annex A (normative) Thermal performance presentation sheet		37
Annex B (normative) Reference conditions for performance prediction.....		39
B.1	General	39
B.2	Pipe diameter and insulation thickness.....	42
B.3	Calculation of cold water temperature at reference location	43
B.4	Additional set of reference conditions for annual performance calculations.....	44
B.5	Reference conditions for the performance of the auxiliary heater.....	47
Annex C (informative) Assessment of the ability of solar DWH systems to resist the extreme climatic conditions.....		48
C.1	Indoor and outdoor test procedure for assessment of the frost resistance of solar DWH systems with outdoor storage tank or system using heat transfer fluid with the risk of freezing.....	48
C.1.1	Objective and applicability.....	48
C.1.2	Apparatus and mounting of the system.....	48
C.1.3	Test procedure.....	49
C.1.4	Test conditions — Determination of the test conditions for freezing period.....	50
C.1.5	Results	50
C.2	Indoor test procedure for assessment of the reliability of solar DWH systems in respect of overheating protection	51
C.2.1	Objective and applicability.....	51
C.2.2	Apparatus and mounting of the system.....	51
C.2.3	Test procedure	53
C.2.4	Test conditions	53
C.2.5	Results	55
Annex D (informative) Ageing test for thermostatic valves.....		57
D.1	General	57
D.2	Test arrangement	57
D.3	Test Procedure	58
D.4	Results	59
Annex E (informative) Lightning protection test for solar heating systems		60
E.1	Field of application.....	60
E.2	Purpose	60
E.3	Requirements.....	60
E.4	Apparatus	61
E.5	Test procedure	61
E.5.1	Test conditions	61
E.5.2	Solar heating system installation.....	61
E.5.3	Separation distance S_t	61

EN 12976-2:2017 (E)

E.5.4	Size of the bonding cable or strip	61
E.5.5	Bridging between tank and supports	61
E.5.6	Bridging between collectors and supports	62
E.5.7	Bridging between collectors and tank	62
E.5.8	Connecting terminal with Lightning Protection System (LPS)	62
E.5.9	Metal sheets covering parts of the solar heating system	62
E.5.10	Heating effects due to lightning currents	62
E.5.11	Mechanical durability due to lightning mechanical loads	62
E.6	Report	62
E.7	Conclusions	62
Annex F (informative) Lightning Protection testing sheet		63
Annex G (normative) Reporting format in the framework of the EU Regulations CDR 811, 812 and 814 dated 2013		67
Annex ZA (informative) Relationship between this European Standard and the energy labelling requirements of Commission Delegated Regulation (EU) No 811/2013 aimed to be covered		68
Annex ZB (informative) Relationship between this European Standard and the energy labelling requirements of Commission Delegated Regulation (EU) No 812/2013 aimed to be covered		70
Annex ZC (informative) Relationship between this European Standard and the ecodesign requirements of Commission Regulation (EU) No 814/2013 aimed to be covered		73
Bibliography		75
<p>ITC STANDARD PREVIEW (standards.iteh.ai)</p>		
<p>SIST EN 12976-2:2017</p> <p>https://standards.iteh.ai/catalog/standards/sist/d15a1529-a2f4-4b2c-81e3-559507c17847/sist-en-12976-2-2017</p>		
Tables		
Table 1	— Division for factory made and custom built solar heating systems	9
Table 2	— Selection of the performance test method	23
Table 3	— Parameter a values for different load volumes	23
Table 4	— Daily heat demand for load profiles	28
Table 5	— Adjustment factors	30
Table 6	— Load profile selection	30
Table A.1	— Presentation of the system performance indicators for solar-plus- supplementary systems	37
Table A.2	— Presentation of the system performance indicators for solar-only and solar preheat systems	38
Table B.1	— Reference conditions for performance presentation	40
Table B.2	— Pipe diameter and insulation thickness for forced-circulation systems	42
Table B.3	— Pipe diameter and insulation thickness for thermosiphon systems	42
Table B.4	— Data for calculation of the cold water temperature at the reference locations	43
Table B.5	— Reference conditions for performance presentation limited to the deviations from Table B.1	44
Table B.6	— Monthly and average annual reference outside air temperatures for two climate zones in °C	46

Table B.7 — Monthly and average annual reference solar irradiation for two climate zones in kWh/m²	46
Table B.8 — Specifications of the average and colder climate hourly data file according to Meteonorm	46
Table B.9 — Reference conditions the performance of the auxiliary heater, limited to the deviations from Table B.1	47
Table C.1 — Test conditions	50
Table F.1 — Size of bonding cable	63
Table F.2 — Size of metal cover sheets	63
Table F.3 — Lightning protection testing sheet	64
Table ZA.1 —Correspondence between this European Standard and Commission Delegated Regulation (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to energy labelling of space heaters, combination heaters, packages of space heaters, temperature control and solar device and packages of combination heater, temperature control and solar device and Commission’s standardisation request ‘M/535/C(2015) 2626’	69
Table ZB.1 — Correspondence between this European Standard and Commission Delegated Regulation (EU) No 812/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to energy labelling of water heaters, hot water storage tanks and packages of water heater and solar device and Commission’s standardisation request ‘M/534/C(2015) 2625’	70
Table ZC.1 — Correspondence between this European Standard and Commission Regulation (EU) No 814/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for water heaters and hot water storage tanks and Commission’s standardisation request ‘M/534/C(2015) 2625’	74
 Figures	
Figure 1 — Dimensions of the system to be measured	18
Figure 2 — Force orthogonal to surface of system — Side view	19
Figure 3 — Energy balance for one-store solar-plus-supplementary systems (example)	25
Figure 4 — Energy balance for solar-only systems	26
Figure 5 — Energy balance for solar preheat systems	27
Figure A.1 — Thermal performance presentation sheet	37
Figure C.1 — Scheme of the test set-up	52
Figure D.1 — Test arrangement for thermostatic valve test	58

EN 12976-2:2017 (E)**European foreword**

This document (EN 12976-2:2017) has been prepared by Technical Committee CEN/TC 312 “Thermal solar systems and components”, the secretariat of which is held by ELOT.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2017, and conflicting national standards shall be withdrawn at the latest by July 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 12976-2:2006.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annexes ZA, ZB or ZC, which are an integral part of this document.

Most significant changes in EN 12976-1:2017 and EN 12976-2:2017 since the 2006 editions of both parts:

The first edition of the EN 12976 series was published in 2000. The standard series provided an important basis for the assessment of the performance as well as the reliability and durability of Factory made solar thermal systems. In the past 15 years or so, several important technological developments and changes of the framework conditions, such as e.g. the aspect of requiring “Energy Labelling”, the EN 12976 series underwent several important changes.

The following modifications are the most important ones that have been implemented in this new edition of EN 12976-2:

- main changes related to ErP and the new mechanical load test;
- Annex ZA (new): harmonisation with Regulation (EC) No 811/2013;
- Annex ZB (new): harmonisation with Regulation (EC) No 812/2013;
- Annex ZC (new): harmonisation with Regulation (EC) No 814/2013.

It is worth to notice that, based on these changes and developments, the need for the elaboration of a future strategy of the structure of the EN 12976 series is foreseen.

EN 12976, *Thermal solar systems and components — Factory made systems*, is currently composed with the following parts:

- *Part 1: General requirements;*
- *Part 2: Test methods.*

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 12976-2:2017

<https://standards.iteh.ai/catalog/standards/sist/d15a1529-a2f4-4b2c-81e3-359307e17847/sist-en-12976-2-2017>

Introduction

Drinking water quality:

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the product covered by this standard:

- a) this standard provides no information as to whether the product may be used without restriction in any of the Member States of the EU or EFTA;
- b) it should be noted that, while awaiting the adoption of verifiable European criteria, existing national regulations concerning the use and/or the characteristics of this product remain in force.

Factory Made and Custom Built solar heating systems:

The standards EN 12976-1, EN 12976-2, EN 12977-1, EN 12977-2, EN 12977-3, EN 12977-4 and EN 12977-5 distinguish two categories of solar heating systems: **Factory Made** solar heating systems and **Custom Built** solar heating systems. The classification of a system as Factory Made or Custom Built is a choice of the final supplier, in accordance with the following definitions:

Factory Made solar heating systems are batch products with one trade name, sold as complete and ready to install kits, with fixed configurations. Systems of this category are considered as a single product and assessed as a whole.

If a Factory Made Solar Heating System is modified by changing its configuration or by changing one or more of its components, the modified system is considered as a new system for which a new test report is necessary. Requirements and test methods for Factory Made solar heating systems are given in EN 12976-1 and EN 12976-2.

Custom Built solar heating systems are either uniquely built, or assembled by choosing from an assortment of components. Systems of this category are regarded as a set of components. The components are separately tested and test results are integrated to an assessment of the whole system. Requirements for Custom Built solar heating systems are given in EN 12977-1; test methods are specified in EN 12977-2; EN 12977-3, EN 12977-4 and EN 12977-5. Custom Built solar heating systems are subdivided into two categories:

- **Large Custom Built systems** are uniquely designed for a specific situation. In general HVAC engineers, manufacturers or other experts design them.
- **Small Custom Built systems** offered by a company are described in a so-called assortment file, in which all components and possible system configurations, marketed by the company, are specified. Each possible combination of a system configuration with components from the assortment is considered as **one** Custom Built system.

Table 1 shows the division for different system types:

Table 1 — Division for factory made and custom built solar heating systems

Factory Made Solar Heating Systems (EN 12976-1 and EN 12976-2)	Custom Built Solar Heating Systems (EN 12977-1, EN 12977-2 and EN 12977-3)
Integrated collector storage systems for domestic hot water preparation	Forced-circulation systems for hot water preparation and/or space heating, assembled using components and configurations described in an assortment file (mostly small systems)
Thermosiphon systems for domestic hot water preparation	
Forced-circulation systems as batch product with fixed configuration for domestic hot water preparation	Uniquely designed and assembled systems for hot water preparation and/or space heating (mostly large systems)

NOTE Forced circulation systems can be classified either as Factory Made or as Custom Built, depending on the market approach chosen by the final supplier.

Both Factory Made and Custom Built systems are performance tested under the same set of reference conditions as specified in Annex B of the present standard and EN 12977-2:2012, Annex A. In practice, the installation conditions may differ from these reference conditions.

A Factory Made System for domestic hot water preparation may have an option for space heating, however this option should not be used or considered during testing as a Factory Made system.

(standards.iteh.ai)

SIST EN 12976-2:2017

<https://standards.iteh.ai/catalog/standards/sist/d15a1529-a2f4-4b2c-81e3-359307e17847/sist-en-12976-2-2017>

EN 12976-2:2017 (E)**1 Scope**

This European Standard specifies test methods for validating the requirements for Factory Made Thermal Solar Heating Systems as specified in EN 12976-1. The standard also includes two test methods for thermal performance characterization by means of whole system testing.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1489, *Building valves — Pressure safety valves — Tests and requirements*

EN 1717:2000, *Protection against pollution of potable water in water installations and general requirements of devices to prevent pollution by backflow*

EN 12976-1:2017, *Thermal solar systems and components — Factory made systems — Part 1: General requirements*

EN 12977-2:2012, *Thermal solar systems and components — Custom built systems — Part 2: Test methods for solar water heaters and combisystems*

EN 15502-1, *Gas-fired heating boilers — Part 1: General requirements and tests*

EN ISO 9488:1999, *Solar energy — Vocabulary (ISO 9488:1999)*

EN ISO 9806:2013, *Solar energy — Solar thermal collectors — Test methods (ISO 9806:2013)*

ISO 9459-1:1993, *Solar heating — Domestic water heating systems — Part 1: Performance rating procedure using indoor test methods*

ISO 9459-2:1995, *Solar heating — Domestic water heating systems — Part 2: Outdoor test methods for system performance characterization and yearly performance prediction of solar-only systems*

ISO 9459-5, *Solar heating — Domestic water heating systems — Part 5: System performance characterization by means of whole-system tests and computer simulation*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 9488:1999 and EN 12976-1:2017 apply.

4 Symbols and abbreviations

$Q_{\text{aux, net}}$ net auxiliary energy demand of a solar heating system delivered by the auxiliary heater to the store or directly to the distribution system (see 5.9.3.2)

Q_d heat demand

Q_L energy delivered at the outlet of the solar heating system

Q_{par}	parasitic energy (electricity) for the collector loop pump(s) and control unit
H_c	hemispherical solar irradiation in the collector plane
Q_l	store heat loss
Q_{ohp}	heat diverted from the store as active overheating protection, if any
Q_{sol}	heat delivered by the collector loop to the store

5 Testing

5.1 Freeze resistance

5.1.1 General

The following checks are given to ensure that the protective anti-freezing provisions are operating properly. There are many possible forms of protective provisions, and the testing authority shall first identify which method has been employed.

The provision shall then be checked in accordance with the appropriate section of the following list (see 5.1.2 to 5.1.6) in accordance with the manufacturer's recommendations.

5.1.2 Systems using antifreeze fluid

The system components which are exposed to low ambient temperature are filled with an antifreeze fluid usually a glycol/water mixture, having a low enough freezing point. For thermosiphon systems declared as freeze resistant down to a specific temperature, one possible test procedure described in AS/NZS 2712 is recommended. This procedure could also be adapted to other systems containing pure water. So far, electrical heater for freeze protection will not be tested for suitability.

For these systems, no freezing test is performed. However, if no sufficient data are available on the freezing point of the antifreeze fluid, the freezing point shall be measured and checked against the minimum system temperature as given by the manufacturer.

NOTE In general, the minimum allowed temperature of the system is equal to the freezing point of the antifreeze fluid. If the concentration of some antifreeze fluids like glycols - exceeds a certain limit, they can freeze without damaging the system. In this case the minimum allowed temperature can be lower than the freezing point of the antifreeze fluid.

Check the freezing point by measuring the glycol concentration (e.g. using a portable refractometer) before and after the over temperature protection test (5.2). The freezing point shall not differ more than 2 K from the value recommended by the manufacturer in agreement with the local climate (minimum expected air temperature, radiative cooling of the collectors).

The composition of the fluid shall be checked to see whether it is in accordance with the manufacturer's specifications.

5.1.3 Drain-back systems

When freezing danger occurs, the fluid in the system components that is exposed to low ambient temperature, is drained into a storage vessel for subsequent reuse.

The collector loop piping should be in accordance with the manufacturer's recommendations in the installer manual and if there is no instruction, according to reference conditions given in Annex B.

Filling may be observed from the pressure gauge or from water level indicator. Switch the pump on, and observe the pressure gauge or water level indicator. If the system does not include a pressure gauge or

EN 12976-2:2017 (E)

level indicator, other means for checking filling provided by the manufacturer shall be used in accordance with the instruction manual.

Drain-back may be observed from the decreasing reading of the pressure gauge or water level indicator. Switch the pump OFF, and observe the pressure gauge or water level indicator. If the system does not include a pressure gauge or level indicator, other means for checking drain-back provided by the manufacturer shall be used in accordance with the instruction manual.

A system in which components and/or piping are subject to damage by freezing shall have the proper fittings, pipe slope and collector design to allow for manual gravity draining and air filling of the affected components and piping. Pipe slope for gravity draining shall be as the manufacturer recommendation or shall have a minimum 2 cm vertical drop for each meter of horizontal length. This also applies to any header pipes or absorber plate riser tubes internal to the collector.

5.1.4 Drain-down systems

The fluid in the system components, which are exposed to low ambient temperature, is drained and run to waste when freezing danger occurs.

To perform checks of the drain-down function the collector loop piping should be in accordance with the manufacturer's recommendations in the installer manual and if there is no instruction, according to reference conditions given in Annex B.

In most cases the systems are equipped with a drain-down valve at the bottom and a vacuum relief valve at the top of the fluid circuit.

The proper opening and closing of the vacuum relief valve shall be checked during drain-down operation and after refilling the system.

If there is a solenoid drain valve independent of the control unit, simulate the opening temperature.

If there is a non-electrically operated freeze protection valve, a check can be made using a freezing spray. The temperature-sensing element shall be sprayed. The measured temperature of the valve opening shall be compared with the nominal value given by the manufacturer. It is important that the sensing part of the freeze protection valve be properly placed.

If the system uses an electrically operated freeze-protection valve, drain down shall be checked while interrupting the power.

The drain-down rate shall be measured (e.g. by using a vessel and a stop-watch) and documented during drain-down operation.

5.1.5 Freeze protection and combined control functions

For systems where the freeze protection and control functions are combined, the control unit shall be checked as follows:

Set the simulated temperature of the freeze-protection sensor to a value deactivating the freeze protection. Decrease the simulated temperature slowly. Measure the temperature T_{FP} (freeze protection) of the related actuator. Compare it with the nominal value given by the manufacturer.

5.1.6 Other systems

For all other systems, the pump control system, drain-down valve or any other freeze protection device or system shall be checked to the manufacturer's specification and the minimum allowed temperature specified by the manufacturer.

For Integrated Collector-Storage Systems (ICS), or other Solar Domestic Hot Water (SDHW) systems with the tank placed outside, special frost resistance tests should be carried out, as described in C.1.

5.2 Over temperature protection

5.2.1 Purpose

The purpose of this test is to determine whether the solar water heating system is protected against damage and the user is protected from scalding hot water delivery after a period of no hot water draw and failure of electrical power.

5.2.2 Apparatus

The following apparatus is required:

- a) a pyranometer having the minimum characteristics specified in EN ISO 9806:2013, 22.1.1.1, to measure the total short wave radiation from both the sun and the sky or the short wave radiation from a solar simulator lamp if the test is to be conducted inside a solar simulation chamber;
- b) equipment to measure the temperature, flow rate and volume of hot water drawn from the system;
- c) an outdoor or an indoor test stand for installing the solar hot water system with the collector array at the manufacturer's specified tilt angle;
- d) a temperature and pressure controlled water supply within the range of 5°C to 25 °C and 200 kPa to 600 kPa or the manufacturer's maximum working pressure whichever is less.

This test may be conducted using a solar simulator or outdoors.

5.2.3 Procedure

The system, both as described in the installation manual and as installed on the test facility, shall be first checked on overheating safety, e.g. if safety valves and other overheating protection devices are present and installed at the right place, if there are no valves between components and relief valves, etc. For systems containing antifreeze fluids, it shall be checked whether sufficient precautions have been taken to prevent the antifreeze fluid from deterioration as a result of high temperature conditions (see also 5.7).

Furthermore, if non-metallic materials are used in any circuit, the highest temperature in the circuit during the over temperature protection test shall be measured at the main water inlet, for use in the pressure resistance test.

The procedure of testing shall be as follows:

- a) assemble the solar water heating system according to the installation instructions with the collector array oriented towards solar noon for the outdoor test, or the simulator lamp may be adjusted to normal incidence for the indoor test;
- b) charge the system from the water supply and, for pressurized storage tanks, maintain the water supply pressure;
- c) energize the system as per installation instructions;
- d)
 - 1) for the outdoor test, operate the system for three consecutive days without any hot water withdrawal with a minimal solar irradiation of 20 MJ/m² per day and with ambient temperature higher than 20 °C during solar noon;