INTERNATIONAL STANDARD

ISO/HL7 21731

> First edition 2006-08-01

Health informatics — HL7 version 3 — Reference information model —

Le de santé - HL7 version e de santé - HL7 version e - Version 1 Hennesserente - Management i de santé - HL7 version e - Version 1 hennesserente - Management i de santé - HL7 version e - Version 1 hennesserente - Management i de santé - HL7 version e - Version 1 Informatique de santé — HL7 version 3 — Modèle d'information de



Reference number ISO/HL7 21731:2006(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



© ISO and HL7 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO or IDF at the respective address below.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 • Switzerland Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland Health Level Seven, Inc. Standards Publishing Department 3300 Washtenaw Avenue, Suite 227 Ann Arbor, MI 48104 • USA E-mail hq@hl7.org Web www.hl7.org

HEALTH LEVEL SEVEN **REFERENCE INFORMATION MODEL, RELEASE 1**

Modeling & Methodology Co-Chair

Editor

Modeling & Methodology Co-Chair

Modeling & Methodology Co-Chair

Editor

Editor

Modeling & Methodology Co-Chair George Beeler, Jr., PhD. Beeler Consulting LLC

James Case, DVM, PhD. University of California, Davis

Jane Curry Sierra Systems & CIHI - HL7 Canada

Ann Hueber Pathology Associates Medical Laboratories

Lloyd Mckenzie JBM Canada & CIHI - HL7 Canada & Alberta Wellnet Gunther Schadow, M.D., PhD. .ailcatalog

Regenstrief Institute for Health Care

Abdul-Malik Shakir Shakir Consulting LLC

Health Level Seven and HL7 are registered trademarks of Health Level Seven, Inc.

Health Level Seven, 3300 Washtenaw Avenue, Suite 227, Ann Arbor, MI 48104-4261. Phone: 734-677-7777 Fax: 734-677-6622, Email: HQ@HL7.org; Internet: http://www.HL7.org

23bbeadball

CONT	PA PA	GE
Foreword vi		
0 0.1 0.2	Introduction Uses of a Reference Information Model (RIM) in Health Informatics Further information	vi
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	1
5 5.1 5.2 5.3	Interpretation of the Specification	7 7 8 9
6	Subject areas	. 15
6.1 6.1.1	FoundationClasses	15 . 15
6.1.2	Entities	. 16
6.1.3		16
7	Classes	. 16
7.1 7.2	Classes in subject area Acts	. 16
7.3	Classes in subject area Roles	. 77
0	Associations	0 <i>E</i>
8 8.1	(0*)ActRelationship :: source :: (11)Act :: outboundRelationship	
8.2	(0*)ActRelationship :: target :: (11)Act :: inboundRelationship	
8.3	(11)Entity :: languageCommunication :: (0*)LanguageCommunication :: entity	. 85
8.4	(0*)Participation :: act :: (11)Act :: participation	
8.5	(0*)Participation :: role :: (11)Role :: participation	
8.6	(0*)Role :: player :: (01)Entity :: playedRole	
8.7 8.8	(0*)Role :: scoper :: (01)Entity :: scopedRole	
8.9	(0*)RoleLink :: source :: (11)Role :: outboundLink (0*)RoleLink :: target :: (11)Role :: inboundLink	
9	Normative Vocabulary Contents	86
9.1	RIM Structural Vocabulary	
9.2	ActClass	
9.3	ActMood	
9.4	ActRelationshipCheckpoint	
9.5	ActRelationshipJoin	
9.6	ActRelationshipSplit	
9.7	ActRelationshipType	
9.8	Aciolatus	107

9.9	ContextControl	108
9.10	EntityClass	110
9.11	EntityDeterminer	112
9.12	EntityStatus	113
9.13	ManagedParticipationStatus	113
9.14	ParticipationType	113
9.15	RelationshipConjunction	
9.16	RoleClass	
9.17	RoleLinkType	
9.18	RoleStatus	
		-
Annex	A (informative) Background of RIM Development	126
A.1	History of the RIM	
A.2	Implications of Balloting the RIM	126
Annex	B (informative) Overview of RIM Design Principles	128
B.1	Purpose	128
B.2	Purpose Overview The Rationale Behind the RIM's Design	128
	The Rationale Behind the RIM's Design	128
B.4	Linking Acts Together: The Semantics of ActRelationship	130
B.5	Definitions of the Six Core Rim Classes	131
B.6	Data Type and Vocabulary Specifications	132
B.7	Definitions of the Six Core Rim Classes Data Type and Vocabulary Specifications HL7 Version 3 Methodology and the RIM C (informative) Summary of Version 3 Data Types	133
-	a data sana distantise	
Annex	C (informative) Summary of Version 3 Data types	134
C.1	Overview of Data Types	134
	C (informative) Summary of Version 3 Data Types	
	rds. Dr.	
	182 B	
	1 star 3ar	
	-sill the	
	metter 221	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

A pilot project between ISO and Health Level Seven Inc. (HL7) has been formed to develop and maintain a group of ISO/HL7 standards in the field of medical devices as approved by Council resolution 7/2002. Under this pilot project, HL7 is responsible for the development and maintenance of these standards with participation and input from ISO member bodies.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/HL7 21731 was prepared by HL7 and Technical Committee ISO/TC 215, Health informatics. Leh SLA standar ailcatalog

0 Introduction

This introduction is confined to discussion of the requirement for a Reference Information Model in standardization. Further information on the development of this model and the rational for advancing it as tan a standard can be found in Annex A.

0.1 Uses of a Reference Information Model (RIM) in Health Informatics

0.1.1 Use of the RIM in ISO TC215

ISO TC215 – Health Informatics has previously advanced ISO 17113, a specification for a framweork for developing health data interchange standards. This framework specification calls for messaging standards to be based on a single, comprehensive model of health information. The RIM presented in the current specification provides one such model. Further, the RIM may provide a reference document that can facilitate the harmonization of the health informatics standards and relaterd specifications within ISO TC 215.

0.1.2 Use of the RIM by HL7

The HL7 RIM is a critical component of the V3 development process. It is the root of all information models and structures developed as part of the V3 development process.

The HL7 V3 standard development process is a model-driven methodology in which a network of inter-related models are developed that depict the static and behavioral aspects of the requirements and design of HL7 standards, as well as the underlying semantics and business rules that govern them.

0 INTRODUCTION

The RIM provides a static view of the information needs of HL7 V3 standards. It includes class and state-machine diagrams and is accompanied by use case models, interaction models, data type models, terminology models, and other types of models to provide a complete view of the requirements and design of HL7 standards. The classes, attributes, state-machines, and relationships in the RIM are used to derive domain-specific information models that are then transformed through a series of constraining refinement processes to eventually yield a static model of the information content of an HL7 standard.

The HL7 V3 standard development process defines the rules governing the derivation of domain information models from the RIM and the refinement of those models into HL7 standard specifications. The rules require that all information structures in derived models be traceable back to the RIM and that their semantic and related business rules not conflict with those specified in the RIM. The RIM therefore is the ultimate source for all information content in HL7 V3 standards.

The RIM is used by HL7 international affiliates to extend HL7 V3 standards to meet local needs. Through a process known as localization, V3 standard specifications are extended using the RIM as the source for new information content. This new information is derived from the RIM and refined in the same manner used to create the original specification.

0.1.3 Uses of the RIM Outside of HL7

The RIM is primarily for use by HL7 and its international affiliates. However, others outside of HL7 have also found the RIM useful. Although HL7 maintains a copyright on the expression of this standard, HL7 does not seek to license or otherwise control the use of information structures or programs that implement this specification. Early adopters of the V3 standards development process have used the RIM to develop HL7-like message specifications in their own environments. These early adopters include vendors, large integrated delivery networks, and government agencies within the United States and internationally. These same early adopters are extremely active in HL7 and provide practical input to the RIM and other aspects of V3 the development process.

Some HL7 member organizations have reported using the RIM as a source of input to their enterprise information architectures or as a starting place for systems analysis and design. The RIM may indeed be useful for such purposes; however, HL7 provides no assurance that the RIM is useful for anything other than as a reference model for HL7 standards development.

The RIM is only one model of healthcare information needs. The abstract style of the RIM and the ability to extend the RIM through vocabulary specifications make the RIM applicable to any conceivable healthcare system information interchange scenario. In fact, it is conceptually applicable to any information domain involving entities playing roles and participating in acts.

The universal applicability of the RIM makes it particularly useful for an organization like HL7 that has to consider the needs of a large and diverse membership. The style of the RIM makes it extremely stable, which is another important characteristic for HL7. The HL7 standards development process calls for the creation of domain specific models derived from the RIM and the incremental refinement of those models into design models that are specific to the problem area. These problem area specific design models narrow the abstractness of the RIM and include constraints on attribute values and class relationships that are use case specific. External organizations considering using the HL7 RIM are advised to adopt a similar process of deriving design models as a transformation of the RIM.

0.2 Further information

Questions or comments about the content of the standard may be addressed to HL7 at (www.hl7.org), to one of the HL7 International Affiliate organizations, or to the Secretariat of ISO TC215 – Health Informatics.

Hensilson and state the state of the state o

Health informatics — HL7 version 3 — Reference information model — Release 1

1 Scope

The Health Level Seven (HL7) Reference Information Model (RIM) is a static model of health and health care information as viewed within the scope of HL7 standards development activities. It is the combined consensus view of information from the perspective of the HL7 working group and the HL7 international affiliates. The RIM is the ultimate source from which all HL7 version 3.0 protocol specification standards draw their information-related content. In the context of ISO TC215 – Health Informatics, the RIM provides a reference model that may be used in developing further health informatics specifications.

2 Conformance

An information model such as the RIM specified in this standard may serve as the basis for other information models that are directly derived from it, and may provide a foundation to support the design of data bases and other information structures. Nevertheless, neither ISO TC 215 nor HL7 believe that it is reasonable to define tests of whether a particular implementation may conform to this standard. Therefore users of this standard shall not claim conformance to this standard. Further, ISO TC215 and HL7, as developers of this standard request that users inform them of particular requirements which caused the users to deviate from this stanard or to extend it. This will allow subsequent releases of the standard to meet a broader range of requirements. 1-8902

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17113, Health informatics — Exchange of information between healthcare information systems — Method for development of messages

ISO/IEC 19501, Information technology — Open Distributed Processing — Unified Modeling Language (UML) Version 1.4.2

ANSI/HL7 V3 DT, R1-2004, HL7 Version 3 Standard: Data Types — Abstract Specification, Release 1

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1

ANSI

American National Standards Institute

4 TERMS AND DEFINITIONS

4.2

association

A reference from one class to another class or to itself, or a connection between two objects (instances of classes).

4.3

association role name

A name for each end of an association. The name is a short verb phrase depicting the role of the class at the opposite end of the association from the perspective of the class adjacent to the role.

4.4

attribute

An abstraction of a particular aspect of a class. Attributes become the data values that are passed in HL7 messages.

4.5

bag

A form of collection whose members are unordered, and need not be unique.

4.6

cardinality

Property of a data element (the number of times a data element may repeat within an individual occurrence of an object view).

4.7

4.7 class An abstraction of a thing or concept in a particular application domain.

4.8 classifier attribute An attribute used in generalization hierarchies to indicate which of the specializations is the focus of the class.

4.9

coded attribute

An attribute in the Reference Information Model (RIM) with a base data type of CD, CE, CS, or CV.

4.10

coding strength

An extensibility qualifier that specifies whether or not a code set can be expanded to meet local implementation needs.

4.11

coding system

A scheme for representing concepts using (usually) short concept identifiers to denote the concepts that are members of the system; defines a set of unique concept codes. Examples of coding systems are ICD-9, LOINC and SNOMED.

4.12

collection

An aggregation of similar objects. The forms of collection used by HL7 are set, bag, and list. Objects which may be found in collections include data types.

4 TERMS AND DEFINITIONS

4.13

connection

In an information model, a specified relationship between two classes .

4.14

data type

The structural format of the data carried in an attribute. It may constrain the set of values an attribute may assume.

4.15

distal class

From the perspective of a class in an information model, it is the class at the opposite end of an association between the two.

4.16

domain

1. A particular area of interest. For example, the domain for HL7 is healthcare.

2. The set of possible values of a data type , attribute, or data type component. See also vocabulary domain.

4.17

event

1. A stimulus that causes a noteworthy change in the state of an object, or a signal that invokes the behavior 15-itel al catalos of an object.

2. A vocabulary domain value for Mood.

4.18

extensibility qualifier

A vocabulary domain qualifier used in a domain specification, which indicates whether or not the existing vocabulary domain can be extended with additional values. There are two possible values: CNE (coded, no extension) and CWE (coded with extension). nttp

4.19

generalization

An association between two classes, referred to as superclass and subclass, in which the subclass is derived from the superclass. The subclass inherits all properties from the superclass, including attributes, relationships, and states, but also adds new ones to extend the capabilities of the parent class. Essentially, a specialization from the point-of-view of the subclass.

4.20

generalization hierarchy

All superclasses and subclasses with a common root superclass.

4.21

graphical expression

A visual representation of a model that uses graphic symbols to represent the components of the model and the relationships that exist between those components.

idd.

4.22

Health Level Seven

HL7

A standards developing organization based in the United States of America.

4.23

identifier attribute

An attribute used to identify an instance of a class.

4.24

information model

A structured specification, expressed graphically and/or narratively, of the information requirements of a domain. An information model describes the classes of information required and the properties of those classes, including attributes, relationships, and states. Examples in HL7 are the Domain Reference Information Model, Reference Information Model, and Refined Message Information Model.

4.25

inheritance

In a generalization relationship, the subclass inherits all properties from the superclass, including attributes, relationships, and states, unless otherwise specified.

4.26

instance

A case or an occurrence. For example, an instance of a class is an object. leatalo

4.27

list

A form of collection whose members are ordered, and need not be unique.

4.28

literary expression

A representation of a model in text. The literary expression seeks to balance the need for a rigorous, unambiguous description of the model with the need for a rendition that can be easily read and interpreted by individuals who understand the general concepts underlying object-oriented models, but who may not be schooled in formal model definition languages.

4.29

mandatory

If an attribute is designated as mandatory, all message elements which make use of this attribute must contain a non-null value or they must have a default that is not null.

4.30

mandatory association

An association with a multiplicity minimum greater than zero on one end. A fully mandatory association is one with a multiplicity minimum greater than zero on both ends.

4.31

methodology

Methods or rules followed in a particular discipline.

4 TERMS AND DEFINITIONS

ISO 21731:2005(E) & ANSI/HL7 RIM R1-2003

4.32

model

A representation of a domain that uses abstraction to express the relevant concepts.

4.33

multiplicity

In the information model, multiplicity is a specification of the minimum and maximum number of objects from each class that can participate in an association. Multiplicity is specified for each end of the association.

4.34

namespace

A namespace is a part of the model in which names are defined and used, where each name has a unique meaning.

4.35

object

An instance of a class. A part of an information system containing a collection of related data (in the form of attributes) and procedures (methods) for operating on that data.

4.36

object identity

The feature that the existence of an object is independent of any values associated with the object.

4.37

object-based

Any method, language, or system that supports object identity, classification, and encapsulation. An object-based system does not support specialization. Ada is an example of an object-based implementation language.

4.38 property Any attribute, association, method, or state model defined for a class or object.

4.39

Reference Information Model

RIM

The HL7 information model from which all other information models (e.g., R-MIMs) and messages are derived.

4.40

role

1. A function or position.

2. A Reference Information Model class that defines the competency of an Entity class. Each role is played by one Entity (the Entity that is in the role) and is usually scoped by another.

3. In UML, each end of an association is designated as a role to reflect the function that class plays in the association.

4.41 role name See association role name.

© ISO/HL7 2005 - All rights reserved