
Protihrupne ovire za cestni promet - Preskusna metoda za ugotavljanje akustičnih lastnosti - 4. del: Bistvene lastnosti - Terenske vrednosti difrakcije zvoka

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - In situ values of sound diffraction

Lärmschutzvorrichtungen an Straßen - Prüfverfahren zur Bestimmung der akustischen Eigenschaften - Teil 4: Produktspezifische Merkmale - In-situ-Werte der Schallbeugung

Dispositifs de réduction du bruit du trafic routier - Méthode d'essai pour la détermination des performances acoustiques - Partie 4: Caractéristiques intrinsèques - Valeurs in-situ de la diffraction acoustique

Ta slovenski standard je istoveten z: FprEN 1793-4

<https://standards.iteh.ai/catalog/standards/sist/745f90ad-a896-47ee-a157-f24045651d7b/sist-en-1793-4-2015>

ICS:

17.140.01	Akustična merjenja in blaženje hrupa na splošno	Acoustic measurements and noise abatement in general
93.080.30	Cestna oprema in pomožne naprave	Road equipment and installations

kSIST FprEN 1793-4:2014**en,fr,de**

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

FINAL DRAFT
FprEN 1793-4

June 2014

ICS 17.140.30; 93.080.30

Will supersede CEN/TS 1793-4:2003

English Version

**Road traffic noise reducing devices - Test method for
determining the acoustic performance - Part 4: Intrinsic
characteristics - In situ values of sound diffraction**

Dispositifs de réduction du bruit du trafic routier - Méthode
d'essai pour la détermination des performances
acoustiques - Partie 4: Caractéristiques intrinsèques -
Valeurs in-situ de la diffraction acoustique

Lärmschutzeinrichtungen an Straßen - Prüfverfahren zur
Bestimmung der akustischen Eigenschaften - Teil 4:
Produktspezifische Merkmale - In-situ-Werte der
Schallbeugung

This draft European Standard is submitted to CEN members for unique acceptance procedure. It has been drawn up by the Technical Committee CEN/TC 226.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

page

Foreword.....	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms, definitions and symbols.....	7
3.1 Terms and definitions	7
3.2 Symbols	8
4 Sound diffraction index difference measurements	10
4.1 General principle	10
4.2 Dimensions and specifications	10
4.2.1 Added devices	10
4.2.2 Reference walls.....	10
4.2.3 <i>In situ</i> tests	11
4.3 Positions of the sound source	11
4.4 Position of the microphone(s).....	12
4.5 Free-field measurements	13
4.6 Measured quantity	17
4.7 Measuring equipment.....	18
4.7.1 Components of the measuring system	18
4.7.2 Sound source.....	19
4.7.3 Test signal	20
4.8 Data processing.....	20
4.8.1 Calibration	20
4.8.2 Sample rate.....	20
4.8.3 Background noise	21
4.8.4 Measurement points.....	21
4.8.5 Adrienne temporal window.....	21
4.8.6 Placement of the Adrienne temporal window.....	22
4.8.7 Low frequency limit and sample size	23
4.9 Positioning of the measuring equipment.....	24
4.9.1 Selection of the measurement positions	24
4.9.2 Reflecting objects	24
4.9.3 Safety considerations	25
4.10 Sound diffraction index difference	25
4.11 Single-number rating of sound diffraction index difference DL_{ADI}	25
4.12 Sample surface and meteorological conditions.....	26
4.12.1 Condition of the sample surface	26
4.12.2 Wind	26
4.12.3 Air temperature	26
5 Measurement uncertainty	26
6 Measuring procedure	26
6.1 General.....	26
6.2 Test report	27
Annex A (informative) Indoor measurements for product qualification	29
A.1 General.....	29
A.2 Parasitic reflections.....	29
A.3 Reverberation time of the room	29
Annex B (informative) Measurement uncertainty.....	30

B.1	General	30
B.2	Expression for the calculation of sound diffraction index.....	30
B.3	Contributions to measurement uncertainty.....	31
B.4	Expanded uncertainty of measurement	32
B.5	Measurement uncertainty based upon reproducibility data	32
	Bibliography.....	33

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN 1793-4:2015](https://standards.iteh.ai/catalog/standards/sist/745f90ad-a896-47ce-a157-f24045651d7b/sist-en-1793-4-2015)

<https://standards.iteh.ai/catalog/standards/sist/745f90ad-a896-47ce-a157-f24045651d7b/sist-en-1793-4-2015>

FprEN 1793-4:2014 (E)**Foreword**

This document (FprEN 1793-4:2014) has been prepared by Technical Committee CEN/TC 226 “Road equipment”, the secretariat of which is held by AFNOR.

This document is currently submitted to the UAP.

This document will supersede CEN/TS 1793-4:2003.

The major changes compared to the previous published version are:

- the airborne sound insulation characteristics of the reference wall are specified in terms of the minimum values of the Sound Insulation Index, measured according to EN 1793-6, it needs to have;
- the sound absorbing characteristics of the reference wall are specified in terms of the minimum values of the sound absorption coefficient, measured according to EN ISO 354, it needs to have when lined on the source side with an absorptive flat layer of a single porous material;
- the sound source positions have been reduced from six to four and are now all obligatory;
- the microphone positions have been reduced from 12 to 10 and are now all obligatory;
- a “free-field” impulse response to be measured for each microphone position and therefore a geometrical spreading correction factor is no more needed in Formula (1);
- consideration of the measurement uncertainty has been added (see Clause 5 and Annex B);
- the summary of the test procedure (Clause 6) has been updated to reflect the changes compared to the previous published version.

This document should be read in conjunction with:

EN 1793-1, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 1: Intrinsic characteristics of sound absorption under diffuse sound field conditions* 651d7b/sist-en-1793-4-2015

EN 1793-3, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 3: Normalized traffic noise spectrum*

CEN/TS 1793-5, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 5: Intrinsic characteristics — In situ values of sound reflection and airborne sound insulation.*

EN 1793-6, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 6: Intrinsic characteristics – In situ values of airborne sound insulation under direct sound field conditions*

Introduction

Part of the market of road traffic noise reducing devices is constituted of products to be added on the top of noise reducing devices and intended to contribute to sound attenuation acting primarily on the diffracted sound field. These products will be called added devices. This European Standard has been developed to specify a test method for determining the acoustic performance of added devices.

The test method can be applied *in situ*, i.e. where the traffic noise reducing devices and the added devices are installed. The method can be applied without damaging the traffic noise reducing devices or the added devices.

The method can be used to qualify products before the installation along roads as well as to verify the compliance of installed added devices to design specifications. Repeated application of the method can be used to verify the long term performance of added devices.

This method could be used to qualify added devices for other applications, e.g. to be installed along railways or nearby industrial sites. In this case, special care needs to be taken into account in considering the location of the noise sources and the single-number ratings should be calculated using an appropriate spectrum.

No other national or international standard exists about the subject of this European Standard.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

SIST EN 1793-4:2015

<https://standards.iteh.ai/catalog/standards/sist/745f90ad-a896-47ce-a157-f24045651d7b/sist-en-1793-4-2015>

1 Scope

This European Standard describes a test method for determining the intrinsic characteristics of sound diffraction of added devices installed on the top of traffic noise reducing devices. The test method prescribes measurements of the sound pressure level at several reference points near the top edge of a noise reducing device with and without the added device installed on its top. The effectiveness of the added device is calculated as the difference between the measured values with and without the added devices, correcting for any change in height (the method described gives the acoustic benefit over a simple barrier of the same height; however, in practice the added device can raise the height and this could provide additional screening depending on the source and receiver positions).

The test method is intended for the following applications:

- preliminary qualification, outdoors or indoors, of added devices to be installed on noise reducing devices;
- determination of sound diffraction index difference of added devices in actual use;
- comparison of design specifications with actual performance data after the completion of the construction work;
- verification of the long term performance of added devices (with a repeated application of the method);
- interactive design process of new products, including the formulation of installation manuals.

The test method can be applied both *in situ* and on samples purposely built to be tested using the method described here.

Results are expressed as a function of frequency, in one-third octave bands between 100 Hz and 5 kHz. If it is not possible to get valid measurements results over the whole frequency range indicated, the results shall be given in the restricted frequency range and the reasons of the restriction(s) shall be clearly reported. A single-number rating is calculated from frequency data.

For indoors measurements see Annex A.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1793-3, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 3: Normalized traffic noise spectrum*

EN 1793-6, *Road traffic noise reducing devices — Test method for determining the acoustic performance — Part 6: Intrinsic characteristics — In situ values of airborne sound insulation under direct sound field conditions*

EN 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

EN ISO 354, *Acoustics — Measurement of sound absorption in a reverberation room (ISO 354)*

ISO/IEC Guide 98, *Guide to the expression of uncertainty in measurement (GUM)*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purpose of this document, the following terms and definitions apply.

3.1.1

structural elements

those elements whose primary function is to support or hold in place acoustic elements

3.1.2

acoustical elements

those elements whose primary function is to provide the acoustic performance of the device

3.1.3

noise barrier

noise reducing device which obstructs the direct transmission of airborne sound emanating from road traffic

3.1.4

added device

acoustic element added on the top of a noise reducing device and intended to contribute to sound attenuation acting primarily on the diffracted sound field

3.1.5

roadside exposure

use of the product as a noise reducing device installed alongside roads

3.1.6

sound diffraction index

result of a sound diffraction test whose components are described by the formula in 4.6

Note 1 to entry: The symbol for the sound diffraction index includes information on the setup used during the test: $DI_{x,refl}$ refers to measurements on a reflective reference wall. $DI_{x,abs}$ refers to measurements on an absorptive reference wall. $DI_{x,situ}$ refers to *in situ* measurements; where x is "0" when the added device is not on the top of the test construction and "ad" when the added device is on the top of the test construction (see 3.2).

3.1.7

sound diffraction index difference

difference between the results of sound diffraction tests on the same reference wall with and without an added device on the top, described by the formulae in 4.10

3.1.8

test construction

construction on which the added device is placed

Note 1 to entry: For *in situ* measurements the test construction is an installed noise reducing device; for qualification tests it is a reference wall (see 4.2).

3.1.9

reference plane of the test construction

vertical plane passing through the midpoint of the top edge of the construction (reference wall or installed noise reducing device) on which the added device has to be placed (see Figure 1, Figure 2, Figure 4, Figure 5 and Figure 8)

3.1.10

reference height of the test construction without the added device, $h_{ref,0}$

height of the highest point of the test construction in relation to the surrounding ground surface

FprEN 1793-4:2014 (E)

Note 1 to entry: This highest point is not necessarily lying in the plane of longitudinal symmetry of the reference test construction, if this symmetry exists (Figure 1).

3.1.11**reference height of the test construction with the added device on the top, $h_{ref,add}$**

height of the highest point of the added device installed on the test construction in relation to the surrounding ground surface

Note 1 to entry: This highest point is not necessarily lying in the plane of longitudinal symmetry of the reference test construction, if this symmetry exists (Figure 4).

3.1.12**free-field measurement for sound diffraction index measurements**

measurement carried out placing the loudspeaker and the microphone as specified in 4.3, 4.4 and 4.5 without any obstacle, including the test construction with or without added device, between them (see for example Figure 7)

3.1.13**Adrienne temporal window**

composite temporal window described in 4.8.5

3.1.14**background noise**

noise coming from sources other than the source emitting the test signal

3.1.15**signal-to-noise ratio, S/N**

difference in decibels between the level of the test signal and the level of the background noise at the moment of detection of the useful event (within the Adrienne temporal window)

3.1.16**impulse response**

time signal at the output of a system when a Dirac function is applied to the input

Note 1 to entry: The Dirac function, also called δ function, is the mathematical idealisation of a signal infinitely short in time that carries a unit amount of energy

<https://standards.iteh.ai/catalog/standards/sist/745f90ad-a896-47ce-a157-f24045651d7b/sist-en-1793-4-2015>

3.2 Symbols

For the purposes of this document, the following symbols and abbreviations apply.

Table 1 – Symbols and abbreviations

Symbol or abbreviation	Designation	Unit
α	Sound absorption coefficient measured according to EN ISO 354	-
DI_j	Sound diffraction index in the j -th one-third octave frequency band	dB
$DI_{0,refl}$	Sound diffraction index for the reflective reference wall without the added device	dB
$DI_{ad,refl}$	Sound diffraction index for the reflective reference wall with the added device	dB
$DI_{0,abs}$	Sound diffraction index for the absorptive reference wall without the added device	dB
$DI_{ad,abs}$	Sound diffraction index for the absorptive reference wall with the added device	dB

$DI_{0,situ}$	Sound diffraction index for the <i>in situ</i> test construction without the added device	dB
$DI_{ad,situ}$	Sound diffraction index for the <i>in situ</i> test construction with the added device	dB
ΔDI_{refl}	Sound diffraction index difference for the test sample on the reflective reference wall	dB
ΔDI_{abs}	Sound diffraction index difference for the test sample on the absorbing reference wall	dB
ΔDI_{situ}	Sound diffraction index difference for the test sample on an <i>in situ</i> test construction	dB
$DL_{\Delta DI,refl}$	Single-number rating of sound diffraction index difference for the test sample on the reflective reference wall	dB
$DL_{\Delta DI,abs}$	Single-number rating of sound diffraction index difference for the test sample on the absorbing reference wall	dB
$DL_{\Delta DI,situ}$	Single-number rating of sound diffraction index difference for the test sample on the <i>in situ</i> test construction	dB
δ_i	Any input quantity to allow for uncertainty estimates	-
Δf_j	Width of the <i>j</i> -th one-third octave frequency band	Hz
f	Frequency	Hz
F	Symbol of the Fourier transform	-
f_{min}	Low frequency limit of sound diffraction index measurements	Hz
f_s	Sample rate	Hz
f_{co}	Cut-off frequency of the anti-aliasing filter	Hz
h_B	Noise barrier height	m
h_{ref}	Reference height of the test construction	m
$h_{ref,0}$	Reference height of the test construction without the added device	m
$h_{ref,ad}$	Reference height of the test construction with the added device	m
$h_i(t)$	Incident reference component of the free-field impulse response	dB
$h_{d,k}(t)$	Diffacted component of the impulse response at the <i>k</i> -th measurement point	dB
j	Index of the <i>j</i> -th one-third octave frequency band (between 100 Hz and 5 kHz)	-
k	Coverage factor	-
k_f	Constant used for the anti-aliasing filter	-
L_b	Minimum length of the reference wall	m
L_d	Minimum length of the added device under test	m
n	Number of measurement points	-
SI	Sound Insulation Index measured according to EN 16272-6	dB
t	Time	s or ms
$T_{W,BH}$	Length of the Blackman-Harris trailing edge of the Adrienne temporal window	ms
$T_{W,ADR}$	Total length of the Adrienne temporal window	ms
u	Standard uncertainty	-