

SLOVENSKI STANDARD
SIST-TS ISO/TS 7849-1:2014**01-februar-2014****Nadomešča:**
SIST ISO/TR 7849:1997

Akustika - Določanje ravni zvočnih moči v zraku, ki jih povzročajo stroji, z merjenjem vibracij - 1. del: Informativna metoda z uporabo konstantnega faktorja sevanja

Acoustics -- Determination of airborne sound power levels emitted by machinery using vibration measurement -- Part 1: Survey method using a fixed radiation factor

iTeh STANDARD PREVIEW
(standards.iteh.ai)Acoustique -- Détermination des niveaux de puissance acoustique aériens émis par les machines par mesurage des vibrations -- Partie 1: Méthode de contrôle employant un facteur de rayonnement fixe
<http://standards.iteh.ai/catalog/standards/sist/ts-iso-ts-7849-1-2014>**Ta slovenski standard je istoveten z: ISO/TS 7849-1:2009****ICS:**

17.140.20	Emisija hrupa naprav in opreme	Noise emitted by machines and equipment
17.160	Vibracije, meritve udarcev in vibracij	Vibrations, shock and vibration measurements

SIST-TS ISO/TS 7849-1:2014**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ISO/TS 7849-1:2014](https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014>

TECHNICAL SPECIFICATION

ISO/TS 7849-1

First edition
2009-03-15

Acoustics — Determination of airborne sound power levels emitted by machinery using vibration measurement —

Part 1: Survey method using a fixed radiation factor

iTeh STANDARD PREVIEW

(standards.iteh.ai)
*Acoustique — Détermination des niveaux de puissance acoustique
aériens émis par les machines par mesurage des vibrations —*

*Partie 1: Méthode de contrôle employant un facteur de rayonnement
fixe*

<https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014>



Reference number
ISO/TS 7849-1:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ISO/TS 7849-1:2014](https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Principle.....	4
5 Measuring instrumentation.....	5
5.1 General.....	5
5.2 Vibration transducer.....	5
5.3 Non-contacting transducers.....	5
5.4 Amplifier	6
5.5 Integrator	6
5.6 Calibration	6
6 Installation and operation of source under test	6
6.1 General.....	6
6.2 Description of the machine.....	7
6.3 Installation.....	7
6.4 Operating conditions.....	7
7 Determination of the vibratory velocity on the vibrating measurement surface	7
7.1 General.....	7
7.2 Vibrating measurement surface.....	7
7.3 Number of measurement positions	8
7.4 Environmental conditions.....	8
7.5 Measurement procedure	9
7.6 Mounting of the vibration transducer	9
8 Calculations.....	9
8.1 Correction for extraneous vibratory velocity.....	9
8.2 Determination of the mean A-weighted vibratory velocity level on the vibrating measurement surface.....	10
8.3 Calculation of the upper limit of the A-weighted airborne sound power level caused by radiation of structure vibration generated sound	11
9 Measurement uncertainty	11
10 Information to be recorded	13
10.1 Machine under test	13
10.2 Measurement conditions	13
10.3 Measuring instrumentation.....	13
10.4 Acoustical data	13
Annex A (informative) Use of the vibration transducer.....	14
Annex B (informative) Guidance on the development of information on measurement uncertainty.....	16
Bibliography	19

ISO/TS 7849-1:2009(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 7849-1 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This first edition of ISO/TS 7849-1, together with ISO/TS 7849-2, cancel and replace the first edition of ISO/TR 7849:1987, which has been technically revised.

ISO/TS 7849 consists of the following parts, under the general title *Acoustics — Determination of airborne sound power levels emitted by machinery using vibration measurement*:

- *Part 1: Survey method using a fixed radiation factor*
- *Part 2: Engineering method including determination of the adequate radiation factor*

The following part is under preparation:

- Part 3: Amplitude and phase measurements

Introduction

This part of ISO/TS 7849 gives a procedure for the determination of the sound power of the airborne noise caused by machinery vibration.

The determination of airborne noise emission of a machine by measuring vibration of the machine's outer surface may be of interest when:

- undesired background noise (e.g. noise from other machines or sound reflected by room boundaries) is high compared with the noise radiated directly by the machine under test;
- noise radiated by structure vibration is to be separated from noise of aerodynamic origin;
- noise radiated by structure vibration is high compared to the aerodynamic component so that the total noise radiation is predominantly affected by the structure vibration;
- sound intensity measurement techniques [ISO 9614 (all parts)^[12]] cannot easily be applied;
- structure vibration generated noise from only a part of a machine, or from a component of a machine set, is to be determined in the presence of noise from the other parts of the whole machine.

ISO/TS 7849 (all parts) describes methods for the determination of the airborne noise emission of a machine caused by vibration of its outer surface, expressed by the associated A-weighted airborne sound power being related to normalized meteorological conditions. This airborne sound power is determined under the assumption that this quantity is proportional to the mean square value of the normal component of the velocity averaged over the area of the vibrating outer surface of the machine, and is directly proportional to the area of the vibrating surface.

The calculation of the airborne sound power needs data of the radiation factor in principle. For this part of ISO/TS 7849 a radiation factor of 1 is assumed allowing the determination of an upper limit for the radiated A-weighted sound power level. For typical machines this upper limit may exceed the true A-weighted sound power level determined by the intensity procedure of ISO 9614 (all parts)^[12] by up to 10 dB. The A-weighted sound power level determined according to this part of ISO/TS 7849 can be used for sound power level comparison of relevant vibrating machinery noise of the same family with similar design.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ISO/TS 7849-1:2014](https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014>

Acoustics — Determination of airborne sound power levels emitted by machinery using vibration measurement —

Part 1: Survey method using a fixed radiation factor

1 Scope

This part of ISO/TS 7849 gives basic requirements for reproducible methods for the determination of an upper limit for the A-weighted sound power level of the noise emitted by machinery or equipment by using surface vibration measurements. The method is only applicable to noise which is emitted by vibrating surfaces of solid structures and not to noise generated aerodynamically.

This vibration measurement method is especially applicable in cases where accurate direct airborne noise measurements, e.g. as specified in ISO 3746^[7], ISO 3747^[8], and ISO 9614 (all parts)^[12], are not possible because of high background noise or other parasitic environmental interferences; or if a distinction is required between the total radiated sound power and its structure vibration generated component.

NOTE 1 One of the applications of this part of ISO/TS 7849 is the distinction between the radiation of airborne sound power generated by structure vibration and the aerodynamic sound power components. Such a distinction is not feasible with ISO 3746^[7] and ISO 9614 (all parts)^[12].

NOTE 2 Problems can occur if the noise is generated by small parts of machinery surfaces (sliding contacts, e.g. slip ring brush or the commutator and the brush in electrical machines).

The methods described in this part of ISO/TS 7849 apply mainly to processes that are stationary with respect to time.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5348, *Mechanical vibration and shock — Mechanical mounting of accelerometers*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

ISO/TS 7849-1:2009(E)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

structure vibration generated sound

airborne sound caused by structure vibration in the audible frequency range

NOTE For the purposes of this part of ISO/TS 7849, structure vibration generated sound is determined either from the vibratory velocity or the vibratory acceleration of the surface of the solid structure.

3.2

machine

(airborne sound power level measurement) equipment which incorporates a single or several noise sources

3.3

vibratory velocity

v

root-mean square (r.m.s.) value of the component of the velocity of a vibrating surface in the direction normal to the surface

NOTE 1 The vibratory velocity, v , is the time integral of the vibratory acceleration, whose r.m.s. value is given for sinusoidal vibration by:

$$v = \frac{a}{2\pi f} \quad (1)$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

where

a is the r.m.s. acceleration;

f is the frequency.

[SIST-TS ISO/TS 7849-1:2014
https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014](https://standards.iteh.ai/catalog/standards/sist/cfd2dde5-3622-4619-b5ed-0c308aeae0e5/sist-ts-iso-ts-7849-1-2014)

The vibratory velocity, v , is the time derivative of the vibratory displacement, s , ds/dt . For sinusoidal vibration, the r.m.s. velocity, v , is given by:

$$v = 2\pi fs \quad (2)$$

where s is the r.m.s. displacement.

NOTE 2 In this part of ISO/TS 7849, the vibratory velocity is usually applied with A-weighting, denoted v_A .

3.4

A-weighted vibratory velocity level

L_{vA}
ten times the logarithm to the base 10 of the ratio of the square of the r.m.s. value of the A-weighted vibratory velocity, v_A , to the square of a reference value, v_0 , expressed in decibels:

$$L_{vA} = 10 \lg \frac{v_A^2}{v_0^2} \text{ dB} \quad (3)$$

where

v_A is the A-weighted r.m.s. value of the vibratory velocity, in metres per second¹⁾;

v_0 is the reference value for the velocity and is equal to 5×10^{-8} m/s²⁾.

NOTE For airborne and structure vibration generated sound, the reference value, $v_0 = 50$ nm/s has the property that it leads, together with $p_0 = 2 \times 10^{-5}$ Pa, to the reference value of the intensity level $I_0 = 1 \times 10^{-12}$ W/m² and to the characteristic impedance of air by $p_0/v_0 = 400$ N s/m³.

3.5

A-weighted radiation factor

ε_A
factor expressing the efficiency of sound radiation given by:

$$\varepsilon_A = \frac{P_A}{Z_c S v_A^2} \quad (4)$$

where

P_A is the A-weighted airborne sound power emitted by the vibrating surface of the machine, determined according to ISO 9614 (all parts)^[12];

S is the area of the defined outer surface of the machine under test (vibrating measurement surface; see 3.8);

v_A^2 is the squared A-weighted r.m.s. value of the vibratory velocity averaged over S ;

Z_c is the characteristic impedance of air.

NOTE The four quantities ε_A , P_A , v_A^2 and Z_c relate to the same period of time and to the same meteorological conditions (atmospheric temperature, θ , and barometric pressure, B).

3.6

A-weighted airborne sound power level

L_{WA}
ten times the logarithm to the base 10 of the ratio of the A-weighted airborne sound power emitted by the surface of a machine, P_A , to a reference value, P_0 , expressed in decibels

$$L_{WA} = 10 \lg \frac{P_A}{P_0} \text{ dB} \quad (5)$$

where the reference value, P_0 , is 10^{-12} W

3.7

upper limit of A-weighted airborne sound power level

$L_{WA,max}$
A-weighted airborne sound power level determined in accordance with the method described in this part of ISO/TS 7849

1) A subscript "eff" is dropped, since only r.m.s. values are used throughout this part of ISO/TS 7849.

2) In ISO 1683^[1], two reference values for the velocity level are mentioned: $v_0 = 10^{-9}$ m/s and 5×10^{-8} m/s. The latter is intended for cases of airborne and structure vibration generated sound and is therefore used in this part of ISO/TS 7849. A choice of $v_0 = 10^{-9}$ m/s results in a vibratory velocity level which is 34 dB higher than the level used in this part of ISO/TS 7849. Therefore, if $v_0 = 10^{-9}$ m/s is used, subtract 34 dB from the right-hand sides of Equations (7), (8), and (11).