INTERNATIONAL STANDARD

ISO 14096-1

First edition 2005-06-15

Non-destructive testing — Qualification of radiographic film digitisation systems —

Part 1:

Definitions, quantitative measurements of image quality parameters, standard iTeh STreference film and qualitative control

(standards.iteh.ai) Essais non destructifs — Qualification des systèmes de numérisation

https://standards.iteh. Partie 4: Définitions, mesures quantitatives des paramètres de qualité c d'image film de référence normalisé et contrôle qualitatif



Reference number ISO 14096-1:2005(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14096-1:2005</u> https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14096-1 was prepared by the European Committee for Standardization (CEN) (as EN 14096-1:2003) and was adopted, under a special "fast-track procedure", by Technical Committee ISO/TC 135, *Non-destructive testing*, Subcommittee SC 5, *Radiation methods* ISO/TC in parallel with its approval by the ISO member bodies.

ISO 14096 consists of the following parts, under the general title *Non-destructive testing* — *Qualification of radiographic film digitisation systems*:

ISO 14096-1:2005

- Part 1: Definitions, quantitative measurements of image quality parameters, standard reference film and qualitative control
- Part 2: Minimum requirements

Contents

Page

Foreword3		.3
Introdu	Introduction	
1	Scope	.5
2	Normative references	.5
3	Terms and definitions	.5
4	Evaluation procedures	.8
5	Standard reference film	12
6	Qualitative control and long term stability of the digitisation system	14

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14096-1:2005</u> https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

Foreword

This document (EN 14096-1:2003) has been prepared by Technical Committee CEN/TC 138, "Non-destructive testing", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2003, and conflicting national standards shall be withdrawn at the latest by October 2003.

EN 14096 comprises a series of European Standards for radiographic film digitisation systems which is made up of the following:

EN 14096-1, Non-destructive testing – Qualification of radiographic film digitisation systems – Part 1: Definitions, quantitative measurements of image quality parameters, standard reference film and qualitative control

EN 14096-2, Non-destructive testing – Qualification of radiographic film digitisation systems – Part 2: Minimum requirements

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and the United Kingdom.

(standards.iteh.ai)

<u>ISO 14096-1:2005</u> https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

Introduction

Radiographic film systems are used for industrial inspection by X- and gamma rays. To apply modern means of computer support for analysis, transmission and storage the information stored in the radiographic film should be converted into digital data (digitisation). This European Standard defines minimum requirements to ensure that the relevant information for evaluation of the digital data is preserved during the film digitisation process.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14096-1:2005</u> https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

1 Scope

This European Standard specifies procedures for the evaluation of basic performance parameters of the radiographic film digitisation process such as spatial resolution and spatial linearity, density range, density contrast sensitivity and characteristic transfer curve. They can be integrated into the system software and together with a standard reference film (as described in clause 5) used for quality control of the digitisation process. This reference film provides a series of test targets for performance evaluation. The test targets are suitable for evaluating a digitisation system with a spatial resolution down to $25 \,\mu$ m, a density contrast sensitivity down to 0.02 optical density, a density range of 0.5 to 4.5 and a film size capacity of (350×430) mm². This standard does not address signal processing and display of the digitised data.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 584-1, Non-destructive testing - Industrial radiographic film - Part 1: Classification of film systems for industrial radiography.

EN 14096-2, Non-destructive testing — Qualification of radiographic film digitisation systems — Part 2: Minimum requirements.

<u>ISO 14096-1:2005</u> https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

3 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

3.1

radiographic film digitisation system

digitiser

sequential application of the two functions below:

- a) detection of the diffuse transmittance of a small unit area of the film (pixel, picture element) by means of an optical detector, giving an electric output signal (geometrical digitisation);
- b) conversion of the above electrical signal into a numerical value (densitometrical digitisation)

3.2

scanning aperture

 S_{A}

spatial extension (area) on the radiographic film through which the digitiser performs the scanning of one pixel for geometrical digitisation

The size of the scanning aperture corresponds:

3.3 pixel size

Р

geometrical centre-to-centre distance between adjacent pixels in a row (horizontal pitch) or column (vertical pitch) of the scanned image

3.4 optical density D

logarithmic value to the base 10 of the diffuse light intensity ratio in front of (I_0) and behind (I_D) the radiographic film according to equation (1):

$$D = \lg \frac{I_0}{I_D}$$
(1)

3.5

edge spread function ESF

resulting profile across a step function after digitisation

NOTE This function can be either as light intensity or optical density.

3.6 digitiser unsharpness

 U_{D}

iTeh STANDARD PREVIEW

blurring of sharp edges by the scanning aperture, scattered light, flare or electronic bandwidth

It is determined from the geometrical distance of the 10% and 90% point of the Edge Spread Function (ESF) from a light intensity step function. ISO 14096

https://standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21c1a8beba5646/iso-14096-1-2005

3.7 spatial frequency

described by a sinusoidal intensity variation along a geometrical axis

The period of this function is measured in number of line pairs per millimetre (lp/mm).

3.8

spatial frequency maximum value

 f_{c}

in theory, this value, in number of line pairs per millimetre, is given by the Nyquist sampling theorem, see equation (2):

$$f_{\rm c} = 1/(2*P)$$

(2)

Practically, the scanning aperture, the mechanics and the electronics of the digitiser reduce this theoretical value.

3.9

modulation transfer function

MTF normalised magnitude of the Fourier-transform (FT) of the differentiated spatial optical density edge spread function (ESF) (see Figure 1)

It describes the unsharpness function of the digitiser (contrast transmission as a function of the object size).

NOTE This MTF calculation is based on optical densities, which correspond to the X-ray dose.

3.10 density range

 D_{R}

range of maximum and minimum optical densities, which can be measured by the digitiser

Depending on the construction of the digitiser, this density range can be split into several working ranges (e.g. by a different illumination power and/or a different detector integration time).

3.11

characteristic transfer curve

CTC

relationship between the optical density of the film and the digitised data

3.12

digital resolution in bit

number of bits provided by the analogue-to-digital converter of the digitiser used for densitometrical digitisation

A digital resolution of N bits corresponds to 2^N digital values. NOTE

3.13

density sampling pitch

 ΔD_{SP}

optical density variation corresponding to an increase of 1 in the digitised value

NOTE This density variation depends on the characteristic transfer curve of the digitiser. The density sampling pitch can be a function of the density.

3.14

ISO 14096-1:2005

density contrast sensitivity//standards.iteh.ai/catalog/standards/sist/d6d721a7-6e53-4c97-8a21- $\Delta D_{\rm CS}$ c1a8beba5646/iso-14096-1-2005

minimum density variation of the film, which is resolved by the digitiser

This is mostly determined by the digitisation noise of the digitiser (quantum noise of the light de tor).

3.15

working range

 D_{WR}

range of optical densities, where the digitiser guarantees a minimum density contrast sensitivity in one single acquisition

Only in this density range the digitised data can be used for evaluation. Depending on the digitiser construction there can be more than one working range, e.g. for brighter or darker films.

3.16

single acquisition

digitisation of one radiographic film performed with one single scan

The result of which is a collection of data not subject to any type of further processing. A unique set of parameters of the digitisation system is used for this acquisition.

3.17

standard reference film

photographic image on an industrial radiographic film containing all of the reference targets described in this document

3.18

targets

physical patterns on the standard reference film which are used to evaluate the digitiser