
**Aircraft — Environmental test procedures
for airborne fluid system components —
Resistance to fire in designated fire
zones**

*Aéronefs — Méthodes d'essai en environnement des éléments de
systèmes de fluides embarqués — Tenue au feu dans les zones
désignées «zone de feu»*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23935:2006

<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314-9b15a69b7af6/iso-23935-2006>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23935:2006

<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314-9b15a69b7af6/iso-23935-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 23935 was prepared by Technical Committee ISO/TC 20, Aircraft and space vehicles, Subcommittee SC 10, Aerospace fluid systems and components.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23935:2006

<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314-9b15a69b7af6/iso-23935-2006>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23935:2006

<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314-9b15a69b7af6/iso-23935-2006>

Aircraft — Environmental test procedures for airborne fluid system components — Resistance to fire in designated fire zones

CAUTION — Precautions shall be taken to safeguard the health of personnel conducting tests against the risk of fire, inhalation of smoke and/or toxic products of combustion.

1 Scope

This International Standard specifies the requirements for tests which may be applied to all fluid system components located in zones designated as “fire zones” and built to satisfy the minimum level specified for withstanding fire.

This International Standard does not relate to withstanding fire outside designated fire zones, nor to flammability requirements, or to those conditions induced by the flame coming from the combustion chamber.

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2685:1998, *Aircraft — Environmental test procedure for airborne equipment — Resistance to fire in designated fire zones.*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

designated fire zone

region of an aircraft, for example compartments containing main engines and auxiliary power units, designated as such by the aircraft designer in accordance with the requirements of the approving authority

3.2

component

any part of a fluid system which is to convey and/or contain fluid in liquid or gaseous condition

3.3

fire resistant

grade designating components capable of withstanding the application of heat by a standard flame for 5 min

3.4

fireproof

grade designating components capable of withstanding the application of heat by a standard flame for 15 min

4 Test equipment

The test rig shall be in accordance with ISO 2685:1998.

The test rig shall withstand the test conditions and simulate, as much as possible, the operating conditions of the real fluid circuit.

5 Test requirements

5.1 Test procedure

The following procedure applies to all fire tests.

For general requirements concerning the mounting of the specimen, and the choice and calibration of the burner, ISO 2685:1998 applies.

The test conditions may vary during the fire exposure duration. The regulation of all these test conditions shall be stipulated in the test report.

5.1.1 Standard test conditions

5.1.1.1 Test fluid

Table 1 applies.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Table 1 — Test fluid codes

Code	Test fluid
A	Fuel or high-temperature resisting oil
B	Air or nitrogen

5.1.1.2 Fluid temperature

5.1.1.2.1 For liquid application

The fluid temperature inside the component shall be between 93 °C and 110 °C (200 °F and 230 °F).

5.1.1.2.2 For gaseous application

The fluid temperature inside of the component shall be between 18 °C and 22 °C (64,5 °F and 71,5 °F).

5.1.1.3 Pressure

The pressure shall be the nominal pressure of the component as specified in the relevant procurement specification.

5.1.1.4 Flow rate

The flow rate shall be less than or equal to the minimum working flow under normal operating conditions, as specified in Table 2.

Table 2 — Flow rate

Code	Flow rate $\pm 10\%$	
	dm ³ /min (l/min) ^a	(US gallon/min) ^b
A	No flow	No flow
B	0,006 d^2	1 d^2
C	0,03 d^2	5 d^2

^a d is the minimal internal diameter of the hose as specified in the relevant procurement specification, expressed in millimetres.

^b d is the minimal internal diameter of the hose as specified in the relevant procurement specification, expressed in inches.

5.1.1.5 Vibration level

Components shall be vibrated along or perpendicular to the axis of the component at a frequency between 30 Hz and 60 Hz and with a minimum amplitude of 1,6 mm (0,063 in) in front of the flame.

5.1.1.6 Flame location

The hose to be tested shall be not less than 600 mm (23,6 in) long. Hoses shall be mounted horizontally and shall include one 90° bend. One end fitting and at least 120 mm (4,7 in) of hose shall be enveloped by the test flame.

5.1.1.7 Test duration

The test duration shall be in accordance with the grade designated for the component to resist fire, i.e. fire resistant or fireproof (see 3.3 and 3.4). See Table 3.

Table 3 — Test duration

Code	Duration min
05	5
15	15

5.1.2 Specific test conditions

5.1.2.1 Test fluid

The test conditions of the test fluid shall be equivalent to the normal operating conditions of the working fluid. Test fluid codes are identical to those in 5.1.1.1.

5.1.2.2 Fluid temperature

The fluid temperature inside the component shall be greater than or equal to the maximum working temperature under normal operating conditions.

When “no flow” or low flow rate is applied, these temperatures are only given at the beginning of the fire test.

The fluid temperature shall not be regulated better than under normal operating conditions.

5.1.2.3 Pressure

The pressure shall be greater than or equal to the maximum working pressure under normal operating conditions.

5.1.2.4 Flow rate

The flow rate shall be less than or equal to the minimum working flow under normal operating conditions.

5.1.2.5 Vibration level

The vibration level shall be in accordance with the worst working vibration level (frequency and amplitude) under normal operating conditions.

5.1.2.6 Flame location

The flame shall be located in front of the most critical exposed area of the component in accordance with the working position under normal operating conditions.

5.1.2.7 Test duration

The test duration shall be in accordance with the grade designated for the component to resist fire, i.e. fire resistant or fireproof (see 3.3 and 3.4).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 23935:2006


<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314->

5.2 Test acceptance conditions

As conditions of acceptance, the system components shall show no evidence of leakage over the test duration.


6 Designation

Reference to this International Standard shall be made in one of two ways: either by using standard codes (when standard test conditions are applied) or by using the real test condition values, as specified in Figures 1 and 2, respectively.



EXAMPLE ISO FFFFF CLASS A15B

Figure 1 — Designation using standard codes



^a Optional codification when different test conditions are used during a second part of the test:

EXAMPLE ISO FFFFF A15-0060-210-025-10-0000-210-10

When test conditions are the same for the total duration, the designation shall stop just after the first temperature value:

EXAMPLE ISO FFFFF A15-0060-210-025

When a test condition is unchanged during the second part of the test, it shall not be omitted in the designation.

Figure 2 — Designation using real test condition values
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/dcb33a93-1a3e-4f3e-8314-9b15a69b7af6/iso-23935-2006>