
**Diesel engines — NOx reduction agent
AUS 32 —**

**Part 1:
Quality requirements**

*Moteurs diesel — Agent AUS 32 de réduction des NOx —
Partie 1: Exigences de qualité*
(standards.iteh.ai)

ISO 22241-1:2006

<https://standards.iteh.ai/catalog/standards/sist/42d19cf2-1b2f-4e6f-99bd-5a7ef239915f/iso-22241-1-2006>



Reference number
ISO 22241-1:2006(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 22241-1:2006

<https://standards.iteh.ai/catalog/standards/sist/42d19cf2-1b2f-4e6f-99bd-5a7ef239915f/iso-22241-1-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22241-1 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 5, *Engine tests*.

This first edition cancels and replaces ISO/PAS 22241-1:2005, which has been technically revised.

ISO 22241 consists of the following parts, under the general title *Diesel engines — NO_x reduction agent AUS 32*:

- *Part 1: Quality requirements*
- *Part 2: Test methods*

The following parts are under preparation:

- *Part 3: Packaging, transportation and storage*
- *Part 4: Refilling interface*

Annexes A, B and C are for information only.

Introduction

In order to protect the environment, keeping the air quality as clean as possible, exhaust emissions regulations around the world have been strengthened considerably. In motor vehicles with diesel engines, particulate matters (PM) and nitrogen oxide (NOx) emissions are the main concern, and efforts have been focused on the development of technology which can reduce them effectively with minimum fuel economy penalty. Selective catalytic reduction (SCR) converters using urea solution as the reduction agent is considered to be a key technology for reducing NOx emissions. The quality of the urea solution used for that technology needs to be specified to ensure reliable and stable operation of the SCR converter systems. The ISO 22241 series provides the specifications for quality characteristics, for handling, transportation and storage and for the refilling interface as well as the test methods, needed by the manufacturers of motor vehicles and their engines, by converter manufacturers, by producers and distributors of the urea solution and by fleet operators.

The urea solution as specified in this part of ISO 22241 is commercially available, e.g. under the registered trademark AdBlue®. ISO takes no position concerning the evidence, validity and scope of this trademark right.

Licensees of the trademark AdBlue® have committed themselves to comply with the requirements of this part of ISO 22241.

The holder of this trademark right has assured ISO that he is willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this trademark right is registered with ISO. Information may be obtained from:

VDA - Verband der Automobilindustrie e.V.
60325 Frankfurt/M
Germany

<https://standards.iteh.ai/catalog/standards/sist/42d19cf2-1b2f-4e6f-99bd-5a7ef239915f/iso-22241-1-2006>

This information is given for the convenience of the users of this International Standard and does not constitute an endorsement of the trademark.

Diesel engines — NO_x reduction agent AUS 32 —

Part 1: Quality requirements

1 Scope

This part of ISO 22241 specifies the quality characteristics of the NO_x reduction agent AUS 32 (aqueous urea solution) which is needed to operate converters with selective catalytic reduction, so-called SCR (selective catalytic reduction) converters, in motor vehicles with diesel engines. SCR converters are particularly suitable for selectively reducing the nitrogen oxide (NO_x) emissions of diesel engines.

In the remaining parts of ISO 22241, the term “NO_x reduction agent AUS 32” will be abbreviated to “AUS 32”.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3675, *Crude petroleum and liquid petroleum products — Laboratory determination of density — Hydrometer method*

ISO 4259, *Petroleum products — Determination and application of precision data in relation to methods of test*

ISO 12185, *Crude petroleum and petroleum products — Determination of density — Oscillating U-tube method*

ISO 22241-2, *Diesel engines — NO_x reduction agent AUS 32 — Part 2: Test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

NO_x reduction agent AUS 32

aqueous urea solution, manufactured from technically pure urea – with no addition (see NOTE) of any other substances – and pure water, having a urea content of 32,5 % and with the quality characteristics defined in Clause 5

NOTE With the possible exception of a tracer in accordance with the requirement in Table 1.

3.2

technically pure urea

industrially produced grade of urea with traces of biuret, ammonia and water only, free of aldehydes or other substances such as anticaking agent, and free of contaminants such as sulphur and its compounds, chloride, nitrate or other compounds

NOTE For the contaminants mentioned above, which are not a result of the urea production process, limit values and analytical methods are not considered, as this definition excludes urea grades usually used in agriculture, which might contain such chemical compounds.

3.3 pure water
grade of water, produced for example by single distillation, by de-ionization, by ultra-filtration or by reverse osmosis

NOTE This is based on the definition of water grade 3 of ISO 3696.

4 Designation

AUS 32, in compliance with the requirements of this International Standard, shall be designated with the code AUS 32 and the reference number of this series of International Standards:

AUS 32 ISO 22241

5 Requirements and testing

The quality characteristics of the AUS 32 are specified in Table 1. They shall be continuously monitored by the manufacturer following a valid testing plan.

Compliance with the limits specified in Table 1 shall be verified with the test methods indicated.

NOTE 1 See Annex A with respect to the chemical characteristics of urea and the physical properties of AUS 32.

NOTE 2 See Annex B with respect to precision of the test methods.

6 Handling, transportation and storage

Recommendations for the logistics chain from the factory to the vehicle, in order to maintain the high quality of the product, are given in Annex C.

NOTE Requirements and recommendations for handling, transportation and storage will be specified in ISO 22241-3 which, once published, will replace Annex C.

7 Marking

Distribution pumps and containers for the distribution of AUS 32, in compliance with the requirements of this part of ISO 22241, shall be marked with the designation as specified in Clause 4.

Table 1 — Quality characteristics

Characteristics	Unit	Limits		Test methods
		min.	max.	
Urea content ^a	% (m/m) ^d	31,8	33,2	ISO 22241-2 Annex B ^e ISO 22241-2 Annex C ^e
Density at 20 °C ^b	kg/m ³	1 087,0	1 093,0	ISO 3675 or ISO 12185
Refractive index at 20 °C ^c	—	1,381 4	1,384 3	ISO 22241-2 Annex C
Alkalinity as NH ₃	% (m/m) ^d	—	0,2	ISO 22241-2 Annex D
Biuret	% (m/m) ^d	—	0,3	ISO 22241-2 Annex E
Aldehydes	mg/kg	—	5	ISO 22241-2 Annex F
Insoluble matter	mg/kg	—	20	ISO 22241-2 Annex G
Phosphate (PO ₄)	mg/kg	—	0,5	ISO 22241-2 Annex H
Calcium	mg/kg	—	0,5	ISO 22241-2 Annex I
Iron	mg/kg	—	0,5	
Copper	mg/kg	—	0,2	
Zinc	mg/kg	—	0,2	
Chromium	mg/kg	—	0,2	
Nickel	mg/kg	—	0,2	
Aluminium	mg/kg	—	0,5	
Magnesium	mg/kg	—	0,5	
Sodium	mg/kg	—	0,5	
Potassium	mg/kg	—	0,5	
Identity	—	identical to reference		ISO 22241-2 Annex J

Should it be necessary to add a tracer to AUS 32, it shall be ensured that the quality of AUS 32 specified in this Table is not impaired and that the tracer does not damage the SCR system.

NOTE 1 In establishment of these limit values, the terms of ISO 4259 have been applied in fixing a maximum and minimum value, a minimum difference of $4 \times R$ (R is the Reproducibility of the test method) has been taken into account. However, in case of urea content, the $4 \times R$ rule has not been applied in order to keep the high quality.

NOTE 2 The values quoted regarding urea content, density and refractive index are “true values” (see ISO 4259 for definition of true values).

NOTE 3 The manufacturer of AUS 32 should aim at the target values defined in footnotes a, b and c.

NOTE 4 Should it be necessary to clarify the questions as to whether a given urea solution meets the requirement of the specification, the terms of ISO 4259 should be applied.

^a Target value 32,5 % (m/m).

^b Target value 1 090,0 kg/m³.

^c Target value 1,382 9.

^d For the purposes of this International Standard, the term “% (m/m)” is used to represent the mass fraction of a material.

^e Calculated without subtracting nitrogen from ammonia.

Annex A (informative)

Chemical characteristics

A.1 Chemical description of urea

Chemical formula:	$(\text{NH}_2)_2\text{CO}$;
Molar mass:	60,06 g/mol;
CAS-Nr.:	57-13-6 (CAS : Chemical Abstracts Service).

A.2 Physical properties of AUS 32

Aspect:	colourless clear liquid;
Incipient crystallization:	−11,5 °C;
Viscosity (at 25 °C):	approx. 1,4 mPa·s;
Thermal conductivity (at 25 °C):	approx. 0,570 W/m·K;
Specific heat (at 25 °C):	approx. 3,40 kJ/kg·K;
Surface tension (at 20 °C):	min. 65 mN/m.

iTeH STANDARD PREVIEW
(standards.iteh.ai)
ISO 22241-1:2006
<https://standards.iteh.ai/catalog/standards/sist/42d19cf2-1b2f-4e6f-99bd-5a7ef239915f/iso-22241-1-2006>

Annex B (informative)

Precision of test methods

Characteristics	Unit	Repeatability <i>r</i>	Reproducibility <i>R</i>
Urea content (total nitrogen)	% (m/m)	0,4	1,0
Urea content (refractive index)	% (m/m)	0,1	1,0
Refractive index	—	0,000 1	0,001
Density according to ISO 3675	kg/m ³	0,5	1,2
Density according to ISO 12185	kg/m ³	0,2	0,5
Alkalinity as NH ₃	% (m/m)	0,01	0,2 × <i>x</i>
Biuret	% (m/m)	0,01	0,04
Aldehydes	mg/kg	0,14	0,5 × <i>x</i>
Insoluble matter	mg/kg	0,23 × <i>x</i>	0,38 × <i>x</i>
Phosphate (PO ₄)	mg/kg	0,02	0,03
Calcium	mg/kg	0,02	0,1 × <i>x</i>
Iron	mg/kg	0,01	0,3 × <i>x</i>
Copper	mg/kg	0,01	0,2 × <i>x</i>
Zinc	mg/kg	0,01	0,3 × <i>x</i>
Chromium	mg/kg	0,01	0,3 × <i>x</i>
Nickel	mg/kg	0,01	0,3 × <i>x</i>
Aluminium	mg/kg	0,02	0,3 × <i>x</i>
Magnesium	mg/kg	0,02	0,3 × <i>x</i>
Sodium	mg/kg	0,03	0,5 × <i>x</i>
Potassium	mg/kg	0,03	0,5 × <i>x</i>

x is mean value.

NOTE 1 The precision of the test methods for determination of the density was taken from the existing ISO 3675 and ISO 12185.

NOTE 2 The precision of all other test methods referenced in this part of ISO 22241 was obtained in an interlaboratory test programme conducted in the year 2004 with 18 laboratories in Austria, Germany and the Netherlands participating. The data obtained were evaluated according to ISO 4259.