

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 22282-1](https://standards.iteh.ai/catalog/standards/sist/7fca0463-bf8b-4b02-b8bd-02273678b2ef/iso-dis-22282-1)

<https://standards.iteh.ai/catalog/standards/sist/7fca0463-bf8b-4b02-b8bd-02273678b2ef/iso-dis-22282-1>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols	4
5 Equipment	4
5.1 General	4
5.2 Test section support system	5
5.3 Measuring tube	5
5.4 Isolation of the test section	5
5.5 Measuring and recording devices	6
5.5.1 Measuring devices for water level	6
5.5.2 Measuring devices for flow rate	6
5.5.3 Recording devices	6
5.6 Additional equipment	6
5.7 Calibration	6
6 Planning of geohydraulic investigation and testing	6
6.1 General	6
6.2 Selection of testing locations	7
6.3 Selection of test procedure	8
6.3.1 General	8
6.3.2 Water permeability tests in a borehole using open systems	12
6.3.3 Water pressure test in rocks	12
6.3.4 Pumping tests	13
6.3.5 Infiltrometer tests	14
6.3.6 Water permeability tests in a borehole using closed systems	14
7 Preparation of the test section and installation of equipment	14
7.1 Requirements for drilling and the test sections	14
7.2 Installation of filter	15
7.3 Checking installation	15
7.4 Safety requirements	15
7.5 Decommissioning	16
7.5.1 General	16
7.5.2 Decommissioning of boreholes	16
7.5.3 Decommissioning of surface facilities	16
7.6 Factors influencing the test results	16
7.6.1 General	16
7.6.2 Viscosity of fluid	16
7.6.3 Stratification and fissures	17
7.6.4 Variable groundwater levels	17
Annex A (informative) Examples of possible test section isolation and support methods	18
Annex B (informative) Examples of shape factors	24
Bibliography	25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22282-1 was prepared by Technical Committee ISO/TC 182, *Geotechnics*, Subcommittee SC 1, and by Technical Committee CEN/TC 341, *Geotechnical investigation and testing* in collaboration.

ISO 22282 consists of the following parts, under the general title *Geotechnical investigation and testing — Geohydraulic testing*:

- Part 1: General rules
- Part 2: Water permeability tests in a borehole using an open system
- Part 3: Water pressure test in rocks
- Part 4: Pumping tests
- Part 5: Infiltrometer tests
- Part 6: Water permeability tests in a borehole using a closed system

Introduction

The EU water directive requires the member states to increase the activities to protect groundwater and fresh surface water both quantitatively and qualitatively. At the same time society requires more water and more and deeper constructions below groundwater level. In addition sea level may rise as the result of climate change. This contradiction requires engineers working on construction projects below groundwater level to make more reliable predictions of the effects of such structures on the groundwater conditions. This can partly be achieved by better assessment of the permeability of the ground by in-situ tests as required in EN 1997-1 Clause 3.3.9.1. According to prEN 1997-2 the following shall apply:

“2.1.4 Groundwater –

(1) *Groundwater investigations shall provide all relevant information on groundwater needed for geotechnical design and construction.*

(2) *Groundwater investigations should provide, when appropriate, information on:*

- *the depth, thickness, extent and permeability of water-bearing strata in the ground, and joint systems in rock;*
- *the chemical composition and temperature of groundwater.*

(3) *The information obtained should be sufficient to assess the following aspects, where relevant:*

- *the scope for and nature of groundwater lowering work;*
- *possible harmful effects of the groundwater on excavations or on slopes (e.g. risk of hydraulic failure, excessive seepage pressure or erosion);*
- *any measures necessary to protect the structure (e.g. water proofing, drainage and measures against aggressive water);*
- *effects of groundwater lowering, desiccation, impounding, etc. on the surroundings;*
- *the capacity of the ground to absorb water injected during construction work;*
- *whether it is possible to use local groundwater, given its chemical constitution, for construction purposes.*

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO/DIS 22282-1

<https://standards.iteh.ai/catalog/standards/sist/7fca0463-bf8b-4b02-b8bd-02273678b2ef/iso-dis-22282-1>

Geotechnical investigation and testing — Geohydraulic testing —

Part 1: General rules

1 Scope

This document deals with the general rules and principles for geohydraulic testing in soil and rock as part of the geotechnical investigation services in accordance with EN 1997-1 and prEN 1997-2. It defines concepts and specifies requirements relating to permeability measurement in soil and rock.

The different purposes of geohydraulic testing are to obtain information on the permeability of soil or rock in natural or treated states, transmissivity and storage coefficient, and hydrodynamic parameters of aquifers.

Geohydraulic testing is used for many purposes, such as:

- a) absorption capacity and effectiveness of grouting in rock mass;
- b) assessment of seepage and drainage;
- c) assessment of groundwater lowering work;
- d) effect of cut-offs for dams;
- e) effect of tunnels shaft sinking;
- f) checking fill or cover tightness
- g) assessment of the flow of fluids and suspensions in the ground
- h) planning of remedial measures.

NOTE 1 Geohydraulic testing for water supply is covered by ISO 14686.

NOTE 2 For most type of ground, field permeability tests yield more reliable data than those carried out in the laboratory, because a larger volume of material is tested, and because the ground is tested in situ, thereby including effects resulting from the structure of the ground mass but avoiding the disturbance associated with sampling.

The document deals with the execution of tests with groundwater and does not explicitly consider other fluids and suspensions. The flow of other fluids and suspensions can be considered by applying the different viscosities and relations between transmissivity, permeability (hydraulic conductivity) and absolute permeability.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 791, *Drilling rigs — Safety*.

EN 1990, *Basis of Structural Design - Guidelines for implementation and application.*

EN 1997-1, *Eurocode 7: Geotechnical design — Part 1: General Rules.*

prEN 1997-2, *Eurocode 7: Geotechnical design — Part 2: Ground investigation and testing.*

ISO 14686 Hydrometric determinations — Pumping tests for water wells -- Considerations and guidelines for design, performance and use.

ISO/IEC 17025, *General requirement for the competence of testing and calibration laboratories.*

ISO 22475-1, *Geotechnical investigation and testing — Sampling by drilling and excavation methods and groundwater measurements — Part 1: Technical principle for execution.*

ISO/TS 22475-2, *Geotechnical investigation and testing — Sampling by drilling and excavation methods and groundwater measurements — Part 2: Technical qualification criteria.*

ISO/TS 22475-3, *Geotechnical investigation and testing — Sampling by drilling and excavation methods and groundwater measurements — Part 3: Conformity assessment for enterprises and personnel.*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 1990, EN 1997-1, EN 1997-2, and EN ISO 22475-1 and the following apply.

3.1

flow rate

The volume of water added or discharged from the test section per time unit

<https://standards.iteh.ai/catalog/standards/sist/fca0463-bf8b-4b02-b8bd-02273678b2ef/iso-dis-22282-1>

3.2

hydraulic head

the differential pressure between the test section and the surrounding ground, usually expressed in terms of water level

3.3

test section

a section in a borehole where the test is carried out

skin effect

the effect of the wall of the test section on the test

3.5

permeability coefficient

the flow rate divided by the area unit

NOTE The term "hydraulic conductivity" is also used synonymously for "permeability".

3.6

transmissivity

product of permeability coefficient and thickness of saturated aquifer.

3.7

storage coefficient

volume of water stored or released from a column of aquifer with unit cross section under unit hydraulic head variation.

3.8

steady state

state when hydraulic head and the flow rate are constant with time

3.9

transient state prior to the steady state when the flow rate or hydraulic head are not constant with time

3.10

saturated condition

condition of the tested ground with all voids filled with water

3.11

unsaturated condition

condition of the tested ground with voids partially filled with water and partially filled with air or another gas.

3.12

rising head test

test where the pressure or head in the test section is initially decreased and the rising is recorded

3.13

falling head test

test where the pressure or head in the test section is initially increased and the falling is recorded

3.14

variable head test

rising or falling head test

3.15

constant head test

test where the pressure or head in the test section is kept constant and the change in inflow or outflow is recorded.

3.16

constant rate test

test where the flow rate in the test section is kept constant and change in pressure or head is recorded

3.17

mud cake

Solids deposited on the filter pack or the borehole wall.

3.18

clogging

decrease of flow rate by blocking of flow paths due to sedimentation

3.19

washing

increase of flow rate by widening or opening of flow paths due to erosion

3.20

shape factor

A model factor used for the interpretation of the test results

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 22282-1

<https://standards.iteh.ai/catalog/standards/sist/7fca0463-bf8b-4b02-b8bd-0227367862cf/iso-dis-22282-1>

4 Symbols

Table 1 — Symbols

Symbol	Designation	Unit
A_c	Area of the inner cross section of the casing	m^2
A_m	Area of the inner cross section of the measuring tube	m^2
A_r	Area of the water surface in the reservoir	m^2
D	Borehole diameter, diameter of the test section	m
F	Shape factor	m
H	Hydraulic head	m
H_0	Distance of the water surface from ground level	m
H_1, H_2, H_3	Applied hydraulic heads	m
ΔH	Change in hydraulic head	m
k	Permeability coefficient	$m\ s^{-1}$
K	Intrinsic permeability coefficient	
L	Length (height) of the test section	m
p	Pressure	kPa
Q	flow rate	$m^3\ s^{-1}$
Q_1, Q_2, Q_3	flow rate at test 1, 2 and 3	$m^3\ s^{-1}$
S	Storage coefficient	-
T	Transmissivity ($T = kL$)	$m^2\ s^{-1}$
t	Time	s
t_i	Time needed to reach the equilibrium	s
t_o	Time at test start	s
V	Volume	m^3
η	dynamic viscosity of the fluid	Ns/ m^2
γ	density	kg/ dm^3

5 Equipment

5.1 General

According to the different test methods, the apparatus can comprise the following elements:

- test section support system;
- measuring tube;
- isolation of the test section;

- measuring and recording devices;
- additional equipment.

5.2 Test section support system

A system for supporting the test section shall be used for tests conducted in soil or rock which do not maintain the geometry of the test section throughout the test.

A filter or a gravel pack may be used to support the test section. The filter pack shall be stable against the surrounding ground and the sealing.

The filter material shall be a granular material selected to avoid plugging and/or erosion of the soil particles from or into the surrounding ground. The permeability of the filter material shall be considerably higher than the expected value of the permeability of the ground and shall not affect the test results.

A chemical effect between the filter material and the water shall be avoided.

5.3 Measuring tube

A measuring tube of known cross-section should be used to connect the test section to the ground surface. The tube shall be dimensionally stable with respect to the applied hydraulic head. The measurement tube elements shall be chosen to give a minimum number of joints to minimize leakage. Their diameter shall be adapted to the rate of water level variation.

A valve may be provided on this measuring tube, to allow isolation of the test section or establish contact with the atmosphere. The closing or opening of this valve shall not induce a change in volume which can lead to a change of the water pressure. Such changes can influence the quality of the test.

5.4 Isolation of the test section

The test section can be isolated either by

- the casing;
- a sealing plug;
- single packer;
- double or multiple packers.

NOTE see Annex B.

A packer is a high pressure expanding element which is inflated e.g. by compressed air and tightly pressed against the borehole wall to provide a seal. The sealed length shall depend on the evenness of the borehole wall and the soil and rock type to avoid leakage around the packer and shall not be less than 0,5 m. The effective pressure of the packer on the borehole wall shall be at least 30% higher than the maximum test pressure.

Single packers only seal at the top of a test section while double or multiple packers also can seal at the bottom. Special attention shall be paid to the detection of leakage of the lower packer.

The packer shall be strong enough to resist the inflating pressure with no creep and homogenous enough to avoid any perforation of the membrane.

5.5 Measuring and recording devices

5.5.1 Measuring devices for water level

The changes in water levels may be measured:

- by using an electrical measuring tape (water level meter);
- by using a float system;
- by using a pressure transducer system.

NOTE Rapid changes in depth are measured with greater accuracy with pressure sensing devices since they are able to detect the changes more rapidly than a float. Floats lose most of their accuracy from cable friction along the well walls.

5.5.2 Measuring devices for flow rate

The changes in flow rate shall be measured:

- by using flow meter;
- by using a calibrated container.

5.5.3 Recording devices

The recording shall be carried out:

- manually;
- analogously;
- digitally.

5.6 Additional equipment

Depending on the kind of the test and the possible impact of local conditions additional equipment shall be used in order to be able to make corrections for variations in water temperature and atmospheric pressure.

5.7 Calibration

The instruments and devices used for geohydraulic testing shall be regularly calibrated according to manufacturers' manuals and relevant standards. It shall be checked before starting the test, if the instruments and devices to be used have been calibrated. The calibration shall be recorded and documented and the results added to the test report, cf. ISO 22475-1, 10.1.

6 Planning of geohydraulic investigation and testing

6.1 General

Geohydraulic investigations shall be planned in such a way as to ensure that relevant geological and hydrogeological information and data are available at the various stages of the project. This