



Designation: D1007 – 05

Standard Specification for *sec*-Butyl Alcohol^{1, 2}

This standard is issued under the fixed designation D1007; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers *sec*-butyl alcohol for use in paint, varnish, lacquer, and related products.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.4 For hazard information and guidance, see the supplier’s Material Safety Data Sheet.

2. Referenced Documents

2.1 *ASTM Standards*:³

D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material

D1078 Test Method for Distillation Range of Volatile Organic Liquids

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products

D1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method)

D1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products

D4052 Test Method for Density, Relative Density, and API

¹ This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved May 15, 2005. Published May 2005. Originally approved in 1949. Last previous edition approved in 2000 as D1007 – 00. DOI: 10.1520/D1007-05.

² This compound is also known under the names 2-butanol and secondary butanol.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

Gravity of Liquids by Digital Density Meter
D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

E1 Specification for ASTM Liquid-in-Glass Thermometers
E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E300 Practice for Sampling Industrial Chemicals

2.2 *U.S. Federal Specification*:

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of⁴

3. Properties

3.1 *sec*-butyl alcohol shall conform to the following requirements:

Apparent specific gravity:	
20/20°C	0.807 to 0.809
or	
25/25°C	0.804 to 0.806
Color, Pt-Co scale, max ^A	10
Distillation range, 760 mmHg, °C as:	
Initial boiling point, min	98.0
Dry point, max	101.0
Nonvolatile matter, max, mg/100 mL	5
Water, max, weight %	0.5
Acidity, as acetic acid, max, weight %	0.002 ^B

^A Instrumental Pt-Co color determined by Test Method D5386 have been shown to have no statistically significant difference from Pt-Co color determined by Test Method D1209. However, it is not known whether *sec*-butyl alcohol was part of the sample set included in the interlaboratory study.

^B Equivalent to 0.019 mg of KOH per gram of sample.

4. Sampling

4.1 The material shall be sampled in accordance with Practice E300.

5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

5.1.1 *Apparent Specific Gravity*—Determine the apparent specific gravity at 20 or 25°C by a convenient method that is accurate to the third decimal place. See Guide D268 or Test Method D4052.

5.1.2 *Color*—Test Method D1209 (see Note A in 3.1).

⁴ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098.

*A Summary of Changes section appears at the end of this standard.