
**Information technology — Data
interchange on 90 mm optical disk
cartridges — Capacity: 2,3 Gbytes per
cartridge**

*Technologies de l'information — Échange de données sur cartouches
de disque optique de 90 mm — Capacité: 2,3 Go par cartouche*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[ISO/IEC 22533:2005](https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005)

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 22533:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	vii
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical disk Cartridge (ODC)	1
2.2 Generating system.....	1
2.3 Receiving system.....	2
2.4 Compatibility statement	2
3 Normative references	2
4 Terms and definitions.....	2
5 Conventions and notations	5
5.1 Representation of numbers	5
5.2 Names	5
6 Abbreviations and acronyms	5
7 General description of the optical disk cartridge.....	6
8 General requirements.....	6
8.1 Environments	6
8.2 Temperature shock.....	8
8.3 Safety requirements	8
8.4 Flammability.....	8
9 Reference Drive.....	8
9.1 Optical system	8
9.2 Optical beam	9
9.3 Read channels.....	10
9.4 Tracking	10
9.5 Rotation of the disk	10
Section 2 - Mechanical and physical characteristics	11
10 Dimensional and physical characteristics of the case	11
10.1 General description of the case (see Figure 2).....	11
10.2 Reference planes of the case	11
10.3 Dimensions of the case.....	11
10.4 Mechanical characteristics	18
11 Dimensional, mechanical and physical characteristics of the disk	31
11.1 General description of the disk	31
11.2 Reference axis and plane of the disk.....	31
11.3 Dimensions of the disk (see Figure 13)	31
11.4 Mechanical characteristics	32
11.5 Optical Characteristics.....	34
12 Interface between cartridge and drive	36
12.1 Clamping method.....	36
12.2 Clamping force.....	36
12.3 Capture cylinder (see Figure 14).....	36
12.4 Disk position in operating condition (see Figure 14).....	36

Section 3 - Format of information.....	38
13 Geometry of physical tracks	38
13.1 Physical track shape.....	38
13.2 Direction of track spiral	39
13.3 Physical track pitch	39
14 Track format.....	39
14.1 Logical Track number.....	39
14.2 Logical Track layout	39
14.3 Clock frequencies and periods.....	40
14.4 Radial alignment	40
14.5 Sector number	41
15 Sector format	41
15.1 Sector layout.....	41
15.2 Sector Mark (SM).....	42
15.3 VFO fields.....	42
15.4 Address Mark (AM)	43
15.5 ID fields	43
15.6 Postambles (PA).....	44
15.7 Gap	45
15.8 Sync.....	45
15.9 Data field	45
15.10 VCO lock pattern field (VLP)	46
15.11 Buffer field	46
16 Recording code	46
17 Format of the Information Zone.....	47
17.1 General description of the Information Zone	47
17.2 Division of the Information Zone.....	47
18 Format of the Data Zone.....	51
18.1 Buffer tracks and Test tracks in the Data Zone	51
18.2 Defect Management Areas (DMAs)	51
18.3 Disk Definition Structure (DDS)	55
18.4 Partitioning	55
18.5 Logical block address	55
19 Defect management	57
19.1 Initialization of the disk	57
19.2 Certification	57
19.3 Disks not certified	58
19.4 Write procedure.....	58
19.5 Primary Defect List (PDL).....	58
19.6 Secondary Defect List (SDL).....	59
Section 4 - Characteristics of embossed information.....	60
20 Method of testing	60
20.1 Environment	60
20.2 Use of the Reference Drive	60
20.3 Definition of signals	61
21 Signals from grooves	62
21.1 Divided push-pull signal.....	62
21.2 Phase depth.....	63
21.3 Track location	63
22 Signals from Headers	63
22.1 Sector Mark.....	64
22.2 VFO1 and VFO2	64
22.3 Address Mark, ID field and Postamble.....	64
22.4 Timing jitter.....	64

22.5	Asymmetry	65
23	Signals from embossed Recording fields	65
23.1	Signal amplitude	65
23.2	Timing jitter	65
Section 5 - Characteristics of the recording layer and user data		66
24	Method of testing	66
24.1	Environment	66
24.2	Reference Drive.....	66
24.3	Write conditions	67
24.4	Erase conditions	69
24.5	Definition of signals.....	70
25	Magneto-optical characteristics	70
25.1	Figure of merit.....	70
25.2	Imbalance of the magneto-optical signal	70
26	Write characteristics.....	71
26.1	Resolution	71
26.2	Narrow-band signal-to-noise ratio (NBSNR).....	72
26.3	Cross-talk ratio.....	73
26.4	Timing jitter	73
26.5	Media thermal interaction	73
27	Erase power determination.....	74
Section 6 - Characteristics of user data		75
28	Method of testing	75
28.1	Environment	75
28.2	Reference Drive.....	75
29	Minimum quality of a sector	76
29.1	Headers.....	76
29.2	User-written data.....	77
30	Data interchange requirements	77
30.1	Tracking	77
30.2	User-written data.....	77
30.3	Quality of disk	77
Annex A (normative) Edge distortion test		78
Annex B (normative) Compliance test		79
Annex C (normative) CRC for ID fields		81
Annex D (normative) Interleave, CRC, ECC, Resync for the data field.....		82
Annex E (normative) Contents of the Control Zone		87
Annex F (normative) Determination of the Resync patterns		94
Annex G (normative) Measurement of the figure of merit		99
Annex H (normative) Read Channel for measuring NBSNR and jitter.....		100
Annex I (normative) Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media		103
Annex J (normative) Air cleanliness class 100 000		104
Annex K (normative) Position of the cartridge relative to the reference planes		105
Annex L (normative) Relaxation by zones of the requirements for signals.....		106
Annex M (normative) Test method for measuring the adsorbent force of the hub.....		107
Annex N (informative) Track deviation measurement		109

Annex O (informative) Derivation of the operating climatic environment	113
Annex P (informative) Transportation	118
Annex Q (informative) Office environment	119
Annex R (informative) Values to be implemented in existing and future standards	120
Annex S (informative) Measurement of the vertical birefringence of the substrate	121
Annex T (informative) Sector retirement guidelines	123
Annex U (informative) Laser power calibration for evaluation of media power sensitivity	124

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 22533:2005](https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005)

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22533 was prepared by Ecma (as ECMA-353) and was adopted, under a special fast-track procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digital storage media for information interchange*, in parallel with its approval by national bodies of ISO and IEC.

[ISO/IEC 22533:2005](https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005)

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 22533:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

Information technology — Data interchange on 90 mm optical disk cartridges — Capacity: 2,3 Gbytes per cartridge

Section 1 - General

1 Scope

This International Standard defines the characteristics of 90 mm Optical Disk Cartridges (ODC) with a capacity of 2,3 GB per Cartridge. The Standard specifies only Type R/W for 2 048-byte sectors of such cartridge.

Type R/W provides for data to be written, read and erased many times over the entire recording surface of the disk using the thermo-magnetic and magneto-optical effects. It is also referred to as "fully rewritable". This International Standard provides for 2 048-byte sectors only. All sectors on a disk are of the same size.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated and stored;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written; including the physical disposition of the tracks and sectors, the error correction codes, and the modulation method used;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical disk Cartridge (ODC)

A claim of conformance with this International Standard shall specify the Type of the ODC. It shall be in conformance if it meets all mandatory requirements specified herein for that Type.

2.2 Generating system

A claim of conformance with this International Standard shall specify which Type is supported. A system generating an ODC for interchange shall be in conformance with this International Standard if it meets the mandatory requirements of this International Standard for the Type specified.

2.3 Receiving system

A claim of conformance with this International Standard shall specify which Type is supported. A system receiving an ODC for interchange shall be in conformance with this International Standard if it is able to process any recording made on the cartridge in accordance with 2.1 on the Type specified.

2.4 Compatibility statement

A claim of conformance with this International Standard shall include a statement listing any other International Standard supported by the system for which conformance is claimed. This statement shall specify the number of the Standard(s), the ODC type(s) supported (where appropriate) and whether support includes reading or both reading and writing.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ECMA-287 *Safety of electronic equipment (2002)*

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply:

4.1

band

Part of the Data Zone comprising a fixed number of consecutive physical tracks.

4.2

case

The housing for an optical disk, that protects the disk and facilitates disk interchange.

4.3

Channel bit

The smallest element for the representation of data on a disk. It is recorded as either a space or a mark. Twelve Channel bits are used to represent eight input bits.

4.4

clamping zone

The annular part of the disk within which the clamping force is applied by the clamping device.

4.5

control track

A track containing the information on media parameters and format necessary for writing, reading and erasing the remaining tracks on the optical disk.

4.6

Cyclic Redundancy Check (CRC)

A method for detecting errors in data.

4.7

defect management

A method for handling the defective areas on the disk.

4.8**disk reference plane**

A plane defined by the perfectly flat annular surface of an ideal spindle onto which the clamping zone of the disk is clamped, and which is normal to the axis of rotation.

4.9**embossed mark**

A mark so formed as to be unalterable by magneto-optical means.

4.10**entrance surface**

The surface of the disk on to which the optical beam first impinges.

4.11**Error Correction Code (ECC)**

An error-detecting code designed to correct certain kinds of errors in data.

4.12**field**

A subdivision of a sector.

4.13**format**

The arrangement or layout of information on the disk.

4.14**fully rewritable disk**

An optical disk in which the data in specified areas can be rewritten by an optical beam.

4.15**groove**

See 4.19.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

4.16**hub**

The central feature on the disk which interacts with the spindle of the disk drive to provide radial centring and the clamping force.

4.17**interleaving**

The process of allocating the physical sequence of units of data so as to render the data more immune to burst errors.

4.18**Kerr rotation**

The rotation of the plane of polarization of an optical beam upon reflection from the recording layer, as caused by the magneto-optical effect.

4.19**land and groove**

A trench-like feature of the disk, applied before the recording of any information, and used to define the track location. The groove is located nearer to the entrance surface than the land with which it is paired to form a track.

4.20**logical track**

17 consecutive sectors for disks with 2 048-byte sectors in one or more physical tracks. The first sector of each logical track is assigned sector number 0.

4.21

logical ZCAV

A disk format requiring Zoned Constant Angular Velocity operation and with tracks *n* in the Data Zone all being logical tracks.

4.22

mark

A feature of the recording layer which may take the form of a magnetic domain, a pit, or any other type or form that can be sensed by the optical system. The pattern of marks represents the data on the disk.

NOTE 1 Subdivisions of a sector which are named 'mark' are not marks in the sense of this definition.

4.23

optical disk

A disk that will accept and retain information in the form of marks in a recording layer, that can be read with an optical beam.

4.24

optical disk cartridge (ODC)

A device consisting of a case containing an optical disk.

4.25

physical track

The path which is followed by the focus of the optical beam during one revolution of the disk.

4.26

physical track group

A fixed number of consecutive physical tracks in the Data Zone.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.27

pitch

The distance between adjacent physical track centrelines, measured in a radial direction.

ISO/IEC 22533:2005

<https://standards.iteh.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e97f53ddc/iso-iec-22533-2005>

4.28

polarization

The direction of polarization of an optical beam is the direction of the electric vector of the beam.

NOTE 2 The plane of polarization is the plane containing the electric vector and the direction of propagation of the beam. The polarization is right-handed when to an observer looking in the direction of propagation of the beam, the end-point of the electric vector would appear to describe an ellipse in the clockwise sense.

4.29

read power

The optical power, incident at the entrance surface of the disk, used when reading.

NOTE 3 It is specified as a maximum power that may be used without damage to the written data. Lower power may be used provided that the signal-to-noise ratio and other requirements of this International Standard are met.

4.30

recording layer

A layer of the disk on, or in, which data is written during manufacture and/or use.

4.31

Reed-Solomon code

An error detection and/or correction code which is particularly suited to the correction of errors which occur in bursts or are strongly correlated.

4.32**sector**

The smallest addressable part of a track in the Information Zone of a disk that can be accessed independently of other addressable parts of the zone.

4.33**space**

The area between marks along the track.

4.34**spindle**

The part of the disk drive which contacts the disk and/or hub.

4.35**substrate**

A transparent layer of the disk, provided for mechanical support of the recording layer, through which the optical beam accesses the recording layer.

4.36**zone**

An annular area of the disk.

5 Conventions and notations**5.1 Representation of numbers**

A measured value is rounded off to the least significant digit of the corresponding specified value. It implies that a specified value of 1,26 with a positive tolerance of +0,01, and a negative tolerance of -0,02 allows a range of measured values from 1,235 to 1,275.

Letters and digits in parentheses represent numbers in hexadecimal notation.

The setting of a bit is denoted by ZERO or ONE.

Numbers in binary notation and bit combinations are represented by strings of digits 0 and 1.

Numbers in binary notation and bit combinations are shown with the most significant bit to the left.

Negative values of numbers in binary notation are given in TWO's complement.

In each field the data is recorded so that the most significant byte (byte 0) is recorded first. Within each byte the least significant bit is numbered 0 and is recorded last, the most significant bit (numbered 7 in an 8-bit byte) is recorded first. This order of recording applies also to the data input of the Error Detection and Correction circuits and to their output.

Unless otherwise stated, all track numbers refer to logical tracks.

5.2 Names

The names of entities, e.g. specific tracks, fields, etc., are given with a capital initial.

6 Abbreviations and acronyms

AM	Address Mark
CRC	Cyclic Redundancy Check

DDS	Disk Definition Structure
DMA	Defect Management Area
ECC	Error Correction Code
FA1	Functional Area 1
FA2	Functional Area 2
ID	Identifier
LSB	Least Significant Byte
MO	Magneto-Optical
MSB	Most Significant Byte
ODC	Optical Disk Cartridge
PA	Postamble
PDL	Primary Defect List
RLL (1,7)	Run Length Limited (code)
R/W	Rewritable
SDL	Secondary Defect List
SM	Sector Mark
TIA	Time Interval Analyser
VCO	Voltage Controlled Oscillator
VFO	Variable Frequency Oscillator
ZCAV	Zoned Constant Angular Velocity

STANDARD PREVIEW
(standards.itech.ai)
ISO/IEC 22533:2005
<https://standards.itech.ai/catalog/standards/sist/534bea41-8567-47f8-86a1-217e9753ddc/iso-iec-22533-2005>

7 General description of the optical disk cartridge

The optical disk cartridge which is the subject of this International Standard consists of a case containing an optical disk.

The case is a protective enclosure for the disk. It has access windows covered by a shutter. The windows are automatically uncovered by the drive when the cartridge is inserted into it.

The optical disk is recordable on one side. Data can be written onto the disk as marks in the form of magnetic domains in the recording layer and can be erased from it with a focussed optical beam, using the thermo-magnetic effect. Data may be directly written over existing data by modulating the intensity of the optical beam. The data can be read with a focussed optical beam, using the magneto-optical effect. The beam accesses the recording layer through the transparent substrate of the disk.

8 General requirements

8.1 Environments

8.1.1 Testing environment

The test environment is the environment where the air immediately surrounding the optical disk cartridge has the following properties:

temperature	: 23 °C ± 2 °C
relative humidity	: 45 % to 55 %

atmospheric pressure	: 60 kPa to 106 kPa
air cleanliness	: Class 100 000 (see Annex J)

No condensation on or in the optical disk cartridge shall occur. Before testing, the optical disk cartridge shall be conditioned in this environment for 48 h minimum. It is recommended that, before testing, the entrance surface of the optical disk shall be cleaned according to the instructions of the manufacturer of the disk.

Unless otherwise stated, all tests and measurements shall be made in this test environment.

8.1.2 Operating environment

This International Standard requires that an optical disk cartridge which meets all requirements of this International Standard in the specified test environment provides data interchange over the specified ranges of environmental parameters in the operating environment.

The operating environment is the environment where the air immediately surrounding the optical disk cartridge has the following properties:

Temperature	: 5 °C to 55 °C
relative humidity	: 3 % to 85 %
absolute humidity	: 1 g/m ³ to 30 g/m ³
atmospheric pressure	: 60 kPa to 106 kPa
temperature gradient	: 10 °C/h max.
relative humidity gradient	: 10 %/h max.
air cleanliness	: Office environment (see Annex Q.1)
magnetic field strength at the recording layer for any condition under which a beam is in focus	: 36 000 A/m max. (see Annex Q.2)
magnetic field strength at the recording layer during any other condition	: 48 000 A/m max.

No condensation on or in the optical disk cartridge shall occur. If an optical disk cartridge has been exposed to conditions outside those specified in this Clause, it shall be acclimatized in an allowed operating environment for at least 2 h before use. (See also Annex O)

8.1.3 Storage environment

The optical disk cartridge without any protective enclosure shall not be stored in an environment outside the range allowed for storage. The storage environment is defined as an environment where the air immediately surrounding the optical disk cartridge has the following properties:

temperature	: - 10 °C to 55 °C
relative humidity	: 3 % to 90 %
absolute humidity	: 1 g/m ³ to 30 g/m ³
atmospheric pressure	: 60 kPa to 106 kPa
temperature gradient	: 15 °C /h max.
relative humidity gradient	: 10 %/h max.
air cleanliness	: Office environment (see Annex Q.1)
magnetic field strength at the recording layer	: 48 000 A/m max.