
**Petroleum and natural gas industries —
Pipeline transportation systems —
Pipeline valves**

*Industries du pétrole et du gaz naturel — Systèmes de transport par
conduites — Robinets de conduites*

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 14313:2007](https://standards.itih.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007)

<https://standards.itih.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 14313:2007](https://standards.itih.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007)

<https://standards.itih.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vi
1 Scope	1
2 Conformance.....	1
2.1 Units of measurement.....	1
2.2 Rounding.....	1
2.3 Compliance to standard.....	1
3 Normative references.....	2
4 Terms and definitions.....	4
5 Symbols and abbreviated terms.....	7
5.1 Symbols.....	7
5.2 Abbreviated terms.....	7
6 Valve types and configurations.....	8
6.1 Valve types.....	8
6.2 Valve configurations.....	9
7 Design.....	23
7.1 Design standards and calculations.....	23
7.2 Pressure and temperature rating.....	24
7.3 Sizes.....	24
7.4 Face-to-face and end-to-end dimensions.....	25
7.5 Valve operation.....	39
7.6 Pigging.....	40
7.7 Valve ends.....	40
7.8 Pressure relief.....	41
7.9 Bypasses, drains and vents.....	42
7.10 Injection points.....	42
7.11 Drain, vent and sealant lines.....	42
7.12 Drain, vent and sealant valves.....	43
7.13 Hand-wheels and wrenches — Levers.....	43
7.14 Locking devices.....	43
7.15 Position of the obturator.....	43
7.16 Position indicators.....	43
7.17 Travel stops.....	44
7.18 Actuator, operators and stem extensions.....	44
7.19 Lifting.....	44
7.20 Drive trains.....	44
7.21 Stem retention.....	45
7.22 Fire type-testing.....	45
7.23 Anti-static device.....	45
7.24 Design documents.....	45
7.25 Design document review.....	45
8 Materials.....	46
8.1 Material specification.....	46
8.2 Service compatibility.....	46
8.3 Forged parts.....	46
8.4 Composition limits.....	46
8.5 Toughness test requirements.....	47
8.6 Bolting.....	48

8.7	Sour service.....	48
8.8	Vent and drain connections.....	48
9	Welding.....	48
9.1	Qualifications.....	48
9.2	Impact testing.....	48
9.3	Hardness testing.....	49
9.4	Repair.....	49
10	Quality control.....	51
10.1	NDE requirements.....	51
10.2	Measuring and test equipment.....	51
10.3	Qualification of inspection and test personnel.....	51
10.4	NDE of repairs.....	52
10.5	Weld end NDE.....	52
10.6	Visual inspection of castings.....	52
11	Pressure testing.....	52
11.1	General.....	52
11.2	Stem backseat test.....	53
11.3	Hydrostatic shell test.....	53
11.4	Hydrostatic seat test.....	54
11.5	Testing of drain, vent and sealant injection lines.....	55
11.6	Draining.....	55
12	Coating.....	55
13	Marking.....	56
14	Preparation for shipment.....	58
15	Documentation.....	58
	Annex A (normative) Requirements for non-destructive examination.....	59
	Annex B (normative) Supplementary test requirements.....	63
	Annex C (informative) Supplementary documentation requirements.....	67
	Annex D (informative) Purchasing guidelines.....	68
	Annex E (informative) Marking example.....	75
	Bibliography.....	77

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14313 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 2, *Pipeline transportation systems*.

This second edition cancels and replaces the first edition (ISO 14313:1999), which has been technically revised, principally by the following.

- Clause 2, on the requirements for conformity to this International Standard, has been added for clarification.
- Clause 7, on the requirements for allowable stresses and allowable deflection on design, has been revised and clarified.
- Clause 8, on material, has been revised to align the requirements with global industry practice for carbon content and carbon equivalent for pressure-containing, pressure-controlling, welding ends and parts requiring welding.
- New requirements on repairs and NDE of welding repairs have been added to Clause 9 on Welding.
- A new table (Table D.2) has been added to Annex D (informative) to provide more guidance for those requirements listed in the text as requiring agreement between the manufacturer/purchaser.

Introduction

This International Standard is the result of harmonizing the requirements of ISO 14313:1999 and API Spec 6D-2002^[5].

The revision of ISO 14313 is developed based on input from both ISO/TC67/SC2 WG2 and API 6D TG technical experts. The technical revisions have been made in order to accommodate the needs of industry and to move this International Standard to a higher level of service to the petroleum and natural gas industry.

Users of this International Standard should be aware that further or differing requirements can be needed for individual applications. This International Standard is not intended to inhibit a manufacturer from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the manufacturer should identify any variations from this International Standard and provide details.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 14313:2007](https://standards.iteh.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007)

<https://standards.iteh.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007>

Petroleum and natural gas industries — Pipeline transportation systems — Pipeline valves

1 Scope

This International Standard specifies requirements and provides recommendations for the design, manufacturing, testing and documentation of ball, check, gate and plug valves for application in pipeline systems meeting the requirements of ISO 13623 for the petroleum and natural gas industries.

This International Standard is not applicable to subsea pipeline valves, as they are covered by a separate International Standard (ISO 14723).

This International Standard is not applicable to valves for pressure ratings exceeding PN 420 (Class 2 500).

2 Conformance

2.1 Units of measurement

In this International Standard, data are expressed in both SI units and USC units. For a specific order item, unless otherwise stated, only one system of units shall be used, without combining data expressed in the other system.

For data expressed in SI units, a comma is used as the decimal separator and a space is used as the thousands separator. For data expressed in USC units, a dot (on the line) is used as the decimal separator and a comma is used as the thousands separator.

2.2 Rounding

Except as otherwise required by this International Standard, to determine conformance with the specified requirements, observed or calculated values shall be rounded to the nearest unit in the last right-hand place of figures used in expressing the limiting value, in accordance with the rounding method of ISO 31-0:1992, Annex B, Rule A.

2.3 Compliance to standard

A quality system should be applied to assist compliance with the requirements of this International Standard.

NOTE ISO/TS 29001 gives sector-specific guidance on quality management systems.

The manufacturer shall be responsible for complying with all of the applicable requirements of this International Standard. It shall be permissible for the purchaser to make any investigation necessary in order to be assured of compliance by the manufacturer and to reject any material that does not comply.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments, corrigendum, and maintenance agency output) applies.

ISO 31-0,1992, *Quantities and units — Part 0: General principles*

ISO 148-1, *Metallic materials — Charpy pendulum impact test — Part 1: Test method*

ISO 228-1, *Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 5208:1993, *Industrial valves — Pressure testing of valves*

ISO 7268, *Pipe components — Definition of nominal pressure*

ISO 9606-1, *Approval testing of welders — Fusion welding — Part 1: Steels*

ISO 9712, *Non-destructive testing — Qualification and certification of personnel*

ISO 10474, *Steel and steel products — Inspection documents*

ISO 10497, *Testing of valves — Fire type-testing requirements*

ISO 15156 (all parts), *Petroleum and natural gas industries — Materials for use in H₂S-containing environments in oil and gas production*

ISO 15607, *Specification and qualification of welding procedures for metallic materials — General rules*

ISO 15609 (all parts), *Specification and qualification of welding procedures for metallic materials — Welding procedure specification*

ISO 15614-1, *Specification and qualification of welding procedures for metallic materials — Welding procedure test — Part 1: Arc and gas welding of steels and arc welding of nickel and nickel alloys*

ISO 23277, *Non-destructive testing of welds — Penetrant testing of welds — Acceptance levels*

ISO 23278, *Non-destructive testing of welds — Magnetic particle testing of welds — Acceptance levels*

ASME B1.20.1¹⁾, *Pipe Threads, General Purpose, Inch*

ASME B16.5-1996, *Pipe Flanges and Flanged Fittings : NPS 1/2 through 24*

ASME B16.10-2000, *Face-to-Face and End-to-End Dimensions of Valves*

ASME B16.34-2004, *Valves, Flanged, Threaded, and Welding End*

ASME B16.47-2006, *Large Diameter Steel Flanges : NPS 26 Through NPS 60 Metric/Inch Standard*

ASME B31.4-2006, *Pipeline Transportation Systems for Liquid Hydrocarbons and Other Liquids*

ASME B31.8-2003, *Gas Transmission and Distribution Piping Systems*

ASME Boiler and Pressure Vessel Code, Section V: *Nondestructive Examination*

1) American Society of Mechanical Engineers International, 345 East 47th Street, NY 10017-2392, USA

ASME Boiler and Pressure Vessel Code — Section VIII: *Rules for Construction of Pressure Vessels* Division 1, *Rules for Construction of Pressure Vessels*

ASME Boiler and Pressure Vessel Code — Section VIII: *Rules for Construction of Pressure Vessels* Division 2: *Alternative Rules*

ASME Boiler and Pressure Vessel Code — Section IX: *Welding and Brazing Qualifications*

ASNT SNT-TC-1A²⁾, *Recommended Practice No. SNT-TC-1A — Personnel Qualification and Certification in Non-Destructive Testing*

ASTM A320³⁾, *Standard Specification for Alloy-Steel and Stainless Steel Bolting Materials for Low-Temperature Service*

ASTM A370, *Standard Test Methods and Definitions for Mechanical Testing of Steel Products*

ASTM A388, *Standard Practice for Ultrasonic Examination of Heavy Steel Forgings*

ASTM A435, *Standard Specification for Straight-Beam Ultrasonic Examination of Steel Plates*

ASTM A577, *Standard Specification for Ultrasonic Angle-Beam Examination of Steel Plates*

AWS QC1⁴⁾, *Standard for AWS Certification of Welding Inspectors*

EN 287-1⁵⁾, *Qualification test of welders — Fusion welding — Part 1: Steels*

EN 1092-1, *Flanges and their joints — Circular flanges for pipes, valves, fittings and accessories, PN designated — Part 1: Steel flanges*

EN 10204:2004, *Metallic products — Type of inspection documents*

MSS SP-44, *Steel Pipeline Flanges*

MSS SP-55, *Quality Standard for Steel Castings for Valves, Flanges and Fittings and Other Piping Components — Visual Method for Evaluation of Surface Irregularities*

NACE TM0177-2005, *Standard test method. Laboratory testing of metals for resistance to specific forms of environmental cracking in H₂S environments*

NACE TM0284, *Standard Test Method — Evaluation of Pipeline and Pressure Vessel Steels for Resistance to Hydrogen-Induced Cracking*

2) American Society of Non-Destructive Testing, P.O. Box 28518, 1711 Arlingate Lane, Columbus, OH 43228-0518, USA.

3) ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, USA.

4) The American Welding Society, 550 NW LeJeune Road, Miami, FL 33126, USA.

5) CEN, European Committee for Standardization, Central Secretariat, Rue de Stassart 36, B-1050, Brussels, Belgium.

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1

ASME rating class

numerical pressure design class defined in ASME B16.34 and used for reference purposes

NOTE The ASME rating class is designated by the word "class" followed by a number.

4.2

bi-directional valve

valve designed for blocking the fluid in both downstream and upstream directions

4.3

bleed

drain or vent

4.4

block valve

gate, plug or ball valve that blocks flow into the downstream conduit when in the closed position

NOTE Valves are either single- or double-seated, bi-directional or uni-directional.

4.5

breakaway thrust

breakaway torque

maximum thrust or torque required to operate a valve at maximum pressure differential

4.6

by agreement

agreed between manufacturer and purchaser

4.7

double-block-and-bleed valve

DBB

single valve with two seating surfaces that, in the closed position, provides a seal against pressure from both ends of the valve with a means of venting/bleeding the cavity between the seating surfaces

NOTE This valve does not provide positive double isolation when only one side is under pressure. See **double-isolation-and-bleed valve** (4.8).

4.8

double-isolation-and-bleed valve

DIB

single valve with two seating surfaces, each of which, in the closed position, provides a seal against pressure from a single source, with a means of venting/bleeding the cavity between the seating surfaces

NOTE This feature can be provided in one direction or in both directions.

4.9

drive train

all parts of a valve drive between the operator and the obturator, including the obturator but excluding the operator

4.10 flow coefficient

K_v

volumetric flow rate of water at a temperature between 5 °C (40 °F) and 40 °C (104 °F) passing through a valve and resulting in a pressure loss of 0,1 MPa (1 bar; 14.5 psi)

NOTE K_v is expressed in SI units of cubic metres per hour.

NOTE K_v is related to the flow coefficient C_v , expressed in USC units of US gallons per minute at 15,6 °C (60 °F) resulting in a 1 psi pressure drop as given by Equation (1):

$$K_v = \frac{C_v}{1,156} \quad (1)$$

4.11 full-opening valve

valve with an unobstructed opening, not smaller than the internal bore of the end connections

4.12 handwheel

wheel consisting of a rim connected to a hub, for example by spokes, and used to manually operate a valve requiring multiple turns

4.13 locking device

part or an arrangement of parts for securing a valve in the open and/or closed position

4.14 manual actuator manual operator

wrench (lever) or hand-wheel with or without a gearbox

4.15 maximum pressure differential

MPD

maximum difference between the upstream and downstream pressure across the obturator at which the obturator may be operated

4.16 nominal pipe size

NPS

numerical imperial designation of size which is common to components in piping systems of any one size

NOTE Nominal pipe size is designated by the abbreviation "NPS" followed by a number.

4.17 nominal pressure class

PN

numerical pressure design class as defined in ISO 7268 and used for reference purposes

NOTE Nominal pressure (PN) class is designated by the abbreviation "PN" followed by a number.

4.18 nominal size

DN

numerical metric designation of size that is common to components in piping systems of any one size

NOTE Nominal size is designated by the abbreviation "DN" followed by a number.

4.19
obturator
closure member

part of a valve, such as a ball, clapper, disc, gate or plug that is positioned in the flow stream to permit or prevent flow

4.20
operator

device (or assembly) for opening or closing a valve

4.21
packing gland

component used to compress the stem packing

4.22
position indicator

device to show the position of the valve obturator

4.23
piggability

capability of a valve to permit the unrestricted passage of a pig

4.24
powered actuator
powered operator

electric, hydraulic or pneumatic device bolted or otherwise attached to the valve for powered opening and closing of the valve

4.25
pressure class

numerical pressure design class expressed in accordance with either the nominal pressure (PN) class or the ASME rating class

NOTE In this International Standard, the pressure class is stated by the PN class followed by the ASME rating class between brackets.

4.26
pressure-containing parts

parts, whose failure to function as intended results in a release of contained fluid into the environment

4.27
pressure-controlling parts

parts, such as seat and obturator, intended to prevent or permit the flow of fluids

4.28
process-wetted parts

parts exposed directly to the pipeline fluid

4.29
reduced-opening valve

valve with the opening through the obturator smaller than at the end connection(s)

4.30
seating surfaces

contact surfaces of the obturator and seat which ensure valve sealing

4.31
stem

part that connects the obturator to the operator and which can consist of one or more components

4.32**stem extension assembly**

assembly consisting of the stem extension and the stem extension housing

4.33**support ribs or legs**

metal structure that provides a stable footing when the valve is set on a fixed base

4.34**through-conduit valve**

valve with an unobstructed and continuous cylindrical opening

4.35**uni-directional valve**

valve designed for blocking the flow in one direction only

4.36**unless otherwise agreed**

⟨modification of the requirements of this International Standard⟩ unless the manufacturer and purchaser agree on a deviation

4.37**unless otherwise specified**

⟨modification of the requirements of this International Standard⟩ unless the purchaser specifies otherwise

4.38**venturi plug valve**

valve with a substantially reduced opening through the plug and a smooth transition from each full-opening end to the reduced opening

5 Symbols and abbreviated terms**5.1 Symbols**

C_v flow coefficient in USC units

K_v flow coefficient in metric units

t thickness

5.2 Abbreviated terms

BM base metal

CE carbon equivalent

DBB double-block-and-bleed

DIB double isolation-and-bleed

DN nominal size

HAZ heat-affected zone

HBW Brinell hardness, tungsten ball indenter

HRC Rockwell C hardness

HV	Vickers hardness
MPD	maximum pressure differential
MT	magnetic-particle testing
NDE	non-destructive examination
NPS	nominal pipe size
PN	nominal pressure
PQR	(weld) procedure qualification record
PT	penetrant testing
PWHT	post-weld heat treatment
RT	radiographic testing
SMYS	specified minimum yield strength
USC	United States Customary (units)
UT	ultrasonic testing
WM	weld metal
WPS	weld procedure specification
WPQ	welder performance qualification

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

6 Valve types and configurations [ISO 14313:2007](https://standards.itih.ai/catalog/standards/iso/7428a124-78d2-44e8-a329-00df641ccb40/iso-14313-2007)

6.1 Valve types

6.1.1 Gate valves

Typical configurations for gate valves with flanged and welding ends are shown, for illustration purposes only, in Figures 1 and 2.

Gate valves shall have an obturator that moves in a plane perpendicular to the direction of flow. The gate can be constructed of one piece for slab-gate valves or of two or more pieces for expanding-gate valves.

Gate valves shall be provided with a back seat or secondary stem sealing feature in addition to the primary stem seal.

6.1.2 Lubricated and non-lubricated plug valves

Typical configurations for plug valves with flanged and welding ends are shown, for illustration purposes only, in Figure 3.

Plug valves shall have a cylindrical or conical obturator that rotates about an axis perpendicular to the direction of flow.