
**Agricultural irrigation equipment —
Irrigation valves —**

**Part 5:
Control valves**

Matériel agricole d'irrigation — Vannes d'irrigation —

Partie 5: Vannes de contrôle
iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 9635-5:2006

<https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e8f2b56542d/iso-9635-5-2006>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 9635-5:2006

<https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e8f2b56542d/iso-9635-5-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Design requirements	2
5 Performance requirements	2
5.1 Mechanical strength	2
5.2 Watertightness	4
5.3 Hydraulic characteristics	4
5.4 Resistance to chemicals and fertilizers.....	5
5.5 Endurance	5
6 Conformity assessment	5
6.1 General.....	5
6.2 Type tests	5
6.3 Control of production process and quality system.....	5
7 Marking	6
8 Packaging	6
Annex A (normative) Test method for hydraulic characteristics of control valves providing flow regulation function	7
Annex B (normative) Test method for hydraulic characteristics of control valves providing pressure regulation function	8
Annex C (normative) Test method for hydraulic characteristics of control valves providing level regulation.....	9
Annex D (normative) Test method for endurance of control valves.....	10
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 9635-5 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 18, *Irrigation and drainage equipment and systems*.

This first edition of ISO 9635-5, together with ISO 9635-1, ISO 9635-2, ISO 9635-3 and ISO 9635-4, cancels and replaces ISO 9635:1990, of which it constitutes a technical revision.

ISO 9635 consists of the following parts, under the general title *Agricultural irrigation equipment — Irrigation valves*:

— *Part 1: General requirements*

— *Part 2: Isolating valves*

— *Part 3: Check valves*

— *Part 4: Air valves*

— *Part 5: Control valves*

<https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e8f2b56542d/iso-9635-5-2006>

Agricultural irrigation equipment — Irrigation valves —

Part 5: Control valves

1 Scope

This part of ISO 9635 specifies construction and performance requirements and test methods for control valves, intended for operation in irrigation systems with water at temperatures not exceeding 60 °C, which can contain fertilizers and other chemicals of the types and concentrations used in agriculture.

It is applicable to hydraulically-operated control irrigation valves of DN 15 (1/2 inch) diameter or greater, designed to operate in any position, from fully open to fully closed. The valves can either be directly operated (i.e. the force applied via a spring or diaphragm to the obturator), or pilot-operated (i.e. the force is applied through an adjustable pilot valve via a diaphragm).

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9635-1:2006, *Agricultural irrigation equipment — Irrigation valves — Part 1: General requirements*

ISO 9635-2:2006, *Agricultural irrigation equipment — Irrigation valves — Part 2: Isolating valves*

ISO 9644, *Agricultural irrigation equipment — Pressure losses in irrigation valves — Test method*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9635-1 and the following apply.

3.1

control valve

device intended to regulate, within specified limits, one or more functions

NOTE The functions are flow rate, water level control and pressure (upstream or downstream).

3.1.1

autonomous control valve

control valve having the integral capability of controlling the function using energy from the conveyed water by adjusting the position of the obturator

3.1.2

non-autonomous control valve

valve that requires external power in order to regulate the specified function

3.1.3

pressure-reducing valve

control valve that reduces higher inlet pressure to a lower and outlet pressure regardless of variations in the flow rate or variations of the inlet pressure

3.1.4

pressure-sustaining valve

control valve that maintains a constant pressure at the inlet regardless of variations in the flow rate or variations of the outlet pressure

3.2

flow coefficient

K_V

coefficient equal to the flow rate, in cubic metres per hour, of water at a temperature between 5 °C and 50 °C, passing through the valve and causing a loss of static head of 1 bar

NOTE 1 $Q = K_V \sqrt{\Delta p}$, where Q is the flow rate in cubic metres per hour (m³/h), and p is the pressure in kilopascals per square centimetre (kPa/cm²).

NOTE 2 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm².

NOTE 3 Adapted from EN 736-3.

3.3

maximum differential pressure

PM

maximum differential pressure of the control valve in operation

NOTE It is a value given by the manufacturer.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 9635-5:2006](https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e8f2b56542d/iso-9635-5-2006)

<https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e8f2b56542d/iso-9635-5-2006>

4 Design requirements

Control valves shall be designed in accordance with ISO 9635-1:2006, Clause 4.

Control valves designed to control pressure or level shall be tightly seated when closed (see ISO 9635-1:2006, Table G.2, Rate A).

The manufacturer shall indicate in the relevant technical documentation the working limits of the valve and any special conditions for installation and commissioning.

5 Performance requirements

All tests are to be performed on the valve as delivered to the test facility.

5.1 Mechanical strength

5.1.1 Resistance of shell and all pressure-containing components to internal pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.1.

If the manufacturer indicates that any feature of the control valve is not designed to withstand a high pressure, the technical documentation shall indicate the appropriate means to be used (e.g. isolating valves of the control system), in order to protect them during the test.

The features protected by these means shall be tested to the pressure given in ISO 9635-1:2006, 5.1.2.

5.1.2 Resistance of obturator to differential pressure

The valve shall comply with the requirement and test of ISO 9635-1:2006, 5.1.2.

If a control valve does not seat tightly, the requirement and test for the obturator shall be modified such that the differential pressure that the obturator can withstand is the lower of $(1,5 \times PM)$ bar and $(PM + 5)$ bar.

After the test, the valve shall meet the performance requirements of 5.3.

5.1.3 Resistance of valves to bending

The requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.3.

The bending moment, M , to be applied during the test shall be in accordance with Table 1, as a function of DN.

Table 1 — Bending moments

DN	Bending moment M N · m
8	610
10	615
20	640
25	670
32	730
40	825
50	525
65	700
80	750
100	1 100
125	1 600
150	2 400
200	3 600
250	5 500
300	7 500
350	9 500
400	12 000
450	14 000
500	16 500

5.1.4 Resistance of valves to operating loads

Applicable only to control valves whose main obturator can be operated manually to override the control function, the requirements and testing shall be in accordance with ISO 9635-1:2006, 5.1.4.

5.2 Watertightness

5.2.1 Watertightness of shell and all pressure-containing components

5.2.1.1 Internal pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.1.1.

5.2.1.2 External pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.1.2.

5.2.2 Seat tightness

Applicable only to control valves where seat tightness is a requirement or is claimed by the manufacturer (see Clause 4).

For level control and pressure control valves, the leakage rate shall be rate A (see ISO 9635-1:2006, Table G.2), under the conditions defined in the manufacturer's documentation. For other valves, the leakage rate shall be in accordance with the manufacturer's documentation.

Seat tightness shall be checked at the highest and lowest values of the differential pressure, as follows:

- a) $1,1 \times \text{PFA}$;
- b) the lowest differential pressure allowed by the manufacturer in his documentation.

In both cases, the requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.2.1, with the values of the differential pressure as given in a) and b), above 2006

<https://standards.iteh.ai/catalog/standards/sist/c98cfbab-8110-4a0d-a847-6e85b562a24a/iso-9635-1-2006>

5.2.3 Maximum operating torque (MOT) for operation and watertightness

Applicable only to control valves whose main obturator can be operated manually to override or limit the control function.

Requirements shall be in accordance with ISO 9635-1:2006, 5.2.3. Testing shall be in accordance with ISO 9635-2:2006, 5.2.3.

If the required MOT exceeds the limits according to this part of ISO 9635, this should be specified in the manufacturer's product literature.

5.2.4 Watertightness and air-tightness of gearboxes to external pressure

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.2.1.2.

5.3 Hydraulic characteristics

5.3.1 Flow coefficient, K_v

The manufacturer shall give the flow coefficient, K_v , obtained from the head loss curve performed in accordance with ISO 9644.

- For autonomous control valves, it shall be given in the fully open position.
- For non-autonomous control valves, the manufacturer shall give K_v as a function of the opening position of the obturator.

When measured in accordance with ISO 9644, the flow coefficient shall be within a range of $\pm 10\%$ of the value given by the manufacturer.

5.3.2 Regulation hydraulic characteristics

Applicable to both autonomous control valves and to non-autonomous control valves where the manufacturer claims specific hydraulic characteristics linked to a designated control system.

5.3.2.1 Control valves providing flow regulation function

The control valve shall be tested in accordance with Annex A. The values obtained shall be within the tolerances given in the manufacturer's documentation.

5.3.2.2 Control valves providing pressure regulation function

The control valve shall be tested in accordance with Annex B. The values obtained shall be within the tolerances given in the manufacturer's documentation.

5.3.2.3 Control valves providing level regulation function

The control valve shall be tested in accordance with Annex C. The values obtained shall be within the tolerances given in the manufacturer's documentation.

5.4 Resistance to chemicals and fertilizers

Requirements and testing shall be in accordance with ISO 9635-1:2006, 5.4.

5.5 Endurance

After completion of the endurance test according to Annex D, the valve shall pass

- the hydraulic tests in accordance with 5.3, with values within the range of $\pm 5\%$ of those measured before the endurance test, and
- the tests in accordance with 5.2.1 and 5.2.2, with the same leakage rate when the valve is claimed to be seat tight.

6 Conformity assessment

6.1 General

Requirements shall be in accordance with ISO 9635-1:2006, 6.1.

6.2 Type tests

Requirements shall be in accordance ISO 9635-1:2006, 6.2. The type tests to be performed shall be those according to Table 2, below.

6.3 Control of production process and quality system

Requirements shall be in accordance with ISO 9635-1:2006, 6.3.

NOTE The production control tests given in Table 2 are for information only.