

SLOVENSKI STANDARD kSIST FprEN 16273:2014

01-julij-2014

Železniške naprave - Zgornji ustroj - Prekovane prehodne tirnice

Railway applications - Track - Forged rail transitions

Bahnanwendungen - Oberbau - Geschmiedete Schienenübergänge

Applications ferroviaires - Voie - Rails forgés

Ta slovenski standard je istoveten z: FprEN 16273

ICS:

45.080 Tračnice in železniški deli Rails and railway

components

kSIST FprEN 16273:2014 en,fr,de

kSIST FprEN 16273:2014

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

FINAL DRAFT FprEN 16273

April 2014

ICS 93.100

English Version

Railway applications - Track - Forged rail transitions

This draft European Standard is submitted to CEN members for unique acceptance procedure. It has been drawn up by the Technical Committee CEN/TC 256.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning: This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page	
Forew	ord	4	
Introd	uction	5	
1	Scope	6	
-	•		
2	Normative references		
3	Terms and definitions	6	
4	Information to be supplied for approval	8	
4.1	By the purchaser		
4.2	By the manufacturer	8	
5	Approval of the manufacturer	8	
6	Requirements for the forging process	8	
6.1	General		
6.2	Forging parameters		
6.3 6.4	Post heat treatment Profile finishing		
6.5	Cutting to length		
6.6	Identification		
7	Procedure approval		
<i>r</i> 7.1	General		
7.2	Test specimen preparation		
7.3	Number of specimens		
7.4	Non-destructive approval tests		
7.4.1	Geometry and dimensions		
7.4.2	Visual inspection		
7.4.3	Surface finish		
7.4.4	Dye penetrant (DPI) or magnetic particle inspection (MPI)		
7.4.5 7.5	Ultrasonic testing (UT) Destructive approval tests		
7.5.1	Hardness distribution		
7.5.1 7.5.2	Switch rails: hardness distribution in the rail head		
7.6	Test report		
7.7	Validity of approval		
8	Production tests	10	
8.1	Switches	_	
8.1.1	General	_	
8.1.2	Geometry and dimensions		
8.1.3	Hardness testing		
8.2	Transition rails		
8.2.1	General	19	
8.2.2	Hardness	20	
Annex	A (informative) Ultrasonic testing	22	
A. 1	Reference line (DAC) generation – reference block	22	
A.2	Reference line (DAC) generation and acceptance criteria	23	
Anney	B (informative). Documentation of approval tosts	24	

B.1	Forged switch rails	24
B.1.1	General information	24
B.1.2	Geometry and dimensions	25
B.1.3	Dye penetrant (DPI) or magnetic particle inspection (MPI)	27
B.1.4	Ultrasonic testing (UT)	27
B.1.5	Hardness distribution on the surface	28
B.1.6	Test results of hardness distribution on the rail head	29
B.1.7	Test results of hardness distribution on the rail foot	31
B.2	Forged transition rails	32
B.2.1	General information	32
B.2.2	Geometry and dimensions	33
B.2.3	Dye penetrant (DPI) or magnetic particle inspection (MPI)	34
B.2.4	Ultrasonic testing (UT)	34
B.2.5	Hardness distribution on the surface	35
B.2.6	Test results of hardness distribution on the rail head	36
B.2.7	Test results of hardness distribution on the rail foot	36
Bibliog	graphy	38

Foreword

This document (FprEN 16273:2014) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This document is currently submitted to the Unique Acceptance Procedure.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

Introduction

This European Standard has 3 main topics:

- requirements of a forged part;
- procedure approval;
- forged rail production following approval.

This European Standard satisfies the needs of the railway authority and the manufacturer should achieve the specified requirements of this standard.

1 Scope

This European Standard specifies the requirements for the approval of a process wherein a rail of one profile has part of its length forged to a different profile, together with the requirements for subsequent forging production and product acceptance.

This European Standard applies to new railway rails according to EN 13674-1, and to switch and crossing rails used in conjunction with railway rails 46 kg/m and above according to EN 13674-2, to be welded or fish plated to make up switch rails or transition rails intended for use on railway infrastructures.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13232-5:2005+A1:2011, Railway applications - Track - Switches and crossings - Part 5: Switches

EN 13674-1, Railway applications - Track - Rail - Part 1: Vignole railway rails 46 kg/m and above

EN 13674-2, Railway applications – Track – Rail – Part 2: Switch and crossing rails used in conjunction with Vignole railway rails 46 kg/m and above

EN ISO 3452-1, Non-destructive testing - Penetrant testing - Part 1: General principles (ISO 3452-1)

EN ISO 9934 (all parts), Non-destructive testing – Magnetic particle testing (ISO 9934)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

manufacturer

company that produces forged switch and transition rails

3.2

purchaser

buyer of the forged switch or transition rails

3.3

railway infrastructure

permanent way of national or private railways

3.4

specimen

portion detached from a forged rail transition and prepared as required for testing

3.5

profile finishing

operation by which the rail or relevant part of the component is returned to required profile

Note 1 to entry: This operation can be by grinding, milling, planing or any other suitable means.