SLOVENSKI STANDARD
SIST EN ISO 10360-12:2017

01-januar-2017

Specifikacija geometrijskih veličin izdelka (GPS) - Preskusi za sprejemljivost in ponovno overjanje koordinatnih merilnih strojev (KMS) - 12. del: Gibljiva roka koordinatnih merilnih strojev (ISO 10360-12:2016)

Geometrical Product Specifications (GPS) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 12: Articulated arm coordinate measurement machines (CMM) (ISO 10360-12:2016)

Geometrische Produktspezifikation (GPS) - Annahme- und Bestätigungsprüfung für Koordinatenmesssysteme (KMS) - Teil 12: Koordinatenmessgeräte (KMG) mit Gelenkausleger (ISO 10360-12:2016)

Spécification géométrique des produits (GPS) - Essais de réception et de vérification périodique des machines à mesurer tridimensionnelles (MMT) - Partie 12: MMT à bras articulés (ISO 10360-12:2016)

Ta slovenski standard je istoveten z: **EN ISO 10360-12:2016**

ICS:

17.040.30	Merila	Measuring instruments
17.040.40	Specifikacija geometrijskih veličin izdelka (GPS)	Geometrical Product Specification (GPS)

SIST EN ISO 10360-12:2017 **en,fr,de**

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN ISO 10360-12

November 2016

ICS 17.040.30

English Version

Geometrical product specifications (GPS) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 12: Articulated arm coordinate measurement machines (CMM) (ISO 10360-12:2016)

Spécification géométrique des produits (GPS) - Essais de réception et de vérification périodique des systèmes de mesure tridimensionnels (SMT) - Partie 12: Machines à mesurer tridimensionnelles à bras articulés (MMT) (ISO 10360-12:2016)

Geometrische Produktspezifikation (GPS) - Annahme- und Bestätigungsprüfung für Koordinatenmesssysteme (KMS) - Teil 12: Koordinatenmessgeräte (KMG) mit Gelenkausleger (ISO 10360-12:2016)

This European Standard was approved by CEN on 27 August 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Ref. No. EN ISO 10360-12:2016 E

Contents

Page

European foreword

This document (EN ISO 10360-12:2016) has been prepared by Technical Committee ISO/TC 213 “Dimensional and geometrical product specifications and verification” in collaboration with Technical Committee CEN/TC 290 “Dimensional and geometrical product specification and verification” the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2017, and conflicting national standards shall be withdrawn at the latest by May 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 10360-12:2016 has been approved by CEN as EN ISO 10360-12:2016 without any modification.

INTERNATIONAL STANDARD

ISO 10360-12

First edition
2016-10-01

Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) —

Part 12: Articulated arm coordinate measurement machines (CMM)

Spécification géométrique des produits (GPS) — Essais de réception et de vérification périodique des systèmes de mesure tridimensionnels (SMT) —

Partie 12: Machines à mesurer tridimensionnelles à bras articulés (MMT)

Reference number
ISO 10360-12:2016(E)

COPYRIGHT PROTECTED DOCUMENT

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

ISO 10360 consists of the following parts, under the general title *Geometrical Product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS)*:

— *Part 1: Vocabulary*

— *Part 2: CMMs used for measuring linear dimensions*

— *Part 3: CMMs with the axis of a rotary table as the fourth axis*

— *Part 4: CMMs used in scanning measuring mode*

— *Part 5: CMMs using single and multiple stylus contacting probing system*

— *Part 6: Estimation of errors in computing of Gaussian associated features*

— *Part 7: CMMs equipped with imaging probing systems*

— *Part 8: CMMs with optical distance sensors*

— *Part 9: CMMs with multiple probing systems*

— *Part 10: Laser trackers for measuring point-to-point distances*

— *Part 12: Articulated arm coordinate measuring machines (CMM)*

Introduction

This part of ISO 10360 is a general GPS standard (see ISO 14638). For more detailed information about the relation of this part of ISO 10360 to other standards and the GPS matrix model, see Annex I.

This part of ISO 10360 is included in the ISO/GPS Masterplan given in ISO 14638, which gives an overview of the ISO/GPS system. The fundamental rules of ISO/GPS given in ISO 8015 apply to this part of ISO 10360 and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this part of ISO 10360, unless otherwise indicated.

The objective of this part of ISO 10360 is to provide a well-defined testing procedure to

— enable manufacturers of articulated arm CMMs to provide specification MPEs, and

— enable users to test articulated arm CMMs to manufacturer specifications using calibrated traceable reference artefacts.

The benefits of these tests are that the measured result has a direct traceability to the unit length, the metre, and that they give information on how the articulated arm CMM will perform on similar length measurements.

Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) —

Part 12: Articulated arm coordinate measurement machines (CMM)

1 Scope

This part of ISO 10360 specifies the acceptance tests for verifying the performance of an articulated arm CMM by measuring calibrated test lengths as stated by the manufacturer. It also specifies the reverification tests that enable the user to periodically reverify the performance of the articulated arm CMM. It applies to articulated arm CMMs using tactile probes and optionally optical distance sensors (also referred to as laser line scanners or laser line probes). Details on tests for scanner accessories are given in Annex E.

This part of ISO 10360 does not specify how often or when testing is performed, if at all, nor does it specify which party should bear the cost of testing.

This part of ISO 10360 specifies

— performance requirements that can be assigned by the manufacturer or the user of the articulated arm CMM,

— the manner of execution of the acceptance and reverification tests to demonstrate the stated requirements,

— rules for proving conformance, and

— applications for which the acceptance and reverification tests can be used.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10360-8:2013, *Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) — Part 8: CMMs with optical distance sensors*

ISO 10360-9:2013, *Geometrical product specifications (GPS) — Acceptance and reverification tests for coordinate measuring systems (CMS) — Part 9: CMMs with multiple probing systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions given in ISO 10360-1 and the following apply.

NOTE The definitions in this section are intended to concisely state the meaning of terms. For metrological characteristics that have numerical values, the complete description of the procedure and derivation of test results in Clause 6 and Annex E are to be followed in determining values.

3.1
articulated arm coordinate measuring machine
system that measures spatial coordinates and comprises

— an open chain of fixed-length segments,

— joint assemblies interconnecting the segments and the probing system and attaching them to the stationary environment, and

— a probing system at the free end of the chain

Note 1 to entry: The probing system may comprise a rigid probe or a sensing system such as a scanner.

Note 2 to entry: Rotary joint assemblies connected to the fixed-length segments are equipped with angular encoders. Cartesian coordinates of each measuring point are calculated from the measured angles and segment lengths.

3.2
joint
connection between adjacent elements of an articulated arm CMM that allows a single rotational degree of freedom between these elements

Note 1 to entry: There are two types of joints: hinge joints, which cause a hinging movement between adjacent arm segments, and swivel joints, which cause a rotary movement around the axis of the connected arm segment.

Note 2 to entry: Each joint ordinarily includes an angle measuring device (rotary encoder).

3.3
joint assembly
assembly of two or more joints between two adjacent elements of an articulated arm CMM

Note 1 to entry: Usually, a joint assembly includes at least a hinge joint and a swivel joint.

Note 2 to entry: In analogy to the human arm, the three main joint assemblies are designated the shoulder, elbow, and wrist.

Note 3 to entry: Current machines have 2 or 3 degrees of freedom each for shoulder (a, b), elbow (c, d), and wrist (e, f, g), as shown in Figure 1. Consequently, articulated arm CMMs are referred to as either six or seven axis machines.



a) With six rotary axes



b) With seven rotary axes

Figure 1 — Articulated arm CMM

3.4
measuring range
diameter of the spherical volume within which an articulated arm CMM is capable of measuring

Note 1 to entry: The measuring range is specified by the manufacturer.

Note 2 to entry: The measuring range is twice the reach of the articulated arm. However, some of the regions that can be reached by the articulated arm may not be within the measuring volume.

3.5
measuring volume
region in space over which the manufacturer specifies the performance of the articulated arm CMM

Note 1 to entry: The measuring volume is restricted by inaccessible zones specified by the manufacturer. For example, there may be an inaccessible zone close to the vertical main axis.

Note 2 to entry: Manufacturers may specify more than one measuring volume for a machine, each measuring volume having a separate performance specification.

Note 3 to entry: Because of the possibility of binding up a joint when adjacent arm segments are brought close together, the size of the measuring volume may depend on the direction of the probe stylus in relation to the outside of the measuring volume or inaccessible zones within the measuring volume. The manufacturer may specify one or more measuring volumes according to the direction of the probe stylus.

3.6
useful arm length
half the measuring range

3.7
coefficient of thermal expansion
CTE
α
linear thermal expansion coefficient of a material at 20 °C

Note 1 to entry: The above definition for CTE does not imply that a user is required to make measurements at 20 °C.