

SLOVENSKI STANDARD
oSIST prEN ISO 19901-7:2018
01-januar-2018

Industrija za predelavo nafte in zemeljskega plina - Posebne zahteve za naftne ploščadi - 7. del: Sistemi za vzdrževanje postaj na plavajočih strukturah in premičnih enotah (ISO/DIS 19901-7:2017)

Petroleum and natural gas industries - Specific requirements for offshore structures - Part 7: Stationkeeping systems for floating offshore structures and mobile offshore units (ISO/DIS 19901-7:2017)

Erdöl- und Erdgasindustrie - Spezielle Anforderungen an Offshore-Anlagen - Teil 7: Betriebssysteme für das Positionshalten schwimmender Anlagen und mobiler Offshore-Einheiten (ISO/DIS 19901-7:2017)

<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-31409a21210a/iso-19901-7-2018>

Industries du pétrole et du gaz naturel - Exigences spécifiques relatives aux structures en mer - Partie 7: Systèmes de maintien en position des structures en mer flottantes et des unités mobiles en mer (ISO/DIS 19901-7:2017)

Ta slovenski standard je istoveten z: prEN ISO 19901-7

ICS:

75.180.10	Oprema za raziskovanje, vrtanje in odkopavanje	Exploratory, drilling and extraction equipment
-----------	--	--

oSIST prEN ISO 19901-7:2018

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 19901-7:2018](https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018)

<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 19901-7

ISO/TC 67/SC 7

Secretariat: BSI

Voting begins on:
2017-11-06Voting terminates on:
2018-01-29

Petroleum and natural gas industries — Specific requirements for offshore structures —

Part 7:

Stationkeeping systems for floating offshore structures and mobile offshore units

*Industries du pétrole et du gaz naturel — Exigences spécifiques relatives aux structures en mer —**Partie 7: Systèmes de maintien en position des structures en mer flottantes et des unités mobiles en mer*

ICS: 75.180.10

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN ISO 19901-7:2018](https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018)<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 19901-7:2017(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN ISO 19901-7:2018](https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018)

<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

1	Scope	8
2	Normative references	9
3	Terms and definitions	9
4	Symbols and abbreviated terms	15
4.1	Symbols	15
4.2	Abbreviated terms	16
5	Overall considerations	18
5.1	General requirements	18
5.2	Functional requirements	18
5.3	Safety requirements	18
5.4	Planning requirements	19
5.5	Rules and regulations	20
5.6	Independent verification	20
5.7	Analytical tools	20
6	Design requirements	20
6.1	Exposure levels	20
6.2	Limit states	21
6.3	Defining design situations	21
6.4	Design situations	21
7	Actions	25
7.1	General	25
7.2	Site-specific data requirements	25
7.3	Environmental actions on mooring lines	27
7.4	Indirect actions	27
8	Mooring analysis	30
8.1	Basic considerations	30
8.2	Actions considerations	31
8.3	Floating structure response	32
8.4	Floating structure offset	37
8.5	Mooring line response	38
8.6	Line tension	38
8.7	Line length and geometry constraints	39
8.8	Anchor forces	40
8.9	Typical mooring configuration analysis and assessment	40
8.10	Thruster-assisted moorings	41
8.11	Transient analysis of floating structure motions	43
9	Fatigue analysis	44
9.1	Basic considerations	44
9.2	Tension-tension (T-T) fatigue	45
9.3	Bending-Tension (B-T) fatigue	53
9.4	Other types of fatigue loading	55
10	Design criteria	56
10.1	Floating structure offset	56
10.2	Line tension limit	56
10.3	Grounded line length	56
10.4	Anchoring systems	57
10.5	Mooring line fatigue safety factor	59
10.6	Corrosion and wear	59
10.7	Clearances	60

STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 19901-7:2017(E)

10.8	Supporting structures	60
10.9	Installation considerations	61
11	Mooring hardware.....	61
11.1	Mooring line components	61
11.2	Winching equipment.....	63
11.3	Winches should meet the provisions specified in internationally recognized design standards, see A.11.2 and the requirements of a RCS.Monitoring equipment	63
12	In-service inspection, monitoring and maintenance.....	64
12.1	General.....	64
12.2	Mobile moorings	64
12.3	Permanent moorings.....	65
13	Dynamic positioning system	67
13.1	Basic considerations.....	67
13.2	Design and analysis	68
13.3	Design, test and maintenance	68
13.4	Operating personnel.....	69
13.5	Determination of stationkeeping capability	69
14	Synthetic fibre rope mooring.....	69
14.1	Basic considerations.....	69
14.2	Fibre rope mooring analysis.....	70
14.3	Fatigue analysis	70
14.4	Creep analysis.....	71
14.5	Design criteria	71
14.6	Model testing.....	72
Annex A	(informative) Additional information and guidance.....	73
A.1	Scope	73
A.2	Normative references	82
A.3	Terms and definitions	82
A.4	Symbols and abbreviated terms	83
A.5	Overall considerations	83
A.6	Design requirements	87
A.7	Actions.....	90
A.8	Mooring analysis.....	100
A.9	Fatigue analysis	125
A.10	Design criteria.....	132
A.11	Mooring hardware.....	161
A.12	In-service inspection, monitoring and maintenance.....	172
A.13	Dynamic positioning system	174
A.14	Synthetic fibre rope mooring.....	177
Annex B	(informative) Regional information	182
B.1	Introduction	182
B.2	Offshore Norway	182
B.3	Canada	186
B.4	Russia	187

iTeh STANDARD PREVIEW
(standards.iteh.ai)

oSIST prEN ISO 19901-7:2018
<https://standards.iteh.ai/catalog/standards/sist/5c99a834-56ad-4054-824e-615c1ba9fca2/osist-pr-en-iso-19901-7-2018>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/XXX
<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-61feba9fca2/iso-19901-7-2018>

This second/third/... edition cancels and replaces the first/second/... edition (), [clause(s) / subclause(s) / table(s) / figure(s) / annex(es)] of which [has / have] been technically revised.

ISO XXXX consists of the following parts. [Add information as necessary.]

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19901-7 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 7, *Offshore structures*.

This third edition cancels and replaces the second edition (ISO 19901-7:2013), which has been technically revised.

ISO/DIS 19901-7:2017(E)

This third edition of ISO 19901-7 includes several changes. The largest changes are the deletion of informative sections related to geotechnical design of anchors to incorporate the same in 19901-4 and the inclusion of OPB fatigue guidance.

ISO 19901 consists of the following parts, under the general title *Petroleum and natural gas industries — Specific requirements for offshore structures*:

- *Part 1: Metocean design and operating considerations*
- *Part 2: Seismic design procedures and criteria*
- *Part 3: Topsides structure*
- *Part 4: Geotechnical and foundation design considerations*
- *Part 5: Weight control during engineering and construction*
- *Part 6: Marine operations*
- *Part 7: Stationkeeping systems for floating offshore structures and mobile offshore units*
- *Part 8: Marine soil investigations*
- *Part 9: Structural integrity management (under preparation).*

ISO 19901 is one of a series of International Standards for offshore structures. The full series consists of the following International Standards:

- ISO 19900, *Petroleum and natural gas industries — General requirements for offshore structures*
- ISO 19901 (all parts), *Petroleum and natural gas industries — Specific requirements for offshore structures*
<https://standards.iteh.ai/catalog/standards/sist/5e99a834-56ad-4054-824e-615efba9fca2/osist-pren-iso-19901-7-2018>
- ISO 19902, *Petroleum and natural gas industries — Fixed steel offshore structures*
- ISO 19903, *Petroleum and natural gas industries — Fixed concrete offshore structures*
- ISO 19904-1, *Petroleum and natural gas industries — Floating offshore structures — Part 1: Monohulls, semi-submersibles and spars*
- ISO 19905 (all parts), *Petroleum and natural gas industries — Site-specific assessment of mobile offshore units*
- ISO 19906, *Petroleum and natural gas industries — Arctic offshore structures*

Introduction

The series of International Standards applicable to types of offshore structure, ISO 19900 to ISO 19906, constitutes a common basis covering those aspects that address design requirements and assessments of all offshore structures used by the petroleum, petrochemical and natural gas industries worldwide. Through their application, the intention is to achieve reliability levels appropriate for manned and unmanned offshore structures, whatever type of structure and nature or combination of materials used.

It is important to recognize that structural integrity is an overall concept comprising models for describing actions, structural analyses, design rules, safety elements, workmanship, quality control procedures and national requirements, all of which are mutually dependent. The modification of one aspect of design in isolation can disturb the balance of reliability inherent in the overall concept or structural system. The implications involved in modifications therefore need to be considered in relation to the overall reliability of all offshore structural systems.

The series of International Standards applicable to types of offshore structure is intended to provide wide latitude in the choice of structural configurations, materials and techniques without hindering innovation. Sound engineering judgement is therefore necessary in the use of these International Standards.

This part of ISO 19901 was developed in response to the worldwide offshore industry's demand for a coherent and consistent definition of methodologies to analyse, design and evaluate stationkeeping systems used for floating production and/or storage platforms of various types (e.g. semi-submersibles, spar platforms, ship-shaped structures) and to assess site-specific applications of mobile offshore units (such as mobile offshore drilling units and flotels) and construction units (such as heavy lift vessels and pipelay units).

Stationkeeping is a generic term covering systems for keeping a floating structure, which is under the constant influence of external actions, at a pre-defined location and/or heading with limited excursions. Stationkeeping systems resist external actions by means of any of the following:

- mooring systems (e.g. spread moorings or single point moorings);
- dynamic positioning systems (generally consisting of thrusters);
- a combination of mooring system and thrusters (thruster assisted)

The external actions generally consist of wind, wave, current and ice actions on the floating structure, mooring and/or risers.

Some background to, and guidance on, the use of this part of ISO 19901 is provided in informative Annex A. The clause numbering in Annex A is the same as in the normative text to facilitate cross-referencing.

Regional information, where available, is provided in informative Annex B.

Petroleum and natural gas industries — Specific requirements for offshore structures —

Part 7:

Stationkeeping systems for floating offshore structures and mobile offshore units

1 Scope

This part of ISO 19901 specifies methodologies for

- a) the design, analysis and evaluation of stationkeeping systems for floating structures used by the oil and gas industries to support any combination of:
 - 1) production,
 - 2) storage,
 - 3) offloading,
 - 4) drilling and well intervention.
- b) the assessment of stationkeeping systems for site-specific applications of mobile offshore units and construction units.

Most stationkeeping systems used with the class of floating structures covered by a) are termed “permanent mooring systems”, for which this part of ISO 19901 is applicable to all aspects of the life cycle and includes requirements relating to the manufacture of mooring components, as well as considerations for in-service inspections. Most stationkeeping systems used with mobile offshore units, the class covered by b), are termed “mobile mooring systems”. Throughout this part of ISO 19901, the term “floating structure”, sometimes shortened to “structure”, is used as a generic term to indicate any member of the two classes, a) and b).

This part of ISO 19901 is applicable to the following types of stationkeeping systems, which are either covered directly in this part of ISO 19901 or through reference to other guidelines:

- spread moorings (catenary, taut-line and semi-taut-line moorings);
- single point moorings, anchored by spread mooring arrangements;
- dynamic positioning systems;
- thruster-assisted moorings.

Descriptions of the characteristics and of typical components of these systems are given in Annex A.

The requirements of this part of ISO 19901 mainly address spread mooring systems and single point mooring systems with mooring lines composed of steel chain and wire rope. This part of ISO 19901 also provides guidance on the application of the methodology to synthetic fibre rope mooring systems, and includes additional requirements related to the unique properties of synthetic fibre ropes.

This part of ISO 19901 is applicable to single anchor leg moorings (SALMs) and other single point mooring systems (e.g. tower soft yoke systems) only to the extent to which the requirements are relevant.

This part of ISO 19901 is not applicable to the vertical moorings of tension leg platforms (TLPs).

The methodology described in this part of ISO 19901 identifies a set of coherent analysis tools that, combined with an understanding of the site-specific metocean conditions, the characteristics of the floating structure under consideration, and other factors, can be used to determine the adequacy of the stationkeeping system to meet the functional requirements of this part of ISO 19901.

NOTE For moorings deployed in ice-prone environments, additional requirements are given in ISO 19906. << Sec 13.7 of 19906 >>

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19900, *Petroleum and natural gas industries — General requirements for offshore structures*

ISO 19901-1, *Petroleum and natural gas industries — Specific requirements for offshore structures — Part 1: Metocean design and operating considerations*

ISO 19901-4, *Petroleum and natural gas industries — Specific requirements for offshore structures — Part 4: Geotechnical and foundation design considerations*

ISO 19901-6, *Petroleum and natural gas industries — Specific requirements for offshore structures — Part 6: Marine operations*

ISO 19901-8, *Petroleum and natural gas industries — Specific requirements for offshore structures — Part 8: Marine soil investigations.* ISO 19904-1, *Petroleum and natural gas industries — Floating offshore structures — Part 1: Monohulls, semi-submersibles and spars*

ISO 19905-3, *Petroleum and natural gas industries — Site-specific assessment of mobile offshore units — Part 3: Floating units* 1)

ISO 19906, *Petroleum and natural gas industries – Arctic Offshore Structures*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 action

external load applied to the structure (direct action) or an imposed deformation or acceleration (indirect action)

EXAMPLE An imposed deformation can be caused by fabrication tolerances, settlement, temperature change or moisture variation.

NOTE An earthquake typically generates imposed accelerations.

[ISO 19900:2013]

3.2 action effect

effect of actions on structural components

[ISO 19900:2013]

1) Under preparation.

ISO/DIS 19901-7:2017(E)

EXAMPLE Internal forces, moments, stresses, strains, rigid body motions or elastic deformations.

3.3**catenary mooring**

mooring system where the restoring action is provided by the distributed weight of mooring lines

[ISO 19900:2013]

3.4**characteristic value**

value assigned to a basic variable, an action or a resistance from which the design value can be found by the application of a partial factor

NOTE 1 The value usually has a prescribed probability of not being violated which, in the case of an action, will normally relate to a reference period.

NOTE 2 Adapted from ISO 19900:2013, definition 2.7.

3.5**common mode/common cause failure:**

failure of similar components on different mooring legs resulting from the same direct cause, occurring within a relatively short time, where these failures are not consequences of another

3.6**damage event**

event-driven damage to mooring components including physical damage, overload, excessive bending, etc., often experienced during the installation phase.

3.7**degradation mechanisms**

time-based physical or chemical mechanisms or processes by which mooring components degrade. Examples are corrosion, wear, fatigue, etc.

3.8**design criteria**

quantitative formulations that describe the conditions to be fulfilled for each limit state

[ISO 19900:2013]

3.9**design service life**

assumed period for which a structure or a structural component is to be used for its intended purpose with anticipated maintenance, but without substantial repair being necessary

NOTE Adapted from ISO 19900:2013, definition 2.12.

3.10**design situation**

set of physical conditions during a certain reference period for which the design will demonstrate that relevant limit states are not exceeded

NOTE Adapted from ISO 19900:2013, definition 2.13.

3.11**disconnectable floating structure**

floating structure capable of discontinuing production and rapidly disconnecting from its ancillary components such as risers, moorings, and/or well systems in response to the occurrence or to the detection of a threshold event.

3.12**dynamic action**

action that induces acceleration of a structure or a structural component of a magnitude sufficient to require specific consideration

3.13**dynamic positioning****DP**

stationkeeping technique consisting primarily of a system of automatically controlled on-board thrusters, which generate appropriate thrust vectors to counter the mean and slowly varying induced actions

3.14**expected value**

first-order statistical moment of the probability density function for the considered variable that, in the case of a time-dependent parameter, can be associated with a specific reference period

3.15**failure causes**

includes the initiators, defects, processes and mechanisms generating damage or degradation which are the basic reasons for failure, and may be introduced into the mooring system across all phases of the mooring system lifecycle from design to operation.

3.16**failure mode**

the manifestation of loss of functionality of a mooring component and it is the manner by which failure is observed

3.17**fit-for-purpose****fitness-for-purpose**

meeting the intent of an International Standard although not meeting specific provisions of that International Standard in local areas, such that failure in these areas will not cause unacceptable risk to life-safety or the environment

[ISO 19900:2013]

3.18**floating structure**

structure where the full weight is supported by buoyancy

[ISO 19900:2013]

NOTE The full weight includes lightship weight, mooring system pre-tension, riser pre-tension, operating weight, etc.

3.19**limit state**

state beyond which the structure no longer fulfils the relevant design criteria

[ISO 19900:2013]

3.20**maintenance**

set of activities performed during the operating life of a structure to ensure it is fit-for-purpose

3.21**minimum breaking strength****MBS**

RCS certified strength of a chain, wire rope, fibre rope or accessories

ISO/DIS 19901-7:2017(E)**3.22****mobile mooring system**

mooring system, generally retrievable, intended for deployment at a specific location for a short-term operation, such as those for mobile offshore units (MOUs)

NOTE Some components of a mobile mooring system might not be retrievable and should be designed following the requirements of permanent mooring system.

3.23**mobile offshore drilling unit****MODU**

structure capable of engaging in drilling and well intervention operations for exploration or exploitation of subsea petroleum resources

3.24**mobile offshore unit****MOU**

structure intended to be frequently relocated to perform a particular function

[ISO 19900:2002]

EXAMPLE Pipelaying vessel or barge, offshore construction structure, accommodation structure (floatel), service structure, or mobile offshore drilling units.

3.25**mooring component**

general class of component used in the mooring of floating structures

EXAMPLE Chain, steel wire rope, synthetic fibre rope, clump weight, buoy, winch/windlass, fairlead or anchor.

3.26**owner**

representative of the company or companies which own a development, who can be the operator on behalf of co-licensees

3.27**permanent mooring system**

mooring system normally used to moor floating structures deployed for long-term operations, such as those for a floating production system (FPS)

3.28**proximity**

closeness in distance

NOTE 1 Mooring systems are considered to be in proximity to a surface installation (or facility) if any part of the other installation lies within a contour described by the set of offsets coinciding with each line reaching 100 % MBS in the intact or redundancy check condition, whichever is larger.

NOTE 2 Mooring systems are considered to be in proximity to a sea floor installation (or facility) if any part of the other installation lies within a polygon formed by the anchor locations.

3.29**RCS****recognized classification society**

member of the international association of classification societies (IACS), with recognized and relevant competence and experience in floating structures, and with established rules and procedures for classification/certification of installations used in petroleum-related activities

3.30**resistance**

capacity of a structure, a component or a cross-section of a component to withstand action effects without exceeding a limit state

NOTE This definition is at variance with that specified in ISO 19900:2002.

3.31**return period**

average period between occurrences of an event or of a particular value being exceeded

NOTE The offshore industry commonly uses a return period measured in years for environmental events. The return period is equal to the reciprocal of the annual probability of exceedance of the event.

[ISO 19901-1:2005]

3.32**riser**

pipings connecting the process facilities or drilling equipment on the floating structure with the subsea facilities or pipelines, or reservoir

NOTE 1 Possible functions include drilling and well intervention, production, injection, subsea systems control and export of produced fluids.

NOTE 2 Adapted from ISO 19900:2002, definition 2.29.

3.33**semi-submersible**

floating structure normally consisting of a deck structure with a number of widely spaced, large cross-section, supporting columns connected to submerged pontoons

NOTE Pontoon/column geometry is usually chosen to minimize global motions in a broad range of wave frequencies.

3.34**serviceability**

ability of a structure or structural component to perform adequately for normal functional use

3.35**significant value**

statistical measure of a zero-mean random variable equal to twice the standard deviation of the variable

3.36**single point mooring**

mooring system that allows the floating structure to which it is connected to vary its heading (weathervane)

EXAMPLE One example of a single point mooring is a turret mooring system where a number of mooring lines are attached to a turret, which includes bearings to allow the structure to rotate.

3.37**ship-shaped structure**

monohull floating structure having a geometry similar to that of ocean-going ships

3.38**spar platform**

deep-draught, small water-plane area floating structure

3.39**splash zone**

part of a structure that is intermittently exposed to air and immersed in the sea