
**Information technology — Real-time
locating system (RTLS) device
performance test methods — Test
methods for air interface communication
at 2,4 GHz**

*Technologies de l'information — Méthodes d'essai des performances
du dispositif des systèmes de localisation en temps réel (RTLS) —
Méthodes d'essai pour la communication d'interface d'air à 2,4 GHz*
(standards.iteh.ai)

ISO/IEC TR 24770:2008

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC TR 24770:2008](https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008)

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Abbreviated terms	2
4 General	2
4.1 Performance requirements	2
4.2 Default conditions applicable to the test methods	3
5 Performance tests for ISO/IEC 24730-2	3
5.1 System locate performance	3
5.2 Tests for mandatory DSSS tag to reader air interface	6
5.3 Test set up	6
5.4 Tests for optional tag to exciter air interface	7
5.5 Tests for optional tag to programmer air interfaces	8

(standards.iteh.ai)

[ISO/IEC TR 24770:2008](https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008)

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In exceptional circumstances, the joint technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the joint technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TR 24770, which is a Technical Report of type 3, was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

Introduction

ISO/IEC 24730 defines the air interfaces and an application programming interface for Real Time Locating Systems (RTLS) devices used in asset management applications.

This Technical Report provides test methods for measuring performance of equipment compliant with ISO/IEC 24730-2.

ISO/IEC TR 24769 contains all measurements required to be made on a product in order to establish whether it conforms to the corresponding part of ISO/IEC 24730.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC TR 24770:2008](https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008)

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC TR 24770:2008

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>

Information technology — Real-time locating system (RTLS) device performance test methods — Test methods for air interface communication at 2,4 GHz

1 Scope

This Technical Report defines the test methods for determining the performance characteristics of 2,4 GHz real time locating system (RTLS) equipment including tags, readers, and excitors which are applicable to the selection of equipment that conforms to ISO/IEC 24730-2 for specific applications. This Technical Report does not apply to the testing in relation to regulatory or similar requirements.

The RTLS equipment performance parameters included in this Technical Report include the mandatory direct sequence spread spectrum (DSSS) 2,4 GHz radio frequency beacon link between tags and readers. It includes the optional on-off keyed/frequency shift keyed (OOK/FSK) short range radio frequency link between tags and programmers. It also includes the optional magnetic air-interface between excitors and tags and between programmers and tags.

Unless otherwise specified, the tests in this Technical Report apply exclusively to RTLS equipment defined in ISO/IEC 24730-2.

2 Normative references

[ISO/IEC TR 24770:2008](https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008)

standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 24730-2:2006, *Information technology — Real-time locating systems (RTLS) — Part 2: 2,4 GHz air interface protocol*

ISO/IEC 24769, *Information technology — Real-time locating system (RTLS) device conformance test methods — Test methods for air interface communication at 2,4 GHz*

ISO/IEC 19762-1, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 1: General terms relating to AIDC*

ISO/IEC 19762-3, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 3: Radio frequency identification (RFID)*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 19762-1 and ISO/IEC 19762-3 apply.

3.2 Abbreviated terms

ARB	arbitrary waveform generator
BPSK	binary phase shift keying
DSSS	direct sequence spread spectrum
DUT	device under test
EIRP	effective isotropic radiated power
EVM	error vector magnitude
FSK	frequency shift keying
OOK	on-off keying
PPM	parts per million
RBW	resolution bandwidth
RTLS	real time location system
TIB	timed interval blink
VBW	video bandwidth

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4 General

[ISO/IEC TR 24770:2008](https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008)

<https://standards.iteh.ai/catalog/standards/sist/81b9f97a-575a-4513-889f-ba88c0eae058/iso-iec-tr-24770-2008>

4.1 Performance requirements

This Technical Report specifies a series of tests to determine the performance characteristics of RTLS equipment relative to the ISO/IEC 24730-2 air interfaces. The results of these tests can be used to determine the suitability of RTLS equipment for applications.

4.1.1 Location accuracy

The primary function of RTLS equipment is to locate tags within the area covered by the readers. Location accuracy determines the primary performance criteria of an RTLS. Location accuracy can be characterized by comparing the system's calculated location for a given set of tags to the actual location of the tags. The system must be able to locate tags to within the applications allowable error.

4.1.2 Tag capacity

A RTLS must typically locate a large number of tags. The number of tag blinks per second that can be processed and located through the readers can be used to determine a systems tag capacity. The system must be able to provide location information for an applications peak tag blink density.

4.1.3 Location latency

The latency between when the tag blink is transmitted and when the RTLS equipment can provide accurate location information determines the suitability of the equipment for the application.

4.1.4 Tag orientation

The ability of an RTLS to provide real time location information should be independent of the orientation of the tag. The location reported by the RTLS should not change as the tag is rotated in any orientation relative to the readers.

4.1.5 System range and packet error rates

The range of the tag-reader 2,4 GHz DSSS link determines the reader density requirements and also effects system capacity. The packet error rate will determine how often the equipment can successfully provide accurate location information for the tag.

The range, packet error rate, and orientation requirements of the optional air interfaces between the tags and excitors, and between the tags and programmers, determine the usability of the system in meeting the applications requirements.

4.2 Default conditions applicable to the test methods

These conditions apply to all tests.

4.2.1 Test environment

Testing shall take place in an environment typical to that of the desired application. Testing can be performed indoors or outdoors with temperature and humidity profiles similar to that expected in the desired application. The RF noise floor at the test location should also represent typical conditions expected within the desired application.

4.2.2 Default tolerance

Unless otherwise specified, a default tolerance of $\pm 5\%$ shall be applied to the quantity values given to specify the characteristics of the test equipment and the test method procedures.

4.2.3 System Logging

The RTLS should provide sufficient data logging to allow determination of the number of packets received and sent, but this is not absolutely required.

5 Performance tests for ISO/IEC 24730-2

5.1 System locate performance

This subclause includes tests for location performance.

5.1.1 Test objective

The objective of this test is evaluate the system locate performance characteristics of the ISO/IEC 24730-2 equipment.

5.1.2 Test set up

The readers shall be connected to omni-directional antennas. It is preferred that the RTLS locate performance characteristics be evaluated with the system installed as it would for the desired application. If that is not possible, then the equipment shall be configured as shown in Figure 1, with four readers at the corners of a square measuring 300 m across the diagonal (outdoor applications) or 200 m across the diagonal (indoor applications). In addition to standalone tags, several tags mounted on the application's locatable assets (or items of comparable size and composition) shall be used to evaluate locate performance.