

SLOVENSKI STANDARD kSIST FprEN 12480:2014

01-oktober-2014

Plinomeri - Plinomeri z rotacijskimi bati

Gas meters - Rotary displacement gas meters

Gaszähler - Drehkolbengaszähler

Compteurs de gaz - Compteurs de gaz à déplacement rotatif

Ta slovenski standard je istoveten z: FprEN 12480

ICS:

91.140.40 Sistemi za oskrbo s plinom Gas supply systems

kSIST FprEN 12480:2014 en,fr,de

kSIST FprEN 12480:2014

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

FINAL DRAFT FprEN 12480

July 2014

ICS 91.140.40

Will supersede EN 12480:2002

English Version

Gas meters - Rotary displacement gas meters

Compteurs de gaz - Compteurs de gaz à déplacement rotatif

Gaszähler - Drehkolbengaszähler

This draft European Standard is submitted to CEN members for unique acceptance procedure. It has been drawn up by the Technical Committee CEN/TC 237.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning: This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page	
Forew	Foreword5		
1	Scope	6	
2	Normative references	6	
3	Terms and definitions	11	
3.1	Definitions		
3.2	Symbols and abbreviations		
4	Operating range	14	
4 .1	General		
4.2	Flowrate range (conformity/individual)		
4.3	Operating pressure range (conformity/individual)		
4.4	Operating temperature range (conformity/individual)	15	
5	Metrological performance	15	
5.1	General		
5.2	Error of indication (conformity/individual)	15	
5.2.1	Requirements		
5.2.2	Test		
5.3	Pressure loss (conformity/individual)		
5.3.1	Requirements		
5.3.2 5.4	Test		
5.4 5.4.1	Metrological repeatability (conformity)		
5.4.1	Test		
5.5	Operating pressure (conformity/individual)		
5.5.1	General		
5.5.2	Requirements		
5.5.3	Pattern approval test		
5.5.4	Individual test		
5.6	Temperature ranges (conformity)		
5.6.1	General	_	
5.6.2	Minimum operational temperature		
5.6.3 5.6.4	Maximum operational temperature Storage temperature range		
5.6. 4 5.7	Condensing ambient conditions (conformity)		
5.7.1	Requirements		
5.7.2	Test		
5.8	Bidirectional meters (conformity)		
5.8.1	Requirements		
5.8.2	Test		
5.9	Influence of oil filling (conformity)		
5.9.1	Requirements		
5.9.2	Tests	20	
6	Design and manufacturing		
6.1	General (conformity/individual)		
6.2	Material		
6.2.1	General (conformity)		
6.2.2 6.2.3	Design methodResistance to external corrosion		
6.2.4	Penetration resistance		
J.Z.4	1 611611 811011 16313181106		

6.2.5	Adhesion of the protective coating	
6.2.6	Materials for pressurized parts	
6.3	Robustness	
6.3.1	Resistance to internal pressure (conformity/individual)	
6.3.2	Fire resistance (conformity)	
6.3.3	External leak tightness (conformity/individual)	
6.3.4	Overload (conformity)	
6.3.5	Bending and torsional moment (conformity)	
6.4	Transportation and storage (conformity/individual)	
6.4.1	Protection against foreign matter	
6.4.2	Protection against damage	
6.5	Connections (conformity)	
6.6	Pressure and temperature tappings (conformity)	
6.6.1	Pressure tappings	
6.6.2	Temperature tappings	
6.7	Manufacturing	30
7	Meter output (conformity)	31
7.1	Index	
7.1.1	General	31
7.1.2	Magnetic coupling	31
7.1.3	Mechanical indicating device	31
7.1.4	Test element	
7.2	Index window	33
7.2.1	Requirements	33
7.2.2	Tests	33
7.3	Output drive shafts	34
7.3.1	Requirements	34
7.3.2	Tests	36
7.4	Pulse generators	36
7.4.1	General	36
7.4.2	Specification for low frequency pulse generator	37
7.4.3	Specification for high frequency pulse generator	37
7.4.4	Electrical Connection	37
8	Durability (conformity)	38
8.1	Requirements	
8.2	Tests	
_		
9	Marking, labelling and packaging (conformity/individual)	
9.1	General	
9.2	Direction of flow	
9.3	Pressure tappings	
9.4	Durability and legibility of marking	
9.4.1	Requirements	
9.4.2	Test	39
10	Documentation (conformity)	39
10.1	General	
10.2	Documentation related to the manufacturer's tests	
10.3	Declaration of conformity	
10.4	Instruction manual	
Annex	A (normative) Pattern approval	41
Annex	B (normative) Individual meter testing	43
	. ,	
Annex	C (normative) Resistance to high temperature (optional)	44
C.1	Requirements	44

C.2	Test	44
C.2.1	Apparatus	44
C.2.2	Test conditions	44
C.2.3	Test procedure	45
C.3	Marking	46
Annex	D (normative) Compliance evaluation for gas meters	47
D.1	General	47
D.2	Quality Management System	47
D.2.1	General	47
D.2.2	Procedures	47
D.2.3	Manufacturer's compliance evaluation	48
D.2.4	Issue of the certificate of compliance	48
Annex	E (normative) Non-destructive testing (NDT)	49
Annex	F (normative) Materials for pressurized parts	51
Annex	G (normative) Additional tests for meters to be used in open locations	62
G.1	General	62
G.2	Weathering	62
G.2.1	Requirements	62
G.2.2	Test	62
Annex	H (normative) Meter family	63
H.1	Definition of meter family	63
H.2	Criteria for grouping meters together in order to form a family	63
Annex	ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2004/22 Measuring Instruments Directive	64
Annex	ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC	68
Riblioc	ıranhv	70

Foreword

This document (FprEN 12480:2014) has been prepared by Technical Committee CEN/TC 237 "Gas meters", the secretariat of which is held by BSI.

This document is currently submitted to the Unique Acceptance Procedure.

This document will supersede EN 12480:2002.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directives.

For relationship with EU Directives, see informative Annex ZA and ZB, which are integral parts of this document.

Note: Due to fact that the Framework Partnership Agreement between the Commission and CEN and CENELEC is not signed yet, there are currently no New Approach Consultants in place for 2014. Therefore the provisions of CEN-CENELEC Guide 15 cannot be met.

This shall not prevent the processing of draft standards nor the offering of harmonized standards to the Commission. In particular, draft standards can be sent to vote without Consultant assessment.

This note will be removed from the Foreword of the finalized publication.

1 Scope

This European Standard specifies ranges, construction, performances, output characteristics and testing of rotary displacement gas meters (hereinafter referred to as RD meters or simply meters) for gas volume measurement.

This European Standard applies to rotary displacement gas meters used to measure the volume of fuel gases of at least the 1st, 2nd and 3rd gas families, the composition of which is specified in EN 437:2003+A1:2009, at a maximum working pressure up to and including 20 bar over an ambient and gas temperature range of at least -10 °C to +40 °C.

This European Standard applies to meters that are installed in locations with vibration and shocks of low significance and in

 closed locations (indoor or outdoor with protection as specified by the manufacturer) with condensing or with non-condensing humidity

or, if specified by the manufacturer,

open locations (outdoor without any covering) with condensing humidity or with non-condensing humidity;

Unless otherwise specified in this standard:

- all pressures used are gauge;
- all influence quantities, except the one under test, are kept relatively constant at their reference value.

This European Standard also applies to meters with a maximum allowable pressure PS and the volume V of less than 6 000 bar \cdot litres or with a product of PS and DN of less than 3 000 bar.

NOTE These limits are the same as in EU directive 97/23/EC.

This European Standard can be used for both pattern approval and individual meter testing. Cross-reference tables are given in:

- Annex A for the tests that need to be undertaken for pattern approval;
- Annex B for individual meter testing.

Some parts of this standard cover meters with mechanical index only.

The risk philosophy adopted in this standard is based on the analysis of hazards on account of pressure. The standard applies principles to eliminate or reduce hazards. Where these hazards cannot be eliminated appropriate protection measures are specified.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 485-2:2013, Aluminium and aluminium alloys - Sheet, strip and plate

EN 586-2:1994, Aluminium and aluminium alloys – Forged parts - Part 2: mechanical characteristics and other required characteristics