
**Graphical symbols for diagrams —
Part 1:
General information and indexes**

Symboles graphiques pour schémas —

Partie 1: Informations générales et index

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 14617-1:2005

<https://standards.iteh.ai/catalog/standards/sist/20f0cdde-c164-4730-9006-440545f55524/iso-14617-1-2005>



Reference number
ISO 14617-1:2005(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 14617-1:2005

<https://standards.iteh.ai/catalog/standards/sist/20f0cdde-c164-4730-9006-440545f55524/iso-14617-1-2005>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Arrangement of ISO 14617	2
5 Registration numbers	3
6 Presentation of graphical symbols	4
7 Application rules and examples	5
8 Use of graphical symbols	5
9 Lettering	5
10 Indexes	6
Annex A (informative) Alphabetical index	7
Annex B (informative) Index of graphical symbol registration numbers	34
Annex C (informative) Cross-reference index	41
Bibliography	55

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14617-1 was prepared by Technical Committee ISO/TC 10, *Technical product documentation*, Subcommittee SC 10, *Process plant documentation and tpd-symbols*.

This second edition cancels and replaces the first edition (ISO 14617-1:2002), of which it constitutes a minor revision.

ISO 14617 consists of the following parts, under the general title *Graphical symbols for diagrams*:

- *Part 1: General information and indexes*
- *Part 2: Symbols having general application*
- *Part 3: Connections and related devices*
- *Part 4: Actuators and related devices*
- *Part 5: Measurement and control devices*
- *Part 6: Measurement and control functions*
- *Part 7: Basic mechanical components*
- *Part 8: Valves and dampers*
- *Part 9: Pumps, compressors and fans*
- *Part 10: Fluid power converters*
- *Part 11: Devices for heat transfer and heat engines*
- *Part 12: Devices for separating, purification and mixing*
- *Part 13: Devices for material processing*
- *Part 14: Devices for transport and handling of material*
- *Part 15: Installation diagrams and network maps*

Introduction

The purpose of ISO 14617 in its final form is the creation of a library of harmonized graphical symbols for diagrams used in technical applications. This work has been, and will be, performed in close cooperation between ISO and IEC. The ultimate result is intended to be published as a standard common to ISO and IEC, which their technical committees responsible for specific application fields can use in preparing International Standards and manuals.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14617-1:2005

<https://standards.iteh.ai/catalog/standards/sist/20f0cdde-c164-4730-9006-440545f55524/iso-14617-1-2005>

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO 14617-1:2005

<https://standards.iteh.ai/catalog/standards/sist/20f0cdde-c164-4730-9006-440545f55524/iso-14617-1-2005>

Graphical symbols for diagrams —

Part 1: General information and indexes

1 Scope

This part of ISO 14617 serves as an introduction to all the other parts. In particular, it gives information on the creation and use of registration numbers for identifying graphical symbols used in diagrams, rules for the presentation and application of these symbols, and examples of their use and application. It includes three indexes: an alphabetical index and an index of registration numbers — both concerned uniquely with ISO 14617 — and an index of cross-references to related items found in other International Standards.

For the fundamental rules of creation and application of graphical symbols in diagrams, see ISO 81714-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 81714-1:1999, *Design of graphical symbols for use in the technical documentation of products — Part 1: Basic rules*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE The list has been restricted to terms whose meaning is not obvious and which have not been defined elsewhere in an International Standard, or which have been defined in various ways in different standards. In preparing these definitions, ISO and IEC standards on terminology have been consulted; see the references in parentheses. However, most of the definitions in those standards were prepared by different technical committees within a restricted scope. This means that many terms so defined have to be given more general or neutral definitions when applied in the context of graphical symbols.

3.1

function

activity proper to anything, mode of action by which it fulfils its purpose

EXAMPLE To measure, to control, to indicate.

3.2

product

thing produced by natural process or manufacture; result

EXAMPLE An element, a component or a device.

3.3

component

constituent part of equipment that cannot be physically divided into smaller parts without losing its character

[IEC 60050-131]

3.4

device

assembly of components to perform a required function

EXAMPLE An actuating device, a centrifuge.

[IEC 60050-151]

3.5

element

part of a component

EXAMPLE A filter element in a filter, a contact in an electromechanical relay.

3.6

graphical symbol

visually perceptible figure used to transmit information independently of language

[ISO 81714-1]

3.7

terminal line

line of a graphical symbol ending at a connect node

NOTE A connect node is a location on a graphical symbol intended for connection (ISO 81714-1).

[ISO 81714-1]

3.8

connecting line

graphical symbol representing a functional connection, a mechanical link, a pipeline, a duct, or an electric connection

[IEC 61082-1]

4 Arrangement of ISO 14617

4.1 Domains of application

The complete ISO 14617 is to consist of a number of other parts in addition to those listed in the Foreword. Among the parts under preparation are ISO 14617-13, concerned with graphical symbols for material processing, and ISO 14617-14, concerned with the symbols representing devices for transport and handling of material.

This part of ISO 14617 is an introduction to all the other parts. ISO 14617-2 to ISO 14617-6 cover graphical symbols for use in most technical fields. ISO 14617-7 to ISO 14617-12 cover those for use in all fields except the electrotechnical. ISO 14617-15 comprises graphical symbols for use in installation diagrams and on network maps for pipelines, ducts and electric connections.

4.2 Subdivision of parts

Each part of ISO 14617 is divided into clauses that each deal with graphical symbols for a particular group of generic products or functions. When appropriate, clauses are given subclauses, as follows using the example of Clause 7 from ISO 14617-2:

Clause 7	Directions
Subclause 7.1	Symbols of basic nature
Subclause 7.2	Application rules for the symbols in 7.1
Subclause 7.3	Symbols giving supplementary information
Subclause 7.4	Application rules for the symbols in 7.3
Subclause 7.5	Application examples

Where certain subclauses are further subdivided, this has been done along the following lines. Take, for example, 4.3 in ISO 14617-2:

Subclause 4.3	Symbols giving supplementary information
Subclause 4.3.1	Input and output labels
Subclause 4.3.2	General functions
Subclause 4.3.3	Mathematical operations
Subclause 4.3.4	Change of discrete state at specified values of a characteristic quantity
Subclause 4.3.5	Logic negation, logic inversion, inputs and outputs for auxiliary power supply

When a cross-reference is made to a particular graphical symbol or application rule or application example, its location is given within parentheses after the registration number of the symbol, rule or example.

EXAMPLE 1 “See R101 (4.2.1)” directs the reader to application rule R101, located in subclause 4.2.1.

When cross-referencing to another part, the part number is also included.

EXAMPLE 2 A cross-reference to symbol 142 in ISO 14617-2 is given as “See 142 (2-4.3.2.28)”.

5 Registration numbers

IMPORTANT — A direct relationship does not necessarily exist between graphical symbols, application rules and application examples using registration numbers that share the same numerals. For example, while graphical symbol 101 correlates to both application rule R101 and application example X101, it correlates as well to application examples X102 to X114; whereas symbol 114, to take just one other example, is unrelated to R114 and X114.

5.1 Graphical symbol

Each graphical symbol is assigned a unique registration number. In principle, this number is arbitrarily chosen. No information can be derived from it. The registration number will remain unchanged throughout the lifetime of the corresponding graphical symbol, including in future revisions of this publication. If a graphical symbol is changed in the future, the registration number shall be supplemented with one or more characters. If the graphical symbol is substantially changed, it shall instead be given a new registration number.

5.2 Application rule

Each application rule has a registration number in the same way as the graphical symbols, except that the registration number starts with the letter R (e.g. R101).

5.3 Application example

Each application example has a registration number in the same way as the graphical symbols, except that the registration number starts with the letter X (e.g. X101).

6 Presentation of graphical symbols

6.1 General

ISO 14617 establishes graphical symbols to be used in diagrams such as overview diagrams, flow diagrams and circuit diagrams.

6.2 Graphical symbols of same shape but different meaning

Graphical symbols having the same shape but different meanings have different registration numbers. This implies that it is possible to distinguish between same-shape graphical symbols in a CAD (computer-aided design) system, provided that each symbol has been recalled from a CAD library using the appropriate registration number.

For a person reading a diagram, the intended meaning can normally be recognized by the context of the diagram. When this is not possible, graphical symbols having the same shape shall be provided with supplementary information. For examples, see the symbols for connections in ISO 14617-3 and the rules for adding symbols giving supplementary information such as application rule R402 in the same part.

6.3 Different forms of graphical symbols

In some cases, different forms of a graphical symbol can occur. These different forms are given separate registration numbers. The primary reason for having two or more forms for the same symbolization is that they convey differing amounts of information.

Symbols having different forms and differing amounts of information (e.g. those for use in overview diagrams and those for use in circuit diagrams) are marked Form 1, Form 2, etc. This marking is also used in some cases where the different forms contain the same amount of information, but where more than one form is justified because of different application methods in the rules for preparing diagrams.

6.4 Dimensions of graphical symbols

The graphical symbols in ISO 14617 have been designed in accordance with the rules given in ISO 81714-1. The module size $M = 2,5 \text{ mm}$ has been used. For small graphical symbols, the symbol is shown double its normal size, applying the same module and the same line width. Such symbols are marked "200 %".

For the auxiliary grid system defined in ISO 81714-1, the module $0,25 M$ has been used.

6.5 Descriptions

In those cases where ISO and IEC have the same term for different items, the term has been provided with ISO and IEC superscripts, for example, line^{ISO} and line^{IEC}.

7 Application rules and examples

The application rules give information on how to design composite symbols and how to apply the graphical symbols in a diagram. The application examples are to be regarded as guidelines.

In order to facilitate their use, the application examples are accompanied by information on which graphical symbols have been used to compose the examples shown.

EXAMPLE “101, 123” in 2-4.5.8 signifies that the example X108 is built up from graphical symbols 101 and 123.

8 Use of graphical symbols

8.1 Choice of graphical symbols

Rules for the choice of graphical symbols are given in the standards for the preparation of diagrams.

8.2 Dimensions of graphical symbols


Symbols may be increased in size, for example, in order to allow all terminals to be represented. They may also be reduced in size. In both cases, the original line width shall be maintained.

Further rules for the use of graphical symbol sizes and line widths are given in the standards dealing with the preparation of diagrams.

8.3 Auxiliary lines

In some cases, the symbol has been shown together with auxiliary lines in order to indicate its correct location in relation to other symbols or the recommended location of connecting lines. Such auxiliary lines are not part of the symbol and are shown dotted (very short dashes).

EXAMPLE 1 Symbol 181 — logic negation — shown at an outline of a symbol indicated by a dotted rectangle.



EXAMPLE 2 An auxiliary line indicating the correct location of the symbol for a connection to a two-way valve, symbol 2101.



8.4 Variants of graphical symbols

The rules for diagram layout give the possibility of arranging circuits horizontally or vertically, and of arranging circuits for feedback and similar signals in a direction opposite to the normal one. For that purpose, different variants of the graphical symbols exist. The rules for the creation of the different variants are given in ISO 81714-1.

9 Lettering

For lettering, see ISO 81714-1.

10 Indexes

The alphabetic index given in Annex A can be used to find a graphical symbol for a certain component, device or function wherever the meaning (description) is known. This index also covers the application examples.

The registration number index given in Annex B can be used to locate a graphical symbol whose registration number is already known.

The cross-reference index given in Annex C is intended as a link between the registration numbers and the corresponding descriptions in other, existing ISO and IEC standards.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 14617-1:2005

<https://standards.iteh.ai/catalog/standards/sist/20f0cdde-c164-4730-9006-440545f55524/iso-14617-1-2005>

Annex A (informative)

Alphabetical index

This alphabetical index can be used to find a graphical symbol for a certain component, device, or function if its meaning (description) is already known. The index also covers the application examples.

Description	Registration number	Location (Part-subclause)	Description	Registration number	Location (Part-subclause)
Above ground hydrant	3122	15-7.2	– Manual ~ in the form of removable handle	686	4-5.1.6
Access chamber			– Manual ~ in the form of treadle	690	4-5.1.10
– Circular-shaped ~, inspection well	3087	15-5.1.7	– Manual ~ operated by pulling	683	4-5.1.3
Acoustic signalling device	866	5-10.1.4	– Manual ~ operated by pushing	682	4-5.1.2
Active area			– Manual ~ operated by pushing and pulling	684	4-5.1.4
– Double-acting hydraulic actuator with different ~s	721	4-6.1.11	– Manual ~ operated by turning	685	4-5.1.5
– Double-acting pneumatic actuator with different ~s	722	4-6.1.12	– Manual ~ with special shape for safety purpose	691	4-5.1.11
Actuating device	741	4-7.1.1	– operating when actual temperature is less than set value	X717	4-6.5.5
– of double-acting diaphragm actuator type	X743	4-7.5.3	– Single-acting diaphragm ~	725	4-6.1.15
– of electric motor type	X2131	8-4.5.4.1		X2136	8-4.5.4.6
– of pneumatic motor type	X742	4-7.5.2		X2138	8-4.5.4.8
– of single-acting fluid cylinder type	X741	4-7.5.1		X2152	8-5.5.2
– operated by pneumatic power stored inside actuator	X747	4-7.5.7	– Single-acting hydraulic ~	717	4-6.1.7
– operating with touch effect	X744	4-7.5.4	– Single-acting pneumatic ~	718	4-6.1.8
– Spring-operated ~ with manual spring charging	X745	4-7.5.5	Actuators		
– Spring-operated ~ with spring charging by electric motor	X746	4-7.5.6	– Automatic ~	–	4-6
– Spring-loaded ~	X2005	7-4.5.5	See also <i>Hydraulic actuators, Pneumatic actuators, Manually operated actuators</i>		
Actuating devices	–	4-7	Additional simplifications	–	3-9
Actuator			Adjustability	201	2-5.1.1
– Cam-operated ~	714	4-6.1.4			8-4.3.1.3
– Device for restricted access to ~	692	4-5.1.12			8-5.3.3
– Double-acting diaphragm ~	726	4-6.1.16			9-4.3.1
– Double-acting ~ of fluid cylinder type	X2107	8-4.5.1.7			10-4.3.1
– Double-acting hydraulic ~	719	4-6.1.9			10-5.3.1
– Double-acting, hydraulic ~ with different active areas	721	4-6.1.11			14-4.3.1
– Double-acting, pneumatic ~	720	4-6.1.10	– Non-linear ~	202	2-5.1.2
– Double-acting pneumatic ~ with different active areas	722	4-6.1.12	– Pre-set ~	203	2-5.1.3
– Flow-target-operated ~	716	4-6.1.6			8-4.3.1.4
		7-4.1.5			8-5.3.4
		4-6.1.5			10-4.3.2
		7-4.1.4	– Resistor with continuous ~	X203	2-5.5.3
– in the form of a double-acting fluid cylinder	724	4-6.1.14	– Resistor with electric-motor-operated ~	X205	2-5.5.5
	X713	4-6.5.3	– Resistor with manual ~	X204	2-5.5.4
	X2107	8-4.5.1.7	– Resistor with pre-set ~	X201	2-5.5.1
			– Resistor with ~ in five steps	X202	2-5.5.2
– in the form of a hydraulic motor with alternative directions of flow	2407	4-6.1.17	See also <i>Variability</i>		
– in the form of a pneumatic motor	X712	4-6.5.2	Adjustable capacity		
– in the form of a pneumatic motor with alternative directions of flow	2408	4-6.1.18	– Hydraulic pump with ~	X2401	10-4.5.1
– in the form of a single-acting fluid cylinder	723	4-6.1.13		X2402	10-4.5.2
– Manual ~	681	4-5.1.1	– Liquid pump with ~	X2301	9-4.5.1
– Manual ~ in the form of key	687	4-5.1.7		X2302	9-4.5.2
– Manual ~ in the form of lever	688	4-5.1.8	– Over-centre hydraulic pump with ~	X2407	10-4.5.7
– Manual ~ in the form of pedal	689	4-5.1.9	Adjustable gain		
			– Amplifier with ~	X207	2-5.5.7
			Adjustable hydraulic rotary torque converter	X2431	10-5.5.1
			Adjustable restrictor (valve)	X2211	8-6.5.3.1
				X2212	8-6.5.3.2

Description	Registration number	Location (Part-subclause)
– with adjustable flow in one direction and restricted flow in the other	X2213	8-6.5.3.3
Adjustable speed		
– Hydraulic motor with ~	X2415	10-4.5.15
– Hydraulic pump driven by shaft with ~	X2404	10-4.5.4
– Liquid pump driven by shaft with ~	X2303	9-4.5.3
Adsorption pump	2335	9-5.1.5
	2336	9-5.1.6
Affected area	2177	8-6.3.7
Agglomeration		
– Size enlarging by sintering, ~ coagulation, or flocculation	2809	13-4.3.9
Air conditioner	X3152	15-9.5.2
– for pneumatic systems	2691	12-7.1.1
Air conditioning	3151	15-9.3.2
Air fin cooler with induced draft	X2505	11-4.5.5
Air lubricator	X2674	12-6.5.4
Alarm	3066	15-4.3.16
– High pressure ~	X1062	6-7.5.22
– Indicating and transmitting of level, registering, and ~	X1065	6-7.5.25
– Light ~	3067	15-4.3.17
Air conditioner for pneumatic systems	2691	12-7.1.1
Air fin cooler with induced draft	X2505	11-4.5.5
Air lubricator	X2674	12-6.5.4
Alarm		
– High pressure ~	X1062	6-7.5.22
– Indicating and transmitting of level, registering, and ~	X1065	6-7.5.25
Alarming	1051	6-7.3.11
All-or-nothing relay		
– Electromechanical ~ with some contacts delayed	X653	4-4.5.3
– Electromechanical ~, the whole relay delayed when coil is energized	X654	4-4.5.4
Alternative directions		
– Direction of propagation, energy, or signal flow, ~ (half-duplex)	250	2-7.1.8 6-4.3.3
– Gas pump, compressor, fan with ~ of flow	2304	9-4.1.4
– Hydraulic pump/motor with ~ of flow	2413	10-4.1.13
– Hydraulic motor with ~ of flow	2407	10-4.1.7
– Hydraulic pump with ~ of flow	2403	10-4.1.3
– in general, except for energy and signal flow	245	2-7.1.5 14-4.3.3
	246	2-7.1.6
– Limited circular motion in ~	X253	2-7.5.8
– Liquid pump with ~ of flow	2303	9-4.1.3
– of circular motion	256	2-7.1.14
– of propagation, energy, or signal flow (half-duplex)	250	2-7.1.8
– Pneumatic motor with ~ of flow	2408	10-4.1.8
– Pneumatic pump, compressor with ~ of flow	2404	10-4.1.4
– Pneumatic pump/motor with ~ of flow	2414	10-4.1.14
– Rectilinear motion in ~ with intermediate dwell	X256	2-7.5.11
Amplification	115	2-4.3.2.5 6-7.3.3.1
Amplifier	891	5-12.1.1
	892	5-12.1.2
– Differential ~	X910	5-12.5.10
– Summing ~	X909	5-12.5.9
– with adjustable gain	X207	2-5.5.7
– with return channel	893	5-12.1.3
	894	5-12.1.4

Description	Registration number	Location (Part-subclause)
– with the gain compensated for frequency variations	X110	2-4.5.10
Amplifying equipment		
– Enclosure with ~	X3081	15-5.5.1
Analogue signal	234	2-6.1.14 6-4.3.5
Analogue signal processing		
– Devices for ~	–	5-12
Anchor point	3004	15-4.1.4
AND-elements		
– Component consisting of two identical ~	X346	2-11.5.3
	X347	2-11.5.4
AND-function (Logic ~)	142	2-4.3.2.28 6-7.3.3.12
Angle		
– Measuring transducer for ~	X769	5-4.5.19
Angled globe type spring-loaded vacuum valve operating when pressure is lower than set value	X2125	8-4.5.3.5
Angled two-way valve	2102	8-4.1.2
Annealing		
– Heat treatment, for example, ~ or tempering	2807	13-4.3.7
Anti-clockwise rotation	X250	2-7.5.5
	X251	2-7.5.6
	X2416	10-4.5.16
	X2417	10-4.5.17
	X2419	10-4.5.19
	X2422	10-4.5.22
	X2423	10-4.5.23
Anti-siphon trap	2038	7-5.1.12 15-10.3.5
Approximately constant force, motion, or flow	223	2-6.1.3
Area		
– Affected ~	2177	8-6.3.7
Areas		
– Double-acting hydraulic actuator with different active ~	721	4-6.1.11
– Double-acting pneumatic actuator with different active ~	722	4-6.1.12
Arrestor		
– Flame ~	2036	7-5.1.10
Automatic actuators	–	4-6
Automatic closing		
– Quick-release coupling element of female type with ~	567	3-8.1.6
– Quick-release coupling element of male type with ~	566	3-8.1.5
– Quick-release coupling element which fits into another coupling element of the same type with ~	568	3-8.1.7
Automatic operation	144	2-4.3.2.30
– of final controlling element	1022	6-6.1.2
– of pump	X1031	6-6.5.11
– of valve controlled by analogue signal	X1028	6-6.5.8
	X1035	6-6.5.15
– of valve with infinite number of stable positions	X1034	6-6.5.14
	X1036	6-6.5.16
– of valve with automatic return to closed position	X1026	6-6.5.6
– of valve with automatic return to open position	X1027	6-6.5.7
– of valve with automatic return towards closed position	X1029	6-6.5.9
– of valve with automatic return towards open position	X1030	6-6.5.10

Description	Registration number	Location (Part-subclause)
– of valve with two stable positions, open and closed	X1032	6-6.5.12
	X1033	6-6.5.13
Automatic return		
– Control-switch operated by turning with ~ from two extreme positions	X686	4-5.5.6
– device	654	4-4.1.9
		6-6.3.4
– Directional control valve with ~	X688	4-5.5.8
– Single-acting hydraulic cylinder with ~	X2442	10-6.5.2
– Manually operated control-switch with ~	X685	4-5.5.5
– Manually operated valve with ~	X1022	6-6.5.2
– Valve with diaphragm actuator and ~	X2101	8-4.5.1.1
Auxiliary location		
– in central control room	1102	6-7.3.4.2
– in local control room or on local control panel	1104	6-7.3.4.4
Auxiliary power supply		
– Input or output for ~	183	2-4.3.5.3
Averaging		
– Device for ~	X903	5-12.5.3
– function component	X105	2-4.5.5
Back-pressure control valve, self-operating	X2132	8-4.5.4.2
Back-up		
– function	6-9	
– Temperature indication and control performed by computer with ~ by discrete device	X1081	6-9.5.1
Bag	2068	7-6.1.8
Bag filter	X2606	12-4.5.6
Ball	2014	7-4.1.20
	2015	7-4.1.21
Ball type	2122	8-4.3.2.2
– control valve, operated by diaphragm actuator or by manual actuator	X2138	8-4.5.4.8
– Spring-loaded ~ non-return valve	X2115	8-4.5.2.5
– three-way valve with double-acting cylinder actuator	X2107	8-4.5.1.7
Barrel	2067	7-6.1.7
Basic elements (for actuators and actuating devices)	–	4-4
Bath scrubber	X2622	12-4.5.22
Beam		
– Non-guided, electromagnetic ~	411	3-4.1.7
Bearing	2006	7-4.1.12
Bed filter		
– of fixed type	X2609	12-4.5.9
– of fluidized type	X2610	12-4.5.10
Bed filter element		
– of fixed type	2603	12-4.1.4
– of fluidized type	2604	12-4.1.5
Bellows		
– Expansion ~	533	3-7.1.3
Belt conveyor		
– Mobile ~ with scraper flights and adjustable elevation	X3804	14-4.5.4
– Uni-directional driven ~ by electric motor	X3801	14-4.5.1
– with adjustable length	X3806	14-4.5.6
Belt filter	X2608	12-4.5.8
Belt type	3821	14-4.3.6
– with scraper flights	3822	14-4.3.7
Bending		
– Material forming by ~ or folding	2804	13-4.3.4
Belt filter	X2608	12-4.5.8

Description	Registration number	Location (Part-subclause)
Bias	162	2-4.3.3.2
		6-7.3.3.16
– Device for ~	X904	5-12.5.4
– function component	X103	2-4.5.3
Bidirectional information bus type	443	3-4.3.7
Bidirectional, simultaneously	247	14-4.3.4
Bimetal	327	2-10.1.5
Binary logic elements	–	5-11
Binary logic functions	–	6-8
Binary signal	236	2-6.1.16
		6-4.3.7
Biologic filter	X2634	12-4.5.34
Biologic type	2623	12-4.3.11
Bistable element		
– RS~	X112	2-4.5.12
Bleed line	422	3-4.1.10
Blind	2043	7-5.1.17
– flange pair	517	3-6.1.7
– Spectacle ~ in closed position	2044	7-5.1.18
– Spectacle ~ in open position	2045	7-5.1.19
Blocking device	664	4-4.1.20
		6-6.3.9
Blocking of electric current	3063	15-4.3.13
– Device for ~ in a pipeline	X3011	15-4.5.11
Boiler	2531	11-7.1.1
– feed-water vessel with deaerator	X2071	7-6.5.11
– of electrode type	X2533	11-7.5.3
– of fired type	X2531	11-7.5.1
– with dome	2532	11-7.1.2
– with superheater	X2534	11-7.5.4
Boilers	–	11-7
Bore		
– Reduced ~	2130	8-4.3.2.10
Boring, drilling	2815	13-4.3.15
Boss with		
– insertion pipe	803	5-5.1.3
– Temperature sensor in a ~ well	X801	5-5.5.1
– well	801	5-5.1.1
Brake		
– applied in unactuated state	2012	4-4.1.5
		7-4.1.18
– disengaged in unactuated state	2011	4-4.1.4
		7-4.1.17
– Solenoid-operated ~ applied at no-voltage	X652	4-4.5.2
Branches		
– Connection with n parallel identical ~	601	3-9.1.1
– Eight connections, four of them branching	X602	3-9.5.2
– Three parallel identical ~	X601	3-9.5.1
Branching of a bundle	X607	3-9.5.7
	X608	3-9.5.8
Brazed joint	515	3-6.1.5
Breaking		
– Size reduction by crushing, ~, or pulverisation	2808	13-4.3.8
Buffer head	2007	7-4.1.13
Buffer		
– Hydraulic ~	X2007	7-4.5.7
– Spring equipped ~	X2006	7-4.5.6
Bulldozer	3867	14-7.1.7
Burglar detector	X3141	15-8.5.11
Buffer head	2007	7-4.1.13
Bundle		
– Branching of a ~	X607	3-9.5.7
	X608	3-9.5.8
– Exit from or entrance into a ~	603	3-9.1.3
Bunker	2064	7-6.1.4
– Open ~	X2074	7-6.5.14