



# SLOVENSKI STANDARD

## SIST ISO 12151-1:2014

01-marec-2014

Nadomešča:  
SIST ISO 12151-1:2000

---

**Fluidna tehnika - Hidravlika - Spoji za hidravliko in za splošno uporabo - Cevne armature - 1. del: Cevne armature s tesnilko O po ISO 8434-3**

Connections for hydraulic fluid power and general use - Hose fittings - Part 1: Hose fittings with ISO 8434-3 O-ring face seal ends

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Raccordements pour transmissions hydrauliques et applications générales -- Raccords de flexible -- Partie 1: Raccords de flexible avec embouts à joints faciaux toriques conformes à l'ISO 8434-3

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>

**Ta slovenski standard je istoveten z: ISO 12151-1:2010**

---

**ICS:**

23.040.70	Gumene cevi in armature	Hoses and hose assemblies
23.100.40	Cevna napeljava in sklopke	Piping and couplings

**SIST ISO 12151-1:2014**

**en,fr**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 12151-1:2014

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>

# INTERNATIONAL STANDARD

**ISO**  
**12151-1**

Second edition  
2010-06-15

---

---

## Connections for hydraulic fluid power and general use — Hose fittings —

### Part 1: Hose fittings with ISO 8434-3 O-ring face seal ends

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

*Raccordements pour transmissions hydrauliques et applications  
générales — Raccords de flexible —*

*Partie 1: Raccords de flexible avec embouts à joints faciaux toriques  
conformes à l'ISO 8434-3*

SIST ISO 12151-1:2014

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>



Reference number  
ISO 12151-1:2010(E)

© ISO 2010

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 12151-1:2014](https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword .....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	2
3 Terms and definitions .....	2
4 Performance requirements .....	2
5 Designation of hose fittings .....	3
6 Design .....	3
7 Manufacture .....	4
8 Assembly instructions .....	4
9 Procurement information .....	5
10 Marking .....	5
11 Identification statement (reference to this part of ISO 12151) .....	5
Annex A (informative) Illustrations of applications for short, medium and long ISO 12151-1 hose fittings .....	14
Bibliography .....	15

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12151-1 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 4, *Connectors and similar products and components*.

This second edition cancels and replaces the first edition (ISO 12151-1:1999), which has been technically revised.

ISO 12151 consists of the following parts, under the general title *Connections for hydraulic fluid power and general use — Hose fittings*:

- Part 1: Hose fittings with ISO 8434-3 O-ring face seal ends
- Part 2: Hose fittings with ISO 8434-1 and ISO 8434-4 24° cone connector ends with O-rings
- Part 3: Hose fittings with ISO 6162-1 or ISO 6162-2 flange ends
- Part 4: Hose fittings with ISO 6149 metric stud ends
- Part 5: Hose fittings with ISO 8434-2 37° flared ends
- Part 6: Hose fittings with ISO 8434-6 60° cone ends

## Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. In general applications, the fluid can be conveyed under pressure.

Components are connected through their ports by stud ends on fluid conductor connectors to tubes/pipes or to hose fittings and hoses.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 12151-1:2014](https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014)

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 12151-1:2014

<https://standards.iteh.ai/catalog/standards/sist/04f6cac7-2521-4ecd-a633-5063f097b120/sist-iso-12151-1-2014>



# Connections for hydraulic fluid power and general use — Hose fittings —

## Part 1: Hose fittings with ISO 8434-3 O-ring face seal ends


### 1 Scope

This part of ISO 12151 specifies the general and dimensional requirements for the design and performance of hose fittings with O-ring face seal ends in accordance with ISO 8434-3, made of carbon steel, for nominal hose inside diameters of 6,3 mm to 38 mm, inclusive, in accordance with ISO 4397.

NOTE 1 Materials other than carbon steel can be supplied as agreed between the manufacturer and user.

NOTE 2 For hose fittings used in hydraulic and pneumatic braking systems on road vehicles (as defined in the scope of ISO/TC 22, *Road vehicles*), see ISO 4038, ISO 4039-1 and ISO 4039-2.

These hose fittings (see Figure 1 for a typical example) are for use in hydraulic fluid power systems with hose that meets the requirements of the respective hose standards and in general applications with suitable hose.



#### Key

- |                                      |   |
|--------------------------------------|---|
| 1 hose fitting                       | 4 adapter in accordance with ISO 8434-3 |
| 2 port in accordance with ISO 6149-1 | 5 nut                                   |
| 3 O-ring seal                        | 6 O-ring seal                           |

Figure 1 — Typical example of a hose-fitting connection with O-ring face seal end

## ISO 12151-1:2010(E)

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 68-2, *ISO general-purpose screw threads — Basic profile — Part 2: Inch screw threads*

ISO 263, *ISO inch screw threads — General plan and selection for screws, bolts and nuts — Diameter range 0,06 to 6 in*

ISO 4397, *Fluid power systems and components — Connectors and associated components — Nominal outside diameters of tubes and nominal hose sizes*

ISO 4759-1:2000, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 5864:1993, *ISO inch screw threads — Allowances and tolerances*

ISO 6149-1, *Connections for hydraulic fluid power and general use — Ports and stud ends with ISO 261 metric threads and O-ring sealing — Part 1: Ports with truncated housing for O-ring seal*

ISO 6605, *Hydraulic fluid power — Hoses and hose assemblies — Test methods*

ISO 8434-3:2005, *Metallic tube connections for fluid power and general use — Part 3: O-ring face seal connectors*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 19879, *Metallic tube connections for fluid power and general use — Test methods for hydraulic fluid power connections*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 apply.

## 4 Performance requirements

**4.1** Hose assemblies shall meet the performance requirements specified in the appropriate hose specification without leakage or failure.

**4.2** The working pressure of the hose assembly shall be the lower of the pressures given for its size in ISO 8434-3 and in the relevant hose specification.

**4.3** The hose-fitting portion of a hose assembly shall be tested in accordance with ISO 19879, and the complete hose assembly shall be tested in accordance with ISO 6605.

## 5 Designation of hose fittings

**5.1** Hose fittings shall be designated by an alphanumeric code to facilitate ordering. They shall be designated by ISO 12151-1, followed by a spaced hyphen, then the connection end type, shape and style letter symbols (see 5.4), followed by another spaced hyphen, the O-ring face seal end size (nominal tube outside diameter in accordance with ISO 8434-3) and the hose size (nominal hose inside diameter in accordance with ISO 4397), each separated by a multiplication symbol ( $\times$ ).

**EXAMPLE** A swivel hose fitting with a 45° medium elbow, for 12 mm OD tubing and 12,5 mm nominal ID hose is designated as follows:

**ISO 12151-1 - SWE45M - 12  $\times$  12,5**

**5.2** The letter symbol designation of the hose fitting shall consist of the connection end type, immediately followed by the shape of the fitting and the nut style, where applicable.

**5.3** Tube ends are assumed to be male and thus it is not necessary to include them in the code. However, if another end is involved, it shall be designated.

**5.4** The letter symbols as given in Table 1 shall be used.

**Table 1 — Letter symbols used in the designation of hose fittings**

Connection end type		Symbol
Swivel	—	SW
Shape	Straight	S
	90° elbow, short	ES
	90° elbow, medium	EM
	90° elbow, long	EL
	45° elbow, short	E45S
	45° elbow, medium	E45M
Nut sealing surface	Sealing surface not exposed	A
	Sealing surface exposed	B

## 6 Design

**6.1** Hose fitting dimensions shown in Figures 2 to 5 shall conform to those given in Tables 2 to 5 and to the relevant dimensions in ISO 8434-3.

**6.2** Hexagonal tolerances across flats shall be in accordance with ISO 4759-1:2000, product grade C. Minimum across-corner hexagonal dimensions are 1,092 times the nominal width across flats. The minimum side flat is 0,43 times the nominal width across flats.

**6.3** Angular tolerances on axes of ends of elbows shall be  $\pm 3^\circ$  for all sizes.

**6.4** Details of contour shall be as chosen by the manufacturer, provided that the dimensions given in Tables 2 to 5 are maintained.

**6.5** The screw threads on the connection ends of the hose fittings shall be ISO inch screw threads in accordance with ISO 263 and ISO 8434-3:2005, Annex A, except for 1-14 UNS classes 2A and 2B threads, whose dimensions are also found in ISO 8434-3:2005, Annex A.