



**VHF air-ground and air-air Digital Link (VDL)
Mode 4 radio equipment;
Technical characteristics and methods of measurement
for aeronautical mobile (airborne) equipment;
Part 4: Point-to-point functions**

Reference

REN/AERO-00019-4

Keywords

aeronautical, digital, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD
(Standards.iteh.fr)
Full standard:
<http://standards.etsi.org/catalog/standards/sist/302-842-4-v1.3.1-2015-04>

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
Introduction	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.1.1 Basic reference model definitions.....	10
3.1.2 Service conventions definitions	10
3.1.3 General definitions.....	10
3.1.4 Definition of bit order.....	10
3.2 Abbreviations	10
4 General description of VDL Mode 4 mobile station point-to-point services.....	12
4.1 General	12
4.2 Data Link Service (DLS) and Link Management Entity (LME)	12
4.2.1 General.....	12
4.2.2 DLS timers.....	15
4.2.3 DLS counters	16
4.2.4 Toggle bit (T).....	16
4.2.5 State variables (T_t and T_r)	16
4.2.6 Initialize Bit (IB).....	16
4.2.7 More bit (M)	17
4.2.8 Priority (pr)	17
4.2.9 Message fragmentation and concatenation	17
4.2.10 DLS procedures	17
4.2.10.1 Selection of DLS procedures.....	17
4.2.10.2 Short transmission procedures	17
4.2.10.3 Long transmission procedures.....	18
4.2.11 Linking transmissions	20
4.2.11.1 Types of linking	20
4.2.11.2 Combined RTS / DATA DLPDUs.....	20
4.2.11.3 Combined DATA / ACK DLPDUs.....	20
4.2.11.4 Combined RTS / ACK DLPDUs	20
4.2.11.5 Combined CTS / ACK DLPDUs	20
4.2.12 Ground-air link management	20
4.2.13 Air-air link management	21
4.3 Additional VSS services.....	21
5 Minimum performance specification under standard test conditions.....	21
5.1 DLS sublayer.....	21
5.1.1 General.....	21
5.1.1.1 Services	21
5.1.1.2 Data transfer	22
5.1.1.3 DATA DLPDU duplicate suppression and sequencing	22
5.1.1.4 Error detection.....	22
5.1.1.5 Station identification	22
5.1.1.6 Broadcast addressing.....	22
5.1.1.7 DLS Priority	23
5.1.1.8 DLS Link control DLPDUs	23
5.1.2 DLS protocol specification	23
5.1.2.1 State variables	23
5.1.2.2 DLS burst formats	23

5.1.3	DLS system parameters	27
5.1.4	DLS procedures	29
5.1.4.1	Setting of re-transmission parameter.....	29
5.1.4.2	Selection of user data packet for transmission	29
5.1.4.3	Selection of transmission procedures	31
5.1.4.4	Short transmission procedures	31
5.1.4.5	Long transmission procedures.....	32
5.1.4.6	No link with sender	34
5.1.4.7	User data packet reception	35
5.1.4.8	Receipt of ACK DLPDU	35
5.1.4.9	Link reset	36
5.1.4.10	Linking DLS DLPDU transmissions.....	37
5.1.4.11	CTRL DLPDU	38
5.1.4.12	Procedures for air-air communication.....	38
5.2	Link management entity sublayer.....	38
5.2.1	Services.....	38
5.2.1.1	General.....	38
5.2.1.2	Link provision	39
5.2.1.3	Link change notifications	39
5.2.1.4	CTRL DLPDU	39
5.2.1.5	Broadcast link management burst	40
5.2.2	Control (CTRL) parameter formats	40
5.2.2.1	Encoding	40
5.2.2.2	General purpose information parameters	40
5.2.2.3	Mobile-initiated information parameters.....	44
5.2.2.4	Ground-initiated modification parameters	45
5.2.2.5	Ground-initiated information parameters	48
5.2.3	LME timers and parameters.....	50
5.2.3.1	General	50
5.2.3.2	Timer TL1 (maximum link overlap time)	51
5.2.3.3	Parameters TL2 (link initialization time)	51
5.2.3.4	Timer TL4 (leave generation latency).....	51
5.2.4	CTRL DLPDU types and procedures	51
5.2.5	CTRL transmission procedures.....	55
5.2.5.1	Frequency management procedures	55
5.2.5.2	Link connectivity procedures	55
5.2.5.3	Ground Station Identification.....	55
5.2.5.4	Link establishment	56
5.2.5.5	Mobile-initiated handoff	57
5.2.5.6	Mobile-requested ground-initiated handoff.....	58
5.2.5.7	Ground-initiated handoff.....	58
5.2.5.8	Ground-requested mobile-initiated handoff	59
5.2.5.9	Ground-requested broadcast handoff	59
5.2.6	Ground-commanded autotune	60
5.2.6.1	VDL Mode 4 Mobile SubNetwork Dependent Convergence Function (SNDCF).....	60
5.3	Frame mode SNDCF	60
5.3.1	Additional VSS requirements	60
5.3.1.1	Information transfer request protocol specification	60
5.3.1.2	Information transfer request parameters.....	60
5.3.1.3	Information transfer request transmission procedures	62
5.3.2	Information transfer request acknowledgement procedures.....	62
5.3.3	Void	62
5.3.4	Void	62
	Retransmission procedures	63
6	General design requirements	63
7	Protocol test procedures	63
7.1	General	63
7.2	Required test rig	63
7.3	Protocol test-suite description methodology	64
7.4	Detailed protocol test procedures	64

7.4.1	Test-suite overview	64
7.4.2	Declarations	67
7.4.3	Constraints	67
7.4.3.1	Abbreviations	67
7.4.3.1.1	Subfield mnemonics	67
7.4.3.1.2	Special characters used in the subfield definitions	68
7.4.3.1.3	Station addresses and positions	68
7.4.3.1.4	VDL bursts	69
7.4.3.2	Test cases	95
7.4.3.2.1	Test case macros	96
7.4.3.2.2	Test case descriptions	98
Annex A (informative): Cross reference matrix		172
History		185

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/6f444987-5a49-44a0-9d30-878bb11381f7/etsi-en-302-842-4-v1.3.1-2015-04>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Aeronautics (AERO).

The present document is part 4 of a multi-part deliverable covering the VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment, as identified below:

- Part 1: "Physical layer";
- Part 2: "General description and data link layer";
- Part 3: "Additional broadcast aspects";
- Part 4: "Point-to-point functions".**

The present document is accompanied by an equivalent ground-based standard, ETSI EN 301 842 [i.1] parts 1 to 5, covering the VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment.

NOTE: Minimum Operational Performance Specifications (MOPS) are also being developed for VDL Mode 4. EUROCAE have previously published Interim MOPS for VDL Mode 4 [i.2] which are a sub set of ETSI EN 302 842-1 [5], ETSI EN 302 842-2 [6], ETSI EN 302 842-3 [7] and ETSI EN 302 842-4 (the present document). ETSI EN 302 842-1 [5], ETSI EN 302 842-2 [6], ETSI EN 302 842-3 [7] and ETSI EN 302 842-4 (the present document) comply with the requirements of EC Mandate M/318 [i.3].

National transposition dates	
Date of adoption of this EN:	6 April 2015
Date of latest announcement of this EN (doa):	31 July 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2016
Date of withdrawal of any conflicting National Standard (dow):	31 January 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [2].

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- equipment comply with ETSI EN 302 842-1 [5] and ETSI EN 302 842-2 [6].

NOTE: The present document has been produced with a view to maintaining consistency of numbering with the equivalent standard for ground equipment (ETSI EN 301 842 [i.1]). Where requirements are the same, they have been given the same number. Some new airborne requirements have been inserted between requirements that were sequential in ETSI EN 301 842 [i.1]. This has led to a non-standard form of numbering for new requirements in some places.

iTeh STANDARD
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/44a0-9d30-878bb11381f7/etsi-en-302-842-4-v1.3>

1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 aeronautical mobile (airborne) radio transmitters, transceivers and receivers for air-ground and air-air communications operating in the VHF band, using Gaussian Filtered Frequency Shift Keying (GFSK) modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 112,000 MHz to 136,975 MHz as defined in ICAO VDL SARPs [2].

The present document provides part 4 of the technical specifications.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VDL SARPs [2] and ICAO VDL4 Technical Manual [1].

Manufacturers should note that in future the tuning range for the transmitter and receiver may also cover any 25 kHz channel from 108,000 MHz to 111,975 MHz.

The present document applies to "aeronautical mobile (airborne and as applicable also ground vehicles)" equipment which will hereinafter be referred to as "mobile" equipment.

The scope of the present document is limited to mobile stations. The equivalent specification for ground stations is ETSI EN 301 842 [i.1].

A description of the scope of the VDL Mode 4 system is provided in part 2 of ETSI EN 302 842-2 [6], clause 1.

ETSI EN 302 842-1 [5] deals with tests of the physical layer, ETSI EN 302 842-2 [6] deals with core link layer functionality and ETSI EN 302 842-3 [7] with additional broadcast functionality. The present document deals with tests of the datalink layer (DLS) and the link layer sufficient to support point-to-point functionality. Note that, as described in ETSI EN 302 842-2 [6], a system supporting point-to-point functionality is required to conform to ETSI EN 302 842-1 [5], ETSI EN 302 842-2 [6] and the specification in the present document.

The present document is organized as follows:

- clause 2 provides references to relevant documents;
- clause 3 provides general definitions, abbreviations and symbols used;
- clause 4 describes the VDL Mode 4 mobile station point-to-point functions;
- clause 5 provides performance specifications for the VDL Mode 4 mobile station;
- clause 6 provides general design requirements;
- clause 7 provides protocol tests for the point-to-point functions of the system;
- annex A provides a detailed cross-reference to the relevant requirements contained in ICAO VDL4 Technical Manual [1].

Note that the system can support a very wide range of functions. It is not practical to provide specific tests for all aspects of functionality. The approach used is to provide detailed tests for the core point-to-point functionality and to provide tests of those remaining requirements which, if wrongly implemented, could cause a deterioration in the service offered by other VDL Mode 4 stations.

Mandating and Recommendation Phrases

a) "Shall":

- The use of the word "Shall" indicates a mandated criterion; i.e. compliance with the particular procedure or specification is mandatory and no alternative may be applied.

b) "Should":

- The use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicates that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ICAO Doc 9816 (First Edition 2004): "Manual on VHF Digital Link (VDL) Mode 4 - Part 2: Detailed Technical Specifications".
- [2] ICAO Annex 10 to the Convention on International Civil Aviation: "Aeronautical Telecommunications, Volume III: Communication Systems, Part I: Digital Data Communication Systems, chapter 6", including Amendment 88 (applicable 14/11/13)".
- [3] ICAO 9705-CD: "Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN)".
- [4] Void.
- [5] ETSI EN 302 842-1 (V1.3.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 1: Physical layer".
- [6] ETSI EN 302 842-2 (V1.4.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 2: General description and data link layer".
- [7] ETSI EN 302 842-3 (V1.4.1): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment; Part 3: Additional broadcast aspects".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 301 842 (all parts): "VHF air-ground Data Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment".
- [i.2] EUROCAE ED-108A: "MOPS for VDL Mode 4 Aircraft Transceiver for ADS-B", July 2001.

[i.3] EC Mandate M/318: "Mandate to CEN/CENELEC/ETSI for standardisation in the field of air traffic management systems and Galileo local components".

3 Definitions and abbreviations

3.1 Definitions

3.1.1 Basic reference model definitions

See ETSI EN 302 842-2 [6], clause 3.1.1.

3.1.2 Service conventions definitions

See ETSI EN 302 842-2 [6], clause 3.1.2.

3.1.3 General definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 302 842-1 [5] clause 3.1.3, ETSI EN 302 842-2 [6] clause 3.1.3 and the following apply:

long transmission procedure: procedure that allows transfer of DATA packets in reserved slots, avoiding the loss rates and delays associated with random access

NOTE: This includes the ability to link sequences of DATA packets, providing continuous transfer in reserved slots.

More bit (M): bit that controls message fragmentation and concatenation

NOTE: It is set to zero to indicate the end of a message. It is set to 1 to indicate that it is part of a fragmented message and that there are more fragments to follow.

Network Setup Connection Oriented Protocol (NSCOP): protocol that enables a ground-air link between mobiles

priority (pr): priority of a message, or, in the case of an RTS, the priority of the requested data

short transmission procedure: procedure for the sending of a single data packet. It contains a reservation for a subsequent acknowledgement

Toggle bit (T): bit that allows detection and rejection of duplicate DLPDUs

NOTE: The T bit is alternately set to 1 and 0 on each successive DATA transmission, except for retransmissions.

Zero-Overhead Connection-Oriented Protocol (ZOCOP): protocol that enables an air-air link between mobiles

3.1.4 Definition of bit order

In the tables included in the present document to illustrate the format of bursts, the following order is implied:

- bit order in each burst subfield are indicated by subscript numbers. Bit 1 indicates the least significant bit; and
- bits are transmitted octet by octet, starting with the first octet in each table, and within each octet the rightmost bit (as shown in the tables) is transmitted first.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	ACKnowledgement (burst)
ADM	ADMInistration identifier
ADS-B	Automatic Dependent Surveillance-Broadcast
ARS	Administration Region Selector
ATN	Aeronautical Telecommunication Network
CMD	CoMmand

CPR	Compact Position Reporting
CRC	Cyclic Redundancy Code
CTRL	ConTRoL (DLPDU)
CTS	Clear To Send (burst)
DISC	DISConnect
DLE	Data Link Entity
DLPDU	Data Link Protocol Data Unit
DLS	Data Link Service
DM	Disconnected Mode (DLPDU)
DTE	Data Terminal Equipment
EC	European Commission
erid	extended reservation ID
FRMR	FRaMe Reject (DLPDU)
GFSK	Gaussian Filtered Frequency Shift Keying
GSC	Global Signalling Channel
GSIF	Ground Station Information Frame
hex	hexadecimal
HO	Hand Off
IA	International Alphabet
IA-5	International Alphabet - 5
IB	Initialize Bit
ICAO	International Civil Aviation Organization
ID	IDentity
INFO	INFormation (DLPDU)
ISO	International Organization for Standardization
IS-SME	Intermediate System - System Management Entity
LCR	Link Connection Refused
LE	Link Establishment
lg	length
LME	Link Management Entity
M	More bit
MAC	Media Access Control
MOPS	Minimum Operational Performance Specification
NACK	Negative ACKnowledgement
neg	negotiation
NETs	Network Entity Titles
NM	Nautical Mile
NSCOP	Network Setup Connection Orientated Protocol
O	Optional
p	priority
PCO	Point of Control and Observation
PI	Parameter Identifier
pr	priority
QoS	Quality of Service
Res	Reserved header bits
RF	Radio Frequency
rid	reservation ID
RSP	ReSPonse
RTS	Request To Send (DLPDU)
SARPs	Standards And Recommended Practices
seq	sequence
SNDCF	SubNetwork Dependent Convergence Function
SZOM	Start Zero Overhead Mode (DLPDU)
T	Toggle bit
UCTRL	Unacknowledged ConTRoL data broadcast (DLPDU)
UDATA	Unacknowledged DATA broadcast (DLPDU)
UINFO	Unacknowledged user INFormation data broadcast (DLPDU)
VDL	VHF Digital Link
VHF	Very High Frequency
VME	VDL Management Entity
VSS	VDL Mode 4 Specific Services
ZOCOP	Zero-Overhead Connection-Oriented Protocol

4 General description of VDL Mode 4 mobile station point-to-point services

4.1 General

A description of VDL Mode 4 is provided in ETSI EN 302 842-2 [6]. This clause provides a description of the datalink layer and associated services of the VSS and LME required to support point-to-point communications.

The specifications in the present document provide air-to-ground and air-to-air point-to-point services based on the ICAO Technical Manual. The present document includes:

- Point-to-point data and control data transfer functions from the DLS.
- Point-to-point link control within the LME.

Note that the present document covers the mobile response to the establishment, termination and handover of links between ground stations. Decisions made by ground stations to establish, terminate or handover links between ground stations are local issues and beyond the scope of these specifications.

In most respects, the VDL Mode 4 mobile station follows the provisions of the ICAO standards material for VDL Mode 4. Within the ICAO standard, there are some requirements which apply explicitly only to ground stations. Requirements on ground stations are covered in ETSI EN 301 842 (all parts) [i.1].

The scope of the present document is for an mobile station supporting point-to-point applications. Hence the ability to support broadcast communication is not included in the present document.

Note that, although certain protocols will not be used by the mobile station, the ability to recognize the use by ground stations of these protocols and to respond in a consistent manner is an mobile station requirement and is included in the present document.

4.2 Data Link Service (DLS) and Link Management Entity (LME)

4.2.1 General

The Data Link Service (DLS) provides a point-to-point protocol supporting both air-to-ground and air-to-air exchanges. For air-to-ground exchanges, connection management is handled by the LME, using a Negotiated Setup Connection-Orientated Protocol (NSCOP). For air-to-air exchanges, the DLS defines a ZOCOP protocol with link establishment and disestablishment controlled by timers, allowing rapid link negotiation between aircraft.

The specifications in the present document assume that VDL Mode 4 will be used with a network based on ATN protocols (see ICAO ATN SARPs [3]). It should be noted that, in future, it could support other network protocols.

The DLS is a simple information exchange protocol which provides:

- a) Explicit acknowledgement of each DATA packet.
- b) Mechanisms to provide data transfer in reserved slots, avoiding loss rates and delays associated with random access. This includes the ability to link sequences of DATA packets, providing continuous transfer in reserved slots.
- c) Packet fragmentation, to allow long user data packets to be transferred across the link in fragments optimally matched to the link conditions.
- d) Duplicate detection and suppression via a simple toggle-bit mechanism.
- e) Explicit support for the 15 priority levels defined for the ATN, including the ability for high priority messages to be sent in the middle of a fragmented low priority message.

As illustrated in figure 4.1, the DLS:

- Provides services to external users in order to support point-to-point, multi-cast and broadcast communications.
- Provides services to the LME to support link management.
- Supports services between peer DLSs.
- Uses the services of the VSS in order to send and receive messages.




Figure 4.1: Functions of the DLS

Figure 4.2 illustrates the use of various services provided by the DLS and VSS in supporting the DLS User and the LME.

iTeh STANDARD PREVIEW
Full standard:
<https://standards.iteh.ai/catalog/standards/list/6f44987-5a49-44a0-9d30-878bb11381f7/etsi-en-302-842-4-v1.3.1-2015-04>