

SLOVENSKI STANDARD
SIST EN 302 561 V 1.3.2:2014

01-november-2014

**Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) -
Kopenske mobilne storitve - Radijska oprema, ki uporablja modulacijo s
konstantno ali nekonstantno ovojnico in deluje v kanalu s pasovno širino 25 kHz,
50 kHz, 100 kHz ali 150 kHz - Harmonizirani EN, ki zajema bistvene zahteve člena
3.2 direktive R&TTE**

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Land Mobile Service
- Radio equipment using constant or non-constant envelope modulation operating in a
channel bandwidth of 25 kHz, 50 kHz, 100 kHz or 150 kHz - Harmonized EN covering
the essential requirements of article 3.2 of the R&TTE Directive

*iteh STANDARD PREVIEW
(standards.iteh.ai)*

[SIST EN 302 561 V 1.3.2:2014](https://standards.iteh.ai/catalog/standards/sist/74707cae-81dd-4b8c-9a90-199ec07b8296/sist-en-302-561-v-1-3-2-2014)
<https://standards.iteh.ai/catalog/standards/sist/74707cae-81dd-4b8c-9a90-199ec07b8296/sist-en-302-561-v-1-3-2-2014>

Ta slovenski standard je istoveten z: EN 302 561 Version 1.3.2

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.01	Mobilni servisi na splošno	Mobile services in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 302 561 V 1.3.2:2014

<https://standards.iteh.ai/catalog/standards/sist/74707cae-81dd-4b8c-9a90-199ec07b8296/sist-en-302-561-v-1-3-2-2014>

ETSI EN 302 561 V1.3.2 (2014-10)



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
(Land Mobile Service);
Radio equipment using constant or non-constant
envelope modulation operating in a channel bandwidth
of 25 kHz, 50 kHz, 100 kHz or 150 kHz;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

Reference

REN/ERM-TGDMR-316

Keywords

data, mobile, PMR, radio, repeater, TETRA

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 302 561 V 1.3.2:2014

<https://standards.iteh.ai/catalog/standards/sist/74707cae-81dd-4b8c-9a90-199ec07b8> ***Important notice***

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
 All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols	11
3.3 Abbreviations	11
4 General	12
4.1 Presentation of equipment for testing purposes.....	12
4.1.1 Choice of model for testing	12
4.1.1.1 Auxiliary test equipment.....	13
4.1.1.2 Declarations by the provider	13
4.2 Multi-Mode equipment.....	13
4.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	13
5 Test conditions, power sources and ambient temperatures	13
5.1 Normal and extreme test conditions	13
5.2 Test power source.....	13
5.3 Normal test conditions.....	14
5.3.1 Normal temperature and humidity.....	14
5.3.2 Normal test power source	14
5.3.2.1 Mains voltage	14
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	14
5.3.2.3 Other power sources.....	14
5.4 Extreme test conditions	14
5.4.1 Extreme temperatures	14
5.4.2 Extreme test source voltages.....	15
5.4.2.1 Mains voltage	15
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	15
5.4.2.3 Power sources using other types of batteries.....	15
5.4.2.4 Other power sources.....	15
5.5 Procedure for tests at extreme temperatures	15
5.5.1 Procedure for equipment designed for continuous transmission.....	15
5.5.2 Procedure for equipment designed for intermittent transmission	16
6 General test conditions	16
6.1 Arrangements for test signals applied to the receiver input.....	16
6.2 Test load (artificial antenna).....	16
6.3 Test signals (wanted and unwanted signals).....	16
6.3.1 Transmitter test signals	16
6.3.2 Receiver test signals.....	17
6.3.3 Transmitter effective radiated power test signal (C1).....	17
6.4 Encoder	17
6.4.1 Encoder for receiver measurements	17
6.4.2 Encoder for transmitter measurements	18
6.5 Transceiver data interface.....	18
6.6 Impedance	18
6.7 PEP	18

6.8	Duplex equipment	18
6.9	Modes of operation of the transmitter	18
6.10	Measurement filter definition	19
6.11	TMO Repeaters	19
7	Technical characteristics of the transmitter.....	19
7.1	Transmitter output power (conducted)	19
7.1.1	Definitions	19
7.1.2	Method of measurement	20
7.1.3	Limits.....	20
7.2	Maximum effective radiated power.....	20
7.2.1	Definition.....	20
7.2.2	Method of measurement	20
7.2.2.1	Evaluation of CW-to-PEP correction factor for signal C1	20
7.2.2.2	Measurements on a test site.....	21
7.2.3	Limit	22
7.3	Adjacent and alternate channel power.....	22
7.3.1	Definition.....	22
7.3.2	Method of measurement	23
7.3.3	Limits.....	24
7.3.3.1	Limits for TMO Repeaters	24
7.3.3.2	Limits for all non TMO repeater equipment	24
7.4	Unwanted emissions in the spurious domain.....	25
7.4.1	Definition.....	25
7.4.2	Method of measuring the power level	25
7.4.2.1	Measurement options	25
7.4.2.2	Method of measuring conducted spurious emissions (clause 7.4.2.1 a)).....	25
7.4.2.3	Method of measuring the effective radiated power (clause 7.4.2.1 b)).....	26
7.4.2.4	Method of measuring the effective radiated power (clause 7.4.2.1 c))	27
7.4.2.5	Method of measuring wideband noise.....	27
7.4.3	Limits.....	28
7.4.3.1	Spurious emissions power.....	28
7.4.3.2	Wideband noise power.....	29
7.5	Intermodulation attenuation.....	31
7.5.1	Definition.....	31
7.5.2	Method of measurement	31
7.5.2.1	Measurement for TMO repeater equipment	31
7.5.2.2	Measurement for non TMO repeater equipment	32
7.5.3	Limits	33
7.5.3.1	Limits for TMO repeater equipment	33
7.5.3.2	Limits for non TMO repeater equipment	33
7.6	Adjacent channel transient power measurements.....	33
7.6.1	Definition.....	33
7.6.2	Method of Measurement.....	33
7.6.3	Limits.....	34
7.7	Frequency error	34
7.7.1	Definition.....	34
7.7.2	Method of measurement	34
7.7.3	Limits.....	35
7.8	Out of band gain for TMO repeater equipment.....	35
7.8.1	Definition.....	35
7.8.2	Method of measurement	35
7.8.3	Limits.....	36
7.9	Modulation accuracy	36
7.9.1	Definition.....	36
7.9.2	Method of measurement	36
7.9.3	Limits.....	37
8	Technical characteristics of the receiver	37
8.1	Receiver sensitivity (conducted)	37
8.1.1	Definition.....	37
8.1.2	Method of measurement	37

8.1.2.1	Method of measurement with continuous bit streams	37
8.1.2.2	Method of measurement with messages or packets	38
8.1.3	Limits.....	38
8.2	Maximum usable sensitivity (field strength).....	39
8.2.1	Definition.....	39
8.2.2	Method of measurement	39
8.2.2.1	Method of measurement with continuous bit streams	40
8.2.2.2	Method of measurement with messages.....	40
8.2.3	Limits.....	41
8.3	Blocking or desensitization	43
8.3.1	Definition.....	43
8.3.2	Method of measurement	43
8.3.2.1	Method of measurement with continuous transmissions.....	43
8.3.2.2	Method of measurement with messages.....	44
8.3.3	Limits.....	45
8.4	Adjacent channel selectivity	45
8.4.1	Definition.....	45
8.4.2	Method of measurement	45
8.4.2.1	Method of measurement (with continuous bit stream).....	45
8.4.2.2	Method of measurement with messages.....	46
8.4.3	Limits.....	47
8.5	Spurious radiations	47
8.5.1	Definition.....	47
8.5.2	Methods of measurement.....	47
8.5.2.1	Method of measuring the power level in a specified load (clause 8.5.1 a)	47
8.5.2.2	Method of measuring the effective radiated power (clause 8.5.1 b)	48
8.5.2.3	Method of measuring the effective radiated power (clause 8.5.1 c)	49
8.5.3	Limits.....	49
8.6	Co-channel rejection.....	49
8.6.1	Definition.....	49
8.6.2	Method of measurement	50
8.6.2.1	Method of measurement with continuous bit streams.....	50
8.6.2.2	Method of measurement with messages (or packets).....	51
8.6.3	Limits.....	52
8.7	Intermodulation response rejection	52
8.7.1	Definition.....	52
8.7.2	Method of measurement	52
8.7.2.1	Method of measurement (with continuous bit stream).....	52
8.7.2.2	Method of measurement with messages.....	53
8.7.3	Limit	54
9	Measurement uncertainty	54
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	56
Annex B (normative):	Radiated measurement.....	58
B.1	Test sites and general arrangements for measurements involving the use of radiated fields	58
B.1.1	Anechoic chamber.....	58
B.1.2	Anechoic chamber with a conductive ground plane	59
B.1.3	Open Area Test Site (OATS)	60
B.1.4	Test antenna.....	61
B.1.5	Substitution antenna	62
B.1.6	Measuring antenna	62
B.2	Guidance on the use of radiation test sites	62
B.2.1	Verification of the test site	62
B.2.2	Preparation of the EUT.....	62
B.2.3	Power supplies to the EUT	62
B.2.4	Range length.....	63
B.2.5	Site preparation	63

B.3	Coupling of signals.....	64
B.3.1	General	64
B.3.2	Data signals	64
Annex C (normative):	Spectrum analyser specification	65
Annex D (informative):	Void	66
Annex E (informative):	Bibliography	67
History		68

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 561 V 1.3.2:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/74707cae-81dd-4b8c-9a90-199ec07b8296/sist-en-302-561-v-1-3-2-2014>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to mandate M/284 issued from the European Commission under Directive 98/34/EC [i.5] as amended by Directive 98/48/EC [i.6].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.4].

See article 5.1 of Directive 1999/5/EC [i-4] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.4] are summarized in annex A.

SIST EN 302-561 V 1.3.2-2014	
https://standards.ieec.org/standards/199cc07b8296/sist-en-302-561-v-1-3-2-2014	
Date of adoption of this EN:	25 September 2014
Date of latest announcement of this EN (doa):	31 December 2014
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2015
Date of withdrawal of any conflicting National Standard (dow):	30 June 2016

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.4]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations and technical requirements for TMO repeater in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 30 MHz and 3 GHz, with channel separations of 25 kHz, 50 kHz, 100 kHz and 150 kHz.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 3 000 MHz
Receive	30 MHz to 3 000 MHz

It applies to equipment for continuous and/or discontinuous transmission of data and/or digital speech.

The equipment (base station and mobile station) comprises a transmitter and associated encoder and modulator and/or a receiver and associated demodulator and decoder.

The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable);
- TMO Repeater; and **iTeh STANDARD PREVIEW**
- those hand portable stations: **(standards.iteh.ai)**
 - a) fitted with an antenna connector; or
 - b) without an ~~external antenna connector (integral antenna equipment)~~, but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

These specifications do not necessarily include all the characteristics which may be required by a user of equipment, nor do they necessarily represent the optimum performance achievable.

The present document is intended to cover the provisions of article 3.2 of Directive 1999/5/EC [i.4] (R&TTE Directive), which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.4] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [2] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] ETSI TR 102 273 (V1.2.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [4] ANSI C63.5 (2004): "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [5] ETSI EN 300 392-2 (V3.2.1) (09-2007): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (A2)".
SIST EN 302 561 V 1.3.2:2014
<https://standards.etsi.org/catalog/standards/sist/7470/cae-81dd-4b8c-9a90-199ec07b8296/sist-en-302-561-v-1-3-2-2014>

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R SM.329-10 (2003): "Unwanted emissions in the spurious domain".
- [i.2] CEPT/ERC/REC 74-01 (2005): "Unwanted Emissions in the Spurious domain".
- [i.3] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.4] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.5] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.6] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.7] ETSI TS 101 789-1 (V1.1.2): "Terrestrial Trunked Radio (TETRA); TMO Repeaters; Part 1: Requirements, test methods and limits".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

base station: equipment fitted with an antenna connector, for use with an external antenna, and intended for use in a fixed location

bit: binary digit

block: the smallest quantity of information that is sent over the radio channel

NOTE: A constant number of useful bits are always sent together with the corresponding redundancy bits.

broadband repeater: repeater which is designed for operation on any combination of carriers (up to a specified maximum number) within the operating band of the repeater

burst or transmission (physical): one or several packets transmitted between power on and power off of a particular transmitter

channelized repeater: repeater which is designed for operation on a specified subset of carriers within the operating band of the repeater

NOTE: The subset of the channels may be determined during the manufacture of the repeater, or may be programmable.

iTeh STANDARD PREVIEW

conducted measurements: measurements which are made using direct $50\ \Omega$ connection to the equipment under test

(standards.iteh.ai)

data transmission systems: systems which transmit and/or receive data and/or digitized voice

downlink: signal path where base station transmits and mobile or hand portable station receives

hand portable station: equipment either fitted with an antenna connector or integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

integral antenna: antenna designed to be connected to the equipment without the use of a $50\ \Omega$ external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

Listen Before Transmit mode (LBT): monitoring mode in which the RF channel is checked for activity before transmitting

NOTE: Examples for LBT are transceivers or systems implementing squelch or RSSI (Receiver Signal Strength Indicator) algorithms for evaluating the status of the channel.

message: user data to be transferred in one or more packets in a session

mobile station: mobile equipment fitted with an antenna connector, for use with an external antenna, normally used in a vehicle or as a transportable station

packet: one block or a contiguous stream of blocks sent by one (logical) transmitter to one particular receiver or one particular group of receivers

radiated measurements: measurements which involve the absolute measurement of a radiated field

receive band of the equipment: maximum frequency range (declared by the manufacturer) over which the receiver can be operated without reprogramming or realignment

session: set of inter-related exchange of packets occupying one or several windows or part thereof (if applicable)

NOTE: It corresponds to a complete interactive procedure for interchanging data between users, comprising initiation, data transmission and termination procedures. The session can be short (e.g. 2 packets), or long (e.g. one full page of text).

spurious emissions: unwanted emissions in the spurious domain

switching range (sr): maximum frequency range, as specified by the manufacturer, over which the receiver or the transmitter can be operated within the alignment range without reprogramming or realignment

testing laboratory: laboratory that performs tests

TMO Repeater: bi-directional Radio Frequency (RF) amplifier which can amplify and transmit a received Mobile Station (MS) signal in the MS transmit band, simultaneously it can amplify and transmit a received Base Station (BS) RF signal in the BS transmit band

transmit band of the equipment: maximum frequency range (declared by the manufacturer) over which the transmitter can be operated without reprogramming or realignment

Trunked Mode Operation (TMO): mode of operation where a network is used for communication

uplink: signal path where mobile or hand portable station transmits and base station receives

window: set of inter-related transmissions which may be limited in time by an appropriate access protocol and corresponding occupation rules

3.2 Symbols iTeh STANDARD PREVIEW

For the purposes of the present document, the following symbols apply:

(standards.iteh.ai)

α	Filter rolloff factor
dB	decibel
dBm	dB relative to 1 mW
dB μ V	dB relative to 1 μ V
f_c	channel centre frequency
f_{LO}	Local Oscillator frequency
f_{rb}	the frequency offset corresponding to the near edge of the receive band
M1, M2, etc	names of test signals defined in clause 6.3
PR	rms power
PX	maximum Power (Peak Envelope Power)
V_{min}	minimum extreme test Voltage
V_{max}	maximum extreme test Voltage
T_{min}	minimum extreme test Temperature
T_{max}	maximum extreme test Temperature
λ	wavelength

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
ACP	Adjacent Channel Power
ARQ	Automatic Repeat reQuest
BS	Base Station
BW	BandWidth
CBW	Channel BandWidth

CSP	Channel SeParation
CW	Continuous Wave
dBc	decibels relative to the transmitter power
DC	Direct Current
EUT	Equipment Under Test
GMSK	Gaussian Minimum Shift Keying
IF	Intermediate Frequency
LBT	Listen Before Transmit
MBW	Measurement BandWidth
MS	Mobile Station
OATS	Open Area Test Site
PEP	Peak Envelope Power
PMR	Private Mobile Radio
ppm	parts per million
RF	Radio Frequency
rms	root mean square
RSSI	Received Signal Strength Indicator
Rx	Receiver
sr	switching range
TETRA	TErrestrial Trunked RAdio
TMO	Trunked Mode Operation
Tx	Transmitter
VSWR	Voltage Standing Wave Ratio
$\pi/4$ -DQPSK	$\pi/4$ -shifted Differential Quaternary Phase Shift Keying

4 General iTeh STANDARD PREVIEW (standards.iteh.ai)

4.1 Presentation of equipment for testing purposes

SIST EN 302 561 V 1.3.2:2014

Each equipment submitted <http://testbed.iteh.ai/testbed/jsp/717079/pr-8111418n9.00> shall fulfil the requirements of the present document on all frequencies over which it is intended to operate. 199ec07b8296/sist-en-302-561-v-1-3-2-2014

The radio tests shall be performed on the lowest, the highest and the middle radio frequency channels of either the transmit or receive band of the equipment, whichever is appropriate.

The provider or manufacturer shall declare the frequency ranges, the range of operating conditions and power requirements as applicable, to establish the appropriate test conditions. For non TMO repeater equipment information related to radio sub-system of equipment includes the transmit and receive frequency bands, first local oscillator frequency and intermediate frequencies of the receiver.

Additionally, technical documentation and operating manuals, sufficient to make the test, shall be supplied.

For TMO Repeater Equipment manufacturer declarations shall include:

- a) the operating band or bands of the repeater;
- b) the maximum rated output power per channel;
- c) the number of channels supported by the repeater.

4.1.1 Choice of model for testing

The provider or manufacturer shall provide one or more samples of the equipment, as appropriate for testing.

Stand-alone equipment shall be complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters then the tests need only to be performed on the equipment configured with the combination of features considered to be the most complex. Where practicable, equipment to be tested shall provide a $50\ \Omega$ connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have an internal permanent 50Ω connector then it is permissible to supply a second sample of the equipment with a temporary antenna connector fitted to facilitate testing.

The test connector shall also provide any test signalling data.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model.

4.1.1.1 Auxiliary test equipment

All necessary test signal sources, setting up instructions and other product information shall accompany the equipment to be tested.

4.1.1.2 Declarations by the provider

The provider or manufacturer shall declare the necessary information of the equipment with respect to all technical requirements set by the present document.

4.2 Multi-Mode equipment

In the case of equipment supporting more than one channel bandwidth, measurements shall be performed on each channel bandwidth implemented.

4.3 Testing of equipment that does not have an external 50Ω RF connector (integral antenna equipment) (standards.itel.ai)

Where equipment has an internal 50Ω connector it shall be permitted to perform the tests at this connector.

SIST EN 302 561 V 1.3.2:2014

Equipment may also have a temporary internal 50Ω connector installed for the purposes of testing.

199ec07b8296/sist-en-302-561-v-1-3-2-2014

No connection shall be made to any internal permanent or temporary antenna connector during the performance of radiated emissions measurements, unless such action forms an essential part of the normal intended operation of the equipment, as declared by the manufacturer.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Testing shall be performed under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in clauses 5.2 to 5.5.

5.2 Test power source

During testing the power source of the equipment shall be replaced by a test power source capable of producing normal and extreme test voltages as specified in clauses 5.3.2 and 5.4.2. The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of tests, the voltage of the power source shall be measured at the input terminals of the equipment.

For battery operated equipment the battery shall be removed and the test power source shall be applied as close to the battery terminals as practicable.