

# SLOVENSKI STANDARD SIST ETS 300 254 E1:2003

01-december-2003

Satelitske zemeljske postaje in sistemi (SES) – Kopenske mobilne zemeljske postaje (LMES), ki delujejo v pasovih 1,5 GHz in 1,6 GHz, ki zagotavljajo podatkovne komunikacije z nizko bitno hitrostjo (LBRDC)

Satellite Earth Stations and Systems (SES); Land Mobile Earth Stations (LMES) operating in the 1,5/1,6 GHz bands providing Low Bit Rate Data Communications (LBRDC)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ETS 300 254 E1:2003</u> https://standards.iteh.ai/catalog/standards/sist/7043acf5-82e1-4fa6-acad-8542016184af/sist-ets-300-254-e1-2003

Ta slovenski standard je istoveten z: ETS 300 254 Edition 1

ICS:

33.060.30 Radiorelejni in fiksni satelitski Radio relay and fixed satellite

komunikacijski sistemi communications systems

SIST ETS 300 254 E1:2003 en

# iTeh STANDARD PREVIEW (standards.iteh.ai)



# EUROPEAN TELECOMMUNICATION STANDARD

ETS 300 254

May 1994

Source: ETSI TC-SES Reference: DE/SES-05001

ICS: 33.060.30

Key words: LMES, LBRDC

Satellite Earth Stations and Systems (SES);
Land Mobile Earth Stations (LMESs)

operating in the 4,5/4,6 GHz bands
https://standards.itch.ai/catalog/standards/sist/7043acf5-82c1-4fa6-acadproviding Low Bit Rate Data Communications (LBRDCs)

# **ETSI**

European Telecommunications Standards Institute

### **ETSI Secretariat**

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Page 2

ETS 300 254: May 1994

# iTeh STANDARD PREVIEW (standards.iteh.ai)

# **Contents**

Fore	wora	• • • • • • • • • • • • • • • • • • • •		5	
1	Scope.			7	
2	Normat	ive referenc	ces	8	
3	Definitions and abbreviations				
	3.1		าร		
	3.2	Abbrevia	tions	9	
4	Requirements				
	4.1				
	7.1	4.1.1	Mechanical construction		
		4.1.2	Electrical safety, power voltages		
		4.1.3	Radio frequency radiation protection		
	4.2	-	equency (RF)		
		4.2.1	Unwanted emissions outside the bands 1 626,5 - 1 645,5 MHz and 1 656,5 - 1 660,5 MHz		
		4.2.2	Maximum unwanted emission within the 1 626,5 - 1 645,5 MHz and 1 656,5 - 1 660,5 MHz bands		
		4.2.3	Electromagnetic immunity		
		4.2.4	Protection of the radio astronomy service from the LMES operating in t band 1 660,0 - 1 660,5 MHz	he	
	4.3	IMES C	ontrol and Monitoring Functions (CMFs)	1 <i>3</i>	
	4.5				
		iT	Monitoring functions  eh 4,3.1.1 A D Processor monitoring	14	
		11.	4.3.1.2 Transmit frequency sub-system	14	
		4.3.2	Power on/reset r.d.s.iteh.ai)	15	
		4.3.3	Network control reception and authorisation	15	
			4.3.3.1 Network control authorisation	15	
		latte au//at	4.3.3.2 Network control reception	16	
	4.4	Initial bui	andards ifeh a/catalog/standards/sist/7043act5-82e1-4ta6-acad- ist rate transmission 8542016184at/sist-ets-300-254-e1-2003	16	
5	Recomi	mendations	S	17	
	5.1		I safety while loading and unloading hazardous fuels or gases		
	5.2		agnetic immunity - General immunity between 2 GHz and 3 GHz		
	5.3		nce with RF specifications under conditions of shock and vibration		
	5.4 Method of attachment to the vehicle of the Externally Mounted Equipment (EME)				
6	Networl	k Control Fa	acilities (NCFs) for LMES networks	18	
Anne	x A (norr	native):	Environmental conditions	19	
A.1	Environ	mental con	ditions	19	
A.2	Test conditions		19		
Anne	ex B (norr	native):	Out-of-band unwanted emissions above 960 MHz - test procedure	20	
B.1	`	,	·		
B.2					
	Measuring apparatus				
B.3	Equipment Under Test (EUT)				
B.4	Special Test Equipment (STE)				
B.5					
B.6	Measuring procedure				

# Page 4

ETS 300 254: May 1994

B.7	Alternative measuring procedure	21
Anne	ex C (normative): In-band unwanted emissions - test procedure	22
C.1	Introduction	22
C.2	Measuring apparatus	22
C.3	Equipment Under Test (EUT)	22
C.4	Special Test Equipment (STE)	22
C.5	Test set-up	22
C.6	Measuring procedure	23
C.7	Alternative measuring procedure	23
Histo	ry	24

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Page 5 ETS 300 254: May 1994

### **Foreword**

This European Telecommunication Standard (ETS) has been produced by the Satellite Earth Stations and Systems (SES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Every ETS prepared by ETSI is a voluntary standard. This ETS may contain text concerning type approval of the equipment to which it relates. This text does not make this ETS mandatory in its status as a standard. However, this ETS can be referenced, wholly or in part, for mandatory application by decisions of regulatory bodies.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Page 6

ETS 300 254: May 1994

Blank page

# iTeh STANDARD PREVIEW (standards.iteh.ai)

Page 7

ETS 300 254: May 1994

# 1 Scope

This European Telecommunication Standard (ETS) provides specifications for the standardisation of the characteristics of Land Mobile Earth Stations (LMESs) with both transmit and receive capabilities in order to ensure general safety and to limit interference to radio communications services.

The geostationary satellite networks referred to in this ETS operate under the Land Mobile Satellite Service (LMSS). The LMESs operate as part of a geostationary satellite network providing Low Bit Rate Data Communications (LBRDC).

The frequency bands under which the LMESs operate should be within the following bands:

LMES transmit frequencies	LMES receive frequencies
1 626,5 MHz to 1 645,5 MHz	1 525,0 MHz to 1 544,0 MHz
and	and
1 656,5 MHz to 1 660,5 MHz	1 555,0 MHz to 1 559,0 MHz

These LMESs generally have the following characteristics:

- the LMESs could be either vehicle mounted or portable equipment;
- the LMESs could consist of a number of modules including a keyboard interface to the user.

The main specifications are contained in three categories related to:

- safety: to protect personnel, public and goods from unsafe operating conditions or equipment;
- unwanted emissions: to protect terrestrial and satellite radio services from harmful interference;
- (standards.iteh.ai)
   LMES control and monitoring: to specify a minimum set of Control and Monitoring Functions (CMF) that shall be implemented on each LMES in order to minimise the probability that they originate unwanted transmissions that may give rise to harmful interference to other systems.

This ETS deals with two types of specification: ets-300-254-e1-2003

### a) Essential normative requirements (indicated in Clause 4)

Requirements are specified in order to protect other users of the frequency spectrum from unacceptable interference. In addition, requirements are specified for the purposes of general safety.

# b) Recommendations (indicated in Clause 5)

Recommendations are specified relating to matters of general safety, minimisation of interference to other users of the radio spectrum and for the provision of protection of the LMESs against electromagnetic interference from other systems.

All tests related to the requirements shall be performed and the results entered in the data sheets of the test report. The ability to comply with the recommendations shall also be noted in the data sheets of the test report. All parameters and operational conditions declared by the manufacturer shall be entered in the test report.

Page 8

ETS 300 254: May 1994

#### 2 Normative references

This ETS incorporates, by dated or undated references, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

[1]	IEC 215 (1987): "Safety req	uirements for radio transmitting equip	oment".

[2]	CISPR Publication No. 22 (1985): "Limits and methods of measurement of radio
-----	--

interference characteristics of information technology equipment".

[3] IEC 510-2-1 (1978): "Methods of measurement for radio equipment used in

satellite earth stations. Part 2: Measurement for sub-systems".

[4] ETS 300 282: "Satellite Earth Stations and Systems (SES); Network Control

Facilities (NCFs) for Land Mobile Earth Stations (LMESs) operating in the 1,5/1,6 GHz and 11/12/14 GHz bands providing Low Bit Rate Data

Communications (LBRDCs)".

IEC 801-3 (1984): "Electromagnetic compatibility for industrial-process [5]

measurement and control equipment, Part 3: Radiated electromagnetic field

requirements".

CISPR Publication No. 16 (1987): "CISPR" specification for radio interference [6]

measuring apparatus and measurement methods".

# Teh STANDARD PREVIEW **Definitions and abbreviations**

(standards.iteh.ai)

#### 3.1 **Definitions**

3

Installable Equipment (IE), Internally Mounted Equipment (IME) and Externally Mounted Equipment (EME): an Installable Equipment (IE) is an equipment which is intended to be installed in a vehicle. An IE may consist of one or several interconnected modules. The manufacturer shall indicate which modules are intended to be Externally Mounted Equipment (EME); the remaining module(s) will then be defined as Internally Mounted Equipment (IME). Where different specifications apply to IME and EME, this is noted in the text.

Nominated bandwidth: the bandwidth of the LMES radio frequency transmission is nominated by the manufacturer. The nominated bandwidth shall encompass all close-in spectral elements of the transmission which have a level greater than the specified spurious levels. The nominated bandwidth shall be wide enough to take account of the transmit carrier frequency stability. The nominated bandwidth shall be within the LMSS transmit frequency band within which the LMES operates. The value of the nominated bandwidth shall be entered on the data sheet of the test report.

Portable Equipment (PE): a Portable Equipment (PE) is generally intended to be self-contained, free standing and portable. A PE would normally consist of a single module, but may consist of several interconnected modules. In some cases different specifications will apply to PE and this is noted in the

Unwanted emissions: unwanted emissions are those falling outside the nominated bandwidth.

Page 9

ETS 300 254: May 1994

#### 3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

CMF Control and Monitoring Function

EIRP Equivalent Isotropically Radiated Power

EM Electro-Magnetic

EME Externally Mounted Equipment

EUT Equipment Under Test
IE Installable Equipment

Internally Mounted Equipment IME **LBRDC** Low Bit Rate Data Communication **LMSS** Land Mobile Satellite Service **LMES** Land Mobile Earth Station **Network Control Facility** NCF Portable Equipment PΕ RF Radio Frequency rms root mean square STE Special Test Equipment

# 4 Requirements

#### 4.1 Safety

#### 4.1.1 Mechanical construction

#### Purpose:

iTeh STANDARD PREVIEW

Protection of operating personnel, the public and goods from insecure or unsafe structures.

(standards.iteh.ai)

### Specification:

For Installable Equipment (IE) and Portable Equipment (PE) the mechanical design, construction and finish of the equipment shall conform to IEC 215 [1], section 3, paragraph 9.1.

## Verification:

Verification shall be demonstrated by documentary evidence and visual inspection.

### 4.1.2 Electrical safety, power voltages

#### Purpose:

Protection of operating personnel and the public from electric shock.

### Specification:

The electrical safety of the equipment shall be in accordance with paragraphs 13, 14, 15 and 16, and Appendix B of IEC 215 [1].

### Verification:

Conformance shall be determined by documentary evidence and visual inspection.

#### 4.1.3 Radio frequency radiation protection

#### Purpose:

To indicate the distance from the LMES below which RF power densities in excess of 8 W/m<sup>2</sup> may be experienced, when averaged over a 6 minute period.