

---

---

**Space systems — Launch-vehicle-to-  
spacecraft flight environments telemetry  
data processing**

*Systèmes spatiaux — Traitement des données télémétriques des  
environnements de vol entre le lanceur spatial et le véhicule spatial*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 15862:2009](https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009)

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15862:2009

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15862 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15862:2009](https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009)

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>

## Introduction

This International Standard addresses flight environment measurements, data processing and analysis, and reports of analysis results. If launch vehicle (LV) environmental specifications are exceeded, the LV and spacecraft (SC) agencies can perform an analysis to determine the cause of the problem.

Flight environments describe different types of flight mechanical and thermal environments. Measurement fields include parameters characterizing such environments as loads, vibration, shock, acoustics, steady-state pressure and temperature. Requirements include number, location, range and frequency of measurement devices.

Data processing and analysis include data pre-processing, data processing and formats of delivered data.

Flight measurement plan formats are provided.

The report on flight environment analysis results records all the above information.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15862:2009](https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009)

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>

# Space systems — Launch-vehicle-to-spacecraft flight environments telemetry data processing

## 1 Scope

This International Standard provides basic requirements for the measurement of the spacecraft flight environments generated by the launch vehicle, telemetry data processing and formats of analysis reports.

This International Standard defines the field and number of measurement parameters, the principles of data processing, the format of delivered data and the content and the form of the flight environment analysis report.

Flight telemetry data are used to verify if flight environment conditions exceed pre-flight analyses and environmental test results. In the event of a launch failure, adequate flight environment data can assist in investigating and analysing failure causes.

This International Standard is applicable to commercial launch vehicles and related ground processing, no matter which launch vehicle agencies are selected.

## 2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 2.1

#### **cut-off**

load case when the engine thrust begins to decrease from current value to zero

### 2.2

#### **ground transportation**

spacecraft transportation at launch site

### 2.3

#### **lift-off**

launch vehicle motion when the vehicle's contact is terminated with launch pad or other support devices

NOTE This is commonly called "first motion" of the vehicle. Possible abnormal cut-off is also included.

### 2.4

#### **load case**

event in spacecraft service life during which essential mechanical environments are expected

### 2.5

#### **maximum dynamic pressure phase**

flight phase when dynamic pressure reaches its maximum value

### 2.6

#### **minimum sampling frequency**

minimum number of data points of measurement fields collected per second

**2.7 spacecraft-to-launch-vehicle interface**  
**SC/LV interface**  
mechanical interface that connects spacecraft (or spacecraft-provided adapter) to launch-vehicle-provided adapter

**2.8 separation**  
separations of launch vehicle stages, boosters and other structural elements (e.g. fairing jettison)

**2.9 steady-state acceleration**  
constant acceleration that generates static loads.

**2.10 transonic phase**  
flight phase when the Mach number is in the range of 0,8 to 1,2

### 3 Abbreviated terms

LV launch vehicle

PSD power spectral density

SC spacecraft

SPL sound pressure level

SRS shock response spectrum

RMS root mean square

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>

## 4 Flight environments, measurement fields and measurement requirements

### 4.1 Flight environments

#### 4.1.1 General

Different types of mechanical environments and thermal environments are described in 4.1.2 to 4.1.8 below.

#### 4.1.2 Quasi-static load

The quasi-static load is the resultant of all external forces with the exception of gravity applied on the LV centre of gravity.

#### 4.1.3 Low-frequency vibration

Low-frequency vibration is the structural response generated mainly by thrust variation of the LV engines at ignition and cut-off, by fluctuation of the pressure during the transonic phase, and by transient loads at stage separation(s).

#### 4.1.4 High-frequency vibration

High-frequency vibration is the structural response generated mainly by the LV engine noise and by the aerodynamic noise. High-frequency vibration reaches the maximum during lift-off, ascent phase and transonic flight.

#### 4.1.5 Acoustic noise

Acoustic noise is the sound pressure generated mainly by the LV engine noise and by aerodynamics. The maximum fairing internal noise occurs during lift-off, ascent phase and transonic flight.

#### 4.1.6 Shock

Shock environment consists of the transient response generated by the LV fairing jettison, stage separation(s) and SC/LV separation(s).

#### 4.1.7 Steady-state pressure

The steady-state pressure field consists of the instantaneous pressure of air outside the LV and inside the fairing. The fairing internal pressure of air decreases gradually during the LV ascent phase due to air escape. The fairing internal pressure of air is related to the flight trajectory, the shape of the fairing and the vent configurations.

#### 4.1.8 Thermal

The launch phase thermal environment is dependent on the fairing aerodynamic heating, the radiation of the sun and the earth, and the space conditions.

### 4.2 Measurement fields

Measurement fields shall be determined by common agreement between the LV service provider and the SC customer. Unless otherwise specified, the following measurement fields shall be planned and corresponding measurements shall be conducted:

- steady-state acceleration, [ISO 15862:2009](https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009)
- low-frequency vibration, <https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e966862bc/iso-15862-2009>
- high-frequency vibration,
- acoustic noise,
- shock acceleration,
- steady-state pressure, and
- temperature.

### 4.3 Measurement requirements

#### 4.3.1 Number and location of measurements

##### 4.3.1.1 Steady-state acceleration

As a minimum, steady-state acceleration shall be measured at one location in the LV longitudinal axis and the two lateral orthogonal axes. The measurement location shall be close to the SC/LV interface.

NOTE In general, this practice is recommended for developmental flights, but is often not required for operational systems.

**4.3.1.2 Low-frequency vibration**

As a minimum, low-frequency vibration shall be measured at one location in the LV longitudinal axis and the two lateral orthogonal axes. The measurement location shall be close to the SC/LV interface.

**4.3.1.3 High-frequency vibration**

As a minimum, high-frequency vibration shall be measured at one location in the LV longitudinal axis and the two lateral orthogonal axes. The measurement location shall be close to the SC/LV interface.

NOTE In general, this practice is recommended for developmental flights, but is often not required for operational systems.

**4.3.1.4 Acoustic noise**

As a minimum, acoustic sound pressure shall be measured at two points. The measurement location shall be representative of the acoustic field inside the fairing.

**4.3.1.5 Shock acceleration**

As a minimum, shock acceleration shall be measured at one location in the LV longitudinal axis and in one orthogonal axis. The measurement location shall be close to the SC/LV interface.

NOTE In general, this practice is recommended for developmental flights, but is often not required for operational systems.

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

**4.3.1.6 Steady-state pressure**

As a minimum, steady-state pressure shall be measured at one location. The measurement location shall be chosen inside the fairing to indicate the ambient pressure.

ISO 15862:2009  
<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-766e866862b/iso-15862-2009>

NOTE In general, this practice is recommended for developmental flights, but is often not required for operational systems.

**4.3.1.7 Temperature**

As a minimum, temperature shall be measured at one location. The measurement location shall be chosen close to the SC/LV interface.

**4.3.2 Measurement range selection**

The range of measurement shall be properly defined by the LV agency.

**4.3.3 Frequency range and minimum sampling frequency**

Frequency ranges and minimum sampling frequency shall be selected to provide representative measurement results for flight environment characteristics evaluation.

Frequency ranges, corresponding measuring tool parameters and minimum sampling frequencies shall be selected to prevent frequency masking phenomena.

Frequency ranges and minimum sampling frequencies shall be established in technical specifications and/or in a statement of works by agreement between the SC and LV agencies.



#### 4.4 Flight measurement plan

The flight measurement plan shall be properly defined by the LV agency and shall be agreed by the SC customer. It shall include the list, type, location, orientation, characteristics of the measurement sensors, ranges of frequencies, sequence of measurement, as well as the minimal sampling frequency of sensors needed to fulfil the measurement requirements.

For each measurement sensor, the following are examples to be described in the plan:

- identification code,
- type,
- location,
- direction (if applicable),
- units,
- measurement range,
- frequency range,
- sampling rate,
- sensitivity, and
- accuracy.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

[ISO 15862:2009](https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-60c966862bc/iso-15862-2009)

<https://standards.iteh.ai/catalog/standards/sist/8e64b125-aec3-4c47-9e49-60c966862bc/iso-15862-2009>

## 5 Data processing and analysis

### 5.1 Data pre-processing procedure

#### 5.1.1 General

The time history of telemetry data shall be examined for data quality. If the signal time history is inconsistent with corresponding parameter physical nature, the signal shall be regarded as invalid. Telemetry malfunction segments shall be identified and excluded from further processing.

#### 5.1.2 Steady-state acceleration, steady-state pressure and temperature

Because steady-state acceleration, steady-state pressure and temperature change slowly along with time, large and unexpected changes of signal for a very short duration shall be regarded as corrupted data points and shall be deleted or replaced with adjacent data points.

#### 5.1.3 Low-frequency vibration, high-frequency vibration, acoustic noise and shock acceleration

##### 5.1.3.1 Data quality identification

The time history shall be plotted and examined for data quality. The signal amplitude should be properly evaluated to determine whether the signal is regarded as valid or invalid.