

---

---

**Acoustics — Laboratory measurement of  
sound insulation of building elements —  
Part 3:  
Measurement of impact sound insulation**

*Acoustique — Mesurage en laboratoire de l'isolation acoustique des  
éléments de construction —*

**iTeh STANDARD PREVIEW**  
*Partie 3: Mesurage de l'isolation au bruit de choc*  
**(standards.iteh.ai)**

ISO 10140-3:2010

<https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 10140-3:2010](https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010)

<https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword .....	iv
Introduction.....	v
1 Scope .....	1
2 Normative references .....	2
3 Terms and definitions .....	2
4 Facilities and equipment.....	3
5 Test procedure and evaluation .....	3
6 Test arrangement .....	5
7 Limits of performance.....	5
8 Precision.....	5
9 Test report.....	6
Annex A (informative) Measurement using heavy and soft impact sources .....	7
Annex B (informative) Form for the expression of results .....	10
Bibliography.....	12

ISO 10140-3:2010

<https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10140-3 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*.

This first edition of ISO 10140-3, together with ISO 10140-1, ISO 10140-2, ISO 10140-4 and ISO 10140-5, cancels and replaces ISO 140-1:1997, ISO 140-3:1995, ISO 140-6:1998, ISO 140-8:1997, ISO 140-10:1991, ISO 140-11:2005 and ISO 140-16:2006, which have been technically revised.

It also incorporates the Amendments ISO 140-1:1997/Amd.1:2004 and ISO 140-3:1995/Amd.1:2004.

ISO 10140 consists of the following parts, under the general title *Acoustics — Laboratory measurement of sound insulation of building elements*:

- *Part 1: Application rules for specific products*
- *Part 2: Measurement of airborne sound insulation*
- *Part 3: Measurement of impact sound insulation*
- *Part 4: Measurement procedures and requirements*
- *Part 5: Requirements for test facilities and equipment*

## Introduction

ISO 10140 (all parts) concerns laboratory measurement of the sound insulation of building elements (see Table 1).

ISO 10140-1 specifies the application rules for specific elements and products, including specific requirements for preparation, mounting, operating and test conditions. ISO 10140-2 and this part of ISO 10140 contain the general procedures for airborne and impact sound insulation measurements, respectively, and refer to ISO 10140-4 and ISO 10140-5 where appropriate. For elements and products without a specific application rule described in ISO 10140-1, it is possible to apply ISO 10140-2 and this part of ISO 10140. ISO 10140-4 contains basic measurement techniques and processes. ISO 10140-5 contains requirements for test facilities and equipment. For the structure of ISO 10140 (all parts), see Table 1.

ISO 10140 (all parts) was created to improve the layout for laboratory measurements, ensure consistency and simplify future changes and additions regarding mounting conditions of test elements in laboratory and field measurements. It is intended for ISO 10140 (all parts) to present a well-written and arranged format for laboratory measurements.

It is intended to update ISO 10140-1 with application rules for other products. It is also intended to incorporate ISO 140-18 into ISO 10140 (all parts).

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 10140-3:2010](https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010)

<https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010>

Table 1 — Structure and contents of ISO 10140 (all parts)

Relevant part of ISO 10140	Main purpose, contents and use	Detailed content
ISO 10140-1	It indicates the appropriate test procedure for elements and products. For certain types of element/product, it can contain additional and more specific instructions about quantities and test element size and about preparation, mounting and operating conditions. Where no specific details are included, the general guidelines are according to ISO 10140-2 and ISO 10140-3.	Appropriate references to ISO 10140-2 and ISO 10140-3 and product-related, specific and additional instructions on: <ul style="list-style-type: none"> <li>— specific quantities measured;</li> <li>— size of test element;</li> <li>— boundary and mounting conditions;</li> <li>— conditioning, testing and operating conditions;</li> <li>— additional specifics for test report.</li> </ul>
ISO 10140-2	It gives a complete procedure for airborne sound insulation measurements according to ISO 10140-4 and ISO 10140-5. For products without specific application rules, it is sufficiently complete and general for the execution of measurements. However, for products with specific application rules, measurements are carried out according to ISO 10140-1, if available.	<ul style="list-style-type: none"> <li>— Definitions of main quantities measured</li> <li>— General mounting and boundary conditions</li> <li>— General measurement procedure</li> <li>— Data processing</li> <li>— Test report (general points)</li> </ul>
ISO 10140-3	It gives a complete procedure for impact sound insulation measurements according to ISO 10140-4 and ISO 10140-5. For products without specific application rules, it is sufficiently complete and general for the execution of measurements. However, for products with specific application rules, measurements are carried out according to ISO 10140-1, if available.	<ul style="list-style-type: none"> <li>— Definitions of main quantities measured</li> <li>— General mounting and boundary conditions</li> <li>— General measurement procedure</li> <li>— Data processing</li> <li>— Test report (general points)</li> </ul>
ISO 10140-4	It gives all the basic measurement techniques and processes for measurement according to ISO 10140-2 and ISO 10140-3 or facility qualifications according to ISO 10140-5. Much of the content is implemented in software.	<ul style="list-style-type: none"> <li>— Definitions</li> <li>— Frequency range</li> <li>— Microphone positions</li> <li>— SPL measurements</li> <li>— Averaging, space and time</li> <li>— Correction for background noise</li> <li>— Reverberation time measurements</li> <li>— Loss factor measurements</li> <li>— Low-frequency measurements</li> <li>— Radiated sound power by velocity measurement</li> </ul>
ISO 10140-5	It specifies all information needed to design, construct and qualify the laboratory facility, its additional accessories and measurement equipment (hardware).	<p>Test facilities, design criteria:</p> <ul style="list-style-type: none"> <li>— volumes, dimensions;</li> <li>— flanking transmission;</li> <li>— laboratory loss factor;</li> <li>— maximum achievable sound reduction index;</li> <li>— reverberation time;</li> <li>— influence of lack of diffusivity in the laboratory.</li> </ul> <p>Test openings:</p> <ul style="list-style-type: none"> <li>— standard openings for walls and floors;</li> <li>— other openings (windows, doors, small technical elements);</li> <li>— filler walls in general.</li> </ul> <p>Requirements for equipment:</p> <ul style="list-style-type: none"> <li>— loudspeakers, number, positions;</li> <li>— tapping machine and other impact sources;</li> <li>— measurement equipment.</li> </ul> <p>Reference constructions:</p> <ul style="list-style-type: none"> <li>— basic elements for airborne and impact insulation improvement;</li> <li>— corresponding reference performance curves.</li> </ul>

# Acoustics — Laboratory measurement of sound insulation of building elements —

## Part 3: Measurement of impact sound insulation

### 1 Scope

This part of ISO 10140 specifies laboratory methods for measuring the impact sound insulation of floor assemblies.

The test results can be used to compare the sound insulation properties of building elements, classify elements according to their sound insulation capabilities, help design building products which require certain acoustic properties and estimate the *in situ* performance in complete buildings.

The measurements are performed in laboratory test facilities in which sound transmission via flanking paths is suppressed. The results of measurements made in accordance with this part of ISO 10140 are not applicable directly to the field situation without accounting for other factors affecting sound insulation, such as flanking transmission, boundary conditions, and loss factor.

A test method is specified that uses the standard tapping machine (see ISO 10140-5:2010, Annex E) to simulate impact sources like human footsteps when a person is wearing shoes. This part of ISO 10140 is applicable to all types of floors (whether heavyweight or lightweight) with all types of floor coverings. The test method applies only to laboratory measurements.

**NOTE** When the aim of impact sound insulation measurements is to have a strong correlation between a “real” impact source (e.g. a person walking or children jumping) and an artificial impact source (e.g. a tapping machine), it is intended that both sources apply the same input force spectrum to ensure the correct ranking of floors and floor coverings for the “real” and the artificial source, and it is intended that the impedance spectra of the sources be the same. If the “real” impact source is a walking person without shoes and the artificial source is a standard tapping machine such as that specified in Clause 4, the correlation is not strong.

An alternative method, using a heavy/soft impact source for assessing the impact sound insulation of a floor against impact sources with strong low-frequency components, such as human footsteps (bare feet) or children jumping, is given in Annex A. Alternative impact sources (i.e. a proposed modification of the standard tapping machine to make its dynamic source characteristics similar to those of a person walking barefoot and a heavy/soft impact source with dynamic source characteristics similar to those of children jumping) are defined in ISO 10140-5:2010, Annex F.

A method to test floor coverings is described in ISO 10140-1:2010, Annex H, for single- or multi-layer floor coverings installed on specific reference floors. In the case of multi-layer coverings, they can be factory-assembled or assembled at the test site.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 140-2, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 2: Determination, verification and application of precision data*

ISO 717-2, *Acoustics — Rating of sound insulation in buildings and of building elements — Part 2: Impact sound insulation*

ISO 10140-1, *Acoustics — Laboratory measurement of sound insulation of building elements — Part 1: Application rules for specific products*

ISO 10140-4, *Acoustics — Laboratory measurement of sound insulation of building elements — Part 4: Measurement procedures and requirements*

ISO 10140-5, *Acoustics — Laboratory measurement of sound insulation of building elements — Part 5: Requirements for test facilities and equipment*

IEC 60942, *Electroacoustics — Sound calibrators*

IEC 61260, *Electroacoustics — Octave-band and fractional-octave-band filters*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

## 3 Terms and definitions

ISO 10140-3:2010

For the purpose of this document, the following terms and definitions apply.

### 3.1

#### impact sound pressure level

$L_i$

energy average sound pressure level in a one-third octave band in the receiving room when the floor under test is excited by the standardized impact source

NOTE 1  $L_i$  is expressed in decibels.

NOTE 2 The energy average sound pressure level in a room is defined in ISO 10140-4.

### 3.2

#### normalized impact sound pressure level

$L_n$

impact sound pressure level,  $L_i$ , increased by a correction term which is given in decibels, being ten times the common logarithm of the ratio between the measured equivalent absorption area,  $A$ , of the receiving room and the reference equivalent absorption area,  $A_0$

$$L_n = L_i + 10 \lg \frac{A}{A_0} \text{ dB} \quad (1)$$

where  $A_0 = 10 \text{ m}^2$ .

NOTE 1  $L_n$  is expressed in decibels.

NOTE 2 The measured equivalent absorption area,  $A$ , of the receiving room is defined in ISO 10140-4.



## 4 Facilities and equipment

Laboratory test facilities shall comply with the requirements of ISO 10140-5:2010, Annex A.

The tapping machine shall meet the requirements given in ISO 10140-5:2010, Annex E.

Requirements for equipment used to measure the sound level, and for calibration of that equipment, are given in ISO 10140-5.

**NOTE** Alternative methods using a modified tapping machine or a standard heavy/soft impact source can provide information suitable for assessing the impact sound insulation of a floor or a floor covering against common impact sources, for instance a person walking without shoes or a child jumping. Procedures for measurements using a heavy/soft impact source are given in Annex A, with requirements for alternate impact sources given in ISO 10140-5:2010, Annex F.

## 5 Test procedure and evaluation

### 5.1 General procedure

Two vertically adjacent rooms are used, the upper one being designated the “source room” and the lower one the “receiving room”. A floor, which is the test element, separates these two rooms (see Clause 6). The impact source is placed on top of the test element at different positions and the sound pressure levels are measured in the receiving room, normally in the frequency range of 100 Hz to 5 000 Hz (optional down to 50 Hz). The equivalent sound absorption area in the receiving room is calculated from reverberation time measurements. From the sound pressure levels in the receiving room, the quantities described in Clause 3 shall be evaluated by taking into account the equivalent absorption area. The procedures used to determine the energy average sound pressure level corrected for background noise and the reverberation time are specified in ISO 10140-4:2010, 4.2 and 4.3.

Precautions should be taken to verify that airborne sound transmission from the source to the receiving room (including any leakage at the perimeter of the test element) is at least 10 dB below the level of transmitted impact sound in each frequency band.

A method for testing floor coverings is described in ISO 10140-1:2010, Annex H, for single- or multi-layer floor coverings installed on specific reference floors. In the case of multi-layer coverings, they may be factory-assembled or assembled at the test site.

### 5.2 Generation of sound field

The impact sound shall be generated by the standard tapping machine, as specified in Clause 4. Each set of measurements should be made with as many impact source positions as necessary to yield a reliable mean value.

**NOTE** When the aim of impact sound insulation measurements is to have a strong correlation between a “real” impact source (e.g. a person walking or children jumping) and an artificial impact source (e.g. a tapping machine), both sources apply the same input force spectrum, to ensure the correct ranking of floors and floor coverings for the “real” and the artificial source, and the impedance spectra of the sources are the same. If the “real” impact source is a walking person without shoes and the artificial source is a standard tapping machine such as that specified in Clause 4, the correlation is not strong.

An alternative method, using a heavy/soft impact source for assessing the impact sound insulation of a floor against impact sources with strong low-frequency components, such as human footsteps (bare feet) or children jumping, is given in Annex A. Alternative impact sources (i.e. a proposed modification of the standard tapping machine to make its dynamic source characteristics similar to those of a person walking barefoot and a heavy/soft impact source with dynamic source characteristics similar to those of children jumping) are defined in ISO 10140-5:2010, Annex F.

When a floor element includes a soft covering, the standard tapping machine shall fulfil special requirements (specified in ISO 10140-5:2010, Annex E). If the test surface is covered with an extremely soft covering or the

surface is very uneven, such that the hammers are not able to fall down the requisite 40 mm to the surface on which the supports rest, pads may be used under the supports to ensure the correct falling height of 40 mm.

The impact sound pressure levels can reveal a time dependency after the tapping has started. In such a case, the measurements should not begin until the noise level has become steady. The measurement period shall be reported. If stable conditions are not reached after 5 min, the measurements should be carried out over a well-defined measurement period.

For testing a floor, the tapping machine shall be placed in at least four different positions. The minimum distance between tapping machine positions shall be at least 0,7 m. The distance of the tapping machine from the edges of the floor shall be at least 0,5 m.

For heavyweight homogeneous floors, such as solid concrete, the positions and orientation of the tapping machine shall be randomly distributed over the whole area of the floor under test.

For inhomogeneous floor constructions (such as hollow core concrete slabs or lightweight floors with ribs, beams, joists, etc.) or floors with rough and/or irregular floor coverings, additional positions should be used to yield a reliable mean value. The positions shall be randomly distributed on the floor under test. The line of hammers shall be orientated at 45° to the direction of the beams, ribs or joists (see ISO 10140-1:2010, H.4.6.2).

Additional requirements for positioning the tapping machine when testing floor coverings are given in ISO 10140-1:2010, Annex H. Each set of measurements (bare floor and covered floor) shall be made with as many machine positions as necessary to yield a reliable mean value, but the specific locations and the number of positions depend both on the category of floor covering and on the type of reference floor on which the covering is installed.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

The sound field in the receiving room shall not be affected by the presence of people in the source or receiving room during the tests.

ISO 10140-3:2010

**5.3 Data processing** <https://standards.iteh.ai/catalog/standards/sist/41c040ea-8494-4234-b7c9-5ae74c574a47/iso-10140-3-2010>

Calculate the normalized impact sound pressure levels (as defined in Clause 3) from the measured (and, if necessary, corrected-for-background noise) energy average sound pressure levels in the receiving room and the measured reverberation times, as described in ISO 10140-4:2010, 4.2, 4.3, 4.5 and 4.6.

If normalized impact sound pressure levels are needed in octave bands, these values shall be calculated from the three one-third octave band values in each octave band using Equation (2):

$$L_{n,\text{oct}} = 10 \lg \left( \sum_{j=1}^3 10^{L_{n,1/3\text{oct},j}/10} \right) \quad (2)$$

Perform all calculations with the appropriate accuracy and present the final results with a precision no higher than the nearest 0,1 dB.

The evaluation of the single-number rating from the results in one-third octave bands shall be done in accordance with ISO 717-2.

**5.4 Expression of results**

For the statement of the impact sound insulation of the test element, the normalized impact sound pressure level,  $L_n$ , shall be given in decibels at all frequencies of measurement, to one decimal place, both in tabular form and in the form of a curve.

For the statement of the change of impact sound pressure level due to a floor covering, the results shall be given at all frequencies of measurement, to one decimal place, both in tabular form and in the form of a graph.

Graphs in the test report shall show the value, in decibels, plotted against frequency on a logarithmic scale and the following dimensions shall be used:

- a) 5 mm for a one-third octave band;
- b) 20 mm for 10 dB.

The use of a test report form in accordance with Annex B is preferred. For this short version of the test report, state all information of importance regarding the test element, the test procedure and the test results.

## 6 Test arrangement

### 6.1 General

General requirements for the preparation, curing, installation and mounting of test elements are described in this clause. For specific types of elements and products, detailed specifications may be given in related documents; for instance, test codes are covered in ISO 10140-1. When testing the reduction of impact sound pressure level by floor coverings, follow the requirements of ISO 10140-1:2010, Annex H.

### 6.2 Types of installation

#### 6.2.1 Floor element

The size of the floor is determined by the size of the test opening of the laboratory test facility, as defined in ISO 10140-5.

The floor should be installed in a similar manner to the actual construction using normal connections and sealing conditions at the perimeter and at all joints. The mounting conditions shall be stated in the test report.

The impact sound insulation of heavyweight solid floors depends on structural coupling to the laboratory structure. In order to describe the effect of the mounting, it is recommended that the total loss factor be measured and stated in the test report (see ISO 10140-4:2010, 4.7).

#### 6.2.2 Floor covering

The permissible area and location for installation of floor coverings, and requirements for their installation are specified in ISO 10140-1:2010, Annex H. This defines three categories of floor coverings, for which different installation and testing procedures apply depending on the category of floor covering and the type of reference floor on which it is tested.

## 7 Limits of performance

The sound radiated by flanking elements should be negligible compared to the sound radiated from the floor under test. The procedure to check this is given in ISO 10140-5:2010, Annex A.

The laboratory shall suppress airborne sound transmission from the source room into the receiving room, such that the level is at least 10 dB below the level of transmitted impact sound in each frequency band.

## 8 Precision

The measurement procedure shall give satisfactory repeatability. This shall be determined in accordance with the method shown in ISO 140-2 and shall be verified from time to time, particularly when a change is made in the procedure or instrumentation.

NOTE Numerical requirements for repeatability are given in ISO 140-2.