



---

Reference

DTS/ITS-00140

---

Keywords

ITS, testing, TSS&TP

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	5
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations .....	6
4 Test Suite Structure (TSS).....	6
4.1 Structure for MAP-SPAT tests.....	6
4.2 Test groups .....	6
4.2.1 Introduction.....	6
4.2.2 Root .....	6
4.2.3 Groups .....	7
4.2.4 Categories .....	7
5 Test Purposes (TPs).....	7
5.1 Introduction .....	7
5.1.1 TP definition conventions.....	7
5.1.2 TP Identifier naming conventions.....	7
5.1.3 Rules for the behaviour description.....	7
5.1.4 Sources of TP definitions.....	7
5.1.5 Mnemonics for PICS reference.....	7
5.2 Test purposes for MAP-SPAT.....	8
5.2.1 Message dissemination .....	8
5.2.2 Message processing .....	13
<b>Annex A (normative):      Communication Parameter Settings .....</b>	<b>15</b>
<b>Annex B (informative):    Bibliography.....</b>	<b>16</b>
History .....	17

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 2 of a multi-part deliverable covering Conformance test specification for Signal Phase And Timing (SPAT) and Map (MAP), as identified below:

- Part 1: "Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma";
  - Part 2: "Test Suite Structure and Test Purposes (TSS & TP)";**
  - Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- 

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document provides the Test Suite Structure and Test Purposes (TSS & TP) for MAP-SPAT Messages (MAP-SPAT) as defined in SAE J2735 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [5].

The ISO standard for the methodology of conformance testing (ISO/IEC 9646-1 [3] and ISO/IEC 9646-2 [4]) as well as the ETSI rules for conformance testing (ETSI ETS 300 406 [6]) are used as a basis for the test methodology.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] SAE J2735 (2015-04-30): "Dedicated Short Range Communications (DSRC) Message Set Dictionary™".
- [2] ETSI TS 103 191-1 (V1.1.1): "Intelligent Transport Systems (ITS); Testing; Conformance test specifications for Signal Phase And Timing (SPAT) and Map (MAP); Part 1: Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma".
- [3] ISO/IEC 9646-1 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".
- [4] ISO/IEC 9646-2 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 2: Abstract Test Suite specification".
- [5] ISO/IEC 9646-7 (1995): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [6] ETSI ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [7] ETSI EN 302 636-5-1 (V1.2.1): "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 5: Transport Protocols; Sub-part 1: Basic Transport Protocol".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 202 798 (V1.1.1): "Intelligent Transport Systems (ITS); Testing; Framework for conformance and interoperability testing".

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in SAE J2735 [1], ISO/IEC 9646-1 [3] and in ISO/IEC 9646-7 [5] apply.

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATS	Abstract Test Suite
BV	Valid test events for Behaviour tests
BTP	Basic Transport Protocol
GN	GeoNetworking
ISO	International Organization for Standardization
ITS	Intelligent Transport Systems
IUT	Implementation Under Test
MAP	MapData Messages
MSD	Message Dissemination
MSP	Message Processing
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
SAE	Society of Automotive Engineers
SHB	Single Hop Broadcast
SPAT	Signal Phase And Timing Messages
TP	Test Purposes
TSS	Test Suite Structure

## 4 Test Suite Structure (TSS)

### 4.1 Structure for MAP-SPAT tests

Table 1 shows the MAP-SPAT Test Suite Structure (TSS) including its subgroups defined for conformance testing.

**Table 1: TSS for MAP-SPAT**

Root	Group	Category
MAP-SPAT	Message Dissemination	Valid
	Message processing	Valid

The test suite is structured as a tree with the root defined as MAP-SPAT. The tree is of rank 2 with the first rank a Group and the second a category. The second rank is the standard ISO conformance test categories.

### 4.2 Test groups

#### 4.2.1 Introduction

The test suite has a total of three levels. The first level is the root. The second level separates the root into various functional areas. The third level is the standard ISO conformance test categories.

#### 4.2.2 Root

The root identifies the MapData and SPAT Messages given in SAE J2735 [1].

## 4.2.3 Groups

This level contains two functional areas identified as:

- Message Dissemination
- Message Processing

## 4.2.4 Categories

This level contains the standard ISO conformance test categories limited to valid behaviour.

# 5 Test Purposes (TPs)

## 5.1 Introduction

### 5.1.1 TP definition conventions

The TP definition is built according to ETSI EG 202 798 [i.1].

### 5.1.2 TP Identifier naming conventions

The identifier of the TP is built according to table 2.

**Table 2: TP naming convention**

Identifier	TP/<root>/<gr>/<x>/<nn>		
	<root> = root	MAP-SPAT	
	<gr> = group	MSD	Message Dissemination
		MSP	Message Processing
	<x> = type of testing	BV	Valid event tests
	<nn> = sequential number		01 to 99

### 5.1.3 Rules for the behaviour description

The description of the TP is built according to ETSI EG 202 798 [i.1].

SAE J2735 [1] does not use finite state machine concept. As consequence, the test purposes use a generic "Initial State" that corresponds to a state where the IUT is ready for starting the test execution. Furthermore, the IUT shall be left in this "Initial State", when the test is completed.

Being in the "Initial State" refers to the starting point of the initial device configuration. There are no pending actions, no instantiated buffers or variables, which could disturb the execution of a test.

### 5.1.4 Sources of TP definitions

All TPs are specified according to SAE J2735 [1].

### 5.1.5 Mnemonics for PICS reference

To avoid an update of all TPs when the PICS document is changed, table 3 introduces mnemonics name and the correspondence with the real PICS item number.

The PICS item column refers to Table/Item of ETSI TS 103 191-1 [2].

**Table 3: Mnemonics for PICS reference**

Mnemonic	PICS item
PICS_RSU	A.1/1
PICS_VEHICLE	A.1/2

## 5.2 Test purposes for MAP-SPAT

### 5.2.1 Message dissemination

<b>TP Id</b>	TP/MAP-SPAT/MSD/BV-01
<b>Test objective</b>	Verify that when sending a MapData message the DSRCmsgSubID is set to value 1.
<b>Reference</b>	SAE J2735 [1], clause 7.34
<b>PICS Selection</b>	PICS_RSU
<b>Initial conditions</b>	
with { the IUT being in the "initial state" }	
<b>Expected behaviour</b>	
ensure that { when { a MapData message is generated } then { the IUT sends a valid MapData message containing DSRCmsgSubID set to value 1 } }	

<b>TP Id</b>	TP/MAP-SPAT/MSD/BV-02
<b>Test objective</b>	Verify that when sending a SPAT message the DSRCmsgSubID is set to value 1.
<b>Reference</b>	SAE J2735 [1], clause 7.34
<b>PICS Selection</b>	PICS_RSU
<b>Initial conditions</b>	
with { the IUT being in the "initial state" }	
<b>Expected behaviour</b>	
ensure that { when { a SPAT message is generated } then { the IUT sends a valid SPAT message containing DSRCmsgSubID set to value 1 } }	



<b>TP Id</b>	TP/MAP-SPAT/MSD/BV-03
<b>Test objective</b>	Verify that when the IUT sends a new MapData message with a new content the MsgCount is set to one greater than the previous value sent.
<b>Reference</b>	SAE J2735 [1], clause 7.92
<b>PICS Selection</b>	PICS_RSU
<b>Initial conditions</b>	
with { the IUT being in the "initial state" and the IUT has sent a MapData message containing MsgCount set to VALUE_1 }	
<b>Expected behaviour</b>	
ensure that { when { a new MapData message with a new content is generated } then { the IUT sends a valid MapData message containing MsgCount set to VALUE_1 + 1 } }	

<b>TP Id</b>	TP/MAP-SPAT/MSD/BV-04 [1]
<b>Test objective</b>	Verify that when the IUT sends a new MapData message with a new content the MsgCount is set to 0 when the previous sent value was 127.
<b>Reference</b>	SAE J2735 [1], clause 7.92
<b>PICS Selection</b>	PICS_RSU
<b>Initial conditions</b>	
with { the IUT being in the "initial state" and the IUT has sent a MapData message containing MsgCount set to 127 }	
<b>Expected behaviour</b>	
ensure that { when { a new MapData message with a new content is generated } then { the IUT sends a valid MapData message containing MsgCount set to 0 } }	