



**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 3: Medium Access Control (MAC) layer**

Standard Preview
(standards.iteh.ai)
Full standard/catalog/standards/sku/300175-3-2015031741-fc90-438c-b200-79528616a367/etsi-en-300-175-3-v2.5.8-2015031741-fc90-438c-b200-79528616a367

Reference

REN/DECT-000304-3

KeywordsDECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	16
Foreword.....	16
Modal verbs terminology.....	16
1 Scope	17
2 References	17
2.1 Normative references	17
2.2 Informative references.....	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols and abbreviations.....	19
4 Description of the MAC layer	22
4.1 MAC layer reference model	22
4.1.1 General.....	22
4.1.2 Cluster Control Function (CCF)	23
4.1.3 Cell Site Functions (CSF).....	23
4.1.4 Relationship to physical layer elements.....	23
4.2 Frame and multiframe structures.....	24
4.2.1 General.....	24
4.2.2 Frame structure	24
4.2.3 Multiframe structure	25
4.3 State definitions.....	26
4.3.1 PP states.....	26
4.3.2 RFP states	27
5 Overview of MAC layer services	27
5.1 General	27
5.1.0 Service groupings	27
5.1.1 Broadcast Message Control (BMC).....	28
5.1.2 Connectionless Message Control (CMC).....	28
5.1.3 Multi-Bearer Control	28
5.2 Service descriptions.....	28
5.2.1 Common functions.....	28
5.2.2 BMC service	28
5.2.3 CMC service	29
5.2.4 MBC services.....	29
5.3 Logical channels.....	29
5.3.0 Overview	29
5.3.1 MBC connection endpoints (MC-SAP logical channels)	30
5.3.1.1 The higher layer C-plane channels, C	30
5.3.1.2 The higher layer U-Plane channels, I	30
5.3.1.3 The higher layer U-Plane control channels, G _F and G _{FA}	31
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	31
5.3.2 CMC endpoints (MB-SAP logical channels).....	32
5.3.2.1 The connectionless C-Plane channels, CL	32
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	32
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	32
5.3.3 BMC endpoint (MA-SAP logical channel).....	32
5.3.3.1 The slow broadcast channel, B _S	32
5.3.3.2 The ULE broadcast channel, B _U	33
5.3.4 Internal MAC control channels.....	33
5.3.4.1 The system information channel, Q	33
5.3.4.2 Identities channel, N.....	33
5.3.4.3 The MAC control channel, M	33
5.3.4.4 MAC paging channel, P	33
5.3.4.5 The Compound System Information Channel, Q _C	34

5.3.4.6	The Split Identities Channel, N_s	34
5.3.4.7	The ULE MAC Control Channel, M_U	34
5.3.4.8	The ULE Paging Channel, P_U	34
5.4	SAP definitions	34
5.4.0	General.....	34
5.4.1	MA SAP	34
5.4.2	MB SAP.....	35
5.4.3	MC SAP.....	35
5.4.4	ME SAP.....	36
5.4.5	Order of transmission.....	36
5.5	Bearer.....	36
5.5.0	General.....	36
5.5.1	Bearer types	36
5.5.2	Bearer operation.....	37
5.6	Connection oriented services.....	37
5.6.0	General.....	37
5.6.1	Connection types	37
5.6.1.0	General	37
5.6.1.1	Basic connections.....	37
5.6.1.2	Advanced connections	38
5.6.1.2.0	General	38
5.6.1.2.1	Rules for ECN selection in advanced connections	38
5.6.1.2.2	Expedited operations in advanced connections	38
5.6.1.3	Connection identifiers	39
5.6.1.4	Complementary connections	39
5.6.2	Symmetric and asymmetric connections.....	39
5.6.2.0	General	39
5.6.2.1	Symmetric connections	39
5.6.2.2	Asymmetric connections	45
5.7	Broadcast and connectionless services.....	56
5.7.0	General.....	56
5.7.1	The broadcast services	56
5.7.1.0	General	56
5.7.1.1	The continuous broadcast service	56
5.7.1.2	The non-continuous broadcast service	57
5.7.2	The connectionless services	57
5.7.2.0	General	57
5.7.2.1	Connectionless downlink services	57
5.7.2.1.1	Coding of TA and BA bits in connectionless downlink services	58
5.7.2.2	Connectionless uplink services	58
5.8	ULE Broadcast services	59
5.8.0	General.....	59
5.8.1	The continuous ULE broadcast service	59
6	Multiplexing.....	59
6.0	General	59
6.1	CCF multiplexing functions	59
6.2	CSF multiplexing functions.....	59
6.2.0	General.....	59
6.2.1	Bit Mappings (MAP)	65
6.2.1.0	General	65
6.2.1.1	D-field mapping (D-MAP).....	65
6.2.1.1.0	General	65
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	66
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	66
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	67
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	68
6.2.1.2	A-field Mapping (A-MAP)	69
6.2.1.3	B-field Mapping (B-MAP).....	70
6.2.1.3.0	General	70
6.2.1.3.1	Unprotected format.....	70

6.2.1.3.2	Encoded protected format.....	71
6.2.1.3.3	Multisubfield protected format.....	72
6.2.1.3.4	Singlesubfield protected format switches.....	75
6.2.1.3.5	Constant-size subfield protected format.....	76
6.2.2	Time multiplexers.....	79
6.2.2.0	General.....	79
6.2.2.1	Tail MULTipleXer (T-MUX).....	79
6.2.2.1.0	General.....	79
6.2.2.1.1	T-MUX algorithm for RFP transmissions.....	79
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	81
6.2.2.2	B-field control multiplexer (E/U-MUX).....	82
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes.....	84
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield.....	84
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation.....	97
6.2.2.4	Priority scheme in E or E+U mode.....	98
6.2.3	MAC Encryption.....	99
6.2.4	Scrambling.....	99
6.2.5	Error control.....	101
6.2.5.0	General.....	101
6.2.5.1	R-CRC overview.....	101
6.2.5.2	R-CRC generation and checking.....	102
6.2.5.3	X-CRC overview.....	102
6.2.5.4	X-CRC generation and checking.....	102
6.2.5.5	B-CRC generation and checking.....	104
6.2.6	Broadcast controller.....	105
7	Medium access layer messages.....	105
7.0	General.....	105
7.1	Header field.....	106
7.1.1	Overview/formatting.....	106
7.1.2	Tail identification, TA, bits a_0 to a_2	106
7.1.3	The "Q1/BCK" bit, bit a_3	106
7.1.4	B-field identification, BA, bits a_4 to a_6	107
7.1.5	The "Q2" bit, bit a_7	108
7.2	Messages in the tail field.....	108
7.2.1	Overview.....	108
7.2.2	Identities information (N_T).....	109
7.2.3	System information and multiframe marker (Q_T).....	109
7.2.3.1	General.....	109
7.2.3.2	Static system information.....	110
7.2.3.2.1	General, $Q_H = 0, 1$ (hex).....	110
7.2.3.2.2	Q_H and Normal-Reverse (NR).....	110
7.2.3.2.3	Slot Number (SN).....	110
7.2.3.2.4	Start Position (SP).....	111
7.2.3.2.5	ESCAPE bit (ESC).....	111
7.2.3.2.6	Number of transceivers.....	111
7.2.3.2.7	Extended RF carrier information available (M_c).....	112
7.2.3.2.8	RF carriers available (RF-cars).....	112
7.2.3.2.9	Spare bits (SPR).....	112
7.2.3.2.10	Carrier number.....	112
7.2.3.2.11	Extended static system information available (Ext-System-Info) and spare bit.....	113
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	113
7.2.3.3	Extended RF carrier information part 1.....	113
7.2.3.3.1	General, $Q_H = 2$ (hex).....	113
7.2.3.3.2	Further RF carrier extensions.....	114
7.2.3.3.3	Number of RF carriers.....	114
7.2.3.4	Fixed part capabilities.....	114
7.2.3.4.1	General, $Q_H = 3$ (hex).....	114
7.2.3.4.2	Standard capabilities.....	114
7.2.3.5	Extended fixed part capabilities.....	115
7.2.3.5.1	General, $Q_H = 4$ (hex).....	115
7.2.3.5.2	Extended Physical and MAC layer capabilities.....	116

7.2.3.5.3	Extended higher layer capabilities	117
7.2.3.6	Secondary access rights identities	117
7.2.3.6.1	General, $Q_H = 5$ (hex)	117
7.2.3.6.2	SARI message	117
7.2.3.7	Multiframe number	117
7.2.3.7.1	General, $Q_H = 6$ (hex)	117
7.2.3.7.2	Multiframe number	117
7.2.3.8	Escape	118
7.2.3.8.1	General, $Q_H = 7$ (hex)	118
7.2.3.8.2	Escape information	118
7.2.3.9	Extended RF carrier information part 2	118
7.2.3.9.1	General, $Q_H = 9$ (hex)	118
7.2.3.10	Transmit information	118
7.2.3.10.1	General, $Q_H = B$ (hex)	118
7.2.3.11	Extended fixed part capabilities (part 2)	119
7.2.3.11.1	General, $Q_H = C$ (hex)	119
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2)	119
7.2.3.11.3	Extended higher layer capabilities (part 2)	120
7.2.3.12	Extended static system information	120
7.2.3.12.1	General, $Q_H = D$ (hex)	120
7.2.3.12.2	Spare bits (Spare)	121
7.2.3.12.3	RFP slot scheme info	121
7.2.4	Paging Tail (P_T)	121
7.2.4.1	General format	121
7.2.4.1.1	P_T format for full and long page messages	121
7.2.4.1.2	P_T format for short page messages	122
7.2.4.1.3	P_T format for zero length page messages	122
7.2.4.1.4	P_T format for MAC_Resume_and_Control_page message	122
7.2.4.2	P_T header format	123
7.2.4.2.1	General format	123
7.2.4.2.2	Bit a_8 is the extend flag	123
7.2.4.2.3	B_8 SDU length indication	123
7.2.4.3	MAC layer information for P_T	123
7.2.4.3.1	Information type	123
7.2.4.3.2	Fill bits / Blind long slot ($j=640$ / $j=672$) information	124
7.2.4.3.3	Blind full slot information	124
7.2.4.3.4	Bearer description	125
7.2.4.3.5	Escape	125
7.2.4.3.6	Dummy or connectionless downlink bearer marker	125
7.2.4.3.7	Bearer handover/replacement and no-emission mode information	126
7.2.4.3.8	RFP status and modulation types	126
7.2.4.3.9	Active carriers	127
7.2.4.3.10	RFP power level	128
7.2.4.3.11	Blind double slot/RFP-FP interface resource information	128
7.2.4.3.12	Extended modulation types	129
7.2.5	MAC control (M_T)	129
7.2.5.1	General format and contents	129
7.2.5.2	Basic connection control	130
7.2.5.2.1	General	130
7.2.5.2.2	Format for most messages	130
7.2.5.2.3	WAIT	131
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}	131
7.2.5.3	Advanced connection control	131
7.2.5.3.1	General	131
7.2.5.3.2	ACCESS_REQUEST	131
7.2.5.3.3	BEARER_HANDOVER_REQUEST	132
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST	132
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST	132
7.2.5.3.6	BEARER_CONFIRM	132
7.2.5.3.7	WAIT	132
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}	132
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}	135

7.2.5.3.10	Channel_list.....	135
7.2.5.3.11	Unconfirmed_dummy.....	136
7.2.5.3.12	Unconfirmed_handover.....	136
7.2.5.3.13	RELEASE.....	136
7.2.5.4	MAC layer test messages.....	137
7.2.5.4.0	General.....	137
7.2.5.4.1	Basic format.....	137
7.2.5.4.2	FORCE_TRANSMIT.....	138
7.2.5.4.3	LOOPBACK_DATA.....	138
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	139
7.2.5.4.5	ESCAPE.....	139
7.2.5.4.6	NETWORK_TEST.....	140
7.2.5.4.7	CLEAR_TEST_MODES.....	140
7.2.5.4.8	CHANGE_MODULATION_SCHEME.....	140
7.2.5.5	Quality control.....	141
7.2.5.5.0	General.....	141
7.2.5.5.1	Prolonged preamble diversity.....	142
7.2.5.6	Broadcast and connectionless services.....	142
7.2.5.7	Encryption control.....	143
7.2.5.8	B-field setup, first PT transmission.....	144
7.2.5.9	Escape.....	144
7.2.5.10	TARI message.....	145
7.2.5.11	REP connection control.....	145
7.2.5.11.1	General.....	145
7.2.5.11.2	Format for most messages.....	145
7.2.5.11.3	REP CHANNEL MAP REQUEST.....	145
7.2.5.11.4	REP CHANNEL MAP CONFIRM.....	146
7.2.5.12	Advanced connection control part 2.....	146
7.2.5.12.1	General.....	146
7.2.5.12.2	Short description of the advanced connection control part 2 messages.....	146
7.2.5.12.3	Format for most advanced connection control part 2 messages.....	147
7.2.5.12.4	Format for "ready for release with G _{FA} " and "expedited release with G _{FA} " messages.....	147
7.2.5.12.5	Reason codes in "ready for release with G _{FA} " and "expedited release with G _{FA} " messages.....	149
7.2.5.12.6	Format for "Null or GF _A channel transmission" message.....	150
7.3	Messages in the B-field.....	151
7.3.1	Overview.....	151
7.3.2	Advanced connection control.....	152
7.3.2.1	General format.....	152
7.3.2.2	BEARER_REQUEST.....	153
7.3.2.3	BEARER_CONFIRM.....	153
7.3.2.4	WAIT.....	154
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}.....	154
7.3.2.6	BANDWIDTH_B_{Req;Cfm}.....	155
7.3.2.7	CHANNEL_LIST.....	155
7.3.2.8	UNCONFIRMED_DUMMY.....	155
7.3.2.9	UNCONFIRMED_HANDOVER.....	156
7.3.2.10	RELEASE.....	156
7.3.3	Null or I _{PF} segmentation info.....	157
7.3.3.0	General.....	157
7.3.3.1	Spare or I _{PF} segmentation info.....	158
7.3.3.2	Extended NCF bits.....	159
7.3.4	Quality control.....	159
7.3.4.1	General format.....	159
7.3.4.2	Bearer and connection control.....	159
7.3.4.3	RESET.....	161
7.3.4.4	Bearer quality in an asymmetric connection.....	161
7.3.5	Extended system information.....	162
7.3.5.1	General format.....	162
7.3.5.2	TARI messages.....	162
7.3.5.3	"no-emission" mode sync information or ULE Dummy Bearer subfield 2.....	162
7.3.5.3.0	General.....	162

7.3.5.3.1	"no-emission" mode sync information for dummy bearer.....	162
7.3.5.3.2	ULE Dummy Bearer subfield 2.....	163
7.3.5.4	ULE Dummy Bearer subfield 3.....	163
7.3.5.5	ULE Dummy Bearer subfield 0.....	163
7.3.5.6	ULE Dummy Bearer subfield 1.....	164
7.3.6	G _F channel data packet.....	164
7.3.7	Escape.....	164
8	Medium access layer primitives.....	165
8.0	General.....	165
8.1	Connection oriented service primitives.....	165
8.1.0	General.....	165
8.1.1	Connection setup: MAC_CON {req;ind;cfm}.....	165
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}.....	167
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}.....	168
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}.....	168
8.1.5	Restart DLC: MAC_RES_DLC {ind}.....	168
8.1.6	Connection release: MAC_DIS {req;ind}.....	169
8.1.7	MAC bandwidth: MAC_BW {ind;res}.....	169
8.1.8	Encryption.....	169
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}.....	169
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}.....	170
8.1.9	C-plane switching procedure.....	170
8.1.9.1	C-plane switching procedure: MAC_C _S _C _F {req, cfm, ind, res}.....	170
8.1.9.2	C-plane switching procedure: MAC_C _S C _F _END {ind}.....	170
8.2	Connectionless and broadcast service primitives.....	171
8.2.1	Paging: MAC_PAGE {req;ind}.....	171
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}.....	171
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}.....	172
8.2.4	"no-emission" mode.....	172
8.3	Management primitives.....	172
8.3.0	General.....	172
8.3.1	Connection control.....	172
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	172
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}.....	172
8.3.1.3	Bearer release: MAC_ME_REL {req}.....	172
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind}.....	173
8.3.2	System information and identities.....	173
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}.....	173
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}.....	173
8.3.2.3	System information output: MAC_ME_INFO {ind;res}.....	173
8.3.2.4	Extended system info: MAC_ME_EXT. {req;ind;res;cfm}.....	173
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	173
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}.....	174
8.3.5	Error reports: MAC_ME_ERROR {ind;res}.....	174
8.4	Flow control.....	174
8.4.1	MA SAP flow control.....	174
8.4.2	MB SAP flow control.....	174
8.4.3	MC SAP flow control.....	174
9	Broadcast and connectionless procedures.....	176
9.1	Downlink broadcast and connectionless procedures.....	176
9.1.0	General.....	176
9.1.1	Downlink broadcast procedure.....	176
9.1.1.1	Broadcast information.....	176
9.1.1.2	Channel selection for downlink broadcast services.....	177
9.1.1.3	Downlink broadcast procedure description.....	178
9.1.2	Downlink connectionless procedure.....	178
9.1.2.1	Channel selection at the RFP.....	178
9.1.2.2	Downlink connectionless procedure description.....	179
9.1.3	Paging broadcast procedure.....	179
9.1.3.0	General.....	179

9.1.3.1	RFP paging broadcasts.....	179
9.1.3.2	PP paging procedures.....	181
9.1.3.2.1	PP paging detection.....	181
9.1.3.2.2	PP paging processing.....	181
9.1.4	Downlink connectionless procedures for ULE.....	182
9.1.4.0	General.....	182
9.1.4.1	Transmission over the ULE dummy bearer.....	182
9.1.4.2	Transmission over the additional C/L bearers.....	182
9.1.4.2.0	General.....	182
9.1.4.2.1	MAC signalling.....	183
9.1.4.3	Announcement via the B _U paging channel.....	183
9.1.4.4	Routing and instance separation.....	184
9.1.4.5	Additional attributes.....	184
9.1.4.6	Encryption.....	184
9.1.4.7	Destination and addressing: unicast and multicast.....	184
9.1.4.7.0	General.....	184
9.1.4.7.1	C/L downlink unicast service.....	184
9.1.4.7.2	C/L downlink multicast service.....	184
9.1.4.7.3	Identities in C/L downlink multicast service.....	184
9.1.4.8	Scrambling.....	185
9.1.4.9	Time references for the multicast transmission.....	185
9.1.4.9.1	Time reference for transmission over the dummy bearer.....	185
9.1.4.9.2	Time reference for transmission over additional C/L bearers.....	185
9.2	Uplink connectionless procedures.....	185
9.2.1	General.....	185
9.2.2	Bearer selection for the connectionless uplink.....	185
9.2.3	Procedure for the connectionless uplink.....	186
9.2.3.1	Predicates.....	186
9.2.3.2	PT D-field construction.....	186
9.2.3.3	PT transmission sequence.....	186
9.2.3.4	FT procedure.....	187
9.3	Non-continuous broadcast procedure.....	187
9.3.0	General.....	187
9.3.1	Request for specific Q channel information.....	187
9.3.1.0	General.....	187
9.3.1.1	A-field procedure.....	187
9.3.1.2	B-field procedure.....	188
9.3.2	Request for a new dummy bearer.....	188
9.4	"No-emission" mode procedures.....	189
9.4.0	General.....	189
9.4.1	Initiation of the "no-emission" mode.....	189
9.4.1.1	Successful activation (countdown to zero).....	189
9.4.1.2	Multiframe countdown stopped by FT.....	189
9.4.1.3	Multiframe countdown stopped by PT.....	190
9.4.1.4	PT does not receive multiframe countdown "zero".....	190
9.4.2	Behaviour during power-down-mode.....	191
9.4.3	Waking up, FT initiated.....	191
9.4.4	Waking up, PT initiated.....	194
9.5	Ultra Low Energy (ULE) Mode Procedures.....	195
9.5.0	General.....	195
9.5.1	Initiation of the ULE Mode.....	195
9.5.1.0	General.....	195
9.5.1.1	ULE Dummy Bearer Subfield 0.....	196
9.5.1.2	ULE Dummy Bearer Subfield 1.....	196
9.5.1.3	ULE Dummy Bearer Subfield 2.....	198
9.5.1.3.0	General.....	198
9.5.1.3.1	M _U Channel Info 1 coding.....	199
9.5.1.3.2	M _U Channel Info 2 coding.....	200
9.5.1.4	ULE Dummy Bearer Subfield 3.....	200
9.5.1.5	Elements of the ULE paging system.....	201
10	Connection oriented service procedures.....	202

10.1	Overview	202
10.2	C/O connection setup	203
10.2.0	Introduction.....	203
10.2.1	General.....	203
10.2.2	Initiation of a basic and a normal connection setup.....	203
10.2.3	Initiation of a fast connection setup	204
10.2.4	Connection setup procedure description	204
10.2.4.1	Creation of MBCs	204
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	206
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation.....	207
10.2.4.3.0	General	207
10.2.4.3.1	Symmetric connection.....	209
10.2.4.3.2	Asymmetric uplink connection.....	209
10.2.4.3.3	Asymmetric downlink connection.....	209
10.2.4.3.4	Connection established.....	210
10.2.5	Expedited connections	210
10.3	C/O connection modification	210
10.3.1	Advanced connection: bandwidth modification.....	210
10.3.1.0	General	210
10.3.1.1	Suspend and resume	212
10.3.1.1.0	General	212
10.3.1.1.1	Expedited suspend and resume.....	212
10.3.1.2	MAC resume paging	212
10.3.1.3	ULE resume paging.....	213
10.3.2	Advanced connection: service type or slot type modification	213
10.3.2.0	General.....	213
10.3.2.1	Procedure for service type modification	213
10.3.2.2	Procedures for slot type modification	214
10.3.2.2.1	Procedure for slot type modification full to double	214
10.3.2.2.2	Procedure for slot type modification double to full.....	215
10.3.2.2.3	Procedures for slot type modification to/from long.....	215
10.3.2.2.4	Procedure for slot type modification in multibearer connections.....	215
10.3.2.3	Procedure for ECN number modification in an advanced connection	216
10.3.3	Connection type modification.....	216
10.3.3.0	General.....	216
10.3.3.1	Procedure for connection type modification basic to advanced	217
10.3.3.1.1	General procedure	217
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double.....	217
10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	218
10.3.3.2	Procedure for connection type modification advanced to basic	218
10.3.4	Modulation type modification.....	218
10.3.4.0	General	218
10.3.4.1	Adaptive code rate.....	220
10.4	C/O connection release.....	220
10.4.1	General.....	220
10.4.1.0	Release causes.....	220
10.4.1.1	C/O connection release in packet mode connections	221
10.4.2	Procedure description	221
10.5	C/O bearer setup.....	221
10.5.1	Single bearer setup procedures	221
10.5.1.0	General	221
10.5.1.1	Basic bearer setup procedure.....	222
10.5.1.2	A-field advanced single bearer setup procedure	224
10.5.1.2.0	General	224
10.5.1.2.1	PT initiated	224
10.5.1.2.2	FT initiated	227
10.5.1.3	B-field single bearer setup procedure.....	228
10.5.1.3.0	General	228
10.5.1.3.1	PT initiated	228
10.5.1.3.2	FT initiated	230

10.5.1.4	Double simplex setup procedure	231
10.5.1.4.1	Terminology and Predicates	231
10.5.1.4.2	General description.....	231
10.5.1.4.3	Channel selection procedure for circuit mode connections	232
10.5.1.4.4	Channel selection procedure for packet mode connections	232
10.5.1.4.5	Indirect setup procedure	233
10.5.1.4.6	Direct setup procedure.....	234
10.5.1.4.7	Handling of encrypted connections	237
10.5.1.5	Complementary connection bearer setup	238
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	239
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	240
10.5.1.7.0	General	240
10.5.1.7.1	Default rules for TA code "111".....	240
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission".....	241
10.5.1.8	Expedited bearer setup procedures.....	241
10.5.1.8.1	General	241
10.5.1.8.2	Procedure for Single-burst setup and release.....	242
10.5.1.8.3	Procedure for Multi burst setup	243
10.5.1.8.4	Announcement "Ready for Release"	245
10.5.1.8.5	Indirect FT initiated expedited bearer setup procedure	246
10.5.1.8.6	Insertion of U-plane in "Expedited access request" messages.....	246
10.5.1.8.7	Connected state (TBC) in expedited bearer setup.....	246
10.5.1.8.8	Encryption synchronization in expedited bearer setup	247
10.5.1.8.9	Use of short slots in expedited connections.....	247
10.5.2	Channel list procedures.....	248
10.5.2.1	General	248
10.5.2.2	Description of the channel list messages.....	248
10.5.2.3	Usage of the channel list messages	249
10.6	C/O bearer handover	250
10.6.1	General.....	250
10.6.2	Duplex bearer handover procedure.....	251
10.6.3	Double simplex bearer handover	251
10.6.4	Bearer replacement	252
10.6.4.1	General bearer replacement.....	252
10.6.4.2	Frequency replacement	252
10.7	C/O bearer release	253
10.7.1	General.....	253
10.7.2	Bearer release procedure description	254
10.7.2.1	Unacknowledged release procedure.....	254
10.7.2.1.0	General	254
10.7.2.1.1	Crossed bearer release procedure	254
10.7.2.2	Acknowledged release procedure.....	255
10.7.2.3	Fast release procedure	255
10.7.2.4	REP relayed bearer release.....	255
10.7.3	Expedited bearer release procedures.....	256
10.7.3.0	General	256
10.7.3.1	General Expedited Release procedure.....	256
10.7.3.1.0	Usage	256
10.7.3.1.1	Procedure description	256
10.7.3.1.2	Exceptional cases and error handling	257
10.7.3.2	Special cases of expedited release procedures	257
10.7.3.2.1	Single-message expedited release procedure.....	257
10.7.3.2.2	Abnormal expedited release procedure.....	257
10.8	C/O data transfer	258
10.8.1	Higher layer associated signalling (C).....	258
10.8.1.0	General	258
10.8.1.1	C _S channel data	258
10.8.1.1.0	General	258
10.8.1.1.1	Transmission principle	258
10.8.1.1.2	Numbering principle.....	259
10.8.1.2	C _F channel data	259
10.8.1.2.0	General	259

10.8.1.2.1	Transmission principle	259
10.8.1.2.2	Numbering principle.....	259
10.8.1.3	Q1 and Q2 bit settings for all services except $I_{p_error_correct}$	260
10.8.1.3.0	Coding of the bits	260
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I_N	260
10.8.1.3.2	Q1 and Q2 bit settings for MAC service $I_{p_error_detect}$	260
10.8.1.3.3	Q2 bit settings.....	261
10.8.1.3.4	Q1 bit settings.....	262
10.8.1.3.5	Q1 and Q2 settings when B-field is in E-mux modes.....	263
10.8.1.3.6	Q1 and Q2 settings when B-field is in "no-B-field" mode	264
10.8.1.3.7	Q1, Q2 and BCK settings when there are transitions in the coding rules or when the rules applicable to both directions are not the same	264
10.8.1.3.8	Q1 and Q2 settings when B-field mode is unknown	265
10.8.2	MOD-2 protected I channel operation (I_P).....	265
10.8.2.1	General	265
10.8.2.1.0	Introduction to MOD-2 protected I channel operation (I_P).....	265
10.8.2.1.1	Use of selective reception.....	265
10.8.2.2	Limiting the lifetime of packets	266
10.8.2.2.0	General	266
10.8.2.2.1	Lifetime setting and management.....	266
10.8.2.3	A-field shall always be correct.....	268
10.8.2.4	Use of the acknowledge bits.....	268
10.8.2.4.0	General	268
10.8.2.4.1	Q2 and BCK bit setting for $I_{p_error_correction}$ services	268
10.8.2.4.2	BCK bit setting	268
10.8.2.5	Data jump procedures	269
10.8.2.5.0	General	269
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement	269
10.8.2.5.2	Unilateral jump.....	269
10.8.2.5.3	MAC I_P bearer reset.....	271
10.8.2.6	Bearer handover and bearer replacement procedures.....	271
10.8.2.6.1	General	271
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	271
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel	272
10.8.2.7	Exchange of data from/to higher layers	272
10.8.2.7.0	General	272
10.8.2.7.1	Operation if I_{PF} channel is supported.....	273
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_P).....	273
10.8.3.1	$I_{N_minimum_delay}$ service (I_{NA})	273
10.8.3.2	$I_{N_normal_delay}$ service (I_{NB}).....	273
10.8.3.3	$I_{p_error_detection}$ service	274
10.8.3.3.1	Operation if I_{PF} channel is supported.....	274
10.8.3.4	$I_{p_encoded_protected}$ service (I_{PX})	274
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux.....	274
10.8.4.1	Purpose of the I_{PF} channel	274
10.8.4.2	Activation of the E+U type mux mode	275
10.8.4.3	I_{PF} procedures	275
10.8.4.3.0	General	275
10.8.4.3.1	I_{PF} basic procedures.....	275
10.8.4.3.2	I_{PF} advanced procedures	276
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	276
10.8.4.4	I_{PF} Mod-2 protected operation.....	276
10.8.4.5	$I_{PF_error_detect}$ operation	277
10.8.4.6	I_{PF} operation with I_N service	277
10.8.4.7	Backcompatibility rule	277
10.9	C/O procedures for FT connections with CRFP.....	278
10.9.0	General.....	278
10.9.1	Dual C/O bearer setup.....	278
10.9.2	C/O connection release of connection with CRFP.....	278
10.9.3	C/O connection suspend and resume	278

11	Medium access layer management procedures	279
11.1	Broadcasting.....	279
11.1.1	RFP transmission.....	279
11.1.2	PP reception.....	279
11.2	Extended system information.....	279
11.2.1	PP requests.....	279
11.2.2	RFP response.....	279
11.3	PP states and state transitions.....	279
11.3.0	General.....	279
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	279
11.3.2	Entry into the Idle_Locked state.....	279
11.3.3	Actions in the Idle_Locked state.....	280
11.3.3.0	General.....	280
11.3.3.1	Page detection in Idle_Locked state.....	280
11.3.3.2	Setup detection in Idle_Locked state.....	281
11.3.4	Idle_Locked and Active_Locked state transitions.....	281
11.4	Physical channel selection.....	282
11.4.0	General.....	282
11.4.1	The channel selection lists.....	282
11.4.2	Physical channel and RFP selection at the PP.....	284
11.4.3	Physical channel selection at the RFP.....	285
11.4.4	Hand over criteria due to in-connection base identification.....	287
11.4.5	Handover criteria due to interference.....	287
11.4.6	Exception in channel selection rules for Ultra Low Energy devices.....	288
11.5	In-connection quality control.....	288
11.5.1	RFPI handshake.....	288
11.5.2	Frequency control.....	288
11.5.2.1	RFP measurement of frequency error.....	288
11.5.2.2	PT frequency correction.....	288
11.6	Maximum allowed system load at RFPs.....	288
11.7	PMID and FMID definitions.....	288
11.7.1	FMID definition.....	288
11.7.2	PMID definition.....	288
11.7.2.0	General.....	288
11.7.2.1	'X'PMID definition.....	289
11.8	RFP idle receiver scan sequence.....	289
11.9	PT receiver scan sequence.....	290
11.10	Management of connections associated with Broadband data links.....	290
11.11	Management procedures for "no-emission" mode.....	290
11.11.0	General.....	290
11.11.1	Behaviour during "no-emission" mode.....	290
11.12	Physical channel selection procedures for DECT Ultra Low Energy (ULE).....	291
11.12.1	General.....	291
11.12.2	Overall architecture of ULE channel selection processes.....	291
11.12.3	Process M0 (RFP side pre-selection process).....	292
11.12.4	Broadcast mechanism.....	292
11.12.5	Process M1 (PP side channel selection process).....	293
11.12.6	Setup attempt and evaluation of responses.....	294
11.12.7	Process M2 (collision handling/collision avoidance process).....	295
11.12.7.0	General.....	295
11.12.7.1	Equations.....	296
11.12.7.2	Algorithm.....	296
12	Medium access layer test message procedure.....	296
12.1	Introduction.....	296
12.2	General.....	297
12.2.0	Overview of test modes and messages.....	297
12.2.1	Portable part testing.....	298
12.2.2	Fixed part testing.....	298
12.2.3	Applicability of test messages.....	298
12.3	FORCE_TRANSMIT.....	299
12.3.1	Portable part.....	299