



SLOVENSKI STANDARD
SIST EN 300 175-4 V2.6.1:2015
01-november-2015

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 4.
del: Plast krmiljenja podatkovnih povezav (DCL)**

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4:
Data Link Control (DLC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 175-4 V2.6.1**
SIST EN 300 175-4 V2.6.1:2015
<https://standards.iteh.ai/catalog/standards/sist/b0e1b114-c6b5-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015>

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
35.100.20	Podatkovni povezovalni sloj	Data link layer

SIST EN 300 175-4 V2.6.1:2015 **en,fr,de**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-4 V2.6.1:2015

<https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015>

ETSI EN 300 175-4 V2.6.1 (2015-07)



Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer

[SIST EN 300 175-4 V2.6.1:2015](https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015>

Reference

REN/DECT-000304-4

KeywordsDECT, DLC, IMT-2000, mobility, radio, TDD,
TDMA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)SIST EN 300 175-4 V2.6.1:2015<https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab785/etsi-en-300-175-4-v2-6-1-2015>
Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
Modal verbs terminology.....	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	16
4 Data Link Control (DLC) layer overview	19
4.1 General	19
4.2 C-plane services	19
4.3 U-plane services	20
4.4 Lower Layer Management Entity (LLME)	24
5 C-plane service characteristics	24
5.1 Data link service (LAPC+Lc).....	24
5.1.1 General.....	24
5.1.2 LAPC types of operation	25
5.1.3 Establishment of information transfer modes	25
5.1.3.1 Data Link Identifier (DLI)	25
5.1.3.2 LAPC states.....	25
5.2 Broadcast service (Lb).....	26
6 Frame structures for C-plane services.....	27
6.1 Data link service frame structure.....	27
6.1.0 Frame format type FA.....	27
6.1.1 General frame structure	27
6.1.2 Lc frame delimiting and transparency	28
6.1.3 Transmission order	28
6.1.4 Routing to logical channels.....	28
6.1.4.0 General	28
6.1.4.1 C _F /CL _F logical channel.....	29
6.1.4.2 C _S /CL _S logical channel.....	29
6.1.5 Invalid frames	29
6.2 Broadcast service frame structure.....	30
6.2.1 Standard frame structure	30
6.2.2 Extended frame structure	30
7 Elements of procedures and formats of fields for C-plane peer-to-peer communication.....	31
7.1 General	31
7.2 Address field formats	31
7.3 Address field parameters	31
7.3.1 RESErved bit (RES).....	31
7.3.2 Command Response (C/R) bit	31
7.3.3 SAPI field	31
7.3.4 New Link Flag (NLF) bit.....	32
7.3.5 LLN-field.....	32
7.3.6 Data Link Identifiers (DLI).....	32
7.4 Control field formats	32
7.5 Control field parameters	33
7.5.1 Poll/Final (P/F) bit	33
7.5.2 Multiple frame operation variables and sequence numbers	33
7.5.2.1 Modulus	33
7.5.2.2 Send state Variable V(S).....	33

7.5.2.3	Acknowledge state Variable V(A)	34
7.5.2.4	Send sequence Number N(S)	34
7.5.2.5	Receive state Variable V(R).....	34
7.5.2.6	Receive sequence Number N(R).....	34
7.5.3	Unacknowledged operation variables and sequence numbers	34
7.5.4	Supervisory and Unnumbered function bits S and U.....	34
7.6	Length indicator field format.....	34
7.7	Length indicator field parameters.....	35
7.7.1	Length indicator field extension bit (N).....	35
7.7.2	More data bit (M).....	35
7.7.3	Length parameter (L _I)	35
7.7.4	Extended length parameter (L _{JJ})	36
7.7.5	Reserved bit (RES)	36
7.8	Fill field format	36
7.9	Checksum field format	36
7.10	Checksum field parameters	36
7.11	Commands and responses	37
7.11.0	General.....	37
7.11.1	Information (I) command.....	38
7.11.2	Receive Ready (RR) command/response.....	38
7.11.3	Receive Not Ready (RNR) command/response.....	39
7.11.4	REJect (REJ) command/response	39
7.11.5	Set Asynchronous Balanced Mode (SABM) command.....	39
7.11.6	Disconnect Mode (DM) response	39
7.11.7	Unnumbered Information (UI) command	39
7.11.8	DISConnect (DISC) command	40
7.11.9	Unnumbered ACK (UA) response.....	40
8	Primitives	40
8.1	Primitive types.....	40
8.2	Primitives to the MAC layer (lower layer).....	40
8.3	Primitives to the NWK layer (higher layer).....	40
8.3.0	General.....	40
8.3.1	Parameter definitions	41
8.3.2	S-SAP primitives	42
8.3.2.0	List of primitives	42
8.3.2.1	DL_ESTABLISH primitive	42
8.3.2.2	DL_RELEASE primitive	42
8.3.2.3	DL_DATA primitive.....	43
8.3.2.4	DL_UNIT_DATA primitive	43
8.3.2.5	DL_SUSPEND primitive	43
8.3.2.6	DL_RESUME primitive.....	43
8.3.2.7	DL_ENC_KEY primitive.....	44
8.3.2.8	DL_ENCRYPT primitive.....	44
8.3.2.9	DL_SERVICE_MOD primitive.....	44
8.3.3	B-SAP primitives.....	44
8.3.3.0	List of primitives	44
8.3.3.1	DL_BROADCAST primitive.....	45
8.3.3.2	DL_EXPEDITED primitive.....	45
8.4	Primitives to the interworking unit.....	45
8.4.0	General.....	45
8.4.1	Parameter definitions	45
8.4.2	LU _X -SAP primitives	46
8.4.2.0	List of primitives	46
8.4.2.1	DL_U_DATA primitive.....	46
8.4.2.2	DL_U_UNIT_DATA primitive	46
8.4.2.3	DL_U_ERROR primitive.....	46
9	C-plane peer-to-peer procedures	47
9.1	General	47
9.2	Point to point acknowledged operation	47
9.2.1	Procedure for the use of the P/F bit	47

<https://standards.ietf.org/catalog/standards/sist/b0c1bf14-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015>
 IETF STANDARD PREVIEW
 (standards.ietf.org)

9.2.1.1	Class A acknowledged information transfer	47
9.2.1.2	Class B acknowledged information transfer	47
9.2.2	Use of LLN	48
9.2.2.1	Class A operation	48
9.2.2.2	Class B operation	48
9.2.3	Link establishment and information transfer in class A operation.....	48
9.2.3.1	Establishing class A operation	48
9.2.3.2	Class A acknowledged information transfer	49
9.2.3.3	Transmission of class A I-frames	49
9.2.3.4	Reception of class A I-frames	50
9.2.3.5	Receiving acknowledgements	50
9.2.3.6	Waiting for acknowledgement	50
9.2.3.7	Release of class A operation	51
9.2.3.8	Re-establishment of class A operation	51
9.2.4	Establishing class B multiple frame operation.....	51
9.2.4.1	Overview	51
9.2.4.2	Class B multiple frame establishment procedures.....	52
9.2.4.3	Class B LLN assignment procedures	53
9.2.4.3.0	General	53
9.2.4.3.1	PT establishment	53
9.2.4.3.2	FT establishment	54
9.2.5	Link maintenance and information transfer in class B multiple frame operation	54
9.2.5.0	General	54
9.2.5.1	Transmitting I-frames.....	54
9.2.5.2	Receiving I-frames	55
9.2.5.2.0	General	55
9.2.5.2.1	P bit set to 1	55
9.2.5.2.2	P bit set to 0	55
9.2.5.3	Sending and receiving acknowledgements	55
9.2.5.3.1	Sending acknowledgements	55
9.2.5.3.2	Receiving acknowledgements	55
9.2.5.4	Receiving REJ-frames	56
9.2.5.5	Receiving RNR-frames	57
9.2.5.6	LAPC own receiver busy condition	58
9.2.5.7	Waiting acknowledgement.....	58
9.2.5.8	Appropriate supervisory frame.....	59
9.2.6	Release of class B multiple frame operation.....	59
9.2.7	Link suspension and resumption.....	60
9.2.7.1	Link suspension.....	60
9.2.7.1.0	General	60
9.2.7.1.1	Class B acknowledged suspend	60
9.2.7.1.2	Unacknowledged suspend	61
9.2.7.2	Class B link resumption	61
9.2.7.3	Connection handover	62
9.2.7.3.0	General	62
9.2.7.3.1	Class A connection handover	64
9.2.7.3.2	Class B connection handover	64
9.2.7.3.3	Expiry of connection handover timer	65
9.2.8	Re-establishment of class B multi-frame operation	65
9.2.8.1	Criteria for re-establishment.....	65
9.2.8.2	Procedure	65
9.2.9	Exception handling	66
9.2.9.1	General	66
9.2.9.2	Class B exception condition reporting and recovery.....	66
9.2.9.2.0	General	66
9.2.9.2.1	N(S) sequence error	66
9.2.9.2.2	N(R) sequence error	67
9.2.9.2.3	Timer recovery condition	67
9.2.9.2.4	Collision of identical transmitted and received commands	67
9.3	Unacknowledged operation	67
9.3.1	Use of LLN for unacknowledged information transfer.....	67
9.3.2	Class U link establishment.....	67

9.3.3	Unacknowledged information transfer.....	68
9.3.3.1	Transmission of unacknowledged information	68
9.3.3.2	Reception of unacknowledged information	68
9.3.4	Unacknowledged release	68
9.4	Broadcast operation.....	68
9.4.1	Normal operation	68
9.4.1.1	Procedure in the Fixed radio Termination (FT)	68
9.4.1.2	Procedure in the Portable radio Termination (PT)	68
9.4.2	Expedited operation	69
9.4.2.1	Procedure in the Fixed radio Termination (FT)	69
9.4.2.2	Procedure in the Portable radio Termination (PT)	69
9.5	MAC layer interfaces	69
9.5.1	MC-SAP	69
9.5.1.1	C-plane overview	69
9.5.1.2	C-plane service data procedures.....	70
9.5.1.3	U-plane service data.....	70
9.5.2	MB-SAP	70
9.5.2.0	General.....	70
9.5.2.1	C-plane service data procedures.....	71
9.5.2.2	U-plane service data.....	71
9.5.3	MA-SAP	71
9.5.3.1	Overview.....	71
9.5.3.2	Service data procedures.....	71
10	Management procedures.....	72
10.1	Lower Layer Management Entity (LLME)	72
10.2	MAC connection management.....	72
10.2.0	General.....	72
10.2.1	MAC connection set-up.....	72
10.2.2	MAC connection release.....	73
10.2.3	MAC connection modification	73
10.2.4	MAC connection identifiers.....	73
10.2.4.1	Overview.....	73
10.2.4.2	Advanced MAC Connection Identifiers (AMCI).....	74
10.2.4.3	Basic MAC Connection Identifiers (BMCI).....	74
10.2.4.4	MAC Connection Endpoint Identifier (MCEI).....	75
10.2.5	Selection of logical channel (C _S or C _F).....	75
10.3	DLC C-plane (LAPC) management	75
10.3.0	General.....	75
10.3.1	Provision of link signature	75
10.3.2	Routing of connection oriented links	76
10.3.3	Routing of connectionless links	76
10.4	DLC U-plane (LUX) management	76
10.4.0	General.....	76
10.4.1	U-plane establishment.....	76
10.4.2	U-plane release	77
10.4.3	U-plane suspend and resume	77
10.5	Connection handover management	77
10.6	Ciphering management.....	78
10.6.1	Ciphering management in cases where the NWK layer executes the ciphering related MM procedure ...	78
10.6.1.0	General	78
10.6.1.1	Providing a key to the MAC layer	78
10.6.1.2	Starting and stopping the ciphering.....	78
10.6.1.3	Connection handover	78
10.6.2	Ciphering management in cases where the NWK layer does not execute the ciphering related MM procedure	79
10.7	Broadband data link management	79
11	U-plane service characteristics.....	79
11.1	General	79
11.2	LU1 TRansparent UnProtected service (TRUP)	80
11.3	LU2 Frame RELay service (FREL).....	80

11.3.1	General.....	80
11.3.2	Checksum operation	81
11.3.3	Segmentation and transmission class.....	82
11.3.4	Data transmission.....	82
11.3.4.1	Send side procedure	82
11.3.4.2	Receive side procedure	83
11.4	LU3 Frame SWITching service (FSWI).....	83
11.5	LU4 Forward Error Correction (FEC) service.....	84
11.6	LU5 Basic RATE adaption service (BRAT).....	84
11.6.1	Overview	84
11.6.2	Protected service operation	85
11.6.2.1	General	85
11.6.2.2	Data buffering and initial rate adaptation.....	85
11.6.2.3	Multi-channel set multiplexing	86
11.6.2.4	Segmentation of Multiplexed Data Units (MDU).....	88
11.6.2.5	Frame sequencing and addition of control and fill octets.....	88
11.6.2.6	Frame transmission	89
11.6.3	Unprotected service operation	90
11.6.3.1	General	90
11.6.3.2	Data buffering and initial rate adaption.....	90
11.6.3.3	Multi-channel set multiplexing	90
11.6.3.4	Segmentation of MDUs.....	91
11.6.3.5	Frame transmission	92
11.7	LU6 Secondary RATE adaption (SRAT) service	92
11.7.1	General.....	92
11.8	LU16 ESCape Service (ESC).....	93
11.8.1	General.....	93
11.9	LU7 64 kbit/s data bearer service.....	94
11.9.1	General.....	94
11.9.2	Physical layer service.....	94
11.9.3	MAC layer service.....	94
11.9.4	DLC layer service.....	94
11.9.4.1	Architectural model.....	94
11.9.4.1.0	General	94
11.9.4.1.1	Transmit (Tx) frame buffering	95
11.9.4.1.2	Receive (Rx) frame buffering	95
11.9.4.2	Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....	95
11.9.4.2.0	General	95
11.9.4.2.1	Control field	96
11.9.4.2.2	Information field.....	98
11.9.4.2.3	ARQ checksum.....	99
11.9.4.3	Procedures for normal operation	99
11.9.4.3.0	General	99
11.9.4.3.1	Establishment and synchronization procedures	99
11.9.4.3.2	Active phase	101
11.9.4.3.3	Release.....	103
11.9.4.4	Exceptional procedures	103
11.9.4.4.0	General	103
11.9.4.4.1	Invalid frame condition	103
11.9.4.4.2	Establishment	103
11.9.4.4.3	Transmitting frames.....	103
11.9.4.4.4	Receiving frames	103
11.9.4.4.5	Sending acknowledgements	103
11.9.4.4.6	Forwarding of received data.....	103
11.9.4.4.7	N(R) sequence error	103
11.9.4.4.8	N(O) sequence error	104
11.9.4.4.9	N(S) sequence error	104
11.9.4.4.10	Format error.....	104
11.9.4.4.11	Abnormal release.....	104
11.9.4.4.12	Implicit reset.....	105
11.9.5	Network layer service	105
11.9.5.1	LCE service.....	105

11.9.5.2	CC service	105
11.10	LU8 service	105
11.10.0	General.....	105
11.10.1	Physical layer service.....	105
11.10.2	MAC layer service.....	105
11.10.3	DLC layer service.....	105
11.11	LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service	106
11.11.1	Overview	106
11.11.1.0	General	106
11.11.1.1	FU9 frame structure	106
11.11.1.1.1	General frame structure	106
11.11.1.1.2	FU9 buffering procedures.....	107
11.11.1.1.3	Connection handover.....	107
11.11.1.1.4	Transmission order	107
11.11.2	Alignment signal management	107
11.11.2.1	General	107
11.11.2.2	Procedures.....	108
11.11.3	V.24 Signalling	109
11.11.3.1	General	109
11.11.3.2	Transmitter procedures.....	109
11.11.3.3	Receiver procedures	109
11.11.4	Rate Coding	109
11.11.4.1	General	109
11.11.4.2	Transmitter procedures.....	110
11.11.4.3	Receiver procedures	110
11.11.5	DECT Independent Clocking (DIC)	111
11.11.5.1	General	111
11.11.5.2	Measurement of phase differences.....	111
11.11.5.3	Compensation control rules.....	112
11.11.5.3.1	General	112
11.11.5.3.2	Optimizing error resilience.....	112
11.11.6	Information field.....	113
11.11.6.1	General.....	113
11.11.6.2	User data rates.....	113
11.11.6.3	Information field filling rule	113
11.11.7	Primitives.....	114
11.12	LU10 Enhanced Frame RELay (EFREL) service	115
11.12.1	General.....	115
11.12.2	Segmentation and transmission class.....	116
11.12.3	Data transmission.....	116
11.12.3.1	Send side procedures.....	116
11.12.3.1.0	General	116
11.12.3.1.1	"Early transmission" option.....	117
11.12.3.2	Receive side procedure	117
11.12.3.2.0	General	117
11.12.3.2.1	Standard SDU delivery mode	117
11.12.3.2.2	In-sequence SDU delivery mode	117
11.12.3.2.3	PDU-in-sequence delivery mode.....	118
11.12.3.2.4	PDU-as-received delivery mode.....	118
11.12.4	SDU boundaries definition	118
11.12.4.0	General	118
11.12.4.1	Infinite SDU mode	118
11.12.5	Use over C/L downlink channels.....	119
11.12.5.0	General	119
11.12.5.1	Use over C/L downlink channels: unicast mode	119
11.12.5.2	Use over C/L downlink channels: multicast mode.....	119
11.12.5.2.0	General	119
11.12.5.2.1	DLC acknowledgement in multicast mode.....	119
11.13	LU11 service	119
11.13.0	General.....	119
11.13.1	Physical layer service.....	119
11.13.2	MAC layer service.....	119

11.13.3	DLC layer service	119
11.14	LU12 UNprotected Framed service (UNF)	120
11.14.1	General	120
11.14.2	DLC layer service	120
11.14.2.0	General	120
11.14.2.1	Segmentation	121
11.14.2.2	Data transmission	122
11.14.2.2.1	Send side procedure	122
11.14.2.2.2	Receive side procedure	122
11.15	LU13 Enhanced Frame RELay service with CRC (EFREL-CRC)	123
11.15.1	General	123
11.15.2	SDU CRC generation	123
11.15.3	Use over C/L downlink channels	123
11.15.3.0	General	123
11.15.3.1	Use over C/L downlink channels: unicast mode	124
11.15.3.2	Use over C/L downlink channels: multicast mode	124
11.15.3.2.0	General	124
11.15.3.2.1	DLC acknowledgement in multicast mode	124
11.16	LU14 Enhanced Frame RELay service with CCM (EFREL-CCM)	124
11.16.1	General	124
11.16.2	LU14 SDU structure	124
11.16.2.0	General	124
11.16.2.1	SDU sizes	125
11.16.2.2	Security model	125
11.16.2.3	SDU processing	125
11.16.2.4	Limitations	126
11.16.2.5	CCM sequence numbers	126
11.16.2.6	CCM control procedures	126
11.16.3	Use over C/L downlink channels	126
11.16.3.0	General	126
11.16.3.1	Use over C/L downlink channels: unicast mode	126
11.16.3.2	Use over C/L downlink channels: multicast mode	127
11.16.3.2.0	General	127
11.16.3.2.1	DLC acknowledgement in multicast mode	127
12	Frame structures for U-plane services	127
12.1	General	127
12.2	FU1 frame structure	128
12.2.1	General frame structure	128
12.2.2	FU1 buffering procedures	129
12.2.3	Minimum delay (speech) operation	129
12.2.4	Connection handover	130
12.2.5	Transmission order	130
12.3	FU2 frame structure	130
12.3.1	General frame structure	130
12.3.2	FU2 buffering procedures	131
12.3.3	Connection handover	131
12.3.4	Transmission order	131
12.4	FU3 frame structure	131
12.4.1	General frame structure	131
12.4.2	FU3 buffering procedures	132
12.4.3	Connection handover	132
12.4.4	Transmission order	133
12.5	FU4 frame structure	133
12.5.1	General frame structure	133
12.5.2	FU4 buffering procedures	134
12.5.3	Connection handover	134
12.5.4	Transmission order	134
12.6	FU5 frame structure	134
12.6.1	General frame structure	134
12.6.2	FU5 buffering procedures	135
12.6.3	Connection handover	136

12.6.4	Transmission order	136
12.7	FU6 frame structure.....	136
12.7.1	General frame structure	136
12.7.2	FU6 buffering procedures.....	137
12.7.3	Connection handover	137
12.7.4	Transmission order	137
12.8	FU7 frame structure.....	137
12.9	FU8 frame structure.....	137
12.10	FU9 frame structure.....	137
12.11	FU10 frame structure.....	138
12.11.1	General frame structure	138
12.11.1.0	General	138
12.11.1.1	Specific for MAC service I_{PK}	140
12.11.2	Transmission of FU10c and FU10d frames	141
12.11.2.0	General	141
12.11.2.1	Insertion of the FU10c frame in an FU10a frame of the opposite link.....	141
12.11.2.2	Transmission of the F10c frame using the G_F channel.....	141
12.11.2.3	Insertion of the FU10d frame in an FU10a frame of the opposite link	142
12.11.2.4	Transmission of the FU10d frame using the G_{FA} channel.....	142
12.11.3	FU10 buffering procedures.....	142
12.11.4	Connection handover	142
12.11.5	Transmission order	142
12.12	FU12 frame structure.....	143
12.12.1	General frame structure	143
12.12.2	FU12 buffering procedures.....	143
12.12.3	Connection handover	144
12.12.4	Transmission order	144
13	Elements of procedures and formats of fields for U-plane peer-to-peer communication	144
13.1	General	144
13.2	Address elements.....	144
13.2.1	Address field format	144
13.2.2	Address field parameters	145
13.3	Length indicator elements	145
13.3.1	Length indicator field format.....	145
13.3.1.1	Length indicator field format for all services except LU10	145
13.3.1.2	Length indicator field format for service LU10	145
13.3.2	Length indicator field parameters	146
13.3.2.1	Length indicator field parameters for all services except LU10.....	146
13.3.2.2	Length indicator field parameters for LU10 service	147
13.3.2.2.0	General	147
13.3.2.2.1	Meaning of the more (M) bit	149
13.4	Sequence number elements	149
13.4.1	Send sequence number format	149
13.4.2	Send sequence number parameters	150
13.4.3	Receive sequence number format	150
13.4.4	Receive sequence number parameters	150
13.5	Fill elements - Fill field format	150
14	U-plane peer-to-peer procedures	151
14.1	General	151
14.2	Frame transmission principles	151
14.2.1	Sequence numbering.....	151
14.2.2	Acknowledgements.....	151
14.2.2.1	Sending acknowledgements	151
14.2.2.2	Receiving acknowledgements	151
14.2.3	Transmission classes	152
14.2.3.0	General	152
14.2.3.1	Class 0: No LU_X retransmission or sequencing.....	152
14.2.3.2	Class 1: no LU_X retransmission.....	152
14.2.3.2.0	General	152
14.2.3.2.1	Class 1: use over C/L downlink channels.....	153

14.2.3.3	Class 2: variable throughput, limited delay LU _X retransmission.....	153
14.2.3.4	Class 3: fixed throughput LU _X retransmission.....	153
14.2.4	Operation parameter negotiation.....	154
14.3	Frame transmission procedures.....	154
14.3.1	General.....	154
14.3.2	Class 0 procedures.....	154
14.3.2.0	General.....	154
14.3.2.1	Sending side procedure.....	154
14.3.2.2	Receiving side procedure.....	154
14.3.3	Class 1 procedures.....	155
14.3.3.0	General.....	155
14.3.3.1	Sending side procedure.....	155
14.3.3.2	Receiving side procedure.....	155
14.3.4	Class 2 procedures.....	156
14.3.4.0	General.....	156
14.3.4.1	Sending side procedure.....	156
14.3.4.1.0	General.....	156
14.3.4.1.1	Synchronization message sending side procedure (LU10).....	157
14.3.4.1.2	Tx side end-of-activity rule.....	158
14.3.4.1.3	Abnormal SDU termination/abort signal (LU10 only).....	159
14.3.4.1.4	Retransmission procedure.....	159
14.3.4.2	Receiving side procedure.....	159
14.3.4.2.0	General.....	159
14.3.4.2.1	Acknowledgement procedure.....	160
14.3.4.2.2	Rx side end-of-activity rule.....	162
14.3.4.2.3	Retransmission request procedure.....	162
14.3.4.2.4	SDU delivery procedure.....	162
14.3.4.2.5	Synchronization message receiver side procedure (LU10).....	163
14.3.4.2.6	Reception of an abnormal SDU termination/abort signal (LU10).....	164
14.3.5	Class 3 procedures.....	164
14.3.5.0	General.....	164
14.3.5.1	Sending side procedure.....	164
14.3.5.2	Receiving side procedure.....	165
Annex A (normative): System parameters.....		166
A.1	LAPC timer values.....	166
A.2	U-plane timer values.....	167
A.3	Constants.....	167
A.3.1	Retransmission counter (N250).....	167
A.3.2	Maximum number of CHO attempts (N251).....	167
Annex B (normative): Checksum algorithms.....		168
B.1	Arithmetic conventions.....	168
B.2	Coding algorithm.....	168
B.3	Decoding algorithm.....	168
B.4	Some examples.....	168
Annex C (informative): MAC connection states.....		169
Annex D (normative): Mapping of agreed channel rates to MCS sizes.....		170
D.0	General.....	170
D.1	Protected class operation.....	170
D.2	Unprotected class operation.....	171
Annex E (normative): LU12 applications.....		172

E.1	G.729.1 over 32 kb/s channel.....	172
E.1.0	General.....	172
E.1.1	G.729.1 payload format.....	172
E.1.1.0	General.....	172
E.1.1.1	G.729.1 payload header coding.....	172
E.1.2	Operations.....	174
E.1.2.1	Encoder bit rate.....	174
E.1.2.2	Protection against random errors.....	175
Annex F (informative):	Bibliography.....	176
Annex G (informative):	Change history.....	177
History.....		178

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 175-4 V2.6.1:2015](https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/b0e1bf4-c6b3-4c76-9caa-3880c5fccab8/sist-en-300-175-4-v2-6-1-2015>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 4 of a multi-part deliverable ([1] to [8]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2].

National transposition dates	
Date of adoption of this EN:	24 July 2015
Date of latest announcement of this EN (doa):	31 October 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2016
Date of withdrawal of any conflicting National Standard (dow):	30 April 2016

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.