



**Digital Enhanced Cordless Telecommunications (DECT);
New Generation DECT;
Part 5: Additional feature set nr. 1
for extended wideband speech services**

ITERS-CEMARE PREVIEW
<https://standards.iteh.ai/standard/standardlist/9bc5bf61-80e9-4463-a25c-44759e1629f9/etsi-ts-102-527-5-v1.2.1>

Reference

RTS/DECT-NG269-5

Keywords

audio, DECT, radio, security

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	9
Foreword.....	9
1 Scope	10
2 References	10
2.1 Normative references	11
2.2 Informative references.....	12
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	13
3.3 Abbreviations	14
4 Description of Services	15
4.1 Additional feature set nr.1 for extended wideband speech services	15
4.1.1 Back-compatibility with GAP.....	16
4.1.2 Back-compatibility with New Generation DECT; part 1: wideband speech	16
4.1.3 Back-compatibility with New Generation DECT; part 3: extended wideband speech services	16
4.2 Additional features for extended wideband speech services defined in the present document	17
5 Service and feature definitions	17
5.1 New Generation DECT Speech Services	17
5.2 Network (NWK) features	18
5.3 Data Link Control (DLC) service definitions.....	18
5.4 Medium Access Control (MAC) service definitions.....	18
5.5 Physical Layer (PHL) service definitions.....	18
5.6 Speech coding and audio feature definitions.....	18
5.7 Application features	18
6 Inter-operability requirements	18
6.1 General	18
6.1.1 Editorial conventions	19
6.1.2 Radio and audio conformance requirements.....	19
6.2 New Generation DECT Speech Services support status	20
6.3 Services to DECT feature implementation mappings.....	20
6.4 NWK features.....	29
6.5 Data Link Control (DLC) services	30
6.6 Medium Access Control (MAC) services	32
6.7 Physical layer (PHL) services	32
6.8 Speech coding and audio features	33
6.9 Application features	34
6.10 Network (NWK) feature to procedure mapping	34
6.11 Data Link Control (DLC) Service to procedure mapping	43
6.12 Medium Access Control (MAC) service to procedure mapping	44
6.13 Application feature to procedure mapping	46
6.14 General requirements	46
6.14.1 Network (NWK) layer message contents.....	46
6.14.2 Transaction identifier.....	46
6.14.3 Length of a Network (NWK) layer message	47
6.14.4 Handling of error and exception conditions.....	47
6.14.5 Generic Access Profile (GAP) default setup attributes.....	47
6.14.6 Coexistence of Mobility Management (MM) and Call Control (CC) procedures	47
6.14.7 Coding rules for information elements	47
7 Procedure description	47
7.1 Backward compatibility with Generic Access Profile (GAP), New Generation DECT part 1 (wideband speech) and with New Generation DECT part 3 (extended wideband speech services) equipment.....	48

7.1.1	Backward compatibility with Generic Access Profile (GAP); Requirements for NG-DECT, part 5 Fixed Parts (FPs).....	48
7.1.2	Backward compatibility with Generic Access Profile (GAP); Requirements for NG-DECT, part 5 Portable Parts (PPs) registered on GAP compliant FPs	48
7.1.3	Backward compatibility with New Generation DECT, part 1; Requirements for NG-DECT, part 5 Fixed Parts (FPs).....	48
7.1.4	Backward compatibility with New Generation DECT, part 1; Requirements for NG-DECT, part 5 Portable Parts (PPs) registered on NG DECT Part 1 FPs	48
7.1.5	Backward compatibility with New Generation DECT, part 3; Requirements for NG-DECT, part 5 Fixed Parts (FPs).....	49
7.1.6	Backward compatibility with New Generation DECT, part 3; Requirements for NG-DECT, part 5 Portable Parts (PPs) registered on NG DECT Part 3 FPs	49
7.2	Generic Access Profile (GAP) procedures	49
7.3	New Generation DECT; part 1: Wideband Speech and New Generation DECT; part 3: Extended Wideband Speech Services procedures	49
7.3.1	Implementation examples of part 1: Wideband Speech specific procedures	49
7.3.2	Implementation examples of part 3: Extended Wideband Speech Services specific procedures.....	50
7.4	Network (NWK) layer procedures specific to part 5	50
7.4.1	Generic events notification	50
7.4.1.1	General	50
7.4.1.2	Voice Message waiting notification	50
7.4.1.3	Missed call notifications	52
7.4.1.4	List change notification	52
7.4.1.5	Line and diagnostic statuses notifications	52
7.4.1.5.1	General requirements.....	52
7.4.1.5.2	Events triggering 'Line and diagnostic status' list related indications.....	53
7.4.1.6	SMS Message notification	56
7.4.2	Date and Time synchronization	58
7.4.3	Handling of parallel calls	58
7.4.3.1	Parallel call common requirements	58
7.4.3.2	Control messages	58
7.4.3.3	Codec change for parallel calls	60
7.4.3.4	Sending negative acknowledgement	60
7.4.3.5	Common parallel call procedures (external or internal)	60
7.4.3.6	Call transfer	60
7.4.3.7	3-party conference with established external and/or internal calls.....	60
7.4.3.8	Intrusion call (from PP to FP)	60
7.4.3.9	Internal call codec priority.....	60
7.4.3.10	Handling of lines where second calls are signalled in-band.....	60
7.4.4	Handling of single call services	60
7.4.5	Line identification	60
7.4.6	Call identification	60
7.4.6.1	Call identification general requirements	60
7.4.6.2	Call identifier assignment on first outgoing call (FP to PP).....	60
7.4.6.3	Call identifier assignment on first incoming call (FP to PP).....	60
7.4.6.4	Call status indication to the handset (FP to PP)	61
7.4.6.4.1	Call status indication general requirements	61
7.4.6.4.2	Call status indication as call information.....	61
7.4.6.4.3	Call status principles and values.....	61
7.4.6.4.4	Call status reasons summary and MMI mapping.....	63
7.4.6.4.5	Call statuses for a first "Outgoing external call"	64
7.4.6.4.6	Call statuses for a first "Outgoing external call" using early {CC-CONNECT} message	64
7.4.6.4.7	Call statuses for an "Outgoing external call" - user busy	64
7.4.6.4.8	Call statuses for an "Outgoing external call" - number not available	64
7.4.6.4.9	Call statuses for a first "Incoming external call"	64
7.4.6.4.10	Call statuses for a first "Incoming external call"	64
7.4.7	Multiple lines handling	64
7.4.8	Multiple call line handling	64
7.4.9	PP and FP capabilities indication and broadcast.....	64
7.4.9.1	Terminal capability indication	64
7.4.9.2	Higher layer information FP broadcast	66
7.4.9.2.1	Higher layer information in standard FP broadcast (Qh = 3)	66

7.4.9.2.2	Higher layer information in Extended FP broadcast (Qh = 4).....	66
7.4.9.2.3	Extended Higher Layer capabilities part 2 (Qh = 11).....	66
7.4.10	List access service.....	67
7.4.10.1	General considerations	67
7.4.10.2	List change notification.....	70
7.4.10.2.1	General rule	70
7.4.10.2.2	Mandatory notifications.....	72
7.4.10.3	List identifier codings	74
7.4.10.4	List Access Commands	75
7.4.10.4.1	Start and end session	78
7.4.10.4.2	Query supported entry fields	78
7.4.10.4.3	Read entries	78
7.4.10.4.4	Edit entry	82
7.4.10.4.5	Save entry	82
7.4.10.4.6	Delete entry	86
7.4.10.4.7	Delete list.....	86
7.4.10.4.8	Search entries	86
7.4.10.4.9	Negative Acknowledgement.....	87
7.4.10.4.10	Data packet / Data packet last.....	87
7.4.10.4.11	Read selected entries	87
7.4.10.4.12	Write entry.....	90
7.4.10.5	Lists and entry fields	93
7.4.10.5.1	Fields description.....	93
7.4.10.5.2	"List of Supported Lists" entry fields	96
7.4.10.5.3	"Missed Calls List" entry fields.....	96
7.4.10.5.4	"Outgoing Calls List" entry fields	97
7.4.10.5.5	"Incoming Accepted Calls List" entry fields	97
7.4.10.5.6	"All Calls List" entry fields.....	97
7.4.10.5.7	>Contact List" entry fields.....	98
7.4.10.5.8	"Internal Names List" entry fields	98
7.4.10.5.9	"DECT System Settings List" entry fields.....	98
7.4.10.5.10	"Line Settings List" entry fields	98
7.4.10.5.11	"All Incoming Calls List" entry fields	99
7.4.10.5.12	"Line and Diagnostic Statuses List" entry fields	99
7.4.10.6	List access service call and interactions with voice calls	99
7.4.10.7	Generic sequence charts for list access	99
7.4.10.8	Use case examples for list access	99
7.4.10.9	Extended list change notification	99
7.4.10.9.1	General requirements.....	99
7.4.10.9.2	Sending rules	106
7.4.10.10	Log management in case of user interaction	112
7.4.10.10.1	Definitions and applicability of procedure	112
7.4.10.10.2	Maximum partial synchronization time of a local log	112
7.4.10.10.3	Maximum partial access time to a remote list	113
7.4.11	DECT system and line settings	113
7.4.11.1	DECT system and line settings considerations	113
7.4.11.2	Interactions between registration, attachments of handsets and lists	114
7.4.11.3	DECT System Settings List	114
7.4.11.3.1	Field 'Current PIN code'	115
7.4.11.3.2	Field 'Clock master'	115
7.4.11.3.3	Field 'Base reset'	115
7.4.11.3.4	Field 'FP IP address / type'.....	115
7.4.11.3.5	Field 'FP IP address / value'.....	115
7.4.11.3.6	Field 'FP IP address / subnet mask'.....	115
7.4.11.3.7	Field 'FP IP address / gateway'	115
7.4.11.3.8	Field 'FP IP address / DNS server'.....	115
7.4.11.3.9	Field 'FP version / Firmware version'	115
7.4.11.3.10	Field 'FP version / Eeprom version'	115
7.4.11.3.11	Field 'FP version / Hardware version' field.....	115
7.4.11.3.12	Field 'Emission mode'	115
7.4.11.3.13	Field 'New PIN code'	116
7.4.11.3.14	Field 'FP power level'	116

7.4.11.4	Line Settings List	116
7.4.11.5	Virtual Contact List and Call List per Line	116
7.4.12	Calling line identity restriction (CLIR).....	117
7.4.13	Call forwarding (external calls)	117
7.4.14	DTMF handling	117
7.4.15	Tones provision	117
7.4.16	Headset management	117
7.4.17	UTF-8 CNIP	117
7.4.18	Location registration after re-lock	117
7.4.19	PT alerting using pattern signalling	117
7.4.20	Date and Time recovery.....	117
7.4.21	Void	117
7.4.22	Void	117
7.4.23	Void	118
7.4.24	Void	118
7.4.25	Void	118
7.4.26	Void	118
7.4.27	Void	118
7.4.28	Void	118
7.4.29	Void	118
7.4.30	Void	118
7.4.31	Void	119
7.4.32	Contact number and name matching on outgoing call.....	119
7.4.32.1	Contact number and name matching on outgoing call	119
7.4.33	Contact number and name matching on incoming call.....	121
7.4.34	Line and diagnostic information	122
7.4.34.1	General requirements	122
7.4.34.2	Exposed diagnostic information.....	123
7.4.34.3	Line and Diagnostic Statuses List	124
7.4.34.3.1	Field 'Line id'.....	124
7.4.34.3.2	Field 'OK status'.....	125
7.4.34.3.3	Field 'Line use status'.....	125
7.4.34.3.4	Field 'Handset use status'	126
7.4.34.3.5	Field 'Call Forwarding status'	127
7.4.34.3.6	Field 'Diagnostic error status'	127
7.4.34.4	Diagnostic indication	130
7.4.35	Short Message Service	130
7.4.35.1	General requirements	130
7.4.35.2	Incoming SMS handling.....	132
7.4.35.3	Outgoing SMS handling.....	132
7.4.35.4	SMS settings	135
7.4.35.4.1	SMS Settings List.....	135
7.4.35.4.2	SMS settings fields	136
7.4.35.5	SMS related entry fields and lists.....	140
7.4.35.5.1	SMS related entry fields	140
7.4.35.5.2	Incoming SMS List entry fields.....	143
7.4.35.5.3	Sent SMS List entry fields.....	143
7.4.35.5.4	Outgoing SMS List entry fields.....	144
7.4.35.5.5	Draft SMS List entry fields	144
7.4.36	(Digital) Telephone Answering Machine (DTAM)	144
7.4.36.1	DTAM description	144
7.4.36.1.1	General requirements.....	144
7.4.36.1.2	DTAM settings management.....	145
7.4.36.1.3	DTAM incoming and welcome messages management.....	146
7.4.36.2	DTAM profiles.....	148
7.4.36.2.1	Voice oriented DTAM.....	148
7.4.36.2.2	Visual DTAM.....	150
7.4.36.3	DTAM consulting call.....	152
7.4.36.3.1	General description.....	152
7.4.36.3.2	Parallel call during active DTAM consulting call	155
7.4.36.4	DTAM commands.....	156
7.4.36.4.1	DTAM commands general requirements.....	156

7.4.36.4.2	Start DTAM session	156
7.4.36.4.3	Select neighbour message.....	158
7.4.36.4.4	Play message	159
7.4.36.4.5	Delete message	161
7.4.36.4.6	Pause/resume playing of message	162
7.4.36.4.7	Stop playing message	163
7.4.36.4.8	Record welcome message.....	164
7.4.36.4.9	Stop recording welcome message.....	165
7.4.36.4.10	Negative acknowledgement.....	165
7.4.36.4.11	DTAM status command	166
7.4.36.5	DTAM related lists.....	167
7.4.36.5.1	DTAM specific fields description	167
7.4.36.5.2	DTAM Settings List	172
7.4.36.5.3	DTAM Incoming Messages List	173
7.4.36.5.4	DTAM Welcome Message List	174
7.4.36.5.5	List Access service call transformation into a DTAM consulting call	174
7.4.36.5.6	Local DTAM PIN code management	177
7.4.36.6	Call Screening	178
7.4.36.6.1	Screening general requirements.....	178
7.4.36.6.2	Call screening indication (FP to PP).....	179
7.4.36.6.3	Call screening acceptance (PP to FP).....	180
7.4.36.6.4	Call screening rejection (PP to FP).....	181
7.4.36.6.5	Call screening interception (PP to FP).....	182
7.4.36.6.6	FP initiated call screening release (FP to PP).....	183
7.4.36.6.7	Parallel call during active call screening	184
7.4.36.6.8	Call screening of a waiting call	184
7.4.36.6.9	Call screening with screening and non-screening PPs.....	185
7.4.36.6.10	Single/Multiple PP(s) call screening mode.....	187
7.5	Data Link Control (DLC) layer procedures.....	188
7.6	Medium Access Control (MAC) layer procedures.....	188
7.7	Physical layer (PHL) requirements.....	188
7.8	Requirements regarding the speech transmission.....	188
7.9	Management procedures.....	188
7.10	Application procedures.....	188
7.10.1	Easy PIN code and easy pairing registration	188
7.10.2	Handset locator	188
7.10.3	Transmit power control.....	188
7.10.3.1	Base manual transmit power control.....	188
7.10.3.2	Handset adaptive transmit power control.....	189
Annex A (normative):	System parameters.....	190
A.1	CC timers.....	190
A.2	MM timers	190
A.3	Application timers	191
A.4	Constants	191
Annex B (informative):	Recommended implementation of A-field data procedures.....	192
Annex C (informative):	Recommended implementation of telephony procedures	193
Annex D (informative):	Guidelines for implementation of DTMF	194
Annex E (informative):	Tones format in Recommendations ITU-T.....	195
Annex F (normative):	Used normative references and required modifications.....	196
F.1	Required modifications to EN 300 175-5, V2.5.1	196
F.1.1	Required modifications in clause 7.7.41 (Terminal capability).....	196
F.1.2	Required modifications in clause 7.7.57 (List change details)	197

Annex G (informative): DTAM service use case examples	199
G.1 Voice oriented remote DTAM with a DTAM number.....	199
G.1.1 DTAM incoming messages management.....	199
G.1.2 Welcome messages management	200
G.2 Local or remote (visual) DTAM without DTAM number	201
G.2.1 DTAM incoming/Welcome messages management	201
G.3 DTAM message deletion via Delete entry	202
Annex H (normative): Editable fields.....	204
Annex I (informative): Use cases for concurrent access to lists	210
I.1 Use case 1 – Indices misinterpreted	210
I.1.1 Use case 1a – Read entries with pending notification	210
I.1.2 Use case 1b – Read entries crosses notification	211
I.2 Use case 2 – Position indicators misinterpreted.....	212
I.2.1 Use case 2a – Delete entry (by disturbed party) with pending notifications	212
I.2.2 Use case 2b – Delete entry crosses notification.....	215
I.2.3 Use case 2c – Save entry (by disturbed party) with pending notifications	215
Annex J (informative): Bibliography.....	218
History	219

iteh STANDARD PREVIEW
(standards.iteh.a)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/bsi5061-80e9-4463-a25c-44759e162ec9/etsi-ts-102-527-5-v1.2.1>
2014-01

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is based on EN 300 175 parts 1 to 8 ([1], [2], [3], [4], [5], [6], [7] and [8]) and EN 300 444 [11]. General attachment requirements and speech attachment requirements are based on EN 301 406 [10] (replacing TBR 006 [i.2]) and EN 300 176-2 [9] (previously covered by TBR 010 [i.3]). Further details of the DECT system may be found in TR 101 178 [i.1].

The present document has been developed in accordance to the rules of documenting a profile specification as described in ISO/IEC 9646-6 [i.12].

The information in the present document is believed to be correct at the time of publication. However, DECT standardization is a rapidly changing area, and it is possible that some of the information contained in the present document may become outdated or incomplete within relatively short time-scales.

The present document is part 5 of a multi-part deliverable covering the New Generation DECT as identified below:

- Part 1: "Wideband speech";
- Part 2: "Support of transparent IP packet data";
- Part 3: "Extended wideband speech services";
- Part 4: "Light Data Services: Software Update Over The Air (SUOTA), content downloading and HTTP based applications";
- Part 5: "Additional feature set nr. 1 for extended wideband speech services".**

The present document is defined as an extension of TS 102 527-3 [18] so the numbering and order of figures and tables in the present document is aligned with the corresponding numbering and order of figures and tables in TS 102 527-3 [18].

1 Scope

The present document specifies a set of functionalities of the New Generation DECT.

The New Generation DECT provides the following basic new functionalities:

- Wideband speech service (part 1).
- Packet-mode data service supporting Internet Protocol with efficient spectrum usage and [18] high data rates (part 2).
- Extended wideband speech services (part 3).
- Light Data Services: Software Update Over The Air (SUOTA), Content Downloading and HTTP based applications (part 4).
- Additional feature set nr. 1 for extended wideband speech services (part 5).

All New Generation DECT devices will offer at least one or several of these services.

The present document describes the part 5: Additional feature set nr. 1 for extended wideband speech services.

- For the description of the wideband speech service, see TS 102 527-1 [17].
- For the description of the support of transparent IP packet data, see TS 102 527-2 [i.4].
- For the description of the Extended wideband speech services, see TS 102 527-3 [18].
- For the description of the Light Data Services: Software Update Over The Air (SUOTA), Content Downloading and HTTP based applications, see TS 102 527-4 [i.5].

Part 5 ("Additional feature set nr. 1 for extended wideband speech services") is defined as an extension of part 3 ("Extended wideband speech services" [18]) which is itself an extension of part 1 ("Wideband speech service" [17]). Consequently, this means that all devices compliant to the present document will also implement at least all mandatory features and may implement the optional features defined in part 3 and part 1. In addition to that, the present document defines additional mandatory or optional features.

Part 1, and therefore also part 3 and part 5, are defined as extensions of the "Generic Access Profile (GAP)" [11]. All DECT devices offering Wideband speech services (part 1, or part 1 plus part 3, or part 1 plus part 3 plus part 5) are also compliant with the "Generic Access Profile (GAP)" [11], and offer the DECT standard 32 kbit/s voice service according to GAP [11].

All DECT devices claiming to be compliant with this Application Profile will offer at least the basic services defined as mandatory. In addition to that, optional features can be implemented to offer additional DECT services.

The aim of the present document is to guarantee a sufficient level of interoperability and to provide an easy route for development of DECT wideband speech applications, with the features of the present document being a common fall-back option available in all compliant to this profile equipment.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical layer (PHL)".
- [3] ETSI EN 300 175-3 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] ETSI EN 300 175-4 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [5] ETSI EN 300 175-5 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] ETSI EN 300 175-8 (V2.5.1): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [9] ETSI EN 300 176-2: "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech".
- [10] ETSI EN 301 406: "Digital Enhanced Cordless Telecommunications (DECT); Harmonized EN for Digital Enhanced Cordless Telecommunications (DECT) covering the essential requirements under article 3.2 of the R&TTE Directive; Generic radio".
- [11] ETSI EN 300 444 (V2.4.1): "Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [12] Recommendation ITU-T G.726 (1990): "40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM)".
- [13] Recommendation ITU-T G.711 (1988): "Pulse code modulation (PCM) of voice frequencies".
- [14] Recommendation ITU-T G.722 (1988): "7 kHz audio-coding within 64 kbit/s".
- [15] Recommendation ITU-T G.729.1 (2006): "G.729-based Embedded Variable bit-rate coder: An 8-32 kbit/s scalable wideband coder bitstream interoperable with G.729".
- [16] ISO/IEC JTC1/SC29/WG11 (MPEG): International Standard ISO/IEC 14496-3:2005: "Information Technology - Coding of audio-visual objects - Part 3: Audio".
- [17] ETSI TS 102 527-1 (V1.4.1): "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; part 1: Wideband Speech".
- [18] ETSI TS 102 527-3 (V1.6.1): "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; part 3: Extended Wideband Speech Services".
- [19] ETSI TS 123 038 (V11.0.0) (2012-10): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Alphabets and language-specific information (3GPP TS 23.038 version 11.0.0 Release 11)".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A high Level Guide to the DECT Standardization".
- [i.2] ETSI TBR 006: "Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements".
- [i.3] ETSI TBR 010: "Digital Enhanced Cordless Telecommunications (DECT); General terminal attachment requirements: Telephony applications".
- [i.4] ETSI TS 102 527-2: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; part 2: Support of transparent IP packet data".
- [i.5] ETSI TS 102 527-4: "Digital Enhanced Cordless Telecommunications (DECT); New Generation DECT; part 4: Light Data Services; Software Update Over The Air (SUOTA), content downloading and HTTP based applications".
- [i.6] Recommendation ITU-T P.311 (2005): "Transmission characteristics for wideband (150-7000 Hz) digital handset telephones".
- [i.7] Void.
- [i.8] Recommendation ITU-T Q.23 (1988): "Technical features of push-button telephone sets".
- [i.9] Recommendation ITU-T Q.24 (1988): " Multifrequency push-button signal reception".
- [i.10] Recommendation ITU-T E.180: "Technical characteristics of tones for the telephone service".
- [i.11] Recommendation ITU-T E.180- Supplement 2 (1994): "Various tones used in national networks".
- [i.12] ISO/IEC 9646-6: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 6: Protocol profile test specification".
- [i.13] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [i.14] ETSI TS 123 040 (V11.3.0) (2012-10): "Digital cellular telecommunications system (Phase 2+);Universal Mobile Telecommunications System (UMTS);Technical realization of the Short Message Service (SMS) (3GPP TS 23.040 version 11.3.0 Release 11)".
- [i.15] ETSI ES 201 912 (V1.2.1) (2004-08): "Access and Terminals (AT);Short Message Service (SMS) for PSTN/ISDN; Short Message Communication between a fixed network Short Message Terminal Equipment and a Short Message Service Centre".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 444 [11] and the following apply:

attached to a line: PP is "attached to a line" if its associated bit is set in the "Handset bitmap" in the "Attached handsets" field of the "Line Settings List" entry for that line

NOTE: A PP that is attached to a line can send and receive calls on that line.

call status: part of the call information sent from FP to PP about the FP call state toward the peer party

double call with in-band signalling (line): legacy line on which second calls -incoming or outgoing- are handled using signalling "in-band"

FP-managed line selection: mode for an outgoing external call, in which the PP does not indicate the line to be used to the FP and the FP chooses the line where the call is placed

Headset PP (HPP): headset PP is a wireless headset telephone using the DECT air interface

NOTE: A HPP usually has only one speaker and one microphone combined with a limited set of keys (e.g. call button, volume plus, and volume minus). Headsets provide the equivalent functionality of a PP with hands-free operation.

late release: sending of a "CS idle" call status by the FP for a call that has been released a long time before in the network

NOTE: See clause 7.4.3.10.3.1.

line: logical channel, separately accessible from the external world through a dedicated external directory entry (e.g. telephone number, uri, etc.)

NOTE: These lines may be of various types, for example: PSTN, VoIP or ISDN lines.

multiple call line: line supporting several simultaneous (external) calls

NOTE: An example of multiple call line is a VoIP line used with the SIP protocol.

multiple-call mode: configuration mode of a multiple call line from a DECT system point of view, enabling several simultaneous incoming or outgoing calls on different PPs (i.e. this possibility is not disabled by configuration)

new generation DECT: further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements

none: special line identifier value (called "None") is defined in clause 7.7.56 of EN 300 175-5 [5] and is used to indicate that the line id for the external call is not yet known

NOTE: It is used for FP managed line selection (clauses 7.4.3.5.1 and 7.4.5.2.4) and, as a special case, for call intrusion (clause 7.4.3.8).

off-hook CLIP: ability of a network to send CLIP information for a waiting call (also known as "CLIP on call waiting" or "CLIP phase II")

single-call mode: configuration mode of a multiple call line from a DECT system point of view, in which the possibility of making several fully parallel call is (temporarily) disabled

NOTE: This mode may be useful for a user alone in the home. This mode does not prevent several simultaneous calls on the same PP. A line which is not "multiple call" (for instance a PSTN line only enabling double calls) is also said to be in "single call" mode.

super-wideband speech: voice service with enhanced quality compared to ADPCM G.726 and allowing the transmission of a maximum vocal frequency of at least 14 kHz

wideband speech: voice service with enhanced quality compared to ADPCM G.726 and allowing the transmission of a vocal frequency range of at least 150 Hz to 7 kHz, and fulfilling, at least, the audio performance requirements described in the Recommendation ITU-T P.311 [i.6]

3.2 Symbols

For the purposes of the present document, the following symbols apply:

M	mandatory to support (provision mandatory, process mandatory)
O	optional to support (provision optional, process mandatory)
I	out-of-scope (provision optional, process optional) not subject for testing
C	conditional to support (process mandatory)