



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Digital Private Mobile Radio (dPMR) using
FDMA with a channel spacing of 6,25 kHz**

PREVIEW
iTech Standards (www.it-ebooks.info)
https://standards.iteh.ai/catalog/standards/sist/43eb1215-
a524-4ec6-bf7b-94f1846051b3/etsi-102-658-v2-4-1-
2014-06

Reference

RTS/ERM-TGDMR-319

Keywords

air interface, digital, FDMA, PMR, protocol, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	13
Foreword.....	13
Modal verbs terminology.....	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions.....	15
3.2 Symbols.....	17
3.3 Abbreviations	17
4 Overview	19
4.1 Protocol architecture.....	19
4.1.1 Air Interface Physical Layer (layer 1).....	20
4.1.2 Air Interface Data Link Layer (layer 2).....	20
4.1.3 Air Interface Call Control Layer (layer 3).....	21
4.1.4 Architectural Configurations	21
4.1.4.1 Peer-to-Peer Direct Network (Mode 1).....	21
4.1.4.2 Centralized Repeater Network (Mode 2).....	22
4.1.4.3 Managed Centralized Repeater Network (Mode 3).....	22
4.1.4.3.1 Beacon Channel.....	22
4.1.4.3.2 Traffic Channel.....	22
4.1.4.4 Services available.....	23
4.1.5 Channel Access Mechanisms.....	23
4.1.5.1 User Services.....	24
4.1.5.1.1 Voice calls	24
4.1.5.1.2 Status delivery	24
4.1.5.1.3 Status polling	24
4.1.5.1.4 Short Data Delivery.....	24
4.1.5.1.5 Short Data Polling.....	24
4.1.5.1.6 Type 1 data	24
4.1.5.1.7 Type 2 data	24
4.1.5.1.8 Type 3 (packet) data	24
4.1.5.2 Random Access (Mode 1, Mode 2).....	24
4.1.5.3 Regulated Random Access (Mode 3).....	25
4.1.5.4 Polling.....	25
4.1.5.5 Beacon Signal	25
4.2 FDMA Structure.....	25
4.2.1 Overview of the transmission structure	25
4.2.2 Transmission format	26
4.2.2.1 Traffic Channel Message Frame	26
4.2.2.2 Traffic Channel Payload Frame	26
4.2.2.2.1 Traffic Channel Superframe	26
4.2.2.3 Traffic Channel Packet Data Header Frame.....	27
4.2.2.4 Traffic Channel End Frame.....	27
4.2.2.5 Beacon SYScast Frame	27
4.2.2.6 Appended Data Frame.....	27
4.2.3 Transmission sequences.....	28
4.2.3.1 Traffic Channel Voice or data payload item transmission	28
4.2.3.2 Traffic Channel Call set up, service request, etc	28
4.2.3.3 Traffic Channel Acknowledgement:	28
4.2.3.4 Traffic Channel Status request acknowledgements:.....	28
4.2.3.5 Traffic Channel Disconnection:	29

4.2.3.6	Traffic Channel Preservation Message.....	29
4.2.3.7	Mode 3 Beacon Channel	29
4.2.3.8	Mode 1 Call Exchange	29
4.2.3.8.1	Mode 1 Voice Call.....	29
4.2.3.8.2	Mode 1 Data Call.....	31
4.2.3.9	Mode 2 Call Exchange	32
4.2.3.10	Co-channel BS networks	32
4.2.3.11	Mode 3 Operation	33
4.3	Addressing.....	35
4.4	Unified Data Transport Mechanism	35
4.5	Complementary Data.....	35
4.5.1	Support for Voice and Data call services.....	36
4.5.2	Transport of complementary data for MS control.....	36
5	Frame coding.....	36
5.1	Payload Frame [T].....	38
5.2	Message_Frame [BT].....	38
5.2.1	Communications_Start Header [T].....	39
5.2.1.1	Concatenated Superframe to a Communications_Start Header[T]	39
5.2.2	Connection_Request Header [T].....	41
5.2.2.1	Called Party Check [T].....	41
5.2.2.2	Repeat Last Ack(RLA) [T]	42
5.2.2.3	Short Data Delivery Header message [T].....	42
5.2.2.4	Call Diversion [T]	43
5.2.3	Disconnect_Request Header [T].....	43
5.2.4	T_ACK B_ACK Message [T]	43
5.2.4.1	Message Information for acknowledgements.....	44
5.2.5	Maintenance_Message [T].....	44
5.2.5.1	Idle Message [T]	45
5.2.5.2	Preservation message	45
5.2.5.3	Guard_Message [T].....	46
5.2.6	System_Request Header [T]	46
5.2.7	ACK header response to a System Request [T].....	47
5.2.8	System Delivery Header [T]	47
5.2.9	Status Polling Response Message [T].....	47
5.2.10	Status Polling Request Message [T]	48
5.2.11	BS_Command header(U) and response(D) [T].....	48
5.2.12	BS_Access header(U) and response(D) [T].....	48
5.2.13	Broadcast Messages [B] [T].....	49
5.2.13.1	Broadcast Aloha Message [B].....	49
5.2.13.2	Broadcast Announcements [B].....	50
5.2.13.2.1	Broadcast Announcement - Call Timers [B]	51
5.2.13.2.2	Broadcast Announcement - Vote Now [B].....	51
5.2.13.2.3	Broadcast Announcement - Mass Registration [B]	52
5.2.13.2.4	Broadcast Announcement - Real Time [B].....	52
5.2.13.3	Move Channel Broadcast [BT]	53
5.2.13.4	Goto Channel Broadcast [BT].....	53
5.2.13.5	Ambience Listening [T]	53
5.2.14	AHOY/Random Access Request Message [B].....	54
5.2.14.1	B_AHOY Message Downlink [B]	55
5.2.14.2	Random Access Request Uplink [B].....	57
5.2.15	UDT Header messages [B]	58
5.3	End_Frame	59
5.4	Packet Data Header [T]	60
5.5	Field Descriptions.....	60
5.5.1	Active ACTIVE [B].....	61
5.5.2	Appended_Data [BT].....	61
5.5.3	ARQ [T].....	61
5.5.4	Backoff [B]	62
5.5.5	Call Timers [BT].....	62
5.5.6	Communication format [BT]	63
5.5.7	Communication Mode [BT].....	64

5.5.8	COMP [B]	64
5.5.9	Continuation_Flag [T]	64
5.5.10	Day of Week(DAYSOF_WEEK) [B]	65
5.5.11	Digits [BT]	65
5.5.12	Emergency Priority [BT]	65
5.5.13	End_Type [T]	66
5.5.14	Frame numbering [T]	66
5.5.15	Frequency Definitions FR, FT, SEP, BAND [BT]	67
5.5.16	Guard_Kind [T]	67
5.5.17	Long [B]	68
5.5.18	Mask [B]	68
5.5.19	Message Information [BT]	68
5.5.19.1	Message Information for Powersave [T]	69
5.5.19.2	Message Information for Types 1 and 2 data [T]	69
5.5.19.3	Message Information for Type 3 (packet) data [T]	70
5.5.19.4	Message Information for system transactions [T]	70
5.5.19.5	Message Information for B_ACK T_ACK acknowledgements [BT]	71
5.5.19.6	Message Information for Broadcast headers [BT]	71
5.5.19.7	Message Information for BS Command headers [T]	72
5.5.19.8	Message Information for additional services [B]	72
5.5.20	Message_Type [BT]	73
5.5.21	Month B_MONTH	73
5.5.22	NRand_Wait [B]	73
5.5.23	Preservation_Message PM [T]	74
5.5.24	POL_FMT [B]	74
5.5.25	Reason [BT]	74
5.5.26	Reg [B]	77
5.5.27	Reserved [BT]	77
5.5.28	Service Function [B]	77
5.5.29	SLD format [T]	78
5.5.29.1	SLOw Data in the voice superframe	78
5.5.29.2	SLOw Data field use with Type 1 or 2 data	78
5.5.30	Status	79
5.5.30.1	Status for Mode 1 and Mode 2 systems [T]	79
5.5.30.2	Status for Mode 3 systems [B]	79
5.5.31	SYMB [BT]	79
5.5.32	SYScast [B]	79
5.5.32.1	SYScast1 [B]	79
5.5.32.2	SYScast2 or SYScast3 [B]	80
5.5.32.2.1	SYScast2 or SYScast3 Call Timer MS to MS [B]	80
5.5.32.2.2	Call Timer for line connected calls and packet data [B]	80
5.5.32.2.3	SYScast2 or SYScast3 Real Time [B]	80
5.5.32.2.4	SYScast2 or SYScast3 Common Frame Counter [B]	81
5.5.32.2.5	SYScast2, SYScast3 Calling Party Address [B]	81
5.5.33	System Identity Code [B]	82
5.5.34	Tx_Wait [T]	82
5.5.35	UAD [BT]	82
5.5.36	UDT_Format [BT]	83
5.5.37	Version [BT]	83
5.5.38	Vote Now Advice Parameters [B]	83
5.5.39	Withdrawn W [B]	83
5.6	Appended_Data Messages [BT]	84
5.6.1	Appended_Data MS ID Format	84
5.6.2	Appended_Data Binary Format	84
5.6.3	Appended_Data BCD Format	85
5.6.4	Appended_Data (ISO 7 bit character set Format)	85
5.6.5	Appended_Data (ISO 8 bit character set format)	85
5.6.6	Appended_Data NMEA (EN 61162-1) format	86
5.6.7	Appended_Data IPV4 format	87
5.6.8	Appended_Data IPV6 format	87
5.6.9	Appended_Data Filler	87

6	Synchronization.....	88
6.1	Frame synchronization	88
6.1.1	FS1.....	88
6.1.2	FS2.....	88
6.1.3	FS3.....	88
6.1.4	FS4.....	88
6.1.5	Channel Code.....	88
6.1.5.1	Channel Code for Mode 1 and Mode 2 Systems.....	90
6.1.5.2	Channel Code for Mode 3 Systems.....	90
6.1.5.2.1	Channel Code Determined by Frequency.....	90
6.1.5.2.2	Channel Code Determined by Frequency and System Identity Code.....	90
6.1.6	Preamble.....	92
7	Interleaving and FEC coding.....	92
7.1	CRC addition.....	92
7.2	Hamming code	92
7.3	Scrambling	93
7.4	Interleaving.....	93
7.5	FEC coding of CCH (superframe).....	94
7.6	FEC coding of MI (message info) and HI (header info).....	94
7.7	FEC coding of END information	95
7.8	FEC coding of Appended Data.....	95
8	Bearer Services, tele-services and supplementary services.....	95
8.1	Call types.....	96
8.1.1	Individual call.....	96
8.1.2	Group call	96
8.2	Addressing.....	97
8.3	Channel Codes.....	97
8.4	Messages	97
8.4.1	Downlink Traffic Channel messages.....	97
8.4.2	Uplink Traffic Channel messages.....	98
8.4.3	Downlink Beacon messages.....	98
8.4.4	Uplink Beacon messages	99
9	Packet data.....	99
9.1	Format	99
9.2	Receiving party	100
9.3	Packet frame coding	101
9.4	Data frame size.....	101
9.5	Valid data length	102
9.6	Data checksum	102
9.7	Standard Packet Exchange Format.....	103
10	Call procedures.....	104
10.1	Call procedures for Mode 1.....	105
10.1.1	Common procedures for Mode 1 Voice and Data calls.....	105
10.1.1.1	Mode 1 Call set up.....	105
10.1.2	Mode 1 Voice calls	107
10.1.2.1	Mode 1 Voice Call in progress.....	107
10.1.2.2	Mode 1 Voice Call with Slow Data	108
10.1.2.3	Mode 1 Voice Call with Attached Data	108
10.1.2.4	Mode 1 Voice Call Termination.....	108
10.1.3	Mode 1 Data Calls	109
10.1.3.1	Mode 1 T1 and T2 Data calls.....	109
10.1.3.2	Mode 1 T3 (Packet) Data Calls.....	110
10.1.3.3	Mode 1 Individual Status polling.....	113
10.1.3.4	Mode 1 Short Data Delivery	114
10.1.4	Mode 1 Traffic Channel Powersave	116
10.1.4.1	Transmitted format.....	116
10.1.4.2	Receive format	117
10.2	Call procedures for Mode 2.....	117
10.2.1	Mode 2 MS to MS Call set up	118

10.2.2	Mode 2 MS to MS Voice Calls.....	119
10.2.3	Mode 2 Data Calls	120
10.2.3.1	Mode 2 T1 and T2 Data Calls	120
10.2.3.2	Mode 2 T3 (Packet) Data Calls	121
10.2.3.3	MS to MS Status request and responses.....	121
10.2.3.4	MS to MS Short Data.....	122
10.2.4	Mode 2 MS Mode 2 Call Diversion.....	124
10.2.4.1	Setting the diversion.....	125
10.2.4.2	Cancelling the diversion.....	125
10.2.5	Mode 2 Connection to line connected destinations.....	125
10.2.5.1	Voice Call Connection_Request message.....	128
10.2.5.2	Call Matrix for calls to line connected destinations	128
10.2.6	Mode 2 calls from line connected sources	129
10.2.6.1	Call Matrix for calls from line connected destinations	129
10.2.7	Mode 2 Co-channel repeater networks	129
10.2.7.1	MS originated repeater polling.....	129
10.2.7.1.1	Description of the messages	131
10.2.7.2	BS originated repeater polling.....	131
10.2.7.2.1	Description of the messages	132
10.2.7.3	Access and Response timing	133
10.3	Call Procedures for Mode 3.....	133
10.3.1	Mode 3 UDT Mechanism	134
10.3.1.1	Format of the Appended_Data	136
10.3.1.2	UDT Structure.....	137
10.3.1.2.1	UDT Content for Services Carried on the Downlink channel	137
10.3.1.2.2	UDT Mechanism for the Uplink channel	138
10.3.1.3	Single Part and Multi-part call set-up	138
10.3.1.4	MS behaviour to B_AHOY messages.....	138
10.3.2	Mode 3 call examples	139
10.3.2.1	An individual voice call example.....	139
10.3.2.2	A Mode 3 talkgroup call example	140
10.3.2.3	Mode 3 Short Data call example	141
10.3.2.4	Mode 3 Call to PABX/PSTN example.....	141
10.3.2.5	Mode 3 Call from the PABX/PSTN example	142
10.3.2.6	Mode 3 transport of complementary data example	143
10.3.2.7	Mode 3 transport of complementary data and an extended address example.	143
10.3.2.8	Mode 3 Refusal of Service.....	144
10.3.3	Mode 3 Detailed Call procedures	145
10.3.3.1	Mode 3 Procedures common to Voice calls and Data Calls.....	145
10.3.3.1.1	Availability of requesting MS	145
10.3.3.1.2	Call Cancellation	145
10.3.3.1.3	Acknowledgements sent to calling MS	145
10.3.3.1.4	Maintenance of call progress waiting timers	146
10.3.3.1.5	Traffic Channel Assignment.....	146
10.3.4	Mode 3 Voice Call Procedures	147
10.3.4.1	Voice Call Procedures for the BS	147
10.3.4.1.1	BS Response to single-part voice call set-up.....	148
10.3.4.1.2	BS Response to multi-part voice call set-up.....	148
10.3.4.1.3	Acknowledgements sent by the BS to the calling MS (voice).....	148
10.3.4.1.4	Voice Radio Check.....	149
10.3.4.1.5	Availability Check for Voice Calls connected through Gateways	149
10.3.4.2	Voice Call Procedures for MS	149
10.3.4.2.1	Initiating a single-part voice call service	150
10.3.4.2.2	Response to the single-part individual voice service request	150
10.3.4.2.3	Initiating a multi-part voice call service	151
10.3.4.2.4	Response to the multi-part voice service request.....	151
10.3.4.2.5	Acknowledgements received by the calling MS (voice)	151
10.3.4.2.6	Availability Check to the called MS (voice)	152
10.3.4.2.7	Traffic Channel Allocation.....	152
10.3.4.3	Procedures for the Voice Traffic Channel.....	152
10.3.4.3.1	BS Procedures for the Voice Traffic Channel	153
10.3.4.3.2	MS Procedures for the Voice Traffic Channel	154

10.3.5	Mode 3 Data Call Procedures	155
10.3.5.1	Data Call Procedures for the BS	156
10.3.5.1.1	BS Response to single-part data call set-up.....	156
10.3.5.1.2	BS Response to multi-part data call set-up.....	156
10.3.5.1.3	Acknowledgements sent by the BS to the calling MS (data).....	157
10.3.5.1.4	Radio Check for Data	157
10.3.5.1.5	Availability Check for Data Calls connected through Gateways	157
10.3.5.2	Data Call Procedures for MS	157
10.3.5.2.1	Initiating a single-part data call service	158
10.3.5.2.2	Response to the single-part data call service request.....	158
10.3.5.2.3	Initiating a multi-part data call service	159
10.3.5.2.4	Response to the multi-part data service request.....	159
10.3.5.2.5	Acknowledgements received by the calling MS (data)	159
10.3.5.2.6	Availability Check to the called MS (data)	159
10.3.5.2.7	Traffic Channel Allocation	160
10.3.5.3	Procedures for the Data Traffic Channel.....	160
10.3.5.3.1	BS Procedures for the Data Traffic Channel	160
10.3.5.3.2	MS Procedures for the Data Traffic Channel	161
10.3.5.4	Mode 3 Short Data Message Procedure	162
10.3.5.4.1	Short Data Procedures for the BS.....	164
10.3.5.4.2	Short Data Message procedures for MS	165
10.3.5.4.3	Initiating a Short Data Message service	166
10.3.5.4.4	Response to a random access short data message.....	166
10.3.5.4.5	Acknowledgements received by the calling MS.....	167
10.3.5.4.6	Timeout waiting for further signalling	167
10.3.5.4.7	MS receiving a short data message.....	167
10.3.5.5	Mode 3 Short Data Polling Service.....	167
10.3.5.5.1	Short Data Polling Procedures for the BS	169
10.3.5.5.2	Short Data Polling Message procedures for MS	170
10.3.5.5.3	Initiating a Short Data Polling service.....	171
10.3.5.5.4	Response to a random access short data polling message	171
10.3.5.5.5	Final Acknowledgement transmitted by the calling MS.....	171
10.3.5.5.6	Timeout waiting for further signalling	172
10.3.5.5.7	MS receiving a B_AHOY poll for a short polling message	172
10.3.5.6	Mode 3 Status Call Service	172
10.3.5.6.1	Status Service Delivery Procedure	172
10.3.5.7	Mode 3 Call Diversion.....	175
10.3.5.7.1	Call Diversion Service.....	175
10.3.5.7.2	Call set-up to an MS that has a Diverted address	178
10.3.5.8	Mode 3 MS Stun/Revive Procedures	178
10.3.5.8.1	MS Stun/Revive without authentication.....	179
10.3.5.9	Mode 3 MS Kill	180
10.3.5.9.1	Kill procedures for the BS	180
10.3.5.9.2	Kill procedure with ESN check for the MS	181
10.3.5.10	Mode 3 Dynamic Regroup Service	181
10.3.5.10.1	Dynamic Regroup Service.....	181
10.3.5.10.2	Dynamic Regroup Procedures for the BS.....	184
10.3.5.10.3	Dynamic Regroup procedures for MS	184
10.3.6	Message Address Matrix for Mode 3 Call services	186
10.3.6.1	Call Services that require the allocation of a Traffic Channel.....	186
10.3.6.1.1	MS to MS or talkgroup Voice, T1, T2, T3 data call.....	186
10.3.6.1.2	MS call to PSTN, PABXI and other extended addresses	187
10.3.6.1.3	Call from PSTN, PABX, or other line connected address to MS or talkgroup.....	187
10.3.6.2	Call Services that only require the Beacon Channel	188
10.3.6.2.1	MS Short Data Call to MS or talkgroup	188
10.3.6.2.2	Short Data Call from PSTN, PABX, LINEI, DISPATI to MS or talkgroup	189
10.3.6.2.3	Short Data Call from MS to PSTN, PABX, LINEI, DISPATI.....	189
10.3.6.2.4	Short Data Polling from MS to MS	189
10.3.6.2.5	Short Data MS Polling from a gateway.....	190
10.3.6.2.6	Status Transport from MS to MS or talkgroup	190
10.3.6.3	Complementary data	190
10.3.6.4	Other Mode 3 Services.....	191

10.3.6.4.1	Call Diversion Service.....	191
10.3.6.4.2	Registration	192
10.3.6.4.3	Serial Number Check	192
10.3.6.4.4	MS Stun/Revive.....	192
10.3.6.4.5	MS Kill.....	192
11	Channel coding process.....	193
11.1	Voice superframe	193
11.1.1	Voice + Attached data call.....	194
11.2	Type 1 data superframe	196
11.3	Type 2 Data superframe	197
11.4	Type 3 (Packet) Data frame.....	199
11.5	Messages	201
11.6	End frames.....	202
11.7	SYScast Frames.....	203
11.8	Appended Data Frames	204
12	Channel access	205
12.1	Channel access for Mode 1 [M1]	207
12.1.1	Listen Before Transmit (LBT) [M1].....	207
12.1.2	Hang time messages and timers [M1].....	208
12.1.2.1	Definition [M1]	208
12.1.2.2	Action by receiving stations [M1].....	208
12.1.2.3	Call duration timers [M1].....	208
12.1.2.3.1	Item Duration Timer for Voice Calls [M1]	208
12.1.2.3.2	Item Duration Timer for Data Calls [M1]	208
12.1.3	Transmit admit criteria [M1]	208
12.1.3.1	Channel "Politeness" [M1].....	208
12.1.3.2	General Timing [M1]	209
12.1.3.3	Transmission re-tries [M1].....	209
12.1.3.4	Emergency channel access procedures [M1]	209
12.1.3.4.1	Emergency Break-in requests [M1].....	209
12.2	Channel access for Mode 2 [M2]	210
12.2.1	Listen Before Transmit (LBT) [M2].....	211
12.2.2	Hang time messages and timers [M2].....	211
12.2.2.1	Definition [M2]	211
12.2.2.2	Action by receiving stations [M2].....	212
12.2.2.3	Call duration timers [M2].....	212
12.2.2.3.1	Item Duration Timer for Voice Calls [M2]	212
12.2.2.3.2	Item Duration Timer for Data Calls [M2]	212
12.2.2.3.3	Maximum call duration timer for Mode 2 calls	212
12.2.3	Transmit admit criteria [M2]	213
12.2.3.1	Channel "Politeness" [M2].....	213
12.2.3.1.1	MS	213
12.2.3.1.2	BS	213
12.2.3.2	General Timing [M2]	213
12.2.3.3	Transmission re-tries [M2].....	214
12.2.3.4	Emergency channel access procedures [M2]	214
12.2.3.4.1	Emergency Break-in requests [M2].....	215
12.3	Channel access for Mode 3 [M3]	215
12.3.1	Mode 3 Channel Structure	215
12.3.2	Introduction to the Beacon Structure [M3]	216
12.3.2.1	Beacon Timing [M3].....	216
12.3.3	Network architecture [M3]	217
12.3.3.1	Network functions.....	217
12.3.3.1.1	Establishing service	217
12.3.3.1.2	Network Identifier	217
12.3.3.2	MS Location by Registration	217
12.3.4	Trunking methods [M3].....	218
12.3.5	Beacon Channel Formats [M3].....	218
12.3.5.1	Use of the SYScast Frames	219
12.3.5.1.1	SYC1 SYScast Frame.....	219

12.3.5.1.2	SYC2 or SYSC3 SYScast Frame	219
12.3.5.2	Beacon Frame Structure	219
12.3.5.2.1	Frames on the Beacon downlink channel	219
12.3.5.2.2	Frames on the Beacon uplink channel	220
12.3.6	Channel Access for a Beacon Channel	220
12.3.6.1	Basic Structure	220
12.3.6.1.1	Channel Structure	220
12.3.6.1.2	Physical Channel Addressing	221
12.3.6.1.3	Sub-Division of the MS population	221
12.3.7	Random Access Procedures	222
12.3.7.1	The Random Access Principle	222
12.3.7.1.1	Random Access Control	222
12.3.7.1.2	Action after receiving an acknowledgement	230
12.3.7.1.3	MS Arriving on a Beacon Channel	231
12.3.8	Beacon Channel Acquisition and Retention	231
12.3.8.1	Vote Now	232
12.3.8.2	MS Parameter	233
12.3.8.3	Beacon Channel Acquisition Procedures	233
12.3.8.3.1	Entry into Beacon Acquisition Procedures	234
12.3.8.3.2	Identifying a Candidate Beacon Channel	234
12.3.8.3.3	Confirmation - Monitoring the BS downlink channel signal quality	238
12.3.8.3.4	MS Leaving a Beacon Channel	238
12.3.8.3.5	Leaving a Beacon Channel Whilst Waiting for Signalling	238
12.3.8.4	Registration, Power Save, and Authentication Procedures	239
12.3.8.4.1	General	239
12.3.8.4.2	Registration Procedures	241
12.3.9	Mass re-registration	243
12.3.9.1	Procedure for MS on receipt of Mass Re-registration Broadcast	243
12.3.9.2	De-registration	244
12.3.10	Beacon Power Save	245
12.3.10.1	Overview	245
12.3.10.2	Power Save Procedures	245
12.3.10.2.1	Basic Power Save Procedures	245
12.3.11	Electronic Serial Number Check Procedures	247
12.3.11.1	Format of the Electronic Serial Number (ESN)	248
12.3.11.2	ESN Procedures for the BS to authenticate an MS	248
12.3.11.3	ESN Procedures for the MS	249
12.4	Traffic Channel Access for Mode 3	249
12.4.1	Preservation of the traffic channel [M3]	250
12.4.2	Reassignment of the traffic channel for an emergency call	250
13	Timers, constants levels and addresses	251
13.1	Timers	251
13.2	Constants	252
13.3	Levels	253
13.4	Gateways/Identifiers	253
13.5	Message Matrix's	254
14	Physical Layer	255
14.1	General parameters	255
14.1.1	Frequency range	255
14.1.2	RF carrier bandwidth	255
14.1.3	Transmit frequency error	255
14.1.4	Time base clock drift error	255
14.2	Modulation	256
14.2.1	Symbols	256
14.2.2	4FSK generation	256
14.2.2.1	Deviation index	256
14.2.2.2	Square root raised cosine filter	257
14.2.2.3	4FSK Modulator	258
14.3	Transmit Power Ramping	258
Annex A (normative):	Standard User Interface	259

A.1	Numbering and dialling plan	259
A.1.1	Introduction to the numbering and dialling plan	259
A.1.2	Subscriber mapping	260
A.1.2.1	User Interface - Air Interface	260
A.1.2.1.1	Mapping for MS address space	261
A.1.2.1.1.1	The concept of the wildcard character	261
A.1.2.1.1.2	The concept of stored parameters	261
A.1.2.1.1.3	The concept of ad-hoc arrangement	261
A.1.2.1.1.4	The rules for the sender	261
A.1.2.1.1.5	The rules for the recipient	262
A.1.2.1.1.6	Mapping of dialled strings to the AI address space	262
A.1.2.2	Addresses	263
A.1.2.3	Conversion rules	263
A.1.2.3.1	MS addresses	263
A.1.2.3.2	Limiting the length of the destination address	264
A.1.2.3.3	All talkgroup address	264
A.1.3	User dialling plan	264
A.1.3.1	User numbering	264
A.1.3.1.1	Dialling method	264
A.1.3.1.2	Call Type determination	264
A.1.3.1.3	Call modifier strings	264
A.1.3.2	Dialled digits to address mapping	265
A.1.3.3	Storage requirements	265
A.1.3.3.1	MS individual address	265
A.1.3.3.2	Dialled Talkgroups	265
A.1.3.3.3	All MSs	265
A.1.3.3.4	Non-dialable numbers	266
A.1.3.3.5	Talkgroup recognition	266
A.1.3.3.5.1	All numeric talkgroups	266
A.1.3.3.5.2	Talkgroups defined by wildcards	266
A.1.3.3.5.3	MS receives a talkgroup call	266
A.1.3.4	Dialling procedures	267
A.1.3.4.1	MS calls	267
A.1.3.4.1.1	Seven digit dialling	267
A.1.3.4.1.2	Abbreviated dialling	267
A.1.3.4.1.3	Masked dialling	268
A.1.3.4.1.4	Dialling with numbers and wildcards	268
A.1.3.4.2	Gateway Calls	268
A.1.3.4.2.1	Telephone call	268
A.1.3.4.2.2	PABX call	269
A.1.3.4.2.3	IP call	270
A.1.3.4.3	Call modifiers	270
A.1.3.4.3.1	Broadcast call	270
A.1.3.4.3.2	Priority call	270
A.1.3.4.3.3	Emergency Call	270
A.1.3.4.3.4	Status poll call	271
A.1.3.4.3.5	Status delivery call	271
A.1.3.4.3.6	Divert own call	271
A.1.3.4.3.7	Force talkgroup service	271
A.1.3.4.4	Call set-up abandon or call complete	271
A.1.3.4.4.1	Call set-up abandon or call complete - Mode 1	271
A.1.3.4.4.2	Call set-up abandon or call complete - Mode 2	271
A.1.3.4.4.3	Call set-up abandon or call complete - Mode 3	271
Annex B (informative):	Beacon Channel Hunting Procedures	272
B.1	Introduction	272
B.1.1	Resuming a Beacon hunt channel	274
B.1.2	Commanded Beacon hunt channel	274
B.1.2.1	Conditions to enter a Commanded Beacon hunt	274
B.1.2.2	Nominated Channel for the Single Channel Hunt	274
B.1.2.3	Short Hunt Sequence	275

B.1.2.3.1	Conditions to enter a Short Channel Hunt.....	275
B.1.2.4	Comprehensive Hunt Sequence	275
B.1.2.4.1	Conditions to enter a Comprehensive Channel Hunt	275
B.1.2.5	Receiver Sensitivity During Beacon Channel Acquisition	276
History		277

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/43eb1215-a524-4ec6-bf7b-94f18467baf3/etsi-ts-102-658-v2.4.1-2014-06>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
https://standards.iteh.ai/catalog/standards/sis/43eb1215-
a524-4ec6-bf7b-94f18467baf3/etsi-ts-102-658-2.4.1-
2014-06